

no java before code

◆ THE COMPLETE LINE

```
data = request.get_json(force=True)
```

Purpose:

Receive JSON data sent by Spring Boot.

Example incoming JSON:

```
{
  "emailText": "You won a lottery"
}
```

This line reads that JSON and stores it in:

```
data
```

◆ BREAKDOWN

```
data
=
request.get_json(force=True)
```

Let's understand each part.

◆ WHAT IS data?

```
data
```

is a variable name.

It is chosen by the programmer.

It could have been:

```
abc
```

or

```
myData
```

or

```
jsonData
```

But:

```
data
```

is meaningful because it stores incoming data.

◆ WHAT IS = ?

```
=
```

is the assignment operator.

Meaning:

```
Store the value on the right side  
inside the variable on the left side.
```

Example:

```
name = "John"
```

means:

```
Store "John" inside name.
```

Similarly:

```
data = request.get_json(...)
```

means:

```
Store the returned JSON data inside data.
```

◆ WHAT IS request?

```
request
```

is a Flask object.

It represents the current HTTP request.

Think:

```
Spring Boot  
  ↓  
HTTP Request  
  ↓  
Flask
```

Everything sent by Spring Boot arrives inside:

```
request
```

◆ WHAT DOES request CONTAIN?

Suppose Spring Boot sends:

```
POST /predict

{
  "emailText": "You won a lottery"
}
```

Flask receives it as:

```
request
```

Think:

```
request
├── Headers
├── Method
├── URL
└── Body
```

◆ WHAT IS get_json() ?

```
get_json()
```

is a method of the request object.

Meaning:

```
Extract JSON data from the request body.
```

Think:

```
request
  ↓
get_json()
  ↓
JSON extracted
```

◆ WHY DO WE NEED get_json() ?

Suppose Spring Boot sends:

```
{
  "emailText": "You won a lottery"
}
```

Flask cannot directly use:

```
emailText
```

It first needs to read the JSON.

That's what:

```
get_json()
```

does.

◆ WHAT DOES force=True MEAN?

```
force=True
```

is a parameter.

Normally Flask checks:

```
Content-Type: application/json
```

before reading JSON.

If the header is missing or incorrect:

```
get_json()
```

may refuse to read the data.

◆ WITHOUT force=True

Suppose a request comes with:

```
Wrong Content-Type
```

Flask may say:

```
I won't treat this as JSON.
```

and return:

```
None
```

◆ WITH force=True

```
get_json(force=True)
```

tells Flask:

```
Try reading the body as JSON anyway.
```

Think:

```
Normal Mode
↓
Check Header
```

↓
Then Read JSON

VS

force=True
↓
Read JSON regardless

◆ WHAT IS RETURNED?

Suppose Spring Boot sends:

```
{
  "emailText": "You won a lottery"
}
```

Then:

```
request.get_json(force=True)
```

returns:

```
{
  "emailText": "You won a lottery"
}
```

as a Python dictionary.

◆ WHAT IS A DICTIONARY?

A dictionary stores:

Key → Value

Example:

```
{
  "emailText": "You won a lottery"
}
```

Here:

emailText

is the key.

and

You won a lottery

is the value.

◆ FINAL RESULT

After:

```
data = request.get_json(force=True)
```

the variable contains:

```
data =
{
  "emailText": "You won a lottery"
}
```

Now Flask can do:

```
data.get("emailText")
```

to retrieve the email text.

◆ COMPLETE FLOW

```
Spring Boot
  ↓
Sends JSON
  ↓
{
  "emailText": "You won a lottery"
}
  ↓
request
  ↓
get_json(force=True)
  ↓
Convert JSON into Dictionary
  ↓
Store in data
```

◆ NOTE FORMAT

data → variable

= → assignment operator

request → Flask request object containing the incoming HTTP request

get_json() → method used to extract JSON data from the request body

force=True → tells Flask to read the request body as JSON even if the Content-Type header is missing or incorrect

👉 Use: receive JSON data sent by Spring Boot and store it inside the data variable.