Data Contract

Overview

The data contract defines the column names, data types, and nullability that the pipeline expects from the CPAR and AP views, written as an **Apache Avro schema** for each view. The full schema files (`cpar.avsc` and `ap.avsc`) are stored in the repository and are the source of truth. The tables below list every field, grouped by Avro type, and each is followed by a short excerpt of the schema.

CPAR view (56 fields)

Avro type	Fields
`long`	CPARId
`int`	AuditPlanId, Year, SequenceNumber
`string`	CPARNo, AuditType, ForType, TypeOfNC, MinorNC, CauseCode, RootCause, SecondLevelRootCause, OFI, MilitaryFinding, Status, RiskCategory, Company, Title, QSSINo, LOB, Department, Programme, Division, Auditee, Auditor, Assignee, HOD, QM, DGM, GM, PM, QualitySupervisor, Observation, RequirementDetails, Reason, RootCauseDetails, ImmediateCorrectionTaken, CorrectivePreventiveActionIm, VerifiedEvidence, LateVerifyReason, HOD_OverdueExplanation
`long (timestamp-millis)`	CreatedOn, LastUpdatedOn, DueDate, VerificationDuedate, ConcuredDate, CompletedDate, VerificationDate, ApprovedDate, EndorsedDate, NotifiedDate
`boolean`	IsDelete, IsVoid, IsMigratedData, IsOverdueConcurrence, IsOverdueVerification

```
{
  "type": "record",
  "name": "CPAR",
  "namespace": "qsconnect.contract",
  "fields": [
    {"name": "CPARId", "type": ["null", "long"], "default": null},
    {"name": "CPARNo", "type": ["null", "string"], "default": null},
    {"name": "CreatedOn",
     "type": ["null", {"type": "long", "logicalType": "timestamp-millis"}],
     "default": null},
    {"name": "IsDelete", "type": ["null", "boolean"], "default": null}
  ]
}
```

Excerpt only. The full CPAR schema has 56 fields.

AP view (31 fields)

Avro type	Fields
`int`	AuditPlanId
`string`	AuditReportNo, AuditType, ForType, Military, Customer, Authority, Certification, ServiceCenter, Tier, RiskCategory, Stage, LOB, Division, Department, Programme, LeadAuditor, HOD, QM, DGM, GM
`long (timestamp-millis)`	DateCreated, DatePlannedAudit, DateAgreedStart, DateAgreedEnd, DateActualStart, DateActualEnd, DateAuditComplete
`boolean`	IsPlanned, IsLocal, IsDisabled

```
{
  "type": "record",
  "name": "AP",
  "namespace": "qsconnect.contract",
  "fields": [
    {"name": "AuditPlanId", "type": ["null", "int"], "default": null},
    {"name": "AuditReportNo", "type": ["null", "string"], "default": null},
    {"name": "DatePlannedAudit",
     "type": ["null", {"type": "long", "logicalType": "timestamp-millis"}],
     "default": null},
    {"name": "IsPlanned", "type": ["null", "boolean"], "default": null}
  ]
}
```

Excerpt only. The full AP schema has 31 fields.

Notes

- All fields are nullable, written as `["null", type]` in the schema.
- `timestamp-millis` is a date and time stored as milliseconds.
- Type mapping from the database to Avro:

Database type	Avro type
bigint	`long`
int	`int`
nvarchar	`string`
datetime	`long` (timestamp-millis)
bit	`boolean`