

## Time Complexity

## Searching

$$\log n = \log(n^2) < n^{1/2} < n < n \log n = \log n! < n^2 < 2^n < 2^{2n}$$

Recurrence	Runtime
$T(n) = S(0, n-1)T(i) = 2T(n-1)$	$2^n$
$T(n) = 2T(n/2) + O(n)$	$n \log n$
$T(n) = T(n/2) + O(n)$	$n$
$T(n) = 2T(n/2) + O(1)$	$n$
$T(n) = S(0, \sqrt{n})T(i) + \sqrt{n}$	$n$
$T(n) = 2T(n/4) + O(1)$	$\sqrt{n}$
$T(n) = T(n/2) + O(1)$	$\log n$

Search	Runtime
Linear	$n$
Binary	$\log n$
Quickselect	$n$
Knuth Shuffle	$n$
Merkel Tree	$\log n$

Knuth Shuffle:  
for (1, n-1): swap(i, rand(0, i))

## Sorting

Algorithm	Best	Average	Worst	Stable	Space	Remarks
Bubble	$n$	$n^2$	$n^2$	Yes	1	Largest k items are in final k positions
Selection	$n^2$	$n^2$	$n^2$	No	1	Smallest k items are in smallest k positions
Insertion	$n$	$n^2$	$n^2$	Yes	1	First k items are sorted
Merge	$n \log n$	$n \log n$	$n \log n$	Yes	$n$	Groups of $2^x$ are sorted
Quick	$n \log k$	Median/ Rand/Check $n \log k$	Specific $n k$	No	$\log n$	Array is partitioned around pivot $T(n) = pT(n/p) + O(n \log p) = n \log n$ Duplicate: $n^2$ if no 3-way partition
Heap	$n \log n$	$n \log n$	$n \log n$	No	1	Build Heap: $n$ , Get Sort: $n \log n$
Reversal		$n(\log n)^2$				Quicksort with Mergesort around pivot

# Data Trees

Structure	Operation	Remark
Binary Search	h	Full Tree: $n = 2^{(h+1)} - 1$
		<b>Delete</b> if x has 2 child: replace x with successor(x) <b>Successor</b> right.min() or recurse to (left of parent or root)
Scapegoat	logn	Rebuild subtree rooted at scapegoat when triggered
AVL	logn	$h < 1.44 \log n$ or $n > 2^{(h/1.44)}$
		v.left Left Heavy or Balanced: right(v) v.left Right Heavy: left(v.left), right(v) <b>Insert</b> 2 x R <b>Delete</b> 2logn x R
Trie	L	More space due to more overhead
(a,b)	logn	<b>split</b> for insert, <b>merge+share</b> for delete
kd	h	Alternate splitting horizontally and vertically
Heap	logn	1. Heap Ordering: $Pr(\text{parent}) \geq Pr(\text{child})$
		2. Complete Binary Tree <b>Delete</b> Swap(last), Bubble Down Array: $Left(x)=2x+1$ , $Right(x)=2x+2$
Leftist Heap	logn	$\max \text{rightRank} = \log n$ , $\max \text{height} = n$ <b>merge</b> (logn) merge smaller root with right child of other swap if left>right, update rightRank
		<b>Insert</b> merge with single vertex, swap $\leq 1$ <b>GetMax</b> remove root, merge child <b>Delete</b> update rightRank (stop if left child), swap $\leq 1$
Augmented Structure	Remark	
Dynamic Order Statistic	Stores weight of subtree. During functions, rank = left.weight + 1 <b>Select</b> left.weight < rank: left.select(k). Else: right.select(k-rank) <b>Rank</b> recurse to root, if node is right child: rank += parent.left.weight + 1	
Interval Tree	Sort by left endpoint. Stores max endpoint in node's subtree <b>Search</b> (logn) If $x > \max$ or left is null, search(right). Else: search(left) <b>All Overlap</b> (klogn) search node, add to list, delete node, repeat until null	
Orthogonal Range Search	Store all points as leaves of a BST. Internal nodes stores max of left. <b>Range Query</b> (k+logn) find split node. do left & right traversals. <b>2D Range Query</b> (k+(logn) <sup>2</sup> ) for node in x-tree, build y-tree using nodes in subtree. <b>Build2D</b> T(nlogn) S(nlogn)	

# Hashing

Must redefine **hashCode** default returns address and **equals** for **get** to work

Hash Table	Insert	Search	Space	Remarks
Linked List	$h+1 = 1$	$\frac{h+n}{m} = 1$	$m+n$	Simple Uniform Hashing Assumption: Equally mapped to every bucket Worst case for search = $n$
Linked List w/ Resize	$\text{amor}(1)$	$E(1)$	$m+n$	Ideal: $m \rightarrow$ Double Table . $n < m/4 \rightarrow$ Half Table Increment $O(n^2)$ . Double $O(n)$ . Square $O(n^2)$
Open Addressing	$h + \frac{1}{1-a}$	where $a = \frac{n}{m}$ $a < 1$	$n$	Uniform Hashing Assumption: Equally mapped to every permutation Linear Probing - Clusters Double Hashing - $h(k,i) = f(k) + ig(k) \bmod m$ , $(m,g(k)) \rightarrow n^2$ permutations !UHA <b>Delete</b> sets node to tombstone value for <b>search</b>
Fingerprint Bloom	$k$	$k$		False positive. No false negative. <b>Delete</b> (Counter/Tombstone) $\rightarrow$ False negative FHT: $p = P(\text{False positive})$ . $p = 1 - e^{-(n/m)}$ . $n/m \leq \ln(1/1-p)$ BT: $p = (1 - e^{-(kn/m)})^k$ . $\text{opt}(k) = (m \cdot \ln 2)/n$

# Graphs & Trees

Adjacency List  $O(V+E)$  Adjacency Matrix  $O(V^2)$  Edge List  $O(E)$

SSSP	Runtime	Remarks
Bellman-Ford	$VE$	No negative cycles
Dijkstra	$E \log V$ (AVL) $E + V \log V$ (Fibo Heap)	No negative edge $V \times (\text{insert} + \text{deleteMin}) + E \times (\text{decreaseKey})$
Toposort	$V+E$	No directed cycles (Directed Acyclic Graph)
Relax	$E$	Post-order DFS or Kahn's(nodes w/o in-edges)
BFS	$V+E$ (Queue)	Same Weight
DFS	$V+E$ (Stack)	No cycle (Tree)
MED	$nm$	Toposort + Relax

MST	Runtime	Idea
Prim's	$E \log V$ $E(\text{known})$	Add min edge on cut
Kruskal's	$E \log V$ $aE(\text{known})$	Add min edge not in same tree Sort + ExUF = $E \log E + Ea(n)$
Boruvka's	$E \log V$	Every step: Add min edge for every node Search min out-edge = $V+E$ using B/DFS Update component ID = $V$
Rooted Directed	$E$	Add min incoming edge

MST Property

1. Max edge in **cycles** NOT in MST
2. Min edge in **cut** IS in MST

Steiner Tree ( $<2 \times \text{OPT}$ )

1. Run APSP & build new graph
2. Run MST and remove duplicate edges

Union-Find	Find	Union	Union-Find	Find	Union
Quick Find	1	$n$	Weighted Union	$\log n$	$\log n$
Quick Union	$n$	$n$	Weighted Union + Path Compression	$a(m,n)$	$a(m,n)$

## Dynamic Programming

DP	Runtime	Subproblem
LIS	$n^2$	$S[i] = \max(S[j]) + 1$ for all $j > 1$ and $S[j] > S[i]$ . Base: $S[n] = 0$
Lazy Prize	$kE$	$P[v,k] = \max(P[w,k-1]) + W(w,v)$ for all $w$ points to $v$ . Base: $P[v,0] = 0$
Vertex Cover	$V$	$S[v,0] = \sum S[w,1]$ , $w$ neighbour of $v$ $S[v,1] = 1 + \sum \min(S[w,0], S[w,1])$ Base: $S[\text{leaf},0] = 0$ $S[\text{leaf},1] = 1$
APSP	$V^3$	$S[v,w,n] = \min(S[v,w,n-1], S[v,n,n-1] + S[n,w,n-1])$ Base: $S[v,w,0] = W(v,w)$ $P[v,w,n] = P[v,w,n-1] \text{ OR } P[v,n,n-1] \text{ AND } P[n,w,n-1]$

APSP	Runtime	Method
Sparse +ve	$(V^2) \log V$	Dijkstra's
Unweighted	$VE$	BFS
All	$V^3$	Floyd-Warshall