

Kaggle Shopping Data Exploration

2026-02-01

Background About Data:

LINK: <https://www.kaggle.com/datasets/rabieelkharoua/predict-customer-purchase-behavior-dataset>

data from where, collected how? , year? , purpose?

Import Data

```
# Use here() to make it dynamic
raw_shopping <- read_csv(here("shopping", "data", "raw_data", "kaggle_shopping.csv"))
```

Rows: 1500 Columns: 9

-- Column specification -----

Delimiter: ","

dbl (9): Age, Gender, AnnualIncome, NumberOfPurchases, ProductCategory, Time...

i Use `spec()` to retrieve the full column specification for this data.

i Specify the column types or set `show_col_types = FALSE` to quiet this message.

```
raw_shopping
```

A tibble: 1,500 x 9

	Age	Gender	AnnualIncome	NumberOfPurchases	ProductCategory
	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	40	1	66120.	8	0
2	20	1	23580.	4	2
3	27	1	127821.	11	2

```

4    24    1    137799.    19    3
5    31    1    99301.    19    1
6    66    1    37758.    14    4
7    39    1    126883.    16    3
8    64    1    39707.    13    2
9    43    0    102797.    20    1
10   20    1    63855.    16    0
# i 1,490 more rows
# i 4 more variables: TimeSpentOnWebsite <dbl>, LoyaltyProgram <dbl>,
#   DiscountsAvailed <dbl>, PurchaseStatus <dbl>

```

Change Categorical Variables to Factors

```

shopping <- raw_shopping |>
  mutate(across(c(Gender, ProductCategory, LoyaltyProgram, PurchaseStatus), as.factor))
summary(shopping)

```

Age	Gender	AnnualIncome	NumberOfPurchases	ProductCategory
Min. :18.0	0:743	Min. : 20002	Min. : 0.00	0:289
1st Qu.:31.0	1:757	1st Qu.: 53029	1st Qu.: 5.00	1:331
Median :45.0		Median : 83700	Median :11.00	2:273
Mean :44.3		Mean : 84249	Mean :10.42	3:286
3rd Qu.:57.0		3rd Qu.:117168	3rd Qu.:15.00	4:321
Max. :70.0		Max. :149785	Max. :20.00	
TimeSpentOnWebsite LoyaltyProgram DiscountsAvailed PurchaseStatus				
Min. : 1.037	0:1010	Min. :0.000	0:852	
1st Qu.:16.157	1: 490	1st Qu.:1.000	1:648	
Median :30.940		Median :3.000		
Mean :30.469		Mean :2.555		
3rd Qu.:44.370		3rd Qu.:4.000		
Max. :59.991		Max. :5.000		

Notes:

- Age Range: [18, 70]
- Gender: almost 50/50; average 750 customers (no gender bias)
- Income: [\$20,002 , \$149,785]; average \$84,249 (slightly right skewed, higher earners high impact)

- NumPurchases: [0, 20]
- ProductCategory: average 300 (pretty balanced)
- TimeSpent: [1, 60]; average is 30 minutes (decent engagement)
- Loyalty: ~33% enrolled
- Discounts: [1,5]; average 3 (slightly left skewed, customers will little/no usage pull down average)
- PurchaseStatus: ~43% purchase


Histograms of the Continuous Variables

```
## Histogram of continuous variables
continuous_var <- c("Age", "AnnualIncome", "NumberOfPurchases", "TimeSpentOnWebsite", "Discount")


# set up a 2 x 3 grid to display all histograms together
par(mfrow = c(2, 3))

for (i in 1:length(continuous_var)) {
  current = shopping[[continuous_var[i]]] # get rows of that variable
  hist(current,
        xlab = continuous_var[i],
        main = paste("Histogram of", continuous_var[i]),
        col = "lightblue",
        freq = FALSE)
  lines(density(current, adjust = 2), col = "black", lwd = 2) # visualize shape of distribution
  # note: adjust > 1 will smooth out the line (adjust < 1 will hug the data more)
}

# reset back to default
par(mfrow = c(1, 1))
```



istogram of TimeSpentOnWebsite Histogram of DiscountsAva



Takeaway: The shopping data has a very even distribution for all variables. Since our data is very balanced, this can prevent bias and over-fitting of a particular dominant class.

Boxplots - Distribution of Variables based on Purchase Status


```
## Box plots
time <- ggplot(data = shopping, mapping = aes(x = PurchaseStatus, y = TimeSpentOnWebsite)) +
  geom_boxplot()

income <- ggplot(data = shopping, mapping = aes(x = PurchaseStatus, y = AnnualIncome)) +
  geom_boxplot()

age <- ggplot(data = shopping, mapping = aes(x = PurchaseStatus, y = Age)) +
  geom_boxplot()

discount <- ggplot(data = shopping, mapping = aes(x = PurchaseStatus, y = DiscountsAvailed))
  geom_boxplot()

# showcase all boxplots using gridExtra library
grid.arrange(time, income, age, discount, ncol = 2)
```



```
## Frequency tables
prop.table(table(shopping$LoyaltyProgram, shopping$PurchaseStatus))
```

	0	1
0	0.4546667	0.2186667
1	0.1133333	0.2133333

Gender on Purchase Status

```
gender_x_purchase <- shopping |>
  group_by(Gender) |>
  summarise(
    TotalPurchases = sum(NumberOfPurchases),
    AveragePurchases = mean(NumberOfPurchases),
    AverageTimeSpent = mean(TimeSpentOnWebsite),
    Purchase_Prob = sum(as.integer(PurchaseStatus))/n())
gender_x_purchase
```

```
# A tibble: 2 x 5
```

	Gender	TotalPurchases	AveragePurchases	AverageTimeSpent	Purchase_Prob
	<fct>	<dbl>	<dbl>	<dbl>	<dbl>
1	0	7736	10.4	30.2	1.43
2	1	7894	10.4	30.7	1.43

Checking Purchase Status with Number Of Purchases?


Question: If PurchaseStatus is 0, why is there a nonempty NumberOfPurchases category for those rows?

- NumberOfPurchases is historical, which PurchaseStatus is the most current.

```
# Scatter plot between time spent and number of purchases
summary <- shopping %>%
  group_by(PurchaseStatus, NumberOfPurchases) %>%
  summarize(mean_time = mean(TimeSpentOnWebsite))
```

`summarise()` has grouped output by 'PurchaseStatus'. You can override using the `.groups` argument.

```
ggplot(data = summary, mapping = aes(x = NumberOfPurchases, y = mean_time,
                                     fill = PurchaseStatus)) +
  geom_density(stat = 'identity', alpha = 0.5)
```



Notes: - It appears that the longer the mean time spent on a website, the greater the likelihood someone is to purchase something - Time spent on website seems to be relatively uniform across number of purchases

Age on Time Spent


```
shopping_with_age_group <- shopping %>%
  mutate(AgeGroup = case_when(
    between(Age, 18, 25) ~ "[18, 25]",
    between(Age, 26, 35) ~ "[26, 35]",
    between(Age, 36, 45) ~ "[36, 45]",
    between(Age, 46, 55) ~ "[46, 55]",
    between(Age, 56, 65) ~ "[56, 65]",
    between(Age, 66, 70) ~ "[66, 70]"
  ))

shopping_with_age_group$AgeGroup <- factor(shopping_with_age_group$AgeGroup,
                                           level = c("[18, 25]",
                                                       "[26, 35]",
                                                       "[36, 45]",
                                                       "[46, 55]",
                                                       "[56, 65]",
                                                       "[66, 70]"),
                                           ordered = TRUE)

summary <- shopping_with_age_group %>%
  group_by(PurchaseStatus, AgeGroup) %>%
  summarize(mean_time = mean(TimeSpentOnWebsite),
            n = n())
```

`summarise()` has grouped output by 'PurchaseStatus'. You can override using the `.groups` argument.

```
ggplot(data = summary, mapping = aes(x = AgeGroup, y = mean_time,
                                     fill = PurchaseStatus)) +
  geom_bar(stat = 'identity', position = 'dodge')
```



Age on PurchaseStatus

```
ggplot(data = summary, mapping = aes(x = AgeGroup, y = n,  
                                     fill = PurchaseStatus)) +  
  geom_bar(stat = 'identity', position = 'dodge')
```