

MODULE <i>XJupiterH</i>
EXTENDS <i>XJupiter</i> , <i>TLCUtils</i>
VARIABLE <i>list</i> $varsH \triangleq \langle vars, list \rangle$ $TypeOKH \triangleq TypeOK \wedge (list \subseteq List)$
$InitH \triangleq Init \wedge list = \{InitState\}$ $DoH(c) \triangleq Do(c) \wedge list' = list \cup \{state'[c]\}$ $RevH(c) \triangleq Rev(c) \wedge list' = list \cup \{state'[c]\}$ $SRevH \triangleq SRev \wedge list' = list \cup \{state'[Server]\}$
$NextH \triangleq$ $\quad \vee \exists c \in Client : DoH(c) \vee RevH(c)$ $\quad \vee SRevH$ $FairnessH \triangleq$ $\quad \wedge WF_{varsH}(SRevH \vee \exists c \in Client : RevH(c))$ $SpecH \triangleq InitH \wedge \Box[NextH]_{varsH} \wedge FairnessH$
$WLSpec \triangleq$ The weak list specification $Comm!EmptyChannel$ $\Rightarrow \forall l1, l2 \in list :$ $\quad \wedge Injective(l1)$ $\quad \wedge Injective(l2)$ $\quad \wedge Compatible(l1, l2)$
THEOREM $SpecH \Rightarrow \Box WLSpec$

\ * Modification History
 \ * Last modified *Wed Jan 30 21:39:16 CST 2019* by *hengxin*
 \ * Created *Wed Oct 10 15:40:13 CST 2018* by *hengxin*