Registration date: 20 February 2026

Follow-up Notes

Settings Plugin V06

Cegid Retail Y2 – Version 26

Make more possible

cegid

Preamble

This plugin is a set of web services associated with one or more versions of Cegid Retail Y2.
This document describes its scope of implementation, as well as the changes and corrections made.
Please note: All plugin methods and services can be cited in this document. Only public methods for which the contract is published can be used by applications not designed by Cegid.

Legal notices

Permission is granted under this Agreement to download documents held by Cegid and to use the information contained in the documents only internally, provided that: (a) the copyright notice on the documents remains on all copies of the document material; (b) these documents are used for personal and non-commercial purposes, unless it has been clearly defined by Cegid that certain specifications may be used for commercial purposes; (c) documents will not be copied to networked computers or published on any type of media unless expressly authorized by Cegid; and (d) no changes are made to these documents.

Contents

Preamble 2

1. OBJECTIVES 6

Documentation 6

Y2 versions 7

2. BUSINESSAREAS 8

CreateOrUpdate 8

GetDetail 8

GetListDetail 9

3. CIVILITIES 10

Create 10

Delete 10

GetDetail 10

GetListDetail 11

Update 11

4. COUNTRY 12

GetDetail 12

GetListDetail 12

5. CURRENCIES 13

GetDetail 13

GetListDetail 13

GetConversionRates 13

6. DOCUMENTUSERDEFINEDTABLES 15

GetListDetail 15

7. DOCUMENTUSERFIELDS 16

GetListDetail 16

GetDetail 16

8. INCOTERMS 18

CreateOrUpdate 18

Delete 18

GetDetail 19

GetListDetail 19

9. LEGALFORMS 20

Create 20
Delete 20
GetDetail 20
GetListDetail 21
Update 21
10. MARKDOWNREASONS 22
Create 22
Delete 23
GetDetail 23
GetListDetail 24
Update 24
11. MOVEMENTREASONS 25
Create 25
Delete 25
GetDetail 25
GetListDetail 26
Update 26
12. MOVEMENTREASONS2 28
Create 28
Delete 28
GetDetail 29
GetListDetail 29
Update 30
13. OFFICIALDOCUMENTTYPES 32
CreateOrUpdate 32
Delete 32
GetDetail 33
GetListDetail 33
14. OPENINGDRAWERREASONS 34
GetDetail 34
GetListDetail 34
15. PAYMENTMETHODS 36
GetDetail 36
GetListDetail 37
16. PERIODICITIES 38
Evaluate 38

GetDetail 38
GetListDetail 39
CreateOrUpdate 39
Delete 40
17. PRICELISTCATEGORIES 41
CreateOrUpdate 41
GetDetail 41
GetListDetail 42
18. ROUNDINGRULES 43
Evaluate 43
GetDetail 43
GetListDetail 44
19. SHIPPINGMETHODS 45
CreateOrUpdate 45
Delete 45
GetDetail 46
GetListDetail 46
20. ZIPCODES 48
GetListDetail 48
21. OTHER 49
Net Framework 4.8 49
Deployment 49

1. Objectives

The objective of the **Settings** plugin is to provide services relating to the management of settings common to several other plugins.
This service will be gradually enriched.

Reminder: Only public methods for which the contract is published can be used by applications not designed by Cegid. Cegid reserves the right to modify private services without ensuring backward compatibility, and without informing users.

Documentation

The service contract documentation is visible on the IIS server(s) from the software package download page:

"Documentation" is a link that provides access to the list of documentation:

➔ **Web Services**
The screen displayed provides access to the Web Services contracts and their properties
Please note: the absence of a contract in the Web Services documentation screen means that the service is not installed or is not public.

- **Exceptions**
  This part provides access to exceptions, classified by type, and according to the plugin.

- **Installation**
  This page allows you to download Web Services installation and consumption documentation.

Y2 versions

This plugin is compatible with the following version of Cegid Retail Y2:

- Version 26

Note:
The # sign at the beginning of the plugin build number corresponds to the major version of Cegid Retail Y2.

2. BUSINESSAREAS

CreateOrUpdate

➔ Objectives

This method is used either to new, or to modify a Business area in *Cegid Retail Y2*.
The following business rules are applied:

- ➔ The short description is mandatory.
- ➔ If there is an existing value it will be modified.
- ➔ The update does not take into account the translation, the wording must be in the original language of the folder. If the wording changes, the user will have to modify the translations.
- ➔ The creation and modification of a business area are traced in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	July 2022	A2345		125185		

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetDetail

➔ Objectives

This method is used to view the descriptions of a business area.
The following business rules are applied:

- ➔ The business area identifier in the query is mandatory.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	July 2022	A2345		124013	#3.110	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetListDetail

➔ Objectives

This method is used to view a business areas list.
The following business rules are applied:

- ➔ Business areas are returned in alphabetical order of their identifier.
- ➔ If the information is specified, the search is performed on the exact value transmitted. In case of unknown code, no answer is returned

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	July 2022	A2345		123499		

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

3. CIVILITIES

Civility titles are used to give customers their title as a mark of respect and courtesy:

- ➔ Mrs., Miss, Mr.
- ➔ Doctor, Professor, General, Sister
- ➔ HRN

They can be declined by country

- ➔ Sir, Lord, Lady

Create

➔ Objectives

The following business rules are applied:

- ➔ If the abbreviated title is not specified in the query, the first characters of the title are used.
- ➔ An error is returned if the title already exists.
- ➔ The restriction category of the title must exist and have the scope "Titles - Legal forms".
- ➔ The title restriction category must be part of the user's "Titles - Legal-forms" restrictions.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2146				

Delete

➔ Objectives

The following business rules are applied:

- ➔ The title identifier in the query is mandatory.
- ➔ No information is returned if the title does not exist.
- ➔ Title management complies to the restriction rules of the login user.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2146				

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The title identifier in the query is mandatory.

- Title management complies to the restriction rules of the login user.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2146				

GetListDetail

Objectives

The following business rules are applied:

- The titles are returned classified by restriction, then by rank, and in alphabetical order of their identifier.
- The user brings the filtering of the user restriction which is to be compared with the title restriction.
- Restrictions of type " ... " (no restriction) are returned in the contract with an empty string.
- The number of titles in a folder should not exceed 100 in the vast majority of cases. We do not implement a paging mechanism, but a 1,000 (thousand) limit on the number of records returned. A higher number of titles will be considered abnormal, without generating an exception.
  It is up to the caller receiving 1,000 records to detect that this is a partial reply, and that a more precise filter should be added.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2146				

Update

Objectives

The following business rules are applied:

- The title identifier in the query is mandatory. An error is returned if the title does not exist.
- Title management complies to the restriction rules of the login user.
- The restriction category of the title must exist and have the scope "Titles - Legal forms".
- The title restriction category must be part of the user's "Titles - Legal-forms" restrictions.
- An error is returned if the description, short form, restriction and rank are not filled in.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2146				

4. COUNTRY

Countries are available in Cegid Retail Y2, Back Office > Settings > General > Countries.
They include standardized identification information, and environment management.

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The Cegid Retail Y2 country identifier (Id) is mandatory in the query

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
JPM	Sept. 2021	A2205				

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.
- ➔ If the following information is filled in, the search is performed on the exact value transmitted. If the code is unknown, it is returned in the reply with empty:
  - Ids
  - ISO3AlphaNumCode
  - ISO2AlphaNumCode
  - ISO3NumCode

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
JPM	Sept. 2021	A2205				

➔ Improvements

5. CURRENCIES

Creating a currency allows you to specify information such as the currency, its symbol, its ISO codes, and the terminology used to write numbers in letters.

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The currency identifier in the query is mandatory. It is not possible to call this method with an ISO code because it is not unique in the database.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	June 2021	A2203				

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ If the "CountryId" information is filled in, the search is performed on the exact value transmitted. This information is not returned if the code is unknown.
- ➔ If *Closed* property is missing, all currencies matching the other criteria are returned.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	June 2021	A2203				

➔ Improvements

Search for currencies with a collection of alphanumerical ISO codes or with a collection of numerical ISO codes.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
NAC	12/6/2022			207190	#4.353	

GetConversionRates

➔ Objectives

A service operation that returns the exchange rates of a reference currency in one or more conversion currencies.

- ➔ A maximum of 10 conversion currencies is allowed.
- ➔ The Stock Exchange and rate type are mandatory and must be provided by the application using this service.
- ➔ A rate of 1 is systematically returned if the reference currency and the conversion currency are identical.

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ALE	1/27/2022	A2307		101881	#3:41 AM	

➔ Improvements

Slightly optimized control of currencies transmitted in the contract to limit the number of database queries.

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
HDA	6/10/2024			265825	#4.416	

6. DocumentUserDefinedTables

If the information available in the header of a document is not sufficient to characterize it completely, you can add additional information configured in Cegid Retail Y2, for each type of document in the form of user-defined tables.
The management of user-defined tables is configured for all document types in the User-defined tables tab.

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ An exception is returned in the case of a call with a non-existent ID of a document user-defined table.
- ➔ In the case of a user-defined table with the use of a subtable, the "values" section contains data from the table associated with the subtable.
- ➔ An empty collection is returned if no value is associated with the subtable.
- ➔ The values of the user-defined table are returned sorted by Id.
- ➔ The number of values in a user-defined table should not exceed a few hundred. We do not implement a paging mechanism but a limit of 1,000 (thousand) on the number of records returned to avoid any risk of server saturation.
  A higher number of user-defined table values will be considered as abnormal.
  In SOAP exposure, it is up to the caller receiving 1,000 records to detect that this is a partial reply, and that a more precise filter should be added.
  In RESTFULL exposure, an http 206 code "Partial Content" is returned if the list exceeds 1,000 elements.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2170				

7. DocumentUserFields

In addition to user-defined tables, Y2 offers the possibility to manage user fields to fill in additional information about documents.

GetListDetail

➔ Objectives

This service operation allows you to retrieve the settings of the document user fields defined in Y2.

The following business rules are applied:

- ➔ User fields and values are returned sorted by rank.
- ➔ An empty list is returned if the use of user fields is disabled in the folder.
- ➔ An empty list is returned if no field matches the criteria.
- ➔ The MinLength and MaxLength properties are only present in the reply for fields of type character strings.
- ➔ The DecimalNumber et IntegerPart properties are only present in the reply for numerical fields.
- ➔ The "SystemFields" and "Values" sections are present in the reply only if they have been requested in the Fields field.
- ➔ User restrictions are applied to document-type user fields.
- ➔ A paging mechanism is implemented for this method. If no information is entered, only the characteristics of the first 20 user fields are returned.
- ➔ Values In the case of a user field pointing to a subtable, the "Values" section contains the values of the subtable.

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
HDA	1/6/2025	A2507		340758	#5:16 AM	

➔ Improvements

The method is now set to the Beta status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

GetDetail

➔ Objectives

This service operation allows you to retrieve the settings of a particular document user field.

The following business rules are applied:

- ➔ An exception is raised if the user field identifier does not exist.
- ➔ An error is raised if the user field is not allowed.
- ➔ The rules of the GetListDetail method for returning and formatting characteristics are applied.

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
HDA	1/6/2025	A2507		340758	#5:16 AM	

➔ Improvements

The method is now set to the Beta status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

8. INCOTERMS

CreateOrUpdate

➔ Objectives

This method is used either to create, or to modify Incoterms in *Cegid Retail Y2*.
The following business rules are applied:

- ➔ The short description is mandatory.
- ➔ If there is an existing value it will be modified.
- ➔ The update does not take into account the translation, the wording must be in the original language of the folder. If the wording changes, the user will have to modify the translations.
- ➔ The creation and modification of Incoterms are traced in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	January 2023	A2390		148320	#4.80	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

Delete

➔ Objectives

The following business rules are applied:

- ➔ The Incoterm identifier in the query is mandatory.
- ➔ No information is returned if the Incoterm does not exist.
- ➔ The removal of Incoterms is recorded in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	January 2023	A2390		148055		

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetDetail

➔ Objectives

This method is used to view the descriptions of Incoterms.
The following business rules are applied:

- ➔ The Incoterm identifier in the query is mandatory.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	December 2022	A2390		144355	#4:58 AM	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetListDetail

➔ Objectives

This method is used to view a list of Incoterms.
The following business rules are applied:

- ➔ Incoterms are returned in alphabetical order of their identifier.
- ➔ If the information is specified, the search is performed on the exact value transmitted. In case of unknown code, no answer is returned

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	November 2022	A2390		138091		

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

9. LEGALFORMS

Legal forms are used to categorize companies and to prefix their names when creating postal addresses

- ➔ Examples for France: EI, EURL, SARL, SNC, SAS, SA, GIE, SCI, SCOP, SCIC, etc.

These terms are specific to each country.

- ➔ Examples for the UAE: Sole Proprietorship, Civil Company, Limited Liability Company, Partnership Company, Private Shareholding company, Public Shareholding company, etc.

Create

➔ Objectives

The following business rules are applied:

- ➔ If the abbreviated title is not specified in the query, the first characters of the title are used.
- ➔ An error is returned if the Legal form already exists.
- ➔ The restriction category of Legal form must exist and have the scope "Titles - Legal forms".
- ➔ The legal form restriction category must be part of the user's "Titles - Legal-forms" restrictions.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2147				

Delete

➔ Objectives

The following business rules are applied:

- ➔ The legal form identifier in the query is mandatory.
- ➔ No information is returned if the Legal form does not exist.
- ➔ Legal form management complies to the restriction rules of the login user.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2147				

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The legal form identifier in the query is mandatory.

- Legal form management complies to the restriction rules of the login user.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2147				

GetListDetail

Objectives

The following business rules are applied:

- The user brings the filtering of the user restriction which is to be compared with the legal form restriction.
- The Legal forms returned are sorted by restriction, then by rank, and in alphabetical order of their identifier.
- Restrictions of type " ... " (no restriction) are returned in the contract with an empty string.
- The number of legal forms in a folder should not exceed 100 in the vast majority of cases. We do not implement a paging mechanism, but a 1,000 (thousand) limit on the number of records returned. A higher number of legal forms will be considered abnormal, without generating an exception.
  It is up to the caller receiving 1,000 records to detect that this is a partial reply, and that a more precise filter should be added.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2147				

Update

Objectives

The following business rules are applied:

- The legal form identifier in the query is mandatory. An error is returned if the legal form does not exist.
- Legal form management complies to the restriction rules of the login user.
- The restriction category of Legal form must exist and have the scope "Titles - Legal forms".
- The legal form restriction category must be part of the user's "Titles - Legal-forms" restrictions.
- An error is returned if the description, short form, restriction and rank are not filled in.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	March 2021	A2147				

10. MARKDOWNREASONS

Markdown reasons allow you to justify a discount. They can be used by various functional modules in Cegid Retail Y2.
Examples:

- 10% off at checkout through a salesperson's action, "VIP customer" reason .
- 20% off of a group of items granted by a sales condition, "Promotion" reason.
- Preferential rate for an item, "Winter Sale" reason.

The discounts and their reasons are then analyzed by the retailer.
The creations, modifications and deletions of markdown reasons generate a record in the event log (depending on the access rights of the action follow-up.)

Create

➔ Objectives

The following business rules are applied:

- The code of the markdown reason must be alphanumerical (digits and/or letters in upper/lower case.)
- At least one markdown type is mandatory.
- Some markdown types are exclusive and cannot be combined with others:
  - Loyalty
  - Sales conditions
  - Allocations
  - Software extension
- Some markdown types can be combined with each other exclusively:
  - Line discount
  - Price list discount
  - Final selling price
- Each "group" of markdown types has its own constraints for the fields that can be filled in (and therefore used):

Configured fields	Loyalty	Sales cond.	Allocations	Ext. Soft.	Line discount	Price list discount	FSP discount
Rounding	No	No	No	No	Yes	No	No
Minimum %	No	No	No	No	Yes	No	No
Maximum %	No	No	No	No	Yes	No	No
Printable at register	No	No	No	No	Yes	No	No
Customer required	Yes	Yes	Yes	No	Yes	Yes	Yes
Operating period	No	No	No	No	Yes	No	Yes
Periodicity	No	No	No	No	Yes	No	Yes
Exclusion period	No	No	No	No	Yes	No	Yes
Store trigger	No	No	No	No	Yes	No	Yes

Item trigger	No	No	No	No	Yes	No	Yes

- ➔ For operating and exclusion periods:
  - The period must be consistent: start date less than or equal to end date.
  - If it is filled in, the exclusion period must be included in the operating period.
- ➔ The user provides the filtering through the user restriction.
- ➔ The restriction category used should include the "Markdown reasons" scope.
  Note: the above table may not reflect the current input behavior of older versions of Cegid Retail Y2.
- ➔ In the management of the 3 combinable types, the constraints of the most permissive are applied.
  Example: If "Line discount" and "Price list discount" are checked, then it is possible to include the trigger fields in the query (applicable in the case of "Line discount" and only in this case.) It is up to the caller using the plugin in read mode (GetDetail) to target the usable information according to the context.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
LDE	March 2021	A2074 - A2156				

Delete

➔ Objectives

The following business rules are applied:

- ➔ The code of the markdown reason (Id) is mandatory.
- ➔ The user provides the filtering through the user restrictions of GTR_GRPDEMARQUE.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
LDE	March 2021	A2074 - A2156				

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The user provides the filtering through the user restriction.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
LDE	March 2021	A2074				
NAC	March 2021	A2169				

➔ Improvements

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ The user provides the filtering through the user restriction.
- ➔ If the scope of use "Mark-down type" is not specified, no filter will be applied to the markdown type scope.
- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
LDE	March 2021	A2074				

Update

➔ Objectives

The business rules of the "Create" method are applied, with the following additions:

- ➔ The code of the markdown reason (Id) is mandatory.
- ➔ It is not possible to modify the markdown type when it is not combinable.
- ➔ Only combinable types allow you to add a new type:
  Example: It is possible to add "SalesPriceLists" to a reason that is already of type "SalesLines".

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
LDE	March 2021	A2074 - A2156				

11. MOVEMENTREASONS

Movement reasons are used to distinguish and justify some specific lines in documents.
Examples:

- ➔ Justification of an item return.
- ➔ Explanation of a special entry or withdrawal from stock.

Create

➔ Objectives

The following business rules are applied:

- ➔ The identifier, the description and the movement types of the movement reason are mandatory in the query.
- ➔ If the short description is not specified in the query, the first characters of the description are used.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2169				

Delete

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.
- ➔ No error is returned if the movement reason does not exist.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2169				

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2169				

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ If no movement type is entered in the query, no filter is applied to the movement type, otherwise the movement reasons selected are those with a list of authorized movement types with at least one of the requested types.
- ➔ If the description is given in the query, the movement reasons are selected if the label contains the description given in the query.
- ➔ An empty collection is returned if no movement reason matches the requested criteria or if no reason exists

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2169				

➔ Improvements

Update

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.
- ➔ If a field is present in the query, the corresponding data is modified with the value of the field given in the query.
- ➔ If a field is not present in the query, the corresponding data is not modified.
- ➔ The movement types of the movement reason are replaced with those that may be given in the query (cancel and replace if the property is present).
- ➔ At least one of the data (the description, the short description or the movement types) must be specified in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
NAC	March 2021	A2169				

➔ Improvements

Three types of use are managed:

- SpecialInputs: Special movements for inventory input (type I)
- SpecialOutputs: Special movements for inventory output (type J)
- Transfers: Transfers (type K).

The existing "InternalMovements" use is kept in the contracts to ensure
backward compatibility of the service and will later become deprecated. With the following operating:

GetDetail and GetListDetail methods:

- The "InternalMovements" use in a request returns the reasons of type i, J, and K.
- The "InternalMovements" use is added to the reply for each reason of type I, J, and K.

➔ Create/Update methods:

- If "InternalMovements" is present in the request, the reason contains types I, J, and K, regardless of the values specified in the request for the SpecialInputs, SpecialOutputs and Transfers types.
- If "InternalMovements" is not present in the request, the reason contains only the types specified in the request.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
AMO	4/26/2023	A2379		166125	#4.231	

12. MOVEMENTREASONS2

Movement reasons are used to distinguish and justify some specific lines in documents.
Examples:

- ➔ Justification of an item return.
- ➔ Explanation of a special entry or withdrawal from stock.

The MovementReason2 service allows the management of more movement types (usages) for list lookup, creation and modification compared to MovementReason.

Create

➔ Objectives

The following business rules are applied:

- ➔ The identifier, the description and the movement types of the movement reason are mandatory in the query.
- ➔ If the short description is not specified in the query, the first characters of the description are used.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
EPL	June 2023	A2379				

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

Delete

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.
- ➔ No error is returned if the movement reason does not exist.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
EPL	June 2023	A2379				

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
EPL	June 2023	A2379				

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ If no movement type is entered in the query, no filter is applied to the movement type, otherwise the movement reasons selected are those with a list of authorized movement types with at least one of the requested types.

- ➔ If the description is given in the query, the movement reasons are selected if the label contains the description given in the query.
- ➔ An empty collection is returned if no movement reason matches the requested criteria or if no reason exists

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
EPL	June 2023	A2379				

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

Update

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the movement reason is mandatory in the query.
- ➔ If a field is present in the query, the corresponding data is modified with the value of the field given in the query.
- ➔ If a field is not present in the query, the corresponding data is not modified.
- ➔ The movement types of the movement reason are replaced with those that may be given in the query (cancel and replace if the property is present).
- ➔ At least one of the data (the description, the short description or the movement types) must be specified in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
EPL	June 2023	A2379				

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl

ADU	2/4/2025	A2508		352727	#5:41 AM	

13. OFFICIALDOCUMENTTYPES

CreateOrUpdate

➔ Objectives

This method allows you to create or modify an official document type in Cegid Retail Y2

The following business rules are applied:

- ➔ The official document type identifier is mandatory (max. 3 characters)
- ➔ Description is mandatory.
- ➔ The short description is mandatory.
- ➔ If there is an existing value it will be modified.
- ➔ The creation and modification of an official document type are tracked in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
SBE	January 2026	2018661		446001	#5.169	

Delete

➔ Objectives

This method allows you to delete an official document type

The following business rules are applied:

- ➔ The official document type identifier in the query is mandatory.
- ➔ Deletion is **prohibited for the P (Passport) identifier**.
- ➔ Deletion is prohibited if the document type is **used in the MDOCOFFICIEL table**.
- ➔ Deletion is tracked in the **event log.**

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
SBE	January 2026	2018661		446001	#5.169	

GetDetail

➔ Objectives

This method allows you to view an official document type.

The following business rules are applied:

- ➔ The official document type identifier in the query is mandatory.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
ARA	January 2026	2018661		446001	#5.169	

GetListDetail

➔ Objectives

This method allows you to view a list of official document types.

The following business rules are applied:

- ➔ Official document types are returned sorted alphabetically by identifier.
- ➔ Searches can be performed by identifier and/or part of the description.
- ➔ Pagination is supported.
- ➔ When the list of details is empty, the service returns an HTTP **200 (OK)** response with an empty list, not an error.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
ARA	March 2023	2018661		446001	#5.169	

14. OPENINGDRAWERREASONS

The reasons for opening the drawer are set in the Back Office menu "Settings > Font Office"

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The opening reason identifier (Id)for the drawer in Cegid Retail Y2 is mandatory in the query.
- ➔ The search is performed on the exact value transmitted; if the code is unknown an exception will be raised.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
AMO	March 2023	A2425		157507	#4.176	

➔ Improvements

The method is now set to the Beta status

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
LDE	11/21/2023	A2478		203321	#4.342	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.
- ➔ Ids: Collection of drawer opening reason identifiers
  The search is performed on the exact value transmitted. If the code is unknown, it is returned in the reply with empty data:

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
AMO	March 2023	A2425		157507	#4.176	

➔ Improvements

The method is now set to the Beta status

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
LDE	11/21/2023	A2478		203321	#4.342	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

15. PAYMENTMETHODS

Payment methods are used to pay a sales transaction. They include many options depending on the location of the country of sale, and the rules given by the retailers.
Examples:

- ➔ Minimum amount of €1 required to use the "Bank Card" payment method.
- ➔ Maximum cash payment of €1,500 in Greece.
  Source: https://www.europe-consommateurs.eu/en/shopping-internet/cash-payment-limitations.html
- ➔ Maximum cash refund of €60 by merchants in case of payment by bank card in France.
  French government site: https://www.legifrance.gouv.fr/jorf/id/JORFTEXT000037852342
- ➔ Payment method management in the safe

Initially, only the payment methods available in the cash register are taken into account.
The data corresponding to the Characteristics, Front-Office and Cash float tabs are mainly managed by the services. The Addition tab corresponding to EFT is not taken into account, as EFT is managed separately.

GetDetail

➔ Objectives

The business rules of the *GetListDetail* method are applied, as well as:

- ➔ The identifier of the payment mode is mandatory in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
RLO	March 2021	A2149– A2202				

➔ Improvements

Addition of the "CreditRequestType" property in the detail section, which indicates the type of credit request sent to the electronic payment system for payment methods such as "Gift cards", "gift certificates", "Credit notes" and "Already paid deposits" managed by an electronic payment system.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl	Added
NAC	12/5/2023	1250083		PR 206765	#4.348		

PaymentSupplement section to the details section, which provides additional information about payment cards:
The following business rules are applied:

- ➔ PaymentSupplement is not returned unless it is included in the Fields field of the request and unless it is a payment method of the "credit card" or "payment instruments" category. If it is present, a "LIKE" will be performed.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
OEL	10/17/2025			PR 1972451	#5.115	

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ The user provides the filtering through the user restriction.
- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.
- ➔ Only the payment types that are available for the cash register are taken into account (checkbox "Usable at register" in the "Front Office" tab).
- ➔ The minimum cash amount, the maximum cash amount and the alert amount are only filled in, and therefore returned, for the cash payment method.
- ➔ Exceptions per store are taken into account if they exist for the store entered in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
RLO	March 2021	A2149– A2202				

➔ Improvements

Addition of the "CreditRequestType" property in the detail section, which indicates the type of credit request sent to the electronic payment system for payment methods such as "Gift cards", "gift certificates", "Credit notes" and "Already paid deposits" managed by an electronic payment system.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
NAC	12/5/2023	1250083		PR 206765	#4.348	

Added PaymentSupplement section to the details section, which provides additional information about payment cards:

The following business rules are applied:

- ➔ PaymentSupplement is not returned unless it is included in the Fields field of the request and unless it is a payment method of the "credit card" or "payment instruments" category. If it is present, a "LIKE" will be performed.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
OEL	10/17/2025			PR 1972451	#5.115	

16. PERIODICITIES

Periodicities are available in Y2, Back Office > Settings > General >Periodicities.
Generic periodicities are created and usable by different functional modules of Y2.

Example:

➔ Apply a specific sales condition on Fridays from 6 to 8 pm

Evaluate

➔ Objectives

Returns a list of valid periodicities in relation to a submission date (list limited to 1000 periodicities.)
The following business rules are applied:

- ➔ The periodicity is mandatory and must be filled in accurately.
- ➔ The date/time of submission is that of the client station.
- ➔ User restrictions will be applied.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
JMO	January 2023	A2415		150182	#4.103	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetDetail

➔ Objectives

Returns the periodicity settings(periodicity record)
The following business rules are applied:

- ➔ The identifier of the rounding method is mandatory in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
BGI	September 2022	A2073				

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetListDetail

➔ Objectives

Returns a list of periodicities based on defined criteria
The following business rules are applied:

- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
BGI	September 2022	A2073				

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

CreateOrUpdate

➔ Objectives

Is used to create or modify a periodicity.
The following business rules are applied:

- ➔ We work using the cancel and replace method. All periodicity information must therefore be systematically passed on.
- ➔ The periodicity type must have a unique value (weekly or monthly).
- ➔ For a weekly periodicity:
  - At least one day must be entered with a time slot other than the default.
  - Time slots between 00:00 and 23:59 must be consistent (start time < end time).
  - The day of validity within the month, between 1 and 31, must be consistent (start day < end day).
  - In the event of an existing value, the periodicity is modified.

- For monthly periodicity :
  - At least one month must be entered
  - The time slot, between 00:00 and 23:59, must be consistent (start time < end time).
- The creation and modification of a periodicity are reported to the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
BGI	March 2023	A2073				

Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

Default value assigned to properties absent from the periodicity query to be created.

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
NAC	7/18/2024	1423751		279910	#4.423	

Delete

Objectives

Is used to delete a periodicity.
The following business rules are applied:

- The periodicity identifier in the query is mandatory.
- A Boolean is returned confirming whether or not the periodicity has been deleted.
- The removal of a periodicity is reported to the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
BGI	March 2023	A2073				

Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

17. PRICELISTCATEGORIES

CreateOrUpdate

➔ Objectives

This method is used either to create, or to modify a price list category in *Cegid Retail Y2*.
The following business rules are applied:

- ➔ The short description is mandatory.
- ➔ If there is an existing value it will be modified.
- ➔ The update does not take into account the translation, the wording must be in the original language of the folder. If the wording changes, the user will have to modify the translations.
- ➔ The creation and modification of Incoterms are traced in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
RFO	Dec. 2022	A2344		142010	#4:47 AM	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetDetail

➔ Objectives

This method is used to view the descriptions of a price list category.
The following business rules are applied:

- ➔ The price list category identifier in the query is mandatory.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
RFO		A2344		123667	#3.100	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

GetListDetail

➔ Objectives

This method is used to view a list of price list categories
The following business rules are applied:

- ➔ The price list categories are returned in alphabetical order of their identifier.
- ➔ If the information is specified, the search is performed on the exact value transmitted. In case of unknown code, no answer is returned

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
RFO		A2344		123667	#3.100	

➔ Improvements

The method is now set to the Released status

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
LDE	7/12/2023	A2452		179177	#4.298	

18. ROUNDINGRULES

Rounding methods are available in Cegid Retail Y2, Back Office > Settings > Management > Rounding methods. They are used to round up or down an amount according to the 4 values described in the documentation: Threshold (positive or negative) / Weight / Method / Constant.

Please note: The weight of the rounding cannot exceed 2 decimals.

Examples:

Test value	Threshold	Weight	Method	Constant	Result
-12.75	0	0.10	Round down		-12.70
-12.75	0	0.10	Round up		-12.80
12.75	99	0.50	Round down	0.05	#12:45 PM
12.75	99	0.50	Adjust to closer value (0.5 = 0)	0.05	#12:45 PM
12.75	99	0.50	Adjust to closer value (0.5 = 1)	0.05	12.95
12.75	99	0.50	Round up	0.05	12.95
112.75	999	#1:00 AM	Round up	0.50	112.50
1112.75	999,999	#10:00 AM	Round up	#5:00 AM	1115.00

Evaluate

This method applies a rounding method to a transmitted amount.

➔ Objectives

The following business rules are applied:

- ➔ The transmitted amount can be negative, null, or positive, without constraint on the number of its decimals.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	July 2021	A2210				

➔ Improvements

GetDetail

➔ Objectives

The following business rules are applied:

- ➔ The identifier of the rounding method is mandatory in the query.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	July 2021	A2210				

GetListDetail

➔ Objectives

The following business rules are applied:

- ➔ The description is not mandatory; if there is one, a "LIKE" will be performed.

Dev	Date	CEGID's Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
OXY	July 2021	A2210				

19. SHIPPINGMETHODS

CreateOrUpdate

➔ Objectives

This method is used either to create, or to modify Shipping method in *Cegid Retail Y2*.
The following business rules are applied:

- ➔ The short description is mandatory.
- ➔ If there is an existing value it will be modified.
- ➔ The update does not take into account the translation, the wording must be in the original language of the folder. If the wording changes, the user will have to modify the translations.
- ➔ The creation and modification of the Shipping method are traced in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	April 2023	A2391		163941		

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

Delete

➔ Objectives

The following business rules are applied:

- ➔ The Shipping method identifier in the request is mandatory.
- ➔ A Boolean is returned attesting to the effective deletion or not of the shipping method
- ➔ The removal of a Shipping method is traced in the event log.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	March 2023	A2391		158989		

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

GetDetail

➔ Objectives

This method is used to view the descriptions of a Shipping method.
The following business rules are applied:

- ➔ The Shipping method identifier in the request is mandatory.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	March 2023	A2391		158703		

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

GetListDetail

➔ Objectives

This method is used to view a list of Shipping methods
The following business rules are applied:

- ➔ The Shipping methods are returned in alphabetical order of their identifier.

➔ If the information is specified, the search is performed on the exact value transmitted. In case of unknown code, no answer is returned

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EBU	March 2023	A2391		158200		

➔ Improvements

The method is now set to status Beta

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
RLO	9/19/2024	1565857		300491	#4.440	

The method is now set to status Released

Dev	Date	CEGID's Ref.	Pb Ref.	PR	Plugin Build no.	Quality Ctrl
ADU	2/4/2025	A2508		352727	#5:41 AM	

20. ZIPCODES

Zip codes are available for input in Cegid Retail Y2, Back Office > Settings > General> Zip codes.
Note: The uniqueness of a zip code is guaranteed by the "zip code" and the "city", making it possible to record several municipalities with the same zip code.
Example for France:

Zip code	Municipality
10400	Bouy sur Orvin
10400	St Aubin
10400	La Saulsotte
10400	Nogent sur Seine

Depending on the country, the zip code can be attached to a region or a district.

GetListDetail

Only the indexed fields of the table can be used for performance reasons.

➔ Objectives

The following business rules are applied:

- ➔ If the "CountryId" information is filled in, the search is performed on the exact value transmitted. If the code is unknown, it is returned in the reply with empty information.
- ➔ The city not mandatory; if there the city property is present, a “LIKE” will be performed.

Dev	Date	CEGID’s Ref.	Pb Ref.	SVN Rev.	Plugin Build no.	Quality Ctrl
BGI	Sept. 2021	A2208				

➔ Improvements

21. OTHER

Net Framework 4.8

Following Microsoft's announcement about the "end of support for .NET Framework 4.5.2, 4.6 and 4.6.1 as soon as April 26, 2022" the plugin now requires the installation of the .Net Framework 4.8 (runtime) on server components.

Deployment

Added installation kit for ReportService.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
EPL	9/22/2023	1239802		190647	#4.326	

Swagger

Rest/Restful APIs grouped by plugin, with the option of selecting them by plugin name.

Dev	Date	CEGID's Ref.	Pb Ref.	Pull request	Plugin Build no.	Quality Ctrl
ADU	1/15/2025	1543349		344737	#5:36 AM	