: 18.08.2014

Report Date

: BBV9342113HD Material Description : GATE, VLV, HWO, 4 1/16-5K/ 10K, INC Revision Level : 02:500000086739 MTO NO: : 5800; Aker Solutions, Batam Plant WORK ORDER NO: Base Unit of Measure : EA PR. NO: \_\_\_\_\_ : 64.0 LB Gross Weight Net Weight : 64.0 LB ISSUED BY: \_\_\_\_\_ DATE \_\_\_ Basic Material : See BoM for Materials Traceability code : TC2.1 PROPERTY OF PT. Aker Solutions Serial No. Profile : -DOCUMENT MUST BE RETURNED TO THE Q.A Batch Management ⊠ DEPT.IN BATAM PRIOR TO RECEIVING FINAL Shelf life: 0 Day PAYMENT QM Control Key Inspection Setup : 01:Goods receipt insp. for purchase order:Active Master Insp. Char. Classification Attributes Related Drawings : Type:CAD,No:10001174670,Ver:02,Status:Re-issued Constr,Descr:GATE, VALVE, HWO, AM10#, 4-1/16" 10K Other Related Docs : Type:PDC,No:10000024358,Ver:04,Status:Re-issued Constr,Descr:PS-126: STAMPING IDENTIFICATION ON PARTS Type:PDC,No:10000024361,Ver:00,Status:IFC ,Descr:QS-001:Assigning/Maintaining Traceabilit Type:PDC,No:10000096286,Ver:00,Status:IFC ,Descr:MS-368:Ni ALY, UNS N07718, Inconel 718 Type:PDC,No:10000096490,Ver:04,Status:Re-issued Constr,Descr:PS-108: Liquid Penetrant Inspection Type:PDC,No:10000096493,Ver:06,Status:Re-issued Constr,Descr: HARDNESS TESTING OF METALS,PS-113 Type:PDC.No:10000096575,Ver:00.Status:IFC ,Descr:C-114:Indoor Rust Protection for Misc. Type:PDC,No:10000096592,Ver:02,Status:Re-issued Constr,Descr:C-137 HARD FACE COATING Type:PDC,No:10000096609,Ver:01,Status:Re-issued Constr,Descr:C-159:Tungsten Carbide Hardface Type:PDC,No:10000097140,Ver:03,Status:Re-issued Constr,Descr:C-209 HARD FACE COATING Type:PDC,No:10000489707,Ver:02,Status:Re-issued Constr,Descr:CS-001 HVOF HARD FACE COATING Type:SWP,No:10001902737,Ver:00,Status:In Work ,Descr:GATE, VLV, HWO, 4 1/16-5K/ 10K, INC : GATE, AM05#/AM10# VLV, HWO, 4 1/16-5K/ 10K, 718 INC, HD FACED Basic Data Text PSL: 3 Temp: P-X Matl. Class: HH-360 PROCESS SPECIFICATION: 1 MS-368 MATERIAL REQUIREMENT 2 OS-001 UNIOUE TRACEABILITY 3 PS-113 CHECK HARDNESS AT LOCATION SHOWN ON DRAWING 4 PS-108 LIQUID PENETRANT INSPECTIONOF ALL ACCESSIBLE SURFACES AFTER FINAL HT AND MACHINING 5 C-137 AFTER MACHINING COAT FACES AS SHOWN ON DRAWING CS-001 ALTERNATE FACES COAT C-159 ALTERNATE FACES COAT C-209 ALTERNATE FACES COAT 6 - - - LAP BOTH FACES AS SHOWN ON DRAWING 7 PS-126 STAMP AT LOCATION SHOWN ON DRAWING: AS BBV9342113HD

PT. Aker Solutions

MATERIAL REPORT

8 C-114 COAT

#### Characteristics:

\_\_\_\_\_

BoM :

JOH

Item No.	Material Number	Description	Quantity	UoM	Assembly
0010	BBCU05111402636803	CU 5.125 H X 11.500 W X 2.750 LG MS-368	1.000	EA	

# PT. Aker Solutions

ISSUED BY: \_\_\_\_\_ DATE \_\_\_\_

PROPERTY OF PT. Aker Solutions
DOCUMENT MUST BE RETURNED TO THE Q.A
DEPT.IN BATAM PRIOR TO RECEIVING FINAL
PAYMENT


## PT. Aker Solutions

MTO NO: -WORK ORDER NO: \_\_


PR. NO: \_

ISSUED BY: \_\_\_\_\_ DATE

PROPERTY OF PT. Aker Solutions DOCUMENT MUST BE RETURNED TO THE Q.A DEPT.IN BATAM PRIOR TO RECEIVING FINAL PAYMENT



### SECTION A-A



2. MINIMUM COATING THICKNESS ARE .003" PER SIDE

1. WAVINESS OF SURFACE NOT TO EXCEED 6 HELIUM LIGHT BANDS

Ur	less otherwise specified dir	Design file no. SDV10006	Proprietar		
General Machining dimensional tolerances	Dimensional tolerances	mm	inch	SDV10006	proprietary a legally privili or entity to v unauthorise for limited p stored elect documents, parties with relevant Ake is subject to confidentiali treated according.
	BREAK SHARP CORNERS FILLET RADII CONCENTRICITY SQUARENESS PARALLELISM	0.25 .075±0.13 0.25 FIM 0.25 IN 250 0.25 IN 250	.010 .030±0.003 .010 FIM .010 IN 10*	Layout no. 10001154843	
	FRACTIONS	X.XXX±0.25 X.X±0.8 X.±1.5 3.2 µm	± 1/16 X.XXX ±.010 X.XX ±.03 X.X±.06	Similar to 10000171098	
	ANGLE ± 0.50 DEG RFS EXCEPT WHEN (M) MODIFIED		<u>250</u> μin	Manual no.	upon reques use for whice

etary Information
current contains Axer Subsea legal entity
yand confidential Information that is
yand confidential Information that is
year confidential Information that is
year contained to the properties
to which it is addressed and any
that is addressed and any
that is addressed and any
that is addressed and information to the reproducted.
The properties are that in the properties
which the poly within consent of the
other than the poly within consent of the
other than the properties and the properties
which it is a polytomer to the properties
which it is a proposition of the properties
which it was provided.

GATE, VALVE, HWO, AM10™, 4-1/16" 5K &10K. WITH HARDFACE COATING Originator Scale RAHMADI,MEYLAN ADRIAN NURHIDAYAT 1 · 1 Material / Legacy no. V93421-1 Plant 5800 SUHANDA, SUHANDA

SEE ENGINEERING DATA SHEET

AGUSTINUS, AGUSTINUS

**Aker**Solutions Doc. ver ECO no. Document no. 10001174670 500000086739 02 leason for Issue

28-MAY-13 RE-ISSUED FOR CONSTR Size Sheet no A1 1 OF 1  $\bigoplus$ 

#### MATERIAL REPORT

Report Date : 18.08.2014

Material : BBCU05111402636803

Description : CU 5.125 H X 11.500 W X 2.750 LG MS-368

Revision Level

Plant : 5800; Aker Solutions, Batam

Base Unit of Measure : EA Gross Weight : KG Net Weight : KG Basic Material :

Traceability code

Serial No. Profile : —

Batch Management ⊠
Shelf life : 0 Day

QM Control Key : Z00

Inspection Setup : 01;Goods receipt insp. for purchase order;Active

Master Insp. Char. : 0010;5800WC31;5800;QM01

0010;BA2100AA;Identification Marking 0020;BA2100AB;Damage Inspection 0030;BA2100AD;Documentation Correct

Classification :

Attributes :

Related Drawings : Other Related Docs :

Basic Data Text : Cube 5.125 HEIGHT X 11.500 WIDTH X 2.750 LG MS-368

### Characteristics:

BoM : No related BoM exist.

## PT. Aker Solutions

MTO NO:	
WORK ORDER NO: _	
PR. NO:	
ISSUED BY:	_ DATE

PROPERTY OF PT. Aker Solutions
DOCUMENT MUST BE RETURNED TO THE Q.A
DEPT.IN BATAM PRIOR TO RECEIVING FINAL
PAYMENT