

# Classical Mechanics Tutorial II

## Engineering Physics

Indian Institute of Information Technology, Allahabad

# Constraints

**Holonomic constraints** – They can be expressed as an equation connecting the coordinates of the particles.

**Non-holonomic constraints** – Constraints which are not expressible in the form of an equation.

Before moving on, recall that constraints can also be **rheonomous** (explicit time dependence) or **scleronomous** (not explicitly dependent of on time)

## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$

## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$  This a scleronomous holonomic constraint.
- ▶ Constraints which are not expressible in the form of an equation. Consider a particle moving on the surface of the sphere, the constraint becomes  $r^2 - a^2 \geq 0$ .

## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$  This a scleronomous holonomic constraint.
- ▶ Constraints which are not expressible in the form of an equation. Consider a particle moving on the surface of the sphere, the constraint becomes  $r^2 - a^2 \geq 0$ . This is a scleronomous non-holonomic constraint
- ▶ Consider a simple pendulum. The length of string connect the point of support and the bob is fixed. The constraint is scleronomous (holonomic). But what happens if the the point of support begins to move in the horizontal direction? The constraint is now

## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$  This a scleronomous holonomic constraint.
- ▶ Constraints which are not expressible in the form of an equation. Consider a particle moving on the surface of the sphere, the constraint becomes  $r^2 - a^2 \geq 0$ . This is a scleronomous non-holonomic constraint
- ▶ Consider a simple pendulum. The length of string connect the point of support and the bob is fixed. The constraint is scleronomous (holonomic). But what happens if the the point of support begins to move in the horizontal direction? The constraint is now holonomic but rheonomous
- ▶ Consider a gas stored inside a (spherical) container. The gas molecules are constrained to remain inside the container  $\implies |r_i| \leq R$ .

## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$  This a scleronomous holonomic constraint.
- ▶ Constraints which are not expressible in the form of an equation. Consider a particle moving on the surface of the sphere, the constraint becomes  $r^2 - a^2 \geq 0$ . This is a scleronomous non-holonomic constraint
- ▶ Consider a simple pendulum. The length of string connect the point of support and the bob is fixed. The constraint is scleronomous (holonomic). But what happens if the the point of support begins to move in the horizontal direction? The constraint is now holonomic but rheonomous
- ▶ Consider a gas stored inside a (spherical) container. The gas molecules are constrained to remain inside the container  $\implies |r_i| \leq R$ . This is a non-holonomic constrain which is also scleronomous. But let us now suppose that the container can expand. Then the constraint becomes  $|r_i(t)| \leq R(t)$ . So the constraints are now


## Example of constraints

- ▶ In a rigid body, the distance between any two particles remain constant and is a constraint, like, in a dumbbell consisting of two masses, the distance between the masses is fixed  $\implies r_1 - r_2 = \text{const.}$  This a scleronomous holonomic constraint.
- ▶ Constraints which are not expressible in the form of an equation. Consider a particle moving on the surface of the sphere, the constraint becomes  $r^2 - a^2 \geq 0$ . This is a scleronomous non-holonomic constraint
- ▶ Consider a simple pendulum. The length of string connect the point of support and the bob is fixed. The constraint is scleronomous (holonomic). But what happens if the the point of support begins to move in the horizontal direction? The constraint is now holonomic but rheonomous
- ▶ Consider a gas stored inside a (spherical) container. The gas molecules are constrained to remain inside the container  $\implies |r_i| \leq R$ . This is a non-holonomic constrain which is also scleronomous. But let us now suppose that the container can expand. Then the constraint becomes  $|r_i(t)| \leq R(t)$ . So the constraints are now non-holonomic but rheonomous.




## Another example of a non-holonomic constraint

Consider a disc of radius  $R$  rolling (without slipping) on a horizontal plane  $x - y$  plane constrained to move so that the plane of the disc is always vertical. To describe the motion of the disc, we use the following coordinates:  $x, y$  coordinates of the center of the disc, the angle  $\theta$  between the axis of the disc and the  $x$  axis, and the angle of rotation  $\phi$  about the axis of the disc.



## Another example of a non-holonomic constraint



Since the disc remains vertical, the axis of rotation is perpendicular to the  $z$  axis. This tells us that the velocity of the center of the disc has a magnitude  $|v| = R\dot{\phi}$  and its direction is perpendicular to the axis of rotation  $\Rightarrow \dot{x} = v \sin \theta$  and  $\dot{y} = -v \cos \theta$  which implies

$$dx - R \sin \theta d\phi = 0 \text{ and } dy + R \cos \theta d\phi = 0 \quad (1)$$

These constraints are not of the form  $f(x, y, \theta, \phi) = 0$  and are hence non-holonomic. Actually neither of the equations can be integrated without solving the problem first, that is, we cannot first find the integrating factor  $f(x, y, \theta, \phi) = 0$  that will convert them into exact differentials.

## Writing Down a Lagrangian

Consider a hydrogen atom consisting of a proton orbited by an electron at a fixed radius such that the electron is constrained to move on the surface of a sphere about the nucleus. What is the Lagrangian of this system?

## Writing Down a Lagrangian


Consider a hydrogen atom consisting of a proton orbited by an electron at a fixed radius such that the electron is constrained to move on the surface of a sphere about the nucleus. What is the Lagrangian of this system?

- ▶ We will be using spherical polar coordinates  $(r, \theta, \phi)$  to describe this system.

## Writing Down a Lagrangian


Consider a hydrogen atom consisting of a proton orbited by an electron at a fixed radius such that the electron is constrained to move on the surface of a sphere about the nucleus. What is the Lagrangian of this system?

- ▶ We will be using spherical polar coordinates  $(r, \theta, \phi)$  to describe this system.
- ▶ The constraint is the fixed radius  $r = l$ , where  $l$  is an arbitrary constant indicating the fixed length.



© 2013 Encyclopædia Britannica, Inc.

# Spherical Polar Coordinates



## Writing Down a Lagrangian

We shall first obtain the expression of the kinetic energy  $T$  in spherical polar coordinates and then simply subtract the potential energy  $V$  from the kinetic energy to write down the Lagrangian.

Since we are using  $(r, \theta, \phi)$  coordinates, we have the relations

## Writing Down a Lagrangian

We shall first obtain the expression of the kinetic energy  $T$  in spherical polar coordinates and then simply subtract the potential energy  $V$  from the kinetic energy to write down the Lagrangian.

Since we are using  $(r, \theta, \phi)$  coordinates, we have the relations

$$x = l \sin \theta \cos \phi \quad (2)$$

$$y = l \sin \theta \sin \phi \quad (3)$$

$$z = l \cos \theta \quad (4)$$

where  $r = l$  from the constraint equation. The expression for kinetic energy  $T$  is simply given by

$$T = \frac{1}{2}m(\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \quad (5)$$

We can now calculate the derivatives



## Writing Down a Lagrangian

We shall first obtain the expression of the kinetic energy  $T$  in spherical polar coordinates and then simply subtract the potential energy  $V$  from the kinetic energy to write down the Lagrangian.

Since we are using  $(r, \theta, \phi)$  coordinates, we have the relations

$$x = l \sin \theta \cos \phi \quad (2)$$

$$y = l \sin \theta \sin \phi \quad (3)$$

$$z = l \cos \theta \quad (4)$$

where  $r = l$  from the constraint equation. The expression for kinetic energy  $T$  is simply given by

$$T = \frac{1}{2}m(\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \quad (5)$$

We can now calculate the derivatives

$$\dot{x} = l(\cos \theta \cos \phi \dot{\theta} + \sin \theta (-\sin \phi) \dot{\phi}) \quad (6)$$

$$\dot{y} = l(\cos \theta \sin \phi \dot{\theta} + \sin \theta (+\cos \phi) \dot{\phi}) \text{ and } \dot{z} = -l \sin \theta \dot{\theta} \quad (7)$$

So using these equations

$$\dot{x} = l(\cos \theta \cos \phi \dot{\theta} + \sin \theta (-\sin \phi) \dot{\phi}) \quad (8)$$

$$\dot{y} = l(\cos \theta \sin \phi \dot{\theta} + \sin \theta (+\cos \phi) \dot{\phi}) \quad (9)$$

$$\dot{z} = -l \sin \theta \dot{\theta} \quad (10)$$

in

$$T = \frac{1}{2} m (\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \quad (11)$$

gives us

So using these equations

$$\dot{x} = l(\cos \theta \cos \phi \dot{\theta} + \sin \theta (-\sin \phi) \dot{\phi}) \quad (8)$$

$$\dot{y} = l(\cos \theta \sin \phi \dot{\theta} + \sin \theta (+\cos \phi) \dot{\phi}) \quad (9)$$

$$\dot{z} = -l \sin \theta \dot{\theta} \quad (10)$$

in

$$T = \frac{1}{2} m (\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \quad (11)$$

gives us

$$T = \frac{1}{2} m l^2 (\dot{\theta}^2 + \sin^2 \theta \dot{\phi}^2) \quad (12)$$

We can now write the potential energy term as  $V = V(\theta, \phi)$  and obtain the final Lagrangian  $L = T - V$ , that is,

So using these equations

$$\dot{x} = l(\cos \theta \cos \phi \dot{\theta} + \sin \theta (-\sin \phi) \dot{\phi}) \quad (8)$$

$$\dot{y} = l(\cos \theta \sin \phi \dot{\theta} + \sin \theta (+\cos \phi) \dot{\phi}) \quad (9)$$

$$\dot{z} = -l \sin \theta \dot{\theta} \quad (10)$$

in

$$T = \frac{1}{2} m (\dot{x}^2 + \dot{y}^2 + \dot{z}^2) \quad (11)$$

gives us

$$T = \frac{1}{2} m l^2 (\dot{\theta}^2 + \sin^2 \theta \dot{\phi}^2) \quad (12)$$


We can now write the potential energy term as  $V = V(\theta, \phi)$  and obtain the final Lagrangian  $L = T - V$ , that is,

$$L = \frac{1}{2} m l^2 (\dot{\theta}^2 + \sin^2 \theta \dot{\phi}^2) - V(\theta, \phi) \quad (13)$$

## Finding out the Equations of Motion


Let us consider a different problem: A particle of mass  $m$  is constrained to move on the inside surface of a smooth cone of half angle  $\alpha$ . The particle is subject to a gravitational force. First determine a set of generalized coordinates and the constraints, and then find Lagrange's equations of motions.

Let us look at the figure:




# Finding out the Equations of Motion

By looking at the figure,



# Finding out the Equations of Motion


By looking at the figure,



- We can see that using cylindrical polar coordinates  $(r, \theta, z)$  will make the problem easier to solve.

# Finding out the Equations of Motion

By looking at the figure,



- ▶ We can see that using cylindrical polar coordinates  $(r, \theta, z)$  will make the problem easier to solve.
- ▶ The constraint is the fixed radius  $z = r \cot \alpha$ , where we can see that  $r$  is the "height" and  $z$  is the "base" of the triangle formed by cutting the cone vertically. So  $r/z = \tan \alpha$



# Finding out the Equations of Motion

Now, coordinate transformation equations are

## Finding out the Equations of Motion

Now, coordinate transformation equations are

$$x = r \cos \theta \quad (14)$$

$$y = r \sin \theta \quad (15)$$

$$z = z \quad (16)$$

with the constraint  $z = r \cot \alpha$  We can obtain the expression of kinetic energy  $T$  as before and get

## Finding out the Equations of Motion

Now, coordinate transformation equations are

$$x = r \cos \theta \quad (14)$$

$$y = r \sin \theta \quad (15)$$

$$z = z \quad (16)$$

with the constraint  $z = r \cot \alpha$  We can obtain the expression of kinetic energy  $T$  as before and get  $T = 1/2m(\dot{r}^2 + r^2\dot{\theta}^2 + \dot{z}^2)$ , and using the constraint we get,

## Finding out the Equations of Motion

Now, coordinate transformation equations are

$$x = r \cos \theta \quad (14)$$

$$y = r \sin \theta \quad (15)$$

$$z = z \quad (16)$$

with the constraint  $z = r \cot \alpha$  We can obtain the expression of kinetic energy  $T$  as before and get  $T = 1/2 m(\dot{r}^2 + r^2 \dot{\theta}^2 + \dot{z}^2)$ , and using the constraint we get,

$$T = \frac{1}{2} m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) \quad (17)$$

Finally for the potential energy  $V$ , if we choose  $V = 0$  at  $z = 0$  then

## Finding out the Equations of Motion

Now, coordinate transformation equations are

$$x = r \cos \theta \quad (14)$$

$$y = r \sin \theta \quad (15)$$

$$z = z \quad (16)$$

with the constraint  $z = r \cot \alpha$  We can obtain the expression of kinetic energy  $T$  as before and get  $T = 1/2 m(\dot{r}^2 + r^2 \dot{\theta}^2 + \dot{z}^2)$ , and using the constraint we get,

$$T = \frac{1}{2} m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) \quad (17)$$

Finally for the potential energy  $V$ , if we choose  $V = 0$  at  $z = 0$  then

$$V = mgz = mgr \cot \alpha \quad (18)$$

## Finding out the Equations of Motion

So we now have,

$$T = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2)$$

and,

$$V = mgz = mgr \cot \alpha$$

So the Lagrangian can be written as  $L = T - U$

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha \quad (19)$$

## Finding out the Equations of Motion

So we now have,

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha$$

and Lagrange's equations of motions are given by

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}} \right) - \left( \frac{\partial L}{\partial q} \right) = 0 \quad (20)$$

where  $q = r, \theta$ .

## Finding out the Equations of Motion

So we now have,

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha$$

and Lagrange's equations of motions are given by

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}} \right) - \left( \frac{\partial L}{\partial q} \right) = 0 \quad (20)$$

where  $q = r, \theta$ . We note first that since  $L$  does not explicitly contain  $\theta$ . So  $\partial L / \partial \theta = 0$  and the Lagrange's equation for  $q = \theta$

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\theta}} \right) = 0 \implies \frac{\partial L}{\partial \dot{\theta}} = mr^2 \dot{\theta} = \text{const} \quad (21)$$



## Finding out the Equations of Motion

So we now have,

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha$$

and Lagrange's equations of motions are given by

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}} \right) - \left( \frac{\partial L}{\partial q} \right) = 0 \quad (20)$$

where  $q = r, \theta$ . We note first that since  $L$  does not explicitly contain  $\theta$ . So  $\partial L / \partial \theta = 0$  and the Lagrange's equation for  $q = \theta$

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\theta}} \right) = 0 \implies \frac{\partial L}{\partial \dot{\theta}} = mr^2 \dot{\theta} = \text{const} \quad (21)$$

$\theta$  is a cyclic coordinate in this Lagrangian.

## Finding out the Equations of Motion

So we now have,

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha$$
$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\theta}} \right) = 0 \implies \frac{\partial L}{\partial \dot{\theta}} = mr^2 \dot{\theta} = \text{const} \quad (22)$$

But  $mr^2 \dot{\theta} = mr^2 \omega$  is just the angular momentum about  $z$  – axis. This equation simply gives us the conservation of angular momentum. Similarly, we can calculate Lagrange's equation for the  $r$  coordinate

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{r}} \right) - \left( \frac{\partial L}{\partial r} \right) = 0 \quad (23)$$

Computing the derivatives, we get

## Finding out the Equations of Motion

So we now have,

$$L = \frac{1}{2}m(\dot{r}^2 \csc^2 \alpha + r^2 \dot{\theta}^2) - mgr \cot \alpha$$
$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{\theta}} \right) = 0 \implies \frac{\partial L}{\partial \dot{\theta}} = mr^2 \dot{\theta} = \text{const} \quad (22)$$

But  $mr^2 \dot{\theta} = mr^2 \omega$  is just the angular momentum about  $z$  – axis. This equation simply gives us the conservation of angular momentum. Similarly, we can calculate Lagrange's equation for the  $r$  coordinate

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{r}} \right) - \left( \frac{\partial L}{\partial r} \right) = 0 \quad (23)$$

Computing the derivatives, we get

$$\ddot{r} - r\dot{\theta}^2 \sin^2 \alpha + g \sin \alpha \cos \alpha = 0 \quad (24)$$

## Lagrange's equation of motion for dissipative systems

The Lagrange equation for a system with dissipation is given by


$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}_j} \right) - \frac{\partial L}{\partial q_j} + \frac{\partial \mathcal{F}}{\partial \dot{q}_j} = 0. \quad (25)$$

Here  $\mathcal{F}$  is a scalar function known as Rayleigh's dissipation function and must be specified along with  $L$  to obtain the equations of motion.

One of the advantages of the Lagrangian formulation is that it can be easily extended to systems that are not studied in classical mechanics such as electrical circuits!

## An example of a dissipative system: LCR circuits

We consider a physical system which has a "key" in series with an inductance  $L$ , A capacitance  $C$  and a resistance  $R$ . We first charge the capacitor and then close the key. The capacitor will now begin to discharge. What is equation that captures this situation?



## An example of a dissipative system: LCR circuits

We choose the electric charge  $q$  as our dynamical variable (generalised coordinate).

The inductor will give rise to a kinetic energy term since the energy stored in an inductor contains current  $I$ , the time derivative of  $q$ . The inductance  $L$  is the electrical analogue of mass. So  $= \frac{1}{2} L \dot{q}^2$ .

The capacitor gives us the potential energy. The capacitance term  $1/C$  is analogous to the spring constant  $k$ . So  $U = \frac{1}{2} \frac{q^2}{C}$

## An example of a dissipative system: LCR circuits

If we now introduce a dissipation function

$$\mathcal{F} = \frac{1}{2} R \dot{q}_j^2 \quad (26)$$

We can use

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}_j} \right) - \frac{\partial L}{\partial q_j} + \frac{\partial \mathcal{F}}{\partial \dot{q}_j} = 0. \quad (27)$$

with

$$L = \frac{1}{2} L \dot{q}^2 - \frac{1}{2} \frac{q^2}{C} \quad (28)$$

to get

## An example of a dissipative system: LCR circuits

If we now introduce a dissipation function

$$\mathcal{F} = \frac{1}{2} R \dot{q}_j^2 \quad (26)$$

We can use

$$\frac{d}{dt} \left( \frac{\partial L}{\partial \dot{q}_j} \right) - \frac{\partial L}{\partial q_j} + \frac{\partial \mathcal{F}}{\partial \dot{q}_j} = 0. \quad (27)$$

with

$$L = \frac{1}{2} L \dot{q}^2 - \frac{1}{2} \frac{q^2}{C} \quad (28)$$

to get

$$L \frac{d^2 q}{dt^2} + R \frac{dq}{dt} + \frac{q}{C} = 0 \quad (29)$$

This is exactly what we would get from Kirchhoff's law!



# Taylor Series

Taylor's theorem provides a way of expressing a function as a power series in  $x$ , known as a Taylor series.

It can be applied only to those functions that are continuous and differentiable within the  $x$ -range of interest.

To express  $f(x)$  as a power series in  $x - a$  about the point  $x = a$ . We shall assume that, in a given  $x$ -range,  $f(x)$  is a continuous, single-valued function of  $x$  having continuous derivatives. Then

$$f(x) = f(a) + (x - a)f'(a) + \frac{(x - a)^2}{2!}f''(a) + \cdots + \frac{(x - a)^n}{n!}f^{(n)}(a) + \cdots$$

alternatively setting  $x = a + h$ ,

$$f(a + h) = f(a) + hf'(a) + \frac{h^2}{2!}f''(a) + \cdots + \frac{h^n}{n!}f^{(n)}(a) + \cdots$$

Example:  $\sin(x) = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \cdots = \sum_{n=0}^{\infty} (-1)^n \frac{x^{(2n+1)}}{(2n+1)!}.$

**Taylor Series: More than one variable:** The Taylor series work the same way for functions of two variables. (There are just more of each derivative!) For an analytic function  $f(x, y, z)$ ,

$$f(x, y) \approx f(a, b) + f_x(a, b)(x - a) + f_y(a, b)(y - b) + \frac{f_{xx}(a, b)}{2} (x - a)^2 + f_{xy}(a, b)(x - a)(y - b) + \frac{f_{yy}(a, b)}{2} (y - b)^2 + \cdots \quad (30)$$

Or, with  $x = a + \delta x$  and  $y = b + \delta y$

$$f(a + \delta x, b + \delta y) \approx f(a, b) + f_x(a, b)\delta x + f_y(a, b)\delta y + \frac{f_{xx}(a, b)}{2} (\delta x)^2 + f_{xy}(a, b)\delta x\delta y + \frac{f_{yy}(a, b)}{2} (\delta y)^2 + \cdots \quad (31)$$