≡ File Edit Search Run Compile Debug Project Options

[■] INORDER.C

```
#include<stdio.h>
#include<conio.h>
#include<alloc.h>

struct node {
int empid;
struct node *left;
struct node * right;
};

struct node* createnode(int id){
struct node*temp;
temp = (struct node*) malloc (sizeof(struct node));
temp ->empid= id;
temp ->left= NULL;
temp ->right= NULL;
return temp;
}
struct node* insert(struct node* root, int id) {
if(root==NULL){
return createnode(id);
```

13:71

File Edit Search Run Compile Debug Project Options Wi

INORDER.C

```
}
if (id < root -> empid) {
root->left=insert(root->left,id);
}
else if(id>root->empid)
{
root->right= insert(root->right,id);
}
return root;
}
void inorder(struct node* root) {
if (root!=NULL) {
inorder(root->left);
printf("%d", root->empid);
inorder(root->right);
}
}
void main() {
struct node*root=NULL;
clrscr();
printf("the nodes are: 105,102,110,101,108\n");
```

22:71

≡ File Edit Search Run Compile Debug Project Options

[■] INORDER.C

```
clrscr();
printf("the nodes are: 105,102,110,101,108\n");
root = insert(root,105);
root = insert(root,102);
root = insert(root,110);
root = insert(root,101);
root = insert(root,108);
printf("the answer of inorder is:\n");
inorder(root);

getch();
}
```

41:71


the nodes are: 105,102,110,101,108
the answer of inorder is:
101102105108110