main.c

Run

```c
#include <stdio.h>
#define MAX 5

int stack[MAX];
int top = -1;

void push(int val) {
    if (top == MAX - 1) {
        printf("Stack Overflow\n");
    } else {
        stack[++top] = val;
        printf("Pushed: %d\n", val);
    }
}

void pop() {
    if (top == -1) {
        printf("Stack Underflow\n");
    } else {
        printf("Popped (Undo): %d\n", stack[top--]);
    }
}

void display() {
```

Output

```
--- Stack Implementation ---
Pushed: 10
Pushed: 20
Pushed: 30
Stack elements: 10 20 30
Popped (Undo): 30
Stack elements: 10 20


=== Code Execution Successful ===
```

main.c

Run ▶

```c
void display() {
    if (top == -1) {
        printf("Stack is empty\n");
        return;
    }
    printf("Stack elements: ");
    for (int i = 0; i <= top; i++) {
        printf("%d ", stack[i]);
    }
    printf("\n");
}

int main() {
    printf("--- Stack Implementation ---\n");
    push(10);
    push(20);
    push(30);
    display();

    pop();
    display();

    return 0;
}
```

Output

```
--- Stack Implementation ---
Pushed: 10
Pushed: 20
Pushed: 30
Stack elements: 10 20 30
Popped (Undo): 30
Stack elements: 10 20


=== Code Execution Successful ===
```