FEWT

SET-1:

1. What is NPM primarily used for in a React project?

1 Marks

- Writing JSX code

Managing project dependencies and scripts

Rendering components to the DOM

Styling components with CSS

2. What is the purpose of `ReactDOM.render()`?

1 Marks

- To define a React component

To update the state of a component

To render a React element into the DOM in the supplied container

To manage server-side routing

3. Can web browsers directly understand JSX?

1 Marks

- Yes, all modern browsers support JSX natively.

No, JSX needs to be transpiled into regular JavaScript.

Only Chrome browser can understand JSX directly.

Yes, with a special plugin.

4. After setting up a new React project with `npx create-react-app@latest my-app`, what is the next typical step to run the application locally?

1 Marks

- Open `index.html` directly in the browser.

Navigate into the `my-app` directory and run `npm start`.

Run `npm build` to compile the project.

Execute `node app.js` from the root directory.

5. Consider the following JavaScript code snippet: const a = [5,3,4]; const b = a.map((temp)=>temp*2); What is the initial value of the array `a`?

1 Marks

- **[5, 3, 4]**

[10, 6, 8]

[5, 3, 4, 2]

undefined

6. What is the primary purpose of the `import React from 'react';` statement in a React application?

1 Marks

- **To import the core React library for building user interfaces.**

To import a specific component named 'React'.

To define the styling for React components.

To manage the state of server-side data.

7. To display 'Hello World' in an HTML `div` with `id="root"`, what is the correct React code snippet?

1 Marks

- ReactDOM.render(Hello World , document.body);

React.render('Hello World', document.getElementById('root'));

ReactDOM.render(<h1>Hello World</h1>, document.getElementById('root'));

document.getElementById('root').innerHTML = 'Hello World';

8. Which React method is primarily used to render a React element into the actual DOM?

1 Marks

- React.renderElement()

ReactDOM.mount()

ReactDOM.render()

React.updateDOM()

9. Which operator is commonly used for conditional rendering when you want to render something or nothing at all?

1 Marks

- Logical OR (||)

Logical AND (&&)

Ternary operator (? :)

Nullish coalescing (??)

10. Which command is used to update all dependencies listed in `package.json` to their latest compatible versions?

1 Marks

- **npm update**

npm refresh

npm upgrade

npm install --force

11. Which of the following is NOT a benefit of using ReactJS?

1 Marks

- Component-based architecture

Improved performance with Virtual DOM

Steep learning curve compared to other libraries

Strong community support

12. In const name = "darshan university - rajkot";, what keyword is used to declare a constant variable?

1 Marks

- let

var

const

name

13. What is a React Component?

1 Marks

- A global variable that stores application data.

A JavaScript function or class that returns React elements.

A special type of HTML tag.

A styling declaration for the user interface.

14. What file in a React project typically lists all installed packages and their exact versions, ensuring consistent installations across environments?

1 Marks

- package.json

index.js

webpack.config.js

package-lock.json

15. In the mounting and updating phases, what does the `getDerivedStateFromProps()` method typically return?

1 Marks

- The updated JSX to render.

An object to update the component's state, or null to indicate no state change.

A boolean value indicating whether the component should update.

A snapshot value that componentDidUpdate() can use.

16. After running 'npm install', where are the installed packages stored locally in a React project?

1 Marks

- **node_modules folder**

src folder

public folder

dist folder

17. Which command is used to install a new React project using Create React App?

1 Marks

- npm run build

npm create-react-app my-app

npx create-react-app@latest my-app

npm start my-app

18. Which JavaScript operator is often used for inline conditional rendering in JSX, especially for rendering a component or element only if a condition is true?

1 Marks

- The ternary operator (condition ? true : false)

The OR operator (||)

The logical AND operator (&&)

The NULLish coalescing operator (??)

19. You have a button and want to execute a function `handleClick` when it's clicked. How do you bind this event handler in JSX?

1 Marks

- <button onclick="handleClick()">Click Me</button>

<button onClick={handleClick}>Click Me</button>

<button on-click="handleClick">Click Me</button>

<button event:click="handleClick">Click Me</button>

20. What is the purpose of the logical && operator in conditional rendering?

1 Marks

- To render both components if both conditions are true.

To render the second component only if the first condition is true.

To render the first component only if the second condition is false.

To always render the second component regardless of the condition.

21. Which of the following code snippets correctly defines a basic React class component named 'Welcome'?

1 Marks

- **class Welcome extends React.Component { render() { return <h1>Hello, World!</h1>; } }**

function Welcome() { return <h1>Hello, World!</h1>; }

const Welcome = () => <h1>Hello, World!</h1>;

class Welcome { render() { return <h1>Hello, World!</h1>; } }

22. What does NPM stand for in the context of React development?

1 Marks

- New Project Module

Node Package Manager

Native Program Maker

Network Protocol Module

23. If you have a React component <App /> and a DOM element in your HTML with id="root", how would you render the component into that element?

1 Marks

- React.attachComponent(<App />, 'root')

document.getElementById('root').appendChild(<App />)

ReactDOM.render(<App />, document.getElementById('root'))

ReactDOM.mount(<App />, '#root')

24. In a class component, which lifecycle method is called immediately after a component is mounted (inserted into the tree)?

1 Marks

- componentWillMount()

render()

componentDidMount()

componentDidUpdate()

25. What is ReactJS primarily used for?

1 Marks

- Backend API development

Database management

Building user interfaces (UI)

Operating system development

26. What is the significance of the `root.render()` method in React 18?

1 Marks

- It only renders class components.

It allows for concurrent features and improved performance.

It only works with server-side rendering.

It is deprecated and should not be used.

27. The `react-dom/client` module, as seen in `import ReactDOM from 'react-dom/client';`, is primarily used for which rendering environment?

1 Marks

- Server-side rendering (SSR)

Desktop application rendering

Client-side browser rendering

Mobile application rendering

28. Can a child component directly modify its props?

1 Marks

- Yes, props are mutable and can be changed by the child.

No, props are read-only and cannot be directly modified by the child component.

Yes, but only if the prop is a number.

Only if the parent component explicitly allows it.

29. Given the following React component: function Welcome(){ const names = ["Darshan University","BCA","BSCIT"]; const nameElements = names.map((n)=><h1>Welcome from { n }</h1>); return(nameElements); } What will this `Welcome` component render when it is used in a React application?

1 Marks

- **An array containing three <h1> elements: "Welcome from Darshan University", "Welcome from BCA", and "Welcome from BSCIT".**

A single <h1> element with the text "Welcome from Darshan University".

An error, because map cannot directly return JSX elements.

A string array ["Darshan University", "BCA", "BSCIT"].

30. Consider the following React component snippet: function Greeting({ isLoggedIn }) { return ({isLoggedIn ? (<h1>Welcome back!</h1>) : (Please log in.)}); } If the `Greeting` component is rendered with `isLoggedIn` set to `false`, what output will be rendered on the screen?

1 Marks

- An <h1> element containing the text "Welcome back!"

A element containing the text "Please log in."

Both an <h1> element and a element will be rendered simultaneously.

Nothing will be rendered due to a syntax error in the conditional logic.

SET-2:

1. How can you render nothing from a React component?

1 Marks

- By returning an empty string `""`

By returning `null` or `false`

By throwing an error

By returning an empty object `{}`

2. Which operator is commonly used for conditional rendering when you want to render something or nothing at all?

1 Marks

- Logical OR (||)

Logical AND (&&)

Ternary operator (? :)

Nullish coalescing (??)

3. In React, what does an 'element' primarily represent in the context of rendering?

1 Marks

- A physical DOM node in the browser.

A plain JavaScript object describing what should appear on the screen.

A React component class or function.

A data structure representing the application's state.

4. When rendering elements, what does React use to efficiently update the UI?

1 Marks

- Direct DOM manipulation

Virtual DOM

Shadow DOM

Real DOM diffing

5. Which array method is commonly used in React to transform an array of data into a list of JSX elements?

1 Marks

- reduce()

filter()

map()

forEach()

6. How do you pass data from a parent component to a child component in React?

1 Marks

- Using state directly in the child component

Using props

Using local storage

Using global variables

7. What is the significance of the `root.render()` method in React 18?

1 Marks

- It only renders class components.

It allows for concurrent features and improved performance.

It only works with server-side rendering.

It is deprecated and should not be used.

8. If you have a React component <App /> and a DOM element in your HTML with id="root", how would you render the component into that element?

1 Marks

- React.attachComponent(<App />, 'root')

document.getElementById('root').appendChild(<App />)

ReactDOM.render(<App />, document.getElementById('root'))

ReactDOM.mount(<App />, '#root')

9. In the mounting and updating phases, what does the `getDerivedStateFromProps()` method typically return?

1 Marks

- The updated JSX to render.

An object to update the component's state, or null to indicate no state change.

A boolean value indicating whether the component should update.

A snapshot value that componentDidUpdate() can use.

10. What does SPA stand for in the context of web development, a concept frequently associated with ReactJS?

1 Marks

- Server Page Architecture

Single Page Application

System Performance Analyzer

Secure Protocol Access

11. Which file in a React project, managed by NPM, lists all the project dependencies?

1 Marks

- index.html

app.js

package.json

webpack.config.js

12. In JSX, how do you specify a CSS class for an element?

1 Marks

- Using the 'class' attribute

Using the 'className' attribute

Using the 'cssClass' attribute

Using the 'styleClass' attribute

13. In React, `props` are _____.

1 Marks

- Mutable and can be changed by the child component

Immutable and passed down from parent to child

Global variables accessible anywhere

Used for managing internal component data

14. Which command is used to update all dependencies listed in `package.json` to their latest compatible versions?

1 Marks

- **npm update**

npm refresh

npm upgrade

npm install --force

15. Which of the following describes the 'Unmounting' phase in a React component's lifecycle?

1 Marks

- When the component is first created and inserted into the DOM.

When the component is updated due to changes in props or state.

When the component is removed from the DOM.

When the component's state is initialized.

16. What file in a React project typically lists all installed packages and their exact versions, ensuring consistent installations across environments?

1 Marks

- package.json

index.js

webpack.config.js

package-lock.json

17. To optimize performance and prevent unnecessary re-renders of a component when its props or state haven't significantly changed, which lifecycle method would you implement to control this behavior?

1 Marks

- componentDidUpdate()

render()

shouldComponentUpdate()

getSnapshotBeforeUpdate()

18. What is a React Component?

1 Marks

- A global variable that stores application data.

A JavaScript function or class that returns React elements.

A special type of HTML tag.

A styling declaration for the user interface.

19. Given in index.html, which code snippet correctly renders an <h1> element?

1 Marks

- ReactDOM.render(<h1>Hello</h1>, document.getElementById('root'));

const root = ReactDOM.createRoot(document.getElementById('root'));
root.render(<h1>Hello</h1>);

document.getElementById('root').innerHTML = '<h1>Hello</h1>';

React.display(<h1>Hello</h1>, 'root');

20. Which of the following JSX expressions correctly embeds a JavaScript variable `name`?

1 Marks

- **<h1>Hello, {name}</h1>**

<h1>Hello, name</h1>

<h1>Hello, $name</h1>

<h1>Hello, $(name)</h1>

21. The `react-dom/client` module, as seen in `import ReactDOM from 'react-dom/client';`, is primarily used for which rendering environment?

1 Marks

- Server-side rendering (SSR)

Desktop application rendering

Client-side browser rendering

Mobile application rendering

22. Which of the following JSX expressions is valid?

1 Marks

- Hello

** Hello **

Hello

Hello

23. What is JSX in React?

1 Marks

- A JavaScript framework

A syntax extension for JavaScript that looks like HTML

A new programming language

A database query language

24. How can you conditionally render components in React?

1 Marks

- **Using `if` statements or ternary operators within JSX**

By defining separate HTML files for each condition

By directly manipulating the `display` CSS property

Conditional rendering is not supported in React

25. Consider the following React component snippet: function Greeting({ isLoggedIn }) { return ({isLoggedIn ? (<h1>Welcome back!</h1>) : (Please log in.)}); } If the `Greeting` component is rendered with `isLoggedIn` set to `false`, what output will be rendered on the screen?

1 Marks

- An <h1> element containing the text "Welcome back!"

A element containing the text "Please log in."

Both an <h1> element and a element will be rendered simultaneously.

Nothing will be rendered due to a syntax error in the conditional logic.

26. Given the following event handler in a React component: const handleClick = (param) => { console.log(param); }; How would you pass the string "Hello" as param when a button is clicked?

1 Marks

- <button onClick={handleClick("Hello")}>Click</button>

<button onClick={() => handleClick("Hello")}>Click</button>

<button onClick={handleClick, "Hello"}>Click</button>

<button onClick={handleClick("Hello")()}>Click</button>

27. What would be the output in the DOM if you try to render `<div>Hello {null} World</div>` using `ReactDOM.render()`?

1 Marks

- Hello null World

Hello World

It would throw a JavaScript error.

Hello {null} World

28. Which of the following is NOT a valid way to define a React component?

1 Marks

- Function component

Class component

HTML component

Arrow function component

29. What are the two main types of components in React?

1 Marks

- Static and Dynamic

Class and Function

Parent and Child

Stateful and Stateless

30. Consider the following functional component: function Welcome(props) { return <h1>Hello, {props.name}</h1>; } How would you render this component with the name 'Darshan'?

1 Marks

- **<Welcome name="Darshan" />**

<Welcome>Darshan</Welcome>

Welcome({ name: 'Darshan' });

<Welcome > props.name = 'Darshan' </Welcome>

SET-3:

1. What does a React component's `render()` method typically return?

1 Marks

- A string of HTML

A JavaScript object representing the component's state

A React element (e.g., JSX)

A Promise

2. Consider the following JavaScript code snippet: const a = [5,3,4]; const b = a.map((temp)=>temp*2); What will be the first element of array `b` after the code execution?

1 Marks

- 5

10

3

4

3. What is the correct way to pass an argument to an event handler in React?

1 Marks

- <button onClick={this.handleClick(arg)}>Click</button>

<button onClick={() => this.handleClick(arg)}>Click</button>

<button onClick={this.handleClick, arg}>Click</button>

<button onclick={this.handleClick.bind(this, arg)}>Click</button>

4. How do you access props inside a React class component's render() method?

1 Marks

- props.value

this.props.value

state.props.value

value

5. Can a child component directly modify its props?

1 Marks

- Yes, props are mutable and can be changed by the child.

No, props are read-only and cannot be directly modified by the child component.

Yes, but only if the prop is a number.

Only if the parent component explicitly allows it.

6. You have a button and want to execute a function `handleClick` when it's clicked. How do you bind this event handler in JSX?

1 Marks

- <button onclick="handleClick()">Click Me</button>

<button onClick={handleClick}>Click Me</button>

<button on-click="handleClick">Click Me</button>

<button event:click="handleClick">Click Me</button>

7. What is the significance of the `root.render()` method in React 18?

1 Marks

- It only renders class components.

It allows for concurrent features and improved performance.

It only works with server-side rendering.

It is deprecated and should not be used.

8. Given in index.html, which code snippet correctly renders an <h1> element?

1 Marks

- ReactDOM.render(<h1>Hello</h1>, document.getElementById('root'));

const root = ReactDOM.createRoot(document.getElementById('root'));
root.render(<h1>Hello</h1>);

document.getElementById('root').innerHTML = '<h1>Hello</h1>';

React.display(<h1>Hello</h1>, 'root');

9. What is the primary reason for using JSX in React applications?

1 Marks

- To replace JavaScript entirely

To define database schemas

To write HTML-like code within JavaScript

To improve server performance

10. How are event handlers generally named in React for HTML elements?

1 Marks

- Lowercase, e.g., 'onclick'

CamelCase, e.g., 'onClick'

Snake_case, e.g., 'on_click'

Uppercase, e.g., 'ONCLICK'

**11. What is the output of the following JSX code? Hello {'React' + ' World'} **

1 Marks

- Hello {React + World}

Hello React World

Error: Invalid syntax

Hello ReactWord

12. What does NPM stand for in the context of React development?

1 Marks

- New Project Module

Node Package Manager

Native Program Maker

Network Protocol Module

13. What is the purpose of `ReactDOM.render()`?

1 Marks

- To define a React component

To update the state of a component

To render a React element into the DOM in the supplied container

To manage server-side routing

14. In React, `props` are _____.

1 Marks

- Mutable and can be changed by the child component

Immutable and passed down from parent to child

Global variables accessible anywhere

Used for managing internal component data

15. In the mounting and updating phases, what does the `getDerivedStateFromProps()` method typically return?

1 Marks

- The updated JSX to render.

An object to update the component's state, or null to indicate no state change.

A boolean value indicating whether the component should update.

A snapshot value that componentDidUpdate() can use.

16. Given the following React component: function Welcome(){ const names = ["Darshan University","BCA","BSCIT"]; const nameElements = names.map((n)=><h1>Welcome from { n }</h1>); return(nameElements); } What will this `Welcome` component render when it is used in a React application?

1 Marks

- **An array containing three <h1> elements: "Welcome from Darshan University", "Welcome from BCA", and "Welcome from BSCIT".**

A single <h1> element with the text "Welcome from Darshan University".

An error, because map cannot directly return JSX elements.

A string array ["Darshan University", "BCA", "BSCIT"].

17. Which command is used to install a new React project using Create React App?

1 Marks

- npm run build

npm create-react-app my-app

npx create-react-app@latest my-app

npm start my-app

18. What is the correct file extension for a React component written with JSX?

1 Marks

- .js

.jsx

.react

Both .js and .jsx are commonly used

19. Based on the line `import Welcome from './Welcome';`, what is the primary purpose of the `import` keyword in a modern JavaScript/React application?

1 Marks

- To define a new variable in the current scope.

To bring exported members (like `Welcome`) from another module into the current file's scope.

To execute a script file immediately upon compilation.

To declare a global function available everywhere.

20. What does SPA stand for in the context of web development, a concept frequently associated with ReactJS?

1 Marks

- Server Page Architecture

Single Page Application

System Performance Analyzer

Secure Protocol Access

21. What are React components primarily used for?

1 Marks

- Managing databases

Building reusable UI pieces

Handling HTTP requests

Styling applications with CSS

22. Can web browsers directly understand JSX?

1 Marks

- Yes, all modern browsers support JSX natively.

No, JSX needs to be transpiled into regular JavaScript.

Only Chrome browser can understand JSX directly.

Yes, with a special plugin.

23. Given the following event handler in a React component: const handleClick = (param) => { console.log(param); }; How would you pass the string "Hello" as param when a button is clicked?

1 Marks

- <button onClick={handleClick("Hello")}>Click</button>

<button onClick={() => handleClick("Hello")}>Click</button>

<button onClick={handleClick, "Hello"}>Click</button>

<button onClick={handleClick("Hello")()}>Click</button>

24. Which of the following is a valid JSX expression that renders "Hello React!" inside an <h2> tag, similar to how <h1>Hello world from React</h1> is rendered in the example?

1 Marks

- <h2>{"Hello React!"}</h2>

<h2>Hello React!</h2>

<h2>{Hello React!}</h2>

<h2>`Hello React!`</h2>

25. Given a class component 'Bca' that receives a prop named 'userName', how would you correctly display the value of 'userName' in its render method?

1 Marks

- {userName}

{props.userName}

{this.props.userName}

this.state.userName

26. In React, what does an 'element' primarily represent in the context of rendering?

1 Marks

- A physical DOM node in the browser.

A plain JavaScript object describing what should appear on the screen.

A React component class or function.

A data structure representing the application's state.

27. Which of the following describes 'props' in React?

1 Marks

- Internal data managed by a component

Arguments passed to React components

Lifecycle methods of a component

A tool for debugging React applications

28. Which of the following is a key feature of ReactJS?

1 Marks

- Full-stack framework

Uses a Virtual DOM

Primarily for mobile app development only

Requires server-side rendering exclusively

29. Which of these is NOT a phase in the React component lifecycle?

1 Marks

- Mounting

Updating

Rendering

Unmounting

30. How do you pass data from a parent component to a child component in React?

1 Marks

- Using state directly in the child component

Using props

Using local storage

Using global variables

SET-4:

1. Given in index.html, which code snippet correctly renders an <h1> element?

1 Marks

- ReactDOM.render(<h1>Hello</h1>, document.getElementById('root'));

const root = ReactDOM.createRoot(document.getElementById('root'));
root.render(<h1>Hello</h1>);

document.getElementById('root').innerHTML = '<h1>Hello</h1>';

React.display(<h1>Hello</h1>, 'root');

2. Consider the following JavaScript code snippet: const a = [1,2,3]; const b = a.map((temp)=>temp*2); What is the complete resulting array `b` after the execution of the code?

1 Marks

- [1, 2, 3]

[10, 3, 4]

[2, 4, 6]

undefined

3. Consider the following JSX: {isLoggedIn && <WelcomeMessage />}. What will happen if `isLoggedIn` is `false`?

1 Marks

- An error will be thrown.

<WelcomeMessage /> will still render.

Nothing will be rendered for <WelcomeMessage />.

The component will display 'false'.

4. Which library provides the `createRoot` method, often used to mount a React application into the DOM?

1 Marks

- React

ReactDOM

NPM

JSX

5. What are the two main types of components in React?

1 Marks

- Static and Dynamic

Class and Function

Parent and Child

Stateful and Stateless

6. Which command is used to install a new React project using Create React App?

1 Marks

- npm run build

npm create-react-app my-app

npx create-react-app@latest my-app

npm start my-app

7. Which React library is primarily responsible for rendering React components to the web browser's DOM?

1 Marks

- React Router

React Native

ReactDOM

Redux

8. If `Welcome` is imported using `import Welcome from './Welcome';`, what kind of export must `Welcome.js` have?

1 Marks

- A named export with the name `Welcome`.

A default export.

Multiple named exports.

A namespace export.

9. ReactJS allows developers to break down the UI into small, reusable pieces. What are these pieces called?

1 Marks

- Modules

Components

Fragments

Elements

10. Which of the following describes the 'Unmounting' phase in a React component's lifecycle?

1 Marks

- When the component is first created and inserted into the DOM.

When the component is updated due to changes in props or state.

When the component is removed from the DOM.

When the component's state is initialized.

11. In React, `props` are _____.

1 Marks

- Mutable and can be changed by the child component

Immutable and passed down from parent to child

Global variables accessible anywhere

Used for managing internal component data

12. The `react-dom/client` module, as seen in `import ReactDOM from 'react-dom/client';`, is primarily used for which rendering environment?

1 Marks

- Server-side rendering (SSR)

Desktop application rendering

Client-side browser rendering

Mobile application rendering

13. Which operator is commonly used for conditional rendering when you want to render something or nothing at all?

1 Marks

- Logical OR (||)

Logical AND (&&)

Ternary operator (? :)

Nullish coalescing (??)

14. What is the primary reason for using JSX in React applications?

1 Marks

- To replace JavaScript entirely

To define database schemas

To write HTML-like code within JavaScript

To improve server performance

15. What does NPM stand for in the context of React development?

1 Marks

- New Project Module

Node Package Manager

Native Program Maker

Network Protocol Module

16. Which of these is NOT a phase in the React component lifecycle?

1 Marks

- Mounting

Updating

Rendering

Unmounting

17. You have a button and want to execute a function `handleClick` when it's clicked. How do you bind this event handler in JSX?

1 Marks

- <button onclick="handleClick()">Click Me</button>

<button onClick={handleClick}>Click Me</button>

<button on-click="handleClick">Click Me</button>

<button event:click="handleClick">Click Me</button>

18. Which of the following is NOT a benefit of using ReactJS?

1 Marks

- Component-based architecture

Improved performance with Virtual DOM

Steep learning curve compared to other libraries

Strong community support

19. What is the correct file extension for a React component written with JSX?

1 Marks

- .js

.jsx

.react

Both .js and .jsx are commonly used

20. Which command is typically used to install all dependencies listed in `package.json` for a React project?

1 Marks

- npm start

npm run build

npm init

npm install

21. Which React method is primarily used to render a React element into the actual DOM?

1 Marks

- React.renderElement()

ReactDOM.mount()

ReactDOM.render()

React.updateDOM()

22. What is the output of the following JavaScript array map() method: [10, 20, 30].map(num => num + 5)?

1 Marks

- [10, 20, 30, 5]

[15, 25, 35]

[10, 20, 30]

Undefined

23. What would be the output in the DOM if you try to render `<div>Hello {null} World</div>` using `ReactDOM.render()`?

1 Marks

- Hello null World

Hello World

It would throw a JavaScript error.

Hello {null} World

24. After setting up a new React project with `npx create-react-app@latest my-app`, what is the next typical step to run the application locally?

1 Marks

- Open `index.html` directly in the browser.

Navigate into the `my-app` directory and run `npm start`.

Run `npm build` to compile the project.

Execute `node app.js` from the root directory.

25. Which of the following is NOT a valid way to define a React component?

1 Marks

- Function component

Class component

HTML component

Arrow function component

26. In a scenario where you need to read information from the DOM (e.g., scroll position) *before* it potentially changes due to an update, which lifecycle method provides access to the DOM state before the update is committed?

1 Marks

- componentDidMount()

componentDidUpdate()

getSnapshotBeforeUpdate()

render()

27. Which method is commonly used for conditional rendering in JSX when you want to render either one thing or another?

1 Marks

- For loops

If/else statements outside JSX and then render the result

The `switch` statement

The `while` loop

28. In React, what does an 'element' primarily represent in the context of rendering?

1 Marks

- A physical DOM node in the browser.

A plain JavaScript object describing what should appear on the screen.

A React component class or function.

A data structure representing the application's state.

29. Consider the following React functional component: function Welcome(props) { return <h1>Hello, {props.name}!</h1>; } How would you render this component to display 'Hello, Students!'?

1 Marks

- **<Welcome name="Students" />**

<Welcome >Students</Greet>

<Welcome value="Students" />

<Welcome id="Students" />

30. In the mounting and updating phases, what does the `getDerivedStateFromProps()` method typically return?

1 Marks

- The updated JSX to render.

An object to update the component's state, or null to indicate no state change.

A boolean value indicating whether the component should update.

A snapshot value that componentDidUpdate() can use.