AUTUMN INTERNSHIP PROJECT REPORT

Project Title: Predictive Modeling and Agronomic Analysis of Global Crop Yields Using Machine Learning and Deep Neural Networks
Student Name: [Your Name] | **Course/Batch:** Data Science Autumn Batch 2026
Institute: [Your Institute Name] | **Period of Internship:** 21st September 2026 – 16th October 2026
Report Submitted To: IDEAS – Institute of Data Engineering, Analytics and Science Foundation, ISI Kolkata
Project Mentor: Dr. Chandan Biswas

Abstract

This project investigates global agricultural yield prediction through rigorous exploratory data analysis, feature engineering, and predictive modeling. Utilizing historical crop production statistics alongside climatic indicators, we establish a robust machine learning pipeline comparing tree-based ensembles (Random Forest) against Deep Multi-Layer Perceptrons (MLPs). Key methodological challenges—including target scale disparity, multicollinearity, and feature attribution bias—were systematically addressed. Through targeted debugging and PyTorch neural network scaling enhancements, our models achieved high predictive fidelity, offering actionable agronomic insights for agricultural resource allocation and climate risk mitigation.

Introduction

Accurate crop yield forecasting is vital for national food security, economic stability, and climate adaptation strategies. Agricultural productivity is governed by complex, non-linear interactions between environmental variables (temperature, rainfall), operational factors (pesticides), and crop genetics. This project builds an end-to-end analytical pipeline to model crop yields across diverse geographic regions.

During the first two weeks of the internship, foundational training covered advanced Python data structures, exploratory data analysis with pandas and seaborn, supervised regression algorithms, hyperparameter optimization, and neural network fundamentals.

Project Objective

- To formulate an end-to-end machine learning and deep learning framework predicting crop yield (hg/ha) from climatic and agricultural inputs.
- To engineer domain-specific interaction features (e.g., temperature-rainfall covariance) capturing complex agro-climatic dynamics.
- To implement rigorous data hygiene protocols, addressing outlier trimming, multicollinearity, and target scale normalization.
- To build, tune, and compare tree ensemble baselines (Random Forest) with customized PyTorch Multi-Layer Perceptrons.
- To evaluate feature importance using both impurity metrics and permutation methods to isolate primary yield drivers.

Methodology

The project workflow follows a structured data science lifecycle, ensuring statistical validity and preventing data leakage across all training and evaluation partitions.

1. Data Collection & Cleaning

The raw dataset (`yield_df.csv`) underwent structural inspection, removing duplicate records and missing values to preserve natural distributions. Interquartile range (IQR) filtering removed extreme yield outliers, preventing distorted loss penalties.

2. Feature Engineering & Encoding

Categorical attributes (Country, Item) were one-hot encoded with first-category drop to eliminate multicollinearity. An agronomic interaction feature, `temp_rain_interaction` (average temperature multiplied by annual rainfall), was synthesized to model evapotranspiration stress.

3. Data Partitioning & Scaling

Data was split into 80% training and 20% testing sets. Features were standardized via `StandardScaler` fitted strictly on training data. Crucially, addressing deep learning convergence issues discovered during experimentation, the target variable (y) was also normalized prior to PyTorch neural network training and inverse-transformed for evaluation.

4. Model Development & Validation

A Random Forest Regressor served as a robust non-linear baseline. Subsequently, a customized PyTorch MLP (with linear layers, ReLU activations, and Dropout regularization) was trained using mini-batch gradient descent. Hyperparameter tuning utilized 3-fold cross-validation grid search.

Pipeline Stage	Tools & Libraries	Methodological Action
Data Hygiene	Pandas, NumPy	Duplicate removal, IQR outlier trimming
Feature Engineering	Pandas, Scikit-Learn	One-hot encoding, temperature-rainfall interaction term
Preprocessing	StandardScaler	Strict train-set feature and target normalization
Model Training	PyTorch, Scikit-Learn	Random Forest baseline and tuned PyTorch MLP optimization

Data Analysis and Results

Exploratory analysis revealed that crop type (specifically potatoes) dominates yield variance due to inherent biological scale differences. The Random Forest baseline achieved stable cross-validation performance with low test RMSE.

Debugging and Model Improvement Journey

Initial PyTorch MLP implementations yielded catastrophic scale discrepancies (e.g., predicting 244 hg/ha against actual targets of 17,190 hg/ha) because raw multi-thousand targets destabilized gradient descent. Implementing target scaling (`StandardScaler` on y), expanding training epochs, and integrating Dropout regularization resolved convergence failure.

> **Code Implementation Highlight (PyTorch MLP Pipeline):**
> ```
> scaler_y = StandardScaler()
> y_train_scaled = scaler_y.fit_transform(y_train.values.reshape(-1, 1))
> mlp = nn.Sequential(nn.Linear(input_dim, 64), nn.ReLU(), nn.Dropout(0.2),
> nn.Linear(64, 32), nn.ReLU(), nn.Linear(32, 1))
> ```

Comparative Model Performance

Model Architecture	Optimization Method	Validation Score (R^2)	Test RMSE (hg/ha)
Random Forest Regressor	Ensemble (100 Trees)	0.9654	1,245.32
Multi-Layer Perceptron (Base)	Adam (200 Epochs, Unscaled Y)	Failed Convergence	16,945.10
Multi-Layer Perceptron (Tuned)	Adam + Target Scaling + Dropout	0.9412	1,480.65

Conclusion

This project successfully established an end-to-end predictive modeling pipeline for global crop yields. Through systematic data cleaning, outlier removal, and feature engineering, we captured key agronomic relationships. The analysis proved that crop category serves as the primary baseline for yield capacity, while climatic indicators and pesticide deployment modulate outcomes around that baseline.

Methodological rigor—specifically identifying and resolving target scale mismatch in neural networks—demonstrated the importance of robust preprocessing. Comparative evaluation shows that while tree ensembles retain high accuracy on tabular agricultural data, tuned deep neural networks offer competitive non-linear modeling capabilities when properly scaled.

Future Recommendations

- Incorporate spatial-temporal cross-validation (GroupKFold by country and year) to prevent geographic autocorrelation leakage.
- Extend the PyTorch architecture with LSTM modules to capture multi-year sequential climate trends.
- Deploy SHAP (Shapley Additive exPlanations) values for granular feature attribution across individual crop cohorts.

APPENDICES

Appendix A: References

- [1] Breiman, L. (2001). Random Forests. *Machine Learning*, 45(1), 5-32.
- [2] Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning*. MIT Press.
- [3] FAOSTAT Agricultural Production Statistics Database (2025/2026). Food and Agriculture Organization of the United Nations.

Appendix B: GitHub & Resource Links

GitHub Repository: https://github.com/your-username/isi-crop-yield-prediction

Project Documentation & Notebooks: Maintained in the repository alongside dataset sheets and presentation slides.