

Build a LogiTrack System using Java & Angular

File 1: addcargo.component.ts

Variables:

```
itemForm: FormGroup;  
formModel:any={status:null}; // This is properties variable used to bind front end controls  
showError:boolean=false;  
errorMessage:any;  
cargList:any=[]; //This variable is used to store cargo information inside the method getCargo.  
assignModel: any={};  
driverList:any=[] //This variable is used to store driver information inside the method getDrivers.  
showMessage: any;  
responseMessage: any;
```

Methods:

Constructor()

- In constructor argument create instance for Router, HttpService, FormBuilder, AuthService.
- Implement inbuilt validator required for content, size, status.

ngOnInit(): void:

getCargo()

getDrivers()

onSubmit()

addDriver(value:any)

assignDriver()

File 2: assgin-cargo.component.ts

Variables:

```
showError:boolean=false;  
errorMessage:any;  
cargList:any=[];  
statusModel: any={};  
showMessage: any;  
responseMessage: any;
```

Methods:

Constructor()

- In constructor argument create instance for Router, HttpService, FormBuilder, AuthService.

ngOnInit(): void

getAssginCargo()

addStatus(value:any)

assignDriver()

File 3: dashbaord.component.ts

- **No Code**
-

File 4: login.component.ts

Variables:

```
itemForm: FormGroup;  
formModel:any={};  
showError:boolean=false;  
errorMessage:any;
```

Methods:

- **constructor**
 - **ngOnInit()**
 - **onLogin()**
 - **registration()**
-

File 5: registration.component.ts

Variables:

```
itemForm: FormGroup;  
formModel:any={role:null,email:"",password:"",username:"};  
showMessage:boolean=false;  
responseMessage: any;
```

Methods:

- **constructor**
 - **ngOnInit()**
 - **onRegister()**
-

File 6: viewcargostatus.component.ts

Variables

```
cargo:any={}  
showError:any;  
errorMessage: any;  
cargoIdMd:any;
```

Methods

search()

File 7: app.component.ts

Variables

IsLoggin:any=false;
roleName: string | null;

Methods

Constructor()
Logout()

File 8: auth.service.ts

Variables:

private token: string | null = null;
private isLoggedIn: boolean = false;

Methods

constructor
saveToken(token: string)
SetRole(role:any)
get getRole ():string|null
get getLoginStatus(): boolean
getToken(): string | null
logout()

File 9: http.service.ts

Variables:

public serverName=environment.apiUrl;

Methods:

constructor()
getOrderStatus(cargoId:any):Observable<any>
updateCargoStatus(newStatus:any,cargoId:any):Observable<any>
assignDriver(driverid: any, cargoId: any): Observable<any>
getAssignOrders(driverId:any):Observable<any>
getCargo():Observable<any>
getDrivers():Observable<any>
addCargo(details:any):Observable<any>

Login(details:any):Observable<any>
registerUser(details:any):Observable<any>