Face, Voice, or Both: An Audio-Visual Deepfake Detection Framework and a Voice-Branch Study on ASVspoof 2019

Author One[1], Author Two[1]
[1]*Department of Computer Science and Engineering, University Name, City, Country*
Email: author.one@university.edu, author.two@university.edu

***Abstract*— A manipulated video can carry a synthetic face, a cloned voice, or both, yet most detectors inspect a single channel and are tested on clean clips drawn from the same generators they were trained on. This paper describes a modular audio-visual detector built with both gaps in mind. It pairs an EfficientNet-B0 face branch with a ResNet-18 log-mel voice branch, offers rule-based and learned fusion, and ships a degradation protocol and Grad-CAM explanations. The pipeline is implemented, unit-tested and publicly released. We report the first completed experiment: the voice branch, trained on a class-balanced subset of ASVspoof 2019 LA (5,000 clips per partition) and scored once on the official evaluation partition, where eleven of thirteen attack systems never appear in training. The model reaches an AUC of 0.977 (95% CI 0.973–0.981) and an equal error rate (EER) of 6.2% (5.5–7.0%). Errors are concentrated rather than spread out: attack A17 is flagged in only 1.2% of its clips at the default threshold, and removing it lowers the pooled EER to 3.2%. Validation AUC reached 1.0 by the third epoch and therefore gave no warning of this gap. The visual, fusion and robustness experiments await dataset access and are specified here as a protocol.**

***Index Terms*— deepfake detection, audio anti-spoofing, multimodal fusion, ASVspoof 2019, generalisation, calibration, Grad-CAM**

I. INTRODUCTION

Generative models can now swap a face, replay another person's expressions, or clone a voice from a few seconds of speech. Combined, they let an attacker impersonate someone in both channels at once. A detector that is useful outside a laboratory has to answer three practical questions. Which channel was altered? Does the answer survive the re-encoding that every sharing platform applies? And can a human reviewer see why the system decided as it did?

Existing work answers these questions unevenly. Face-forensics benchmarks [1]–[3] and speech anti-spoofing challenges [4] grew up separately, so face detectors ignore the soundtrack and speech countermeasures ignore the picture. Cross-dataset studies repeatedly show that a high score on the training distribution says little about performance on new generators [5], [6], and a recent in-the-wild benchmark reports AUC losses of roughly half for both video and audio detectors compared with earlier test sets [7]. Decision thresholds and probability calibration, which determine what a deployed system actually flags, receive far less attention than ranking metrics.

This paper makes four contributions.

1) **Framework.** A modular pipeline, from dataset download to demo, with a face branch, a voice branch and two fusion schemes. The code base has an automated test suite and fixed random seeds.
2) **Label-aware fusion.** A formulation in which the overall label is “fake if either channel is fake”, which motivates max and noisy-OR late fusion and a learned fusion layer trained with modality dropout.
3) **Stress protocol.** Seven degradations at three severities each, plus face-only and voice-only conditions, defined before any result was seen.
4) **Voice-branch evidence.** A full analysis of the first trained model, including bootstrap intervals, per-attack behaviour, threshold sensitivity and calibration, together with an account of why validation could not predict the test outcome.

Scope. Only the voice branch has been trained on real data so far; FakeAVCeleb access is still pending. Section III describes the full system, whereas Sections IV and V cover only what has been measured. We avoid any claim about fusion or robustness gains that the data do not yet support.

II. RELATED WORK

A. Datasets

FaceForensics++ supplies four manipulation methods at three compression levels and showed that detection accuracy falls as compression rises [1]. Celeb-DF raised visual quality to reduce telltale artefacts [2], and the DFDC corpus added more than a hundred thousand clips recorded by paid actors under varied conditions [3]. For speech, ASVspoof 2019 pairs bona fide recordings with text-to-speech and voice-conversion attacks, and places attacks in its evaluation partition that are absent from training [4], [8]. FakeAVCeleb is the main resource where the face and the voice are labelled separately, giving four combinations of real or fake video with real or fake audio [9].

B. Face and voice detectors

Early face detectors were small convolutional classifiers such as MesoNet [10], followed by Xception baselines [11] and EfficientNet backbones [12]. Later work targets cues that should transfer across generators, for example blending boundaries [13], self-blended training images [14] and lip-reading features [15]. On the audio side, spectrogram CNNs, raw-waveform models [16], graph-attention networks [17] and self-supervised front ends [18] are all common in ASVspoof work. SpecAugment-style masking [19] is a common regulariser.

C. Audio-visual and multimodal detection

Multimodal learning is usually organised as early, intermediate or late fusion [20]. Randomly hiding a modality during training teaches a model to cope when an input is missing [21]. Audio-visual deepfake detectors exploit identity [22], learned audio-visual correspondence [23], and discourse-level mismatch with temporal localisation [24], [25]. Whether a second modality improves generalisation, rather than merely widening the set of attacks that can be caught, remains an open empirical question.

D. Robustness, explanation and calibration

Corruption benchmarks quantify how fast accuracy decays under blur, noise and compression [26]. Grad-CAM [27] produces coarse class-specific heatmaps, but saliency methods can look plausible while being insensitive to the model's parameters [28], so heatmaps should be read as hints. Modern networks are frequently over-confident [29], which matters whenever a fixed threshold is used.

III. SYSTEM DESIGN

A. Overview

Fig. 1 shows the pipeline. A video is split into frames and an audio track. Face crops feed the visual branch and a log-mel spectrogram feeds the audio branch. Each branch yields a logit and an embedding, and a fusion stage combines them into one probability of fake. Degradations can be inserted before either backbone, and Grad-CAM is computed from the final score. Blue boxes mark the components evaluated in this paper; dashed boxes are implemented and tested but await data.




Fig. 1. Pipeline of the proposed detector. The two branches run in parallel and meet in a fusion stage. Shaded boxes are the components evaluated in Section V.

B. Preprocessing

Frames and faces. Sixteen frames are sampled uniformly from each video. YuNet [30] locates the face, the box is enlarged by a factor of 1.3, and the crop is resized to 224×224. A frame without a detection reuses the previous box.

Audio. The track is decoded with ffmpeg to 16 kHz mono and truncated to ten seconds. A 128-band mel spectrogram is computed with librosa [31] using a 400-sample (25 ms) window, a 160-sample (10 ms) hop and a 512-point FFT, then converted to decibels with a floor of -100 dB. A four-second window gives a 128×401 input: a random crop during training and a centre crop at test time. Each window is standardised to zero mean and unit variance,

$$\tilde{S} = \frac{S - \mu(S)}{\sigma(S) + \varepsilon}, \qquad \varepsilon = 10^{-5} \tag{1}$$

C. Visual branch

An ImageNet-pretrained [32] EfficientNet-B0 [12] from the timm library [33] encodes every valid frame x_t into $\mathbf{f}_t \in \mathbb{R}^{1280}$ (4.0 M parameters). With T the set of frames that contain a face,

$$\mathbf{z}_v = \frac{1}{|\mathcal{T}|} \sum_{t \in \mathcal{T}} \mathbf{f}_t, \qquad \ell_v = \frac{1}{|\mathcal{T}|} \sum_{t \in \mathcal{T}} \mathbf{w}^\top \mathbf{f}_t + b \tag{2}$$

Frames without a face are masked out rather than fed to the network as blanks. The training target is the video label alone, so a real face with a cloned voice counts as real for this branch.

D. Audio branch

An ImageNet-pretrained ResNet-18 [34] treats $\tilde{S}$ as an image; the single channel is repeated three times so the pretrained stem can be reused. The 512-dimensional pooled embedding $\mathbf{z}_a$ passes through dropout (0.3) and a linear layer to give the logit ℓ_a. The backbone has 11.2 M parameters. SpecAugment [19] is applied in training with two frequency masks of at most 16 bands and two time masks of at most 40 frames, filled with the window mean.

E. Fusion

Let $y_v, y_a \in \{0,1\}$ denote the face and voice labels and let the overall label be

$$y = y_v \vee y_a \tag{3}$$

that is, a clip is fake if either channel is fake. With branch probabilities $p_v = \sigma(\ell_v)$ and $p_a = \sigma(\ell_a)$, three training-free late rules are available:

$$p_{\max} = \max(p_v, p_a) \tag{4}$$

$$p_{\text{or}} = 1 - (1 - p_v)(1 - p_a) \tag{5}$$

$$p_w = w\ p_v + (1 - w)\ p_a \tag{6}$$

Max and noisy-OR mirror the logical OR in (3), whereas the weighted mean dilutes a confident detection in one channel with an unsure score from the other. The rule, and w in steps of 0.05, are chosen by validation AUC. The learned alternative concatenates both embeddings with two presence flags $m_v, m_a \in \{0,1\}$,

$$\ell = \mathbf{W}_2\ \mathrm{ReLU}(\mathbf{W}_1[\mathbf{z}_v; \mathbf{z}_a; m_v; m_a] + \mathbf{b}_1) + b_2 \tag{7}$$

with 256 hidden units. During training one modality is hidden with probability 0.2 [21], so that clips lacking a face or a soundtrack are still handled.

F. Training objective

Each branch is trained with class-weighted binary cross-entropy,

$$\mathcal{L} = -\frac{1}{N}\sum_{i=1}^{N}[\lambda\ y_i \log \sigma(\ell_i) + (1 - y_i)\log(1 - \sigma(\ell_i))] \tag{8}$$

where $\lambda = n_{\text{real}}/n_{\text{fake}}$, which equals 1 for the balanced subset used here.

G. Stress protocol

Table I lists the planned degradations. Video operations act on the face-crop sequence, which approximates platform re-encoding of the face region but is not identical to compressing whole frames before detection. Audio operations act on the stored waveform before the spectrogram is computed. Two further conditions, face-only and voice-only, remove one modality entirely. Optional robust training applies a random degradation to each sample with probability 0.5. The design follows the logic of corruption benchmarks [26].

TABLE I
PLANNED DEGRADATION PROTOCOL (IMPLEMENTED, NOT YET RUN)

Modality	Degradation	Mild	Medium	Severe
Video	JPEG quality	90	50	20
Video	H.264 CRF	23	30	40
Video	Gaussian blur σ	1	2	3
Video	Gaussian noise σ	5	15	30
Video	Downscale factor	2×	3×	4×
Audio	White-noise SNR (dB)	20	10	5
Audio	MP3 bitrate (kbit/s)	64	32	16

H. Explanation

For a convolutional layer with activation maps A^k, Grad-CAM [27] weights each map by the spatially averaged gradient of the output logit ℓ,

$$\alpha_k = \frac{1}{Z}\sum_{i,j}\frac{\partial \ell}{\partial A^k_{ij}}, \qquad L = \mathrm{ReLU}\left(\sum_k \alpha_k A^k\right) \tag{9}$$

and upsamples L to the input. We hook the last convolutional block of each branch (EfficientNet `bn2`, ResNet `layer4`), giving a 7×7 map per face and a 4×13 map per spectrogram. For the fused model, one backward pass of the fused logit yields maps for every face frame and for the spectrogram together.

IV. EXPERIMENTAL SETUP

A. Data

Table II places the four datasets in the study. Only ASVspoof 2019 LA has been trained and evaluated so far. We keep its official protocol: the training, development and evaluation partitions become our train, validation and test splits (Fig. 2). Because the full partitions are large, we draw up to 2,500 bona fide and 2,500 spoofed clips per partition with seed 42, giving 5,000 clips per split. The training and development partitions contain attacks A01–A06. The evaluation partition contains A07–A19, of which A16 and A19 reuse the algorithms of A04 and A06 and the other eleven are unseen [4]. Our test set contains 171–209 clips per attack.

TABLE II
DATASETS AND THEIR ROLE IN THE STUDY

Dataset	Role	Status
ASVspoof 2019 LA	Voice-branch training, per-attack testing	Used here
FakeAVCeleb	Main audio-visual training and test; four label categories	Access pending
DFDC (sample)	Pipeline development, visual baseline	Planned
Celeb-DF v2	Cross-dataset test of the visual branch	Planned




Fig. 2. ASVspoof 2019 LA subset used for the voice branch. Each split is balanced; labels inside the bars name the attack systems present.

B. Training configuration

Table III lists the voice-branch settings, taken from the saved run configuration. The model was trained in PyTorch [35] on a single Tesla T4 GPU in Google Colab with mixed precision [36]. We used AdamW [37] with a cosine learning-rate schedule [38]. The classifier head learns ten times faster than the backbone, and the backbone is frozen during the first epoch.

TABLE III
VOICE-BRANCH TRAINING CONFIGURATION

Item	Value
Backbone	ResNet-18, ImageNet initialisation
Input	128×401 log-mel, per-window standardised
Optimiser	AdamW, weight decay 10^{-4}
Learning rate	10^{-4} backbone, 10^{-3} head
Schedule	Cosine annealing, $T_{\max}$=15 epochs
Batch size, dropout	32, 0.3
Gradient clipping	Global norm 1.0
Frozen backbone	First epoch
Early stopping	Validation AUC, patience 3
Augmentation	Random 4 s crop, SpecAugment
Seed	42
Hardware	Colab Tesla T4, PyTorch 2.11 (CUDA 13.0)
Time per epoch	about 157 s

C. Metrics and statistics

Spoof is the positive class and each model outputs P(spoof). We report the area under the ROC curve (AUC) [39] and the equal error rate, the common value of false-alarm rate and miss rate at the threshold where they meet. A detection error trade-off (DET) view [40] is also provided. At fixed thresholds we

give accuracy, precision, recall and F1. Calibration is summarised by the expected calibration error over M=15 equal-width bins [41],

$$\mathrm{ECE} = \sum_{m=1}^{M} \frac{|B_m|}{n} \left|\mathrm{acc}(B_m) - \mathrm{conf}(B_m)\right| \tag{10}$$

together with the Brier score [42] and the negative log-likelihood. Confidence intervals are percentile intervals from 2,000 stratified bootstrap resamples of the test clips [43]. These intervals describe sampling variation of the test set only; they do not capture training randomness, since a single seed was run. Per-attack figures score each attack's clips against all 2,500 bona fide test clips.

D. Model selection and test use

The checkpoint with the best validation AUC was evaluated on the test split once. No hyper-parameter was tuned on test data. The EER threshold is, by definition, computed from the test scores, so metrics at that threshold are post-hoc diagnostics and not attainable operating points.

V. RESULTS AND ANALYSIS

A. Training behaviour

Fig. 3 shows the run. Training loss fell steadily. Validation AUC jumped from 0.855 to 0.99999 once the backbone was unfrozen, and reached exactly 1.0 at epoch 3. Because later epochs never improved on that value, the patience counter expired after epoch 6 and the epoch-3 checkpoint was kept. The six epochs took 15.7 minutes in total.

The validation curve is the first warning sign. The development partition shares its six attack systems with the training partition, so near-perfect validation scores only show that the model has learned those six. The test AUC of 0.977, drawn as a horizontal line in Fig. 3, sits below every validation point from epoch 2 onward.




Fig. 3. Left: training and validation loss per epoch (log scale). Right: validation AUC and accuracy against the final test AUC. The dotted line at epoch 3 marks the selected checkpoint.

B. Aggregate test performance

Table IV gives the headline numbers and Fig. 4 the corresponding curves. The model ranks spoofed speech above bona fide speech with an AUC of 0.977 (0.973–0.981). The EER is 6.2% (5.5–7.0%).

The pooled figures hide a split. Excluding A17, the AUC rises to 0.996 and the EER falls to 3.2%. A17 alone has an AUC of 0.725 and an EER of 34.4% (bootstrap interval 30.4–38.4%). In the DET plot of Fig. 4 the A17 curve crosses the equal-error diagonal near 34%, far from the other two curves.

TABLE IV
TEST RESULTS ON THE ASVSPOOF 2019 LA EVALUATION SUBSET (N=5,000)

Metric	Value (95% CI)
AUC	0.977 (0.973–0.981)
EER (%)	6.2 (5.5–7.0)
Accuracy at threshold 0.5 (%)	91.24
Precision / recall at 0.5	0.991 / 0.832
F1 at 0.5	0.905
Accuracy at EER threshold (%)*	93.8
AUC excluding A17	0.996
EER excluding A17 (%)	3.2
EER on A17 only (%)	34.4 (30.4–38.4)
Brier score / NLL	0.076 / 0.425
ECE (15 bins)	0.083

*Threshold 0.0102 was chosen on the test scores, so this is a diagnostic and not a deployable setting.




Fig. 4. ROC (left) and DET (right) curves for all attacks, for A17 alone and for all attacks except A17. The star marks the EER operating point. DET axes are probit-scaled.

C. Operating point

At the default threshold of 0.5 the detector accepts 99.2% of bona fide clips (19 false alarms in 2,500) but catches only 83.2% of spoofs; 419 spoofed clips are missed (Fig. 5). The error is lopsided: a false-alarm rate of 0.8% against a miss rate of 16.8%. Fig. 6 shows why. Bona fide scores pile up near zero, but a long tail of spoofs sits at low and intermediate scores. At the EER threshold the two error rates match at 6.2%, yet that threshold is as low as 0.0102, and it flags 155 bona fide clips where the default flags 19. Fig. 9 (right) plots both error rates against the threshold; the default 0.5 lies in a region where the miss rate rises steeply.




Fig. 5. Confusion matrices at the default threshold (left) and at the post-hoc EER threshold (right). Cell values give counts and the share of the true class.




Fig. 6. Distribution of predicted spoof probability on the test set (log-scaled counts). The black outline shows A17 spoofs only. The dashed line marks the default threshold and the dash-dot line marks the EER threshold.

D. Behaviour per attack system

Table V and Fig. 7 break the result down. Eight of thirteen attacks are caught in at least 94% of clips. These include A16 and A19, whose generation algorithms appeared in training; pooled, their EER is 0.3%. The unseen attacks other than A17 trail them, with a pooled EER of 3.3% (AUC 0.995). Familiarity with the algorithm therefore helps, but it is not the whole story: A07–A09 are unseen and are still detected almost perfectly.

Three groups stand out. A07–A09, A11 and A14 are detected almost perfectly even though they are unseen. A10, A12, A13 and A18 are detected in 64–80% of clips at threshold 0.5 while keeping EERs near 4–5%, which means their scores rank correctly but fall on the wrong side of the default threshold. A17 is different in kind: 1.2% of its clips cross 0.5 and its AUC of 0.725 shows poor ranking as well. It accounts for 169 of the 419 missed spoofs (40%) while making up 7% of the spoofed test clips.

TABLE V
PER-ATTACK RESULTS (EACH ATTACK AGAINST ALL 2,500 BONA FIDE TEST CLIPS)

Attack	*n*	Detected (%)	AUC	EER (%)
A07	194	100.0	1.0000	0.06
A08	182	100.0	1.0000	0.08
A09	189	100.0	1.0000	0.10
A10	209	69.4	0.9851	5.19
A11	197	100.0	0.9997	0.79
A12	205	79.5	0.9915	4.30
A13	204	64.2	0.9888	4.41
A14	182	100.0	0.9999	0.45
A15	189	94.2	0.9979	2.14
A16†	178	100.0	0.9999	0.08
A17	171	1.2	0.7248	34.37
A18	207	71.5	0.9884	4.90
A19†	193	99.5	0.9988	0.40

†Same generation algorithm as a training attack (A04 / A06). "Detected" uses threshold 0.5.




Fig. 7. EER (log scale, top) and detection rate at threshold 0.5 (bottom) for each attack system. The dashed line is the pooled EER.

Fig. 8 compares score distributions directly. The A17 curve sits to the right of the bona fide curve, which is why its AUC is above 0.5, but both stay low: 77% of A17 clips score below the EER threshold, against 94% of bona fide clips, and about 82% of A17 clips score below the 95th percentile of bona fide scores. The model treats most A17 clips as ordinary speech and does not flag them as uncertain. The remaining attacks are separated from bona fide speech by several orders of magnitude.




Fig. 8. Empirical cumulative distribution of predicted spoof probability for bona fide speech and for groups of attacks (log-scaled x axis). Dashed and dotted vertical lines mark thresholds 0.5 and 0.0102.

E. Calibration

The reliability curve in Fig. 9 (left) departs clearly from the diagonal, with an ECE of 0.083. The largest deviation comes from the lowest-probability bin, which supplies about 0.049 of the 0.083 total. It holds 2,683 clips, of which 253 (9.4%) are spoofs, although the mean predicted probability in the bin is 0.002. In other words, a score near zero is not a reliable promise of authenticity on unseen attacks. This is consistent with the general finding that modern networks are poorly calibrated

[29], with the specific pattern here being an under-estimate of spoof risk at the low end of the score range.




Fig. 9. Left: reliability curve with 15 bins. Right: false-alarm and miss rates as a function of the decision threshold (log scale). Vertical lines mark threshold 0.5 (dashed) and the EER threshold (dash-dot).

F. Qualitative explanation

Fig. 10 shows a Grad-CAM overlay for a clip synthesised with a built-in operating-system text-to-speech voice. The clip was run through the public demo and is not part of the evaluation set; the model scored it as spoofed with probability near 1. The strongest response covers a mid-band region in the first half of the window. We offer this only as an illustration of the interface. No faithfulness test, such as parameter randomisation [28], has been run on the trained model, and a 4×13 map cannot localise individual artefacts.




Fig. 10. Grad-CAM overlay on the log-mel spectrogram for an informal demonstration clip (system text-to-speech, outside the test set). Warm colours indicate regions that raised the spoof score.

VI. DISCUSSION

Why validation failed. The development partition reuses the training attacks, so validation AUC saturated at 1.0 and offered no basis for choosing a checkpoint or a threshold. Any checkpoint after epoch 2 looked equally good, while test behaviour on unseen attacks may differ between them. A validation split built by holding out whole attack families, for instance leave-one-attack-out, would restore a useful signal; this is the most important methodological change we would make.

A17. The dataset paper describes A17 as a voice-conversion system that shares its VAE-based acoustic model with training attack A05 but replaces the WORLD vocoder with direct waveform filtering [4]. Baseline GMM countermeasures distributed with the dataset also struggled with A17, A13 and A10 [4], so its difficulty is not unique to our model. Our results do not isolate a cause. A13, which also uses waveform filtering, is detected with an EER of 4.4%, and A18, which also converts human speech, reaches 4.9%, so neither the vocoder family nor the human-source input explains A17 alone. One hypothesis is that filtering a genuine utterance leaves the fine structure of natural speech largely intact, giving a vocoder-artefact detector little to find. Testing it would need ablations that we have not run.

Threshold. The gap between the default threshold and the EER threshold, and the large shift between them (0.5 versus 0.0102), mean that reporting accuracy at 0.5 alone would hide the real sensitivity. A deployable threshold must come from data that contain unseen attacks, which again points to a better validation design.

Comparability. Results use a 5,000-clip subset per partition and a single seed, so they should not be compared with published full-benchmark EERs. Our random subset also changes the per-attack mix relative to the full evaluation partition.

Out-of-domain behaviour. In an informal check through the demo, two clips from a built-in text-to-speech voice were both flagged as spoofed. No out-of-domain bona fide recording has been tested, so the false-alarm rate on everyday microphones is unknown; this check is not evidence of generalisation.

Threats to validity. Bootstrap intervals reflect test-sample variation, not seed variation. Each attack has fewer than 210 test clips, so per-attack EERs below 1% rest on very few errors and should be read as "small" rather than as precise values. The balanced subset also removes the class imbalance found in the full protocol, which affects precision-type metrics.

What remains. The face branch, both fusion schemes, the degradation protocol and the fused Grad-CAM analysis are implemented and tested on synthetic inputs but have not been run on real audio-visual data. Until they are, nothing in this paper supports a claim that fusion improves detection or that robust training helps.

VII. CONCLUSION

We presented a modular audio-visual deepfake detector together with its training, stress-testing and explanation tooling, and reported the first completed experiment, a ResNet-18 voice branch on a balanced ASVspoof 2019 LA subset. The model separates bona fide from spoofed speech well overall (AUC 0.977, EER 6.2%), but one unseen attack, A17, is mostly treated as genuine speech, and a default threshold of 0.5 misses a sixth of all spoofs. Because validation shared its attacks with training, it predicted none of this. Next steps are to run the face, fusion and robustness experiments on FakeAVCeleb and Celeb-DF, to build validation sets with held-out attack families, to calibrate thresholds on such sets, and to compare the current spectrogram CNN with self-supervised and graph-attention countermeasures [17], [18].

REPRODUCIBILITY

Code, tests, notebooks and the trained voice checkpoint are available at https://github.com/tanishq1101/robust-multimodal-deepfake. Every number in Section V is computed from the run's saved `history.csv`, `predictions.csv` and `metrics.json` by `paper/make_figures.py`. The interactive demo uses Gradio [44].

REFERENCES

[1] A. Rössler, D. Cozzolino, L. Verdoliva, C. Riess, J. Thies, and M. Nießner, "FaceForensics++: Learning to detect manipulated facial

images," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, 2019, arXiv:1901.08971.
[2] Y. Li, X. Yang, P. Sun, H. Qi, and S. Lyu, "Celeb-DF: A large-scale challenging dataset for DeepFake forensics," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020, pp. 3207–3216.
[3] B. Dolhansky, J. Bitton, B. Pflaum, J. Lu, R. Howes, M. Wang, and C. Canton Ferrer, "The DeepFake detection challenge (DFDC) dataset," *arXiv preprint arXiv:2006.07397*, 2020.
[4] X. Wang, J. Yamagishi, M. Todisco, H. Delgado, A. Nautsch, N. Evans, M. Sahidullah, V. Vestman, T. Kinnunen, K. A. Lee *et al.*, "ASVspoof 2019: A large-scale public database of synthesized, converted and replayed speech," *Comput. Speech Lang.*, vol. 64, p. 101114, 2020.
[5] Z. Yan, Y. Zhang, X. Yuan, S. Lyu, and B. Wu, "DeepfakeBench: A comprehensive benchmark of deepfake detection," in *Proc. NeurIPS Datasets and Benchmarks Track*, 2023.
[6] N. M. Müller, P. Czempin, F. Dieckmann, A. Froghyar, and K. Böttinger, "Does audio deepfake detection generalize?" *arXiv preprint arXiv:2203.16263*, 2022, presented at Interspeech 2022.
[7] N. A. Chandra, H. Lee, R. Murtfeldt, L. Qiu, A. Karmakar, E. Tanumihardja, K. Farhat, B. Caffee, C. Lee, J. Choi, S. Paik, A. Kim, and O. Etzioni, "Deepfake-Eval-2024: A multi-modal in-the-wild benchmark of deepfakes circulated in 2024," *arXiv preprint arXiv:2503.02857*, 2025.
[8] M. Todisco, X. Wang, V. Vestman, M. Sahidullah, H. Delgado, A. Nautsch, J. Yamagishi, N. Evans, T. Kinnunen, and K. A. Lee, "ASVspoof 2019: Future horizons in spoofed and fake audio detection," in *Proc. Interspeech*, 2019, arXiv:1904.05441.
[9] H. Khalid, S. Tariq, M. Kim, and S. S. Woo, "FakeAVCeleb: A novel audio-video multimodal deepfake dataset," in *Proc. NeurIPS Datasets and Benchmarks Track*, 2021.
[10] D. Afchar, V. Nozick, J. Yamagishi, and I. Echizen, "MesoNet: A compact facial video forgery detection network," in *Proc. IEEE Int. Workshop Inf. Forensics Secur. (WIFS)*, 2018.
[11] F. Chollet, "Xception: Deep learning with depthwise separable convolutions," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2017.
[12] M. Tan and Q. Le, "EfficientNet: Rethinking model scaling for convolutional neural networks," in *Proc. Int. Conf. Mach. Learn. (ICML)*, ser. PMLR, vol. 97, 2019, pp. 6105–6114.
[13] L. Li, J. Bao, T. Zhang, H. Yang, D. Chen, F. Wen, and B. Guo, "Face X-ray for more general face forgery detection," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020.
[14] K. Shiohara and T. Yamasaki, "Detecting deepfakes with self-blended images," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2022.
[15] A. Haliassos, K. Vougioukas, S. Petridis, and M. Pantic, "Lips don't lie: A generalisable and robust approach to face forgery detection," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2021.
[16] H. Tak, J. Patino, M. Todisco, A. Nautsch, N. Evans, and A. Larcher, "End-to-end anti-spoofing with RawNet2," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, 2021.
[17] J. Jung, H.-S. Heo, H. Tak, H. Shim, J. S. Chung, B.-J. Lee, H.-J. Yu, and N. Evans, "AASIST: Audio anti-spoofing using integrated spectro-temporal graph attention networks," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, 2022.
[18] H. Tak, M. Todisco, X. Wang, J. Jung, J. Yamagishi, and N. Evans, "Automatic speaker verification spoofing and deepfake detection using wav2vec 2.0 and data augmentation," *arXiv preprint arXiv:2202.12233*, 2022.
[19] D. S. Park, W. Chan, Y. Zhang, C.-C. Chiu, B. Zoph, E. D. Cubuk, and Q. V. Le, "SpecAugment: A simple data augmentation method for automatic speech recognition," in *Proc. Interspeech*, 2019, pp. 2613–2617.
[20] T. Baltrušaitis, C. Ahuja, and L.-P. Morency, "Multimodal machine learning: A survey and taxonomy," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 41, no. 2, 2019.
[21] N. Neverova, C. Wolf, G. W. Taylor, and F. Nebout, "ModDrop: Adaptive multi-modal gesture recognition," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 38, no. 8, 2016.
[22] D. Cozzolino, A. Pianese, M. Nießner, and L. Verdoliva, "Audio-visual person-of-interest DeepFake detection," *arXiv preprint arXiv:2204.03083*, 2023, version 3.
[23] T. Oorloff, S. Koppisetti, N. Bonettini, D. Solanki, B. Colman, Y. Yacoob, A. Shahriyari, and G. Bharaj, "AVFF: Audio-visual feature fusion for video deepfake detection," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2024, pp. 27 102–27 112.
[24] Z. Cai, K. Stefanov, A. Dhall, and M. Hayat, "Do you really mean that? Content driven audio-visual deepfake dataset and multimodal method for temporal forgery localization," *arXiv preprint arXiv:2204.06228*, 2022.
[25] C. Koutlis and S. Papadopoulos, "DiMoDif: Discourse modality-information differentiation for audio-visual deepfake detection and localization," *arXiv preprint arXiv:2411.10193*, 2025.
[26] D. Hendrycks and T. Dietterich, "Benchmarking neural network robustness to common corruptions and perturbations," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019.
[27] R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-CAM: Visual explanations from deep networks via gradient-based localization," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, 2017.
[28] J. Adebayo, J. Gilmer, M. Muelly, I. Goodfellow, M. Hardt, and B. Kim, "Sanity checks for saliency maps," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 31, 2018.
[29] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *Proc. Int. Conf. Mach. Learn. (ICML)*, ser. PMLR, vol. 70, 2017, pp. 1321–1330.
[30] W. Wu, H. Peng, and S. Yu, "YuNet: A tiny millisecond-level face detector," *Mach. Intell. Res.*, vol. 20, no. 5, pp. 656–665, 2023.
[31] B. McFee, C. Raffel, D. Liang, D. P. W. Ellis, M. McVicar, E. Battenberg, and O. Nieto, "librosa: Audio and music signal analysis in Python," in *Proc. 14th Python Sci. Conf. (SciPy)*, 2015, pp. 18–25.
[32] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei, "ImageNet: A large-scale hierarchical image database," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2009, pp. 248–255.
[33] R. Wightman, "PyTorch Image Models," GitHub repository, 2019.
[34] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2016.
[35] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan *et al.*, "PyTorch: An imperative style, high-performance deep learning library," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 32, 2019.
[36] P. Micikevicius, S. Narang, J. Alben, G. Diamos, E. Elsen, D. Garcia, B. Ginsburg, M. Houston, O. Kuchaiev, G. Venkatesh, and H. Wu, "Mixed precision training," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2018.
[37] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019.
[38] ——, "SGDR: Stochastic gradient descent with warm restarts," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2017.
[39] T. Fawcett, "An introduction to ROC analysis," *Pattern Recognit. Lett.*, vol. 27, no. 8, pp. 861–874, 2006.
[40] A. Martin, G. Doddington, T. Kamm, M. Ordowski, and M. Przybocki, "The DET curve in assessment of detection task performance," in *Proc. Eurospeech*, 1997, pp. 1895–1898.
[41] M. P. Naeini, G. F. Cooper, and M. Hauskrecht, "Obtaining well calibrated probabilities using Bayesian binning," in *Proc. AAAI Conf. Artif. Intell.*, 2015, pp. 2901–2907.
[42] G. W. Brier, "Verification of forecasts expressed in terms of probability," *Mon. Weather Rev.*, vol. 78, no. 1, pp. 1–3, 1950.
[43] B. Efron and R. J. Tibshirani, *An Introduction to the Bootstrap*. New York, NY, USA: Chapman & Hall, 1993.
[44] A. Abid, A. Abdalla, A. Abid, D. Khan, A. Alfozan, and J. Zou, "Gradio: Hassle-free sharing and testing of ML models in the wild," in *ICML Workshop on Human in the Loop Learning (HILL)*, 2019, arXiv:1906.02569.