main.pdf

Shri Vile Parle Kelavani Mandal

Document Details

Submission ID
trn:oid:::9832:154304608

Submission Date
Oct 11, 2026, 2:57 PM GMT+5:30

Download Date
Oct 11, 2026, 3:02 PM GMT+5:30

File Name
main.pdf

File Size
278.0 KB

5 Pages

3,429 Words

18,322 Characters

16% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Match Groups

- **19** Not Cited or Quoted 12%
  Matches with neither in-text citation nor quotation marks
- **8** Missing Quotations 2%
  Matches that are still very similar to source material
- **2** Missing Citation 1%
  Matches that have quotation marks, but no in-text citation
- **0** Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

Top Sources

13% Internet sources
14% Publications
12% Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- **19** Not Cited or Quoted 12%
  Matches with neither in-text citation nor quotation marks
- **8** Missing Quotations 2%
  Matches that are still very similar to source material
- **2** Missing Citation 1%
  Matches that have quotation marks, but no in-text citation
- **0** Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

Top Sources

13% Internet sources
14% Publications
12% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Internet	
arxiv.org		3%
2	Submitted works	
University of Warwick on 2025-07-10		2%
3	Publication	
Tom Velez, Oluwakemi Badaki-Makun, Danielle Hirsch, Danielle Claire Mercurio e...		1%
4	Internet	
www.aurumahmad.com		<1%
5	Submitted works	
University of Wolverhampton on 2026-05-05		<1%
6	Internet	
pdfs.semanticscholar.org		<1%
7	Internet	
jstic.ptit.edu.vn		<1%
8	Publication	
Yanchun Ji, Chenhao Wang, Bo Wang, Bian Jin, Chengxi Zhuang, Jingting Xu, Feng ...		<1%
9	Submitted works	
Dublin Business School on 2026-08-14		<1%
10	Internet	
stax.strath.ac.uk		<1%

11	Publication	C. Guedes Soares, F.C. Salvado. "Innovations in Maritime Technology and Enginee... <1%
12	Internet	scienmag.com <1%
13	Submitted works	A. P. Shah Institute of Technology, Thane on 2026-01-25 <1%
14	Internet	ieeevis.b-cdn.net <1%
15	Internet	raw.githubusercontent.com <1%
16	Publication	Bhope, Rahul Atul. "Middleware Systems for Efficient and Robust Distributed Mac... <1%
17	Internet	www.frontiersin.org <1%
18	Submitted works	United International University on 2026-06-28 <1%
19	Submitted works	University of Ulster on 2026-08-14 <1%
20	Internet	flore.unifi.it <1%
21	Publication	Zhongbo Xu, Wenshui Lou, Jianqing Chen, Gaofeng Mao, Xiaoxiao Wang, Lin Zhen... <1%

Federated SHAP: Privacy-Preserving, Per-Node Explainability and Sensitivity Analysis for Pediatric Sepsis Prediction

Tanish Porwal*, Uzair Teli*, Praveen Modi
Department of Engineering
SVKM's NMIMS Indore Campus, Indore, India
Email: tanishporwal2005@gmail.com

***Abstract*—Federated learning enables multi-hospital pediatric sepsis prediction without centralizing patient records, but a federated model remains a black box to the clinicians who must act on it: federation solves privacy, not trust. We present a federated SHAP explainability pipeline that computes Shapley attributions *locally* at each of five simulated ICU-type nodes on a shared global model, aggregates them using the same sample-size weighting FedAvg itself uses for model updates, and never transmits raw patient data or per-patient attributions off a node. On a Feature Tokenizer Transformer trained via FedAvg and FedProx across non-IID ICU nodes derived from the Pediatric Intensive Care (PIC) database with Phoenix Sepsis Criteria labelling, we find that `lactate_max` is the unanimous top feature at all five nodes, and every node's local SHAP ranking correlates strongly with the federated aggregate (Spearman ρ between 0.930 and 0.974 across all five nodes, including the smallest node, CICU, 5.7% of training data, and the largest, General ICU, 49.4%). FedAvg and FedProx further agree on 4 of their top 5 federated features ($\rho = 0.689$, $p = 5.4 \times 10^{-33}$). These results indicate that per-node federated explainability is both computationally practical and robust to severe non-IID node-size imbalance, at least along the algorithm-choice axis evaluated here.**

***Index Terms*—federated learning, explainable AI, SHAP, pediatric sepsis, Phoenix criteria, privacy-preserving machine learning**

I. Introduction

Pediatric sepsis progresses from suspected infection to multi-organ failure within hours, and delays in recognition of even one hour are associated with measurably higher mortality. An estimated 25 million pediatric sepsis cases occur annually worldwide, with mortality ranging from approximately 4% in mild presentations to over 50% in septic shock. The Phoenix Sepsis Criteria [1], [2] replaced the older, non-specific SIRS criteria [3] by scoring organ dysfunction directly across cardiovascular, coagulation, respiratory, and neurological domains, and is the labelling standard used throughout this work.

Federated learning (FL) is increasingly proposed as a way to train sepsis prediction models across multiple hospitals without centralizing patient records, which single-institution studies cannot do and which most jurisdictions' privacy regulations do not permit. FedAvg [4] and FedProx [5] are the two most-cited federated optimization algorithms and are compared directly in this work. However, federated training addresses only who can see the *data*; it does nothing to make the resulting *model* explainable. A clinician at a small-volume Cardiac ICU node has no way to verify that a model trained mostly on a much larger General ICU node's patients is reasoning correctly about their own, potentially very different, patient population.

This is the specific gap this paper addresses. SHAP [6] is the standard framework for post-hoc model explanation in clinical machine learning, and is increasingly treated as a precondition for deploying high-risk medical AI [7]. But SHAP explainability work in the sepsis literature has, to date, only ever been applied to centralized models trained on pooled data [8]. No published study combines federated training with *federated* explainability – i.e., SHAP computed locally at each participating site and aggregated without any node's raw data or per-patient attributions ever leaving that site.

Contributions. This paper makes four contributions: (1) a federated SHAP pipeline that computes GradientSHAP locally at each node and aggregates it with the same sample-size weighting FedAvg uses for model updates; (2) an empirical evaluation showing that per-node explanations agree strongly with the federated aggregate despite severe non-IID node-size imbalance (one node holds 49.4% of all training data, another only 5.7%); (3) a sensitivity analysis confirming this agreement is not an artifact of the choice of federated optimization algorithm; and (4) a fully specified privacy boundary – precisely what is and is not transmitted off a node at explanation time, not just at training time.

II. Related Work

A. Pediatric Sepsis Prediction

Machine learning for sepsis prediction has grown substantially, with systematic reviews cataloguing over 150 published models [9], [10]. The field remains dominated by adult ICU data, chiefly MIMIC-III/IV; pediatric-specific work is comparatively sparse. Le et al. [11] trained one of the few pediatric-specific sepsis models on UCSF PICU data, without a federated or privacy-preserving component. Deng et al. [12] document that data leakage and weak validation are

*Tanish Porwal and Uzair Teli contributed equally to this work and share first authorship.

widespread and underreported across clinical ML studies generally, a concern this work's underlying data pipeline addresses through a systematic leakage audit prior to any model training. Chanci et al. [8] applied Phoenix-labelled sepsis prediction with strong reported performance, but on proprietary, non-federated, single-institution data with no explainability layer – the combination this paper is positioned against.

B. Federated Learning in Clinical ML

FedAvg [4] aggregates local model updates as a weighted average proportional to each participating node's dataset size. FedProx [5] augments local training with a proximal term intended to improve convergence stability under non-IID data distributions, of the kind produced when ICU nodes vary in both size and patient case-mix. Both are evaluated in this work as the two federated optimization strategies whose resulting explanations are compared.

C. Explainable AI in Healthcare

Lundberg and Lee [6] introduced SHAP by grounding feature attribution in Shapley values, the only additive attribution method that simultaneously satisfies local accuracy, missingness, and consistency. For tabular deep learning models such as the Feature Tokenizer Transformer (FT-Transformer) [13] used in this work, gradient-based SHAP approximations (GradientSHAP/DeepSHAP) are the standard choice, as TreeSHAP applies only to tree ensembles. Interpretability is increasingly treated as a precondition for deploying high-risk clinical AI systems [7]. No prior work, to our knowledge, has computed SHAP explanations in a genuinely federated manner – locally per node, aggregated without centralizing raw attributions – for any clinical prediction task, pediatric sepsis included.

D. The PIC Database

The Pediatric Intensive Care (PIC) database [14] is the first publicly accessible ICU database drawn from a Chinese pediatric population, maintained by the Children's Hospital of Zhejiang University School of Medicine and accessible to credentialed researchers via PhysioNet. It is the data source for this work.

III. Methods

A. Dataset and Federated Learning Setup

The dataset comprises a leakage-audited, Phoenix-labelled cohort derived from PIC v1.1.0, restricted to patients with clinically suspected infection. The clean feature matrix contains 225 features per patient. Training data (n = 2,530) is partitioned into five simulated ICU-type nodes by care-unit designation: CICU (Cardiac ICU, n = 144), NICU (Neonatal ICU, n = 421), PICU (Paediatric ICU, n = 213), SICU (Surgical ICU, n = 501), and General ICU (n = 1,251). This partition is deliberately non-IID: the General ICU node alone holds 49.4% of all training data, 8.7× the size of the smallest node (CICU) and 5.9× the PICU node. No patient data crosses node boundaries at any point in training; only model weight updates are communicated to and from the aggregation server.

The shared model architecture is an FT-Transformer [13] (2 transformer blocks, 256-dimensional embeddings, 8 attention heads), trained under two federated optimization strategies – FedAvg [4] and FedProx [5] – for 50 communication rounds with 5 local epochs per round, using inverse-prevalence class weighting to address the sepsis class imbalance. Feature values are standardized using a single StandardScaler fit on the pooled training distribution prior to federated partitioning, consistent with a realistic deployment where feature scaling statistics are agreed upon centrally before training begins, and applied identically at every node thereafter, including at explanation time.

B. Federated SHAP Explainability Pipeline

Given the final global model (from either FedAvg or FedProx), SHAP attributions are computed in five steps:

1) **Distribute weights.** The final global FT-Transformer is sent to each of the five nodes.
2) **Local SHAP, on-site.** At each node, GradientSHAP is computed independently on that node's own held-out test patients. TreeSHAP is not applicable here, as the shared model is a differentiable neural network, not a tree ensemble.
3) **Share summaries only.** Each node computes and transmits only its mean absolute SHAP value per feature – a single 225-dimensional vector – never raw patient data or per-patient attribution vectors.
4) **Weighted aggregation.** A federated feature ranking is formed as

$$\text{federated_SHAP}_j = \sum_{k=1}^{5} \frac{n_k}{N} \cdot \overline{|\text{SHAP}|}_{k,j} \qquad (1)$$

where n_k is node k's sample size, $N = \sum_k n_k$, and $\overline{|\text{SHAP}|}_{k,j}$ is node k's mean absolute SHAP value for feature j – the same sample-size weighting FedAvg itself uses for model updates, applied here to explanations instead.
5) **Compare.** Each node's own local ranking is compared against the federated aggregate via Spearman rank correlation, testing whether the combined explanation is representative of every node or is dominated by the largest one.

C. Sensitivity Analysis Design

Robustness of both model performance and its explanations was assessed along three axes. The algorithm axis – comparing FedAvg-trained and FedProx-trained global models' federated feature rankings via Spearman correlation and top-5 overlap – was completed and is reported in Section IV. Two further axes, cohort definition (the full intermediate ICU cohort versus the infection-restricted cohort used throughout this work) and alternate non-IID partitioning (e.g., by age band rather than care-unit type), were designed but not executed in time for this submission; see Section VI.

D. Privacy Analysis

Table I specifies precisely what data crosses a node boundary at explanation time, mirroring the guarantee FedAvg already provides at training time.

TABLE I
DATA FLOW AT EXPLANATION TIME

Stays at the node	Sent to the aggregator
Raw patient records	One mean |SHAP| vector per node
Per-patient SHAP vectors	Node sample size n_k
Local background sample	(already public: care-unit + count)

IV. RESULTS

A. Federated Learning Performance

TABLE II
FEDERATED MODEL PERFORMANCE

Configuration	AUROC	AUPRC	Sens.	Spec.
FedAvg (50 rounds)	0.9451	0.8897	0.8960	0.8609
FedProx (μ=0.01)	0.9557	0.9096	0.9017	0.8435

B. Node-Level SHAP Rankings

Figure 1 shows, for each of the five nodes, mean absolute SHAP value across the top federated features. `lactate_max` is the unanimous top-ranked feature at every one of the five nodes, the only feature with this property; `platelets_min` and `ddimer_first` are consistently ranked second and third across most nodes as well.




Fig. 1. Per-node mean |SHAP| for the top federated features.

C. Node vs. Federated Agreement

Every node correlates strongly with the federated aggregate, with Spearman ρ ranging narrowly from 0.930 to 0.974. Notably, General ICU – the dominant node at 49.4% of all training data – does *not* show the highest agreement ($\rho = 0.970$, the second-highest of the five); that distinction belongs to PICU ($\rho = 0.974$). The *lowest* agreement instead belongs to CICU, the smallest node at only 5.7% of training data ($\rho = 0.930$), though even this minimum remains high in absolute terms. This is the opposite of the pattern that would indicate the federated aggregate is simply reproducing the dominant node's reasoning: if that were the case, General ICU's agreement would be near-perfect while the smaller nodes trailed well behind. Instead, all five nodes – including both the largest and the smallest – cluster within a 0.044 range of each other, suggesting the federated model has learned a reasoning pattern that generalizes across care-unit types rather than one dominated by whichever node contributed the most training data.

TABLE III
SPEARMAN RANK CORRELATION, NODE RANKING VS. FEDERATED AGGREGATE (FEDAVG)

Node	Spearman ρ	p-value
CICU	0.9297	1.10×10^{-98}
NICU	0.9498	1.77×10^{-114}
PICU	0.9739	1.47×10^{-145}
SICU	0.9661	4.16×10^{-133}
General	0.9704	1.48×10^{-139}




Fig. 2. Spearman rank correlation of each node's local SHAP ranking against the federated aggregate.

D. Sensitivity Analysis: FedAvg vs. FedProx

Figure 3 compares the federated feature ranking produced under each optimization algorithm. The two algorithms agree on 4 of their top 5 federated features – `lactate_max`, `platelets_min`, `ddimer_mean`, and `inr_max` – with an overall Spearman rank correlation across all 225 features of $\rho = 0.689$ ($p = 5.36 \times 10^{-33}$). While lower than the per-node agreement reported above, this still represents a strong positive correlation and confirms that the feature-importance pattern driving Section IV-B's findings is not an artifact of which federated optimizer was used to train the underlying model.




Fig. 3. Federated SHAP ranking under FedAvg vs. FedProx.

V. Discussion

The central empirical question this paper set out to answer was whether a federated model's explanation is trustworthy at every participating site, or only at the site that happened to contribute the most training data. The results in Section IV-C answer this directly: node-level agreement with the federated aggregate is uniformly high (Spearman ρ between 0.930 and 0.974) and does not track node size. If the federated SHAP aggregate were simply amplifying General ICU's reasoning, General ICU's own ranking should align with it almost perfectly while CICU, NICU, SICU, and PICU trailed visibly behind; instead, General ICU sits in the middle of the pack, and the smallest node, CICU, shows only a modestly lower – still high – correlation. This is a reassuring result for multi-site federated deployment: it suggests that aggregating SHAP values with the same sample-size weighting used for model updates does not inherit a bias toward the largest contributor's local feature distribution, at least under the care-unit-based non-IID partition evaluated here.

`lactate_max` being the unanimous top feature across all five nodes reinforces this reading. Lactate is a direct marker of tissue hypoperfusion and a clinically well-established early indicator of septic shock; its consistent dominance across structurally different care units (a Cardiac ICU population and a Neonatal ICU population, for instance, have very different baseline physiology) is consistent with a model that has learned a genuine, generalizable physiological signal rather than a node-specific correlation. The FedAvg/FedProx agreement in Section IV-D (4 of 5 top features shared, $\rho = 0.689$) provides a second, independent line of evidence for the same conclusion: even changing the federated optimization algorithm entirely leaves the core explanation largely intact.

These findings should be read as applying to the single sensitivity axis completed in this work – the choice of federated algorithm – and not yet to variation in cohort definition or node partitioning strategy, both of which remain open questions discussed in Section VI.

VI. Limitations

The federated learning simulation partitions a single database by care-unit designation rather than drawing on genuinely separate institutional data sources; results here establish a lower bound on the practical cost of federation and of federated explainability, not a guarantee that a real multi-hospital deployment would behave identically. Of the three sensitivity axes designed for this work, only the algorithm-choice axis (FedAvg versus FedProx) was completed in time for this submission. The cohort-definition axis (re-running the full pipeline on the complete intermediate ICU cohort rather than the infection-restricted cohort used throughout) and the alternate-partition axis (grouping nodes by a criterion other than care-unit type, such as age band) were designed but not executed, and remain the most direct next steps for strengthening the robustness claims made in Section V.

VII. Conclusion

This paper presented a federated SHAP explainability pipeline for pediatric sepsis prediction, computing Shapley attributions locally at each of five simulated, non-IID ICU-type nodes and aggregating them with the same sample-size weighting used for federated model updates, without any node's raw patient data or per-patient attributions ever leaving that node. Across all five nodes, local SHAP rankings correlated strongly with the federated aggregate (Spearman ρ between 0.930 and 0.974), with no evidence that the dominant node (49.4% of training data) disproportionately shaped the aggregate explanation relative to the smallest node (5.7%). `lactate_max` emerged as the unanimous top feature at every node, and this finding was further confirmed as robust to the choice of federated optimization algorithm, with FedAvg and FedProx agreeing on 4 of their top 5 federated features. Together, these results suggest that per-node federated explainability is both practical to compute and trustworthy across heterogeneous clinical sites, at least along the one sensitivity axis evaluated to date. Extending this evaluation to cohort definition and alternate node partitioning, and validating the approach on genuinely separate institutional data rather than a simulated partition of a single database, are the natural next steps toward a deployable system.

Acknowledgment

The authors thank the PhysioNet platform for providing access to the PIC database.

References

[1] L. N. Sanchez-Pinto, T. D. Bennett, P. E. DeWitt, S. Russell, M. N. Rebull, B. Martin *et al.*, "Development and validation of the Phoenix criteria for pediatric sepsis and septic shock," *JAMA*, vol. 331, no. 8, pp. 675–686, 2024.

[2] L. J. Schlapbach, R. S. Watson, L. R. Sorce, A. C. Argent, K. Menon, M. W. Hall *et al.*, "International consensus criteria for pediatric sepsis and septic shock," *JAMA*, vol. 331, no. 8, pp. 665–674, 2024.

[3] B. Goldstein, B. Giroir, and A. Randolph, "International pediatric sepsis consensus conference: Definitions for sepsis and organ dysfunction in pediatrics," *Pediatric Critical Care Medicine*, vol. 6, no. 1, pp. 2–8, 2005.

[4] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. Agüera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, vol. 54, 2017, pp. 1273–1282.

[5] T. Li, A. K. Sahu, M. Zaheer, M. Sanjabi, A. Talwalkar, and V. Smith, "Federated optimization in heterogeneous networks," *Proceedings of Machine Learning and Systems*, vol. 2, pp. 429–450, 2020.

[6] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems*, vol. 30, 2017, pp. 4765–4774.

[7] V. S. Athukorala and W. M. K. S. Ilmini, "Explainable AI for critical care: A systematic review of interpretable models for sepsis and ICU mortality prediction," *BMC Medical Informatics and Decision Making*, vol. 26, p. 64, 2026.

[8] D. Chanci *et al.*, "Machine learning model for daily prediction of pediatric sepsis using Phoenix criteria," *Pediatric Research*, 2025.

[9] L. M. Fleuren, T. L. T. Klausch, C. L. Zwager, L. J. Schoonmade, T. Guo, L. F. Roggeveen *et al.*, "Machine learning for the prediction of sepsis: A systematic review and meta-analysis of diagnostic test accuracy," *Intensive Care Medicine*, vol. 46, no. 3, pp. 383–400, 2020.

[10] Z. Yang, X. Cui, and Z. Song, "Predicting sepsis onset in icu using machine learning models: A systematic review and meta-analysis," *BMC Infectious Diseases*, vol. 23, no. 1, p. 635, 2023.

[11] S. Le, J. Hoffman, C. Barton, J. C. Fitzgerald, A. Allen, E. Pellegrini, J. Calvert, and R. Das, "Pediatric severe sepsis prediction using machine learning," *Frontiers in Pediatrics*, vol. 7, p. 413, 2019.

[12] H.-F. Deng *et al.*, "Evaluating machine learning models for sepsis prediction: A systematic review of methodologies," *iScience*, vol. 25, no. 2, p. 103651, 2022.

[13] Y. Gorishniy, I. Rubachev, V. Khrulkov, and A. Babenko, "Revisiting deep learning models for tabular data," in *Advances in Neural Information Processing Systems*, vol. 34, 2021, pp. 18 932–18 943.

[14] X. Zeng, G. Yu, Y. Lu, L. Tan, X. Wu, S. Shi, C. Hu, H. Fan, S. Xiao, Y. Chen, J. Liu, and Y. Wang, "A study of the paediatric intensive care (pic) database," *Scientific Data*, vol. 7, p. 184, 2020.