

Pulsar Analytics - Data Sources and Integrations

Effective May 2026

1. Supported data sources

Pulsar connects to managed Postgres (Neon, Supabase, RDS), Snowflake, BigQuery, Databricks, Redshift, and uploaded CSV. Each connection is configured in Workspace > Data sources and can be tested from the same page.

2. Refresh cadence

Each data source has a refresh schedule. The default is every 1 hour for warehouse sources and every 15 minutes for Postgres replicas. Change the cadence from the data source's edit page. Schedules as fast as every 5 minutes are available on Business and Enterprise plans.

3. Schema drift

When a connected table adds, removes, or renames a column, Pulsar flags the dashboard with a yellow warning banner. Click the banner to view a diff and either accept the change (which updates) Tj 0 -20 Td (the dashboard's query auto the previous schema until you fix it manually.

4. Stale data

If a dashboard is showing older values than expected, the cause is almost always one of: (a) the warehouse has not received new rows since the last refresh; (b) the refresh schedule is set to daily instead of hourly; (c) the source credential has expired and the connection is in a failed state. Open Workspace > Data sources to inspect status and last-run timestamps.

5. Webhooks and outbound events

See the API reference for the full list of webhooks Pulsar emits. The most common for downstream automation are: dashboard.published, query.failed, datasource.health.degraded. All three are signed with HMAC-SHA256.

6. Limits

Per query: 10 000 rows returned, 60 second timeout, 1 GB scanned.