

1. Authentication

All requests authenticate with a bearer token issued from Workspace > Settings > API tokens. Tokens are scoped to a single workspace and inherit the issuing user's role. Pass the token in the Authorization header: Authorization: Bearer <token>.

2. Rate limits

The default rate limit is 60 requests per minute per token across the REST API and 600 requests per minute per workspace across all tokens. The /v1/query endpoint is capped at 10 requests per minute per token. Rate-limited responses return HTTP 429 with a Retry-After header in seconds.

3. Endpoints

GET /v1/dashboards - list dashboards in the workspace.

POST /v1/dashboards - create a new dashboard from a JSON spec.

GET /v1/dashboards/{id} - retrieve a dashboard by id.

PATCH /v1/dashboards/{id} - update title, layout, or filters.

POST /v1/query - run an ad-hoc SQL query against the workspace's data sources; returns up to 10 000 rows.

4. Webhooks

Pulsar emits webhooks for the following events: dashboard published, dashboard shared, query failed, data source health degraded, and member invited. Configure webhook URLs in Workspace > Settings > Webhooks. Pulsar signs each delivery with HMAC-SHA256; verify the X-Pulsar-Signature header.

5. SDKs

Official SDKs are available for TypeScript, Python, and Go. All three expose the same surface: dashboards.list, dashboards.create, query.run. The SDKs retry idempotent requests up to three times with exponential backoff on 5xx responses.