

Features:

- Handheld, Small, Light
- 8s splicing time, 26s tube heating time
- 5800mAh and pluggable Li-battery, Typical 200cycles
- USB port for software updating and data records exporting
- ARC calibrated by temperature and air pressure automatically



Technical Specifications

Parameters	Particulars
Applicable Fibers	SM(ITU-T G.652&G657), MM(ITU-T, G652&G657) DS(ITU-T G.652&G657), NZDS(ITU-T G.652&G657)
Fiber Count	Single
Cladding Length	Cladding diameter: 80-150μm, Coating diameter: 160-900μm
Typical Splice Loss	SM:0.02dB /MM:0.01dB /DS:0.04dB/NZDS:0.04dB /G.657:0.02dB (ITU-T Standard)
Return Loss	>60db
Fiber Cleaved Length	10-16mm (coating diameter < 250μm), 16mm (coating diameter: 250-100μm)
Splicing Program	40 groups
Operate Mode	Manual, Automatic
Auto-heating	Available
Typical Splicing Time	8 seconds
Tube Heating Time	26 seconds for 60mm and 40mm shrinkable sleeves
Fiber View Magnification	250X(X or Y view), 125X (X and Y view)
Viewing Method and Display	2 CMOS cameras, 4.3 inch color LCD monitor
Storage of Splice Result	4000 results
Loss Evaluation	Available
Tension Test	1.8~2.2N
Interface	GUL menu interface, easier operation
Battery Capacity	5200mAh Battery Capacity, typical times (splice and tube heat)
Power Supply	Adaptor, input: AC 100-240V (50/60HZ)
Electrode Life	More than 4000 ARC discharges, can be replaced conveniently
Terminals	USB 2.0 port, for uploading splice results and upgrading software
Operating Condition	Altitude: 0-5000m, Humidity: 0-95%, Temperature: -10°C~+50°C; Wind speed: max 15m/s
Dimension	149mm(L)x120mm (W)x127mm(H)
Weight	1.9kg including battery

Standard Package

Item	Qty
Fusion Splicer	1
Fiber Cleaver	1
Spare Electrodes	1 pair
Fiber Stripe	1
Skin Line Stripper	1
Cooling Tray	1
Adaptor	1
Power Cord	1
Carrying Case	1
Manual	1

PDR VIDEOTRONICS (INDIA) PVT. LTD.

99, Old Prabhadevi Road
Mumbai 400 025 India

Tel: +91 22 2430 6494/2430 9536/2436 1647
Mobile: +91 86910 00897/95946 56333

E-mail: info@pdrworld.com
URL: <http://www.pdrworld.com>