



General Description

PDR's PDR8010SG SD/HD/3G-SDI Optical Transceivers broadcasting grade HD Transceiver which can interconvert SD/HD/3G-SDI electric signal and optical signal. The Optical transmission device support HD/HD/3G-SDI video to up to 40KM and Plus, embedded audio and RS485 data via fiber-optic. System support in accordance with SMPTE424M, SMPTE292M, SMPTE259M standard, as well as DVB-ASI (EN50083-9) digital TV signal format.

Features

- SD/HD/3G auto-detection, supported transmission rate from 270M bit/s to 2.97G bit/s
- Transmission distance is from 0km to 40KM via multimode fiber or single mode fiber.
- Support, SMPTE(2.97G) ,SMPTE 259M (1.485Gbps),SMPTE 259M (270Mbps) and DVB-ASI
- Carry 1 channel SDI signal loop out.
- With 2CH Bi-Di data
- Operation status indication by LED

Main Characteristics

Parameters	Specifications
Model	PDR8010SG
Quantity/Type	Single Mode, Single Fiber
Video Port	1CH BNC SDI
SDI Loop Out Interface	1CHBNCSDI
Transmission Distance	0 m-20 Km/40 km optional
Fiber Connector	FC/APC
Wave Length	1310 nm/1550 nm
Transmitted Power	-10 dbm to -3 dbm
Maximum Receiving Sensitivity	<-34 dbm
Signal Type	SD-SDI(270 Mbps)/HD-SDI(1.485 Gbps)/3G-SDI(2.97 Gbps)
Support Input Format	SD: 525i @ 59.94 Hz, 625i @ 50 Hz
	SHD: 720p @ 25 Hz / 29.97 Hz / 30 Hz
	720p @ 50 Hz / 59.94 Hz / 60 Hz
	1080i @ 50 Hz / 59.94 Hz / 60 Hz
	1080p @23.98 Hz/24 Hz/25 Hz/29 Hz/30 Hz/50 Hz/59.94 Hz/60 Hz

Video Standard	SMPTE 292 M, SMPTE 259 M and SMPTE424 M
DATA Comm. Method	2CH RS-485/Half duplex/Industrial terminals
In-out Electrical Level	800 mVp-p±10%
In-Out Ohm	75 Ohm
Digital Audio	248 KHz
AES digital audio channel	8 CH
Power Supply	5 to 24 DC
Power Consumption	3 to 5 Watts
Operating Temperature	0 °C to 60 °C / 32 °F to 140 °F
Storage Temperature	-30 °C to 70 °C / -22 °F to 158 °F
Relative Humidity	20~90%RH(Non-Condensation)
Dimension	176×150×30 mm/6.97×5.90×1.18 in
Weight	900 g (Tx and Rx)

PDR VIDEOTRONICS (INDIA) PVT. LTD.

99, Old Prabhadevi Road
Mumbai 400 025 India

Tel: +91 22 2430 6494/2430 9536/2436 1647
Mobile: +91 86910 00897/95946 56333

E-mail: info@pdrworld.com
URL: <http://www.pdrworld.com>

PARTNER WITH PDR - WE HELP YOU WATCH YOUR BOTTOM LINE