

```

package test6;

import java.util.HashMap;

public class occurance_A {

    public static void main(String[] args) {

        String[] str = {"A", "B", "C", "D", "E", "F", "F", "G", "A" };

        HashMap < String , Integer> map = new HashMap<>();

        for (String ch : str){
            if (map.containsKey(ch)){
                map.put(ch , map.get(ch)+1);
            }else {
                map.put(ch , 1);
            }
        }

        for (String ch: map.keySet()){
            if (ch=="A"){
                System.out.println(ch + " " + map.get(ch));
            }
        }

        // int count=0;
        // for (String ch : str){
        //     if (ch=="A"){
        //         count++;
        //     }
        // }
        // System.out.println(count);
    }
}

```

```

package test6;

public class remove_duplicate {

    public static void main(String[] args) {
        int a[]={58,26,91,26,70,70,91,58,58,58,66};
        int n=a.length;

        int index = 0; // Position to place unique elements

        // Temporary array to hold duplicates
        int[] duplicates = new int[n];
        int dupIndex = 0;

        // Traverse the array
        for (int i = 0; i < n; i++) {
            boolean isDuplicate = false;

```

```

        // Check if a[i] appeared before in the unique section
        for (int j = 0; j < index; j++) {
            if (a[i] == a[j]) {
                isDuplicate = true;
                break;
            }
        }

        if (!isDuplicate) {
            a[index] = a[i];
            index++;
        } else {
            duplicates[dupIndex++] = a[i]; // store duplicate
separately
        }
    }

    // Place duplicates after unique values
    for (int i = 0; i < dupIndex; i++) {
        a[index++] = duplicates[i];
    }

    for (int num : a){
        System.out.println(num);
    }

}
}

```