

MIT

(An Autonomous Institute Affiliated to Savitribai Phule Pune University)

Academy of Engineering

**Subject
(Code):**
Essentials of Data
Science
(2304102L)

EDS CodeTantra Programs

Name	(PRN)	Div- Batch
TANMAY Rahul MUTKULE	(202501090093)	ME2 – M21



Practical 03

3.1 Practice Lab Assignments

3.1.1. Numpy Array Operations

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, r and c , representing the number of rows and the number of columns.
- The next r lines contain c space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Note: Use `reshape()` function to reshape the input array with the specified number of rows and columns.

```
import numpy as np
```

```
rows,cols= map(int,input().split())
```

```
elements = []
```

```
for _ in range(rows):
```

```
    elements.extend(map(int,input().split()))
```

```
array=np.array(elements).reshape(rows,cols)
```

```
print(array)
```

```
print(array.ndim)
```

```
print(array.shape)
```

```
print(array.size)
```

Average time
0.012 s
12.42 ms

Maximum time
0.023 s
23.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 10 out of 10 hidden test case(s) passed

✓ Test case 1 23 ms

DEBUG

^

Expected output	Actual output
3 4	3 4
1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
9 10 11 12	9 10 11 12
[[-1 -2 -3 -4]]	[[-1 -2 -3 -4]]
-[-5 -6 -7 -8]	-[-5 -6 -7 -8]

Terminal

Test cases

3.2 Lab Assignments

3.2.1. NumPy: Matrix Operations

The given code takes two 3×3 matrices, *matrix_a*, and *matrix_b*, as input from the user and converts them into NumPy arrays.

Task: You are required to compute and display the results of the following matrix operations:

1. **Addition** (*matrix_a* + *matrix_b*)
2. **Subtraction** (*matrix_a* - *matrix_b*)
3. **Element-wise Multiplication** (*matrix_a* * *matrix_b*)
4. **Matrix Multiplication** (*matrix_a* • *matrix_b*)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for *matrix_a*, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for *matrix_b*, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

```
import numpy as np
```

```
# Input matrices
```

```
print("Enter Matrix A:")
```

```
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
```

```
print("Enter Matrix B:")
```

```
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])
```

Addition

```
addition_result=matrix_a+matrix_b
```

```
print("Addition (A + B):")
```

```
print(addition_result)
```

Subtraction

```
substraction_result=matrix_a-matrix_b
```

```
print("Subtraction (A - B):")
```

```
print(substraction_result)
```

Multiplication (element-wise)

```
elementwise_multiplication_result=matrix_a*matrix_b
```

```
print("Element-wise Multiplication (A * B):")
```

```
print(elementwise_multiplication_result)
```

Matrix multiplication (dot product)

```
matrix_multiplication_result=np.dot(matrix_a, matrix_b)
```

```
print("A dot B:")
```

```
print(matrix_multiplication_result)
```

Transpose

```
transpose_a=matrix_a.T
```

```
print("Transpose of A:")
```

```
print(transpose_a)
```

Average time

0.054 s

54.00 ms



Maximum time

0.064 s

64.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 64 ms

DEBUG



Expected output

Enter Matrix A:

1 2 3

4 5 6

7 8 9

Enter Matrix B:

1 1 1

1 1 1

1 1 1

Addition (A + B):

[[2 3 4]

[5 6 7]

[8 9 10]]

Subtraction (A - B):

[[0 1 2]

[3 4 5]

[6 7 8]]

Element-wise Multiplication (A * B):

[[1 2 3]

[4 5 6]

[7 8 9]]

A dot B:

[[6 6 6]

[15 15 15]

[24 24 24]]

Transpose of A:

[[1 4 7]

[2 5 8]

[3 6 9]]

Actual output

Enter Matrix A:

1 2 3

4 5 6

7 8 9

Enter Matrix B:

1 1 1

1 1 1

1 1 1

Addition (A + B):

[[2 3 4]

[5 6 7]

[8 9 10]]

Subtraction (A - B):

[[0 1 2]

[3 4 5]

[6 7 8]]

Element-wise Multiplication (A * B):

[[1 2 3]

[4 5 6]

[7 8 9]]

A dot B:

[[6 6 6]

[15 15 15]

[24 24 24]]

Transpose of A:

[[1 4 7]

[2 5 8]

[3 6 9]]

3.2.2. NumPy Horizontal and Vertical Stacking of Arrays

You are given two arrays `arr1` and `arr2`. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).
- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

```
import numpy as np
```

```
# Input matrices
```

```
print("Enter Array1:")
```

```
arr1 = np.array([list(map(int, input().split())) for i in range(3)])
```

```
print("Enter Array2:")
```

```
arr2 = np.array([list(map(int, input().split())) for i in range(3)])
```

```
# Perform horizontal stacking (hstack)
```

```
a=np.hstack((arr1,arr2))
```

```
print("Horizontal Stack:")
```

```
print(a)
```

```
# Perform vertical stacking (vstack)
```

```
b=np.vstack((arr1,arr2))
```

```
print("Vertical Stack:")
```

```
print(b)
```

Average time
0.021 s
20.50 ms

Maximum time
0.023 s
23.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 21 ms

DEBUG

Expected output

Actual output

Enter Array1:
1 2 3
4 5 6
7 8 9

Enter Array1:
1 2 3
4 5 6
7 8 9

Enter Array2:
4 5 6
7 8 9
10 11 12

Enter Array2:
4 5 6
7 8 9
10 11 12

Horizontal Stack:
[[1 2 3 4 5 6]
 [4 5 6 7 8 9]
 [7 8 9 10 11 12]]

Horizontal Stack:
[[1 2 3 4 5 6]
 [4 5 6 7 8 9]
 [7 8 9 10 11 12]]

Vertical Stack:
[[1 2 3]
 [4 5 6]
 [7 8 9]
 [4 5 6]
 [7 8 9]
 [10 11 12]]

Vertical Stack:
[[1 2 3]
 [4 5 6]
 [7 8 9]
 [4 5 6]
 [7 8 9]
 [10 11 12]]

3.2.3. NumPy: Custom Sequence Generation

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:


- The program should print the generated sequence based on the input values.

```
import numpy as np

start = int(input())
stop = int(input())
step = int(input())

arr = np.arange(start,stop,step)

print(arr)
```



3.2.4. NumPy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

```
import numpy as np
```

```
def array_operations(A, B):
```

```
A=np.array(A)
```

```
B=np.array(B)
```

```
sum_result = A+B
```

```
diff_result = A-B
```

```
prod_result = A*B
```

```
mean_A = np.mean(A)
```

```
median_A = np.median(A)
```

```
std_dev_A = np.std(A)
```

```
and_result = A & B
```

```
or_result = A | B
```

```
xor_result = A ^ B
```

```
print("Element-wise Sum:", ' '.join(map(str, sum_result)))
```

```
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
```

```
print("Element-wise Product:", ' '.join(map(str, prod_result)))
```

```
print(f'Mean of A: {mean_A}')
```

```
print(f'Median of A: {median_A}')
```

```
print(f'Standard Deviation of A: {std_dev_A}')
```

```
print("Bitwise AND:", ' '.join(map(str, and_result)))
```

```
print("Bitwise OR:", ' '.join(map(str, or_result)))
```

```
print("Bitwise XOR:", ' '.join(map(str, xor_result)))
```

```
A = list(map(int, input().split())) # Elements of array A
```

```
B = list(map(int, input().split())) # Elements of array B
```

```
array_operations(A, B)
```

Average time
0.022 s
22.33 ms

Maximum time
0.034 s
34.00 ms

✓ 1 out of 1 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 34 ms DEBUG

Expected output

1 2 3 4
5 6 7 8
Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32
Mean of A: 2.5
Median of A: 2.5
Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12

Actual output

1 2 3 4
5 6 7 8
Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32
Mean of A: 2.5
Median of A: 2.5
Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12

3.2.5. NumPy: Copying and Viewing Array

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:
`Original array after modifying view: <original_array>`
`View array: <view_array>`
- After modifying the copy:
`Original array after modifying copy: <original_array>`
`Copy array: <copy_array>`

```
import numpy as np
```

```
inputlist = list(map(int,input().split(" ")))
```

```
original_array = np.array(inputlist)
```

```
view_array =original_array.view()
```

```
copy_array =original_array.copy()
```

```
view_array[0] = 99
```

```
print("Original array after modifying view:", original_array)
```

```
print("View array:", view_array)
```

```
copy_array[1] = 88
```

```
print("Original array after modifying copy:", original_array)
```

```
print("Copy array:", copy_array)
```

Average time
0.006 s
5.75 ms

Maximum time
0.009 s
9.00 ms

✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 9 ms

DEBUG

^

Expected output	Actual output
10 20 30 40 50 60 70 80	10 20 30 40 50 60 70 80
Original array after modifying view: [99 20 30 40 50 60 70 80]	Original array after modifying view: [99 20 30 40 50 60 70 80]
View array: [99 20 30 40 50 60 70 80]	View array: [99 20 30 40 50 60 70 80]
Original array after modifying copy: [99 20 30 40 50 60 70 80]	Original array after modifying copy: [99 20 30 40 50 60 70 80]
Copy array: [10 88 30 40 50 60 70 80]	Copy array: [10 88 30 40 50 60 70 80]

3.2.6. NumPy: Searching, Sorting, Counting, Broadcasting

The given code in the editor takes a single array, `array1`, as space-separated integers as input from the user.

Additionally, it takes the following inputs:

- `search_value`: The value to search for in the array.
- `count_value`: The value to count its occurrences in the array.
- `broadcast_value`: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

1. **Searching**: Find the indices where `search_value` appears in `array1` and print these indices.
2. **Counting**: Count how many times `count_value` appears in `array1` and print the count.
3. **Broadcasting**: Add `broadcast_value` to each element of `array1` using broadcasting, and print the resulting array.

4. Sorting Input Format:

1. A single line containing space-separated integers representing `array1`.
2. An integer `search_value` represents the value to search for in the array.
3. An integer `count_value` represents the value to count in the array.
4. An integer `broadcast_value` represents the value to add to each element of the array.

Output Format:

1. The indices where `search_value` occurs in `array1`.
2. The count of occurrences of `count_value` in `array1`.
3. The array after adding the `broadcast_value` to each element.
4. The sorted array.

```
import numpy as np
```

```
array1 = np.array(list(map(int, input().split())))
```

```
search_value = int(input("Value to search: "))
```

```
count_value = int(input("Value to count: "))
```

```
broadcast_value = int(input("Value to add: "))
```

```
indices=np.where(array1==search_value)[0]
```

```
print(indices)
```

```
count= np.count_nonzero(array1==count_value)
```

```
print(count)
```

```
broadcasted_array= array1+ broadcast_value
```

```
print(broadcasted_array)
```

```
sorted_array= np.sort(array1)
```

```
print(sorted_array)
```




Average time

0.024 s

23.75 ms



Maximum time

0.039 s

39.00 ms



✓ 2 out of 2 shown test case(s) passed

✓ 2 out of 2 hidden test case(s) passed

✓ Test case 1 39 ms

DEBUG



Expected output

1 1 1 2 2 2

Actual output

1 1 1 2 2 2

Value to search: 1

Value to search: 1

Value to count: 2

Value to count: 2

Value to add: 2

Value to add: 2

[0, 1, 2]

[0, 1, 2]

3

3

[3, 3, 3, 4, 4, 4]

[3, 3, 3, 4, 4, 4]

[1, 1, 1, 2, 2, 2]

[1, 1, 1, 2, 2, 2]

3.2.7. Student Data Analysis and Operations

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.

- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject:** Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored ≥ 90 :** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1:** Identify the index positions of students who scored exactly 79 marks in Subject 1.

Note: Fill in the missing code to perform the above-mentioned operations.

```
import numpy as np
```

```
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
```

```
# 1. Print all student details
```

```
print("All student Details:\n", a )
```

```
# 2. print total students
```

```
print("Total Students:", a.shape[0])
```

```
# 3. Print all student Roll numbers
```

```
print("All Student Roll Nos", a[:,0] )
```

```
# 4. Print subject 1 marks
```

```
print("Subject 1 Marks", a[:,1])
```

```
# 5. print minimum marks of Subject 2
```

```
print("Min marks in Subject 2", np.min(a[:,2]) )
```

```
# 6. print maximum marks of Subject 3
```

```
print("Max marks in Subject 3", np.max(a[:,3]) )
```

```
# 7. Print All subject marks
```

```
print("All subject marks:", a[:, 1:] )
```

```
# 8. print Total marks of students
```

```
print("Total Marks", np.sum(a[:,1:],axis=1) )
```

```
# 9. print average marks of each student
```

```
avg= np.mean(a[:,1:],axis=1)
```

```
print(np.round(avg,1))
```

```
# 10. print average marks of each subject
```

```
print("Average Marks of each subject", np.mean(a[:,1:],axis=0) )
```

```
# 11. print average marks of S1 and S2
```

```
print("Average Marks of S1 and S2", np.mean(a[:, 1:3],axis=0) )
```

```
# 12. print average marks of S1 and S3
```

```
print("Average Marks of S1 and S3", np.mean(a[:,[1,3]],axis=0) )
```

```
# 13. print Roll number who got maximum marks in Subject 3
```

```
print("Roll no who got maximum marks in Subject 3", a[np.argmax(a[:, 3]),0])
```

```
# 14. print Roll number who got minimum marks in Subject 2
```

```
print("Roll no who got minimum marks in Subject 2", a[np.argmin(a[:, 2]),0])
```

15. print Roll number who got 24 marks in Subject 2

```
print("Roll no who got 24 marks in Subject 2", a[a[:, 2]==24,0:1] )
```

16. print count of students who got marks in Subject 1 < 40

```
print("Count of students who got marks in Subject 1 < 40", np.sum(a[:, 1]<40)      )
```

17. print count of students who got marks in Subject 2 > 90

```
print("Count of students who got marks in Subject 2 > 90:", np.sum(a[:,2]>90)      )
```

18. print count of students in each subject who got marks >= 90

```
print("Count of students in each subject who got marks >= 90:", np.sum(a[:,1:]>=90,axis=0)      )
```

19. print count of subjects in which each student got marks >= 90

```
print("Roll no:",a[:,0]      )
```

```
print("Count of subjects in which student got marks >= 90:", np.sum(a[:,1:]>=90,axis=1)      )
```

20. Print S1 marks in ascending order

```
print(np.sort(a[:,1]))
```

21. Print S1 marks >= 50 and <= 90

```
print(a[(a[:,1]>=50)&(a[:,1]<=90)])
```

```
print(a)
```

22. Print the index position of marks 79

```
print(np.where(a[:,1]==79))
```



Average time

0.022 s
22.00 ms



Maximum time

0.022 s
22.00 ms



✓ 1 out of 1 shown test case(s) passed

✓ Test case 1 22 ms

DEBUG



Expected output

Actual output

All Student Details:

All Student Details:

· [[301, · · 67, · · 77, · · 88.]]

· [[301, · · 67, · · 77, · · 88.]]

· [302, · · 78, · · 88, · · 77.]]

· [302, · · 78, · · 88, · · 77.]]

· [303, · · 45, · · 56, · · 89.]]

· [303, · · 45, · · 56, · · 89.]]

· [304, · · 88, · · 98, · · 45.]]

· [304, · · 88, · · 98, · · 45.]]

· [305, · · 78, · · 88, · · 99.]]

· [305, · · 78, · · 88, · · 99.]]

· [306, · · 68, · · 78, · · 36.]]

· [306, · · 68, · · 78, · · 36.]]

· [307, · · 79, · · 12, · · 45.]]

· [307, · · 79, · · 12, · · 45.]]

· [308, · · 46, · · 45, · · 77.]]

· [308, · · 46, · · 45, · · 77.]]

· [309, · · 89, · · 32, · · 88.]]

· [309, · · 89, · · 32, · · 88.]]

· [310, · · 79, · · 24, · · 33.]]

· [310, · · 79, · · 24, · · 33.]]

Total Students: · 10

Total Students: · 10

All Student Roll Nos · [301, · 302, · 303, · 304, · 305, · 306, · 307, · 308, · 309, · 310.]]

All Student Roll Nos · [301, · 302, · 303, · 304, · 305, · 306, · 307, · 308, · 309, · 310.]]

Subject · 1 · Marks · [67, · 78, · 45, · 88, · 78, · 68, · 79, · 46, · 89, · 79.]]

Subject · 1 · Marks · [67, · 78, · 45, · 88, · 78, · 68, · 79, · 46, · 89, · 79.]]