Real-Time Systems

ARM Application, MCU, and Real-Time Series of Microprocessors

Dr. Sam Siewert

Electrical, Computer and Energy Engineering

Embedded Systems Engineering Program

Designed for MCU or Apps: ARM M & A Series

- ARM M Series - MCU
  - TIVA TM4C123G (M4), NXP, Cypress, Silicon Labs
  - The Cortex-M4 processor is developed to address digital signal control markets that demand an efficient, easy-to-use blend of control and signal processing capabilities.
  - RT Cyclic Executive would work well with M-Series

- ARM A Series - Advanced Mobile
  - Smart Phone
  - Qualcomm, Broadcomm, NVIDIA
  - Harvard Split L1, Unified L2, L3, Multi-core
  - The processor cluster has one to four cores. Each core has its own L1 instruction and data caches, together with a single shared L2 unified cache.



Designed for Real-Time: ARM R Series

- ARM R Series - Real-Time
  - Redundancy (no SPOFs) - Lock-step MISD
  - Predictable / Deterministic response (TCM)
  - Resilience - recovery and fail-safe
  - ECC memory
  - Flash memory with data protection
  - Software sanity monitoring
  - RT critical services
  - Best-effort services
  - The Cortex-R52 processor meets the rising performance needs of advanced real-time embedded systems.