

Phân tích dữ liệu thông minh

Support Vector Machine


TS. Nguyễn Tiến Huy

ntienhuy@fit.hcmus.edu.vn



Content

- 1 Problem of Classification
- 2 SVM
- 3 Kernel Trick
- 4 Multiclass classification



The Problem of Classification




The Problem of Classification




The Problem of Classification







- Find lines that correctly classify the training data
- Among all such lines, pick the one that has the greatest distance to the points closest to it.




How about errors?




C parameter in SVM



Non-linearly Separable Data



Non-linearly Separable Data




$$X_1 = x_1^2$$


$$X_2 = x_2^2$$

$$X_3 = \sqrt{2}x_1x_2$$



Non-linearly Separable Data



Non-linearly Separable Data



Non-linearly Separable Data



Multiclass classification

- One vs. One
- One vs. Rest

Example

For example consider four class problem having classes A, B, C, and D.

- One vs. Rest
 - Models classifiers_A, classifier_B, classifier_C and classifier_D
 - During prediction here is the probability we get:
 - classifier_A = 40%
 - classifier_B = 30%
 - classifier_C = 60%
 - classifier_D = 50%
 - We assign it class C

Example

- One vs One
 - We train total six classifier with subset of data containing classes involved
 - classifier_AB
 - classifier_AC
 - classifier_AD
 - classifier_BC
 - classifier_BD
 - classifier_CD
 - And during classification
 - classifier_AB assigns class A
 - classifier_AC assigns class A
 - classifier_AD assigns class A
 - classifier_BC assigns class B
 - classifier_BD assigns class D
 - classifier_CD assigns class C
 - We assign it to class A

Conclusion

- SVM for classification
- Kernel tricks
- Multiclass classification

Cảm ơn đã theo dõi!