

The title should simply and concisely convey the main findings.

Avoid nonstandard abbreviations and acronyms.

Ann Author* and Second Author[†]

Authors' affiliations

*Include all institutions where the work was conducted: department or division,
institution, city, state (if relevant),
and country, in this order.*

Charlie Author[‡]

*First affiliation for this author and
second institution for this author*

Delta Author

Authors' institution and/or address

This line break forced with \|

(CLEO Collaboration)

(Dated: May 17, 2026)

Abstract

An article usually includes an abstract, a concise summary of the work covered at length in the main body of the article.

Usage: Secondary publications and information retrieval purposes.

Structure: You may use the `description` environment to structure your abstract; use the optional argument of the `\item` command to give the category of each item.

16 I. FIRST-LEVEL HEADING:

17 THE LINE BREAK WAS FORCED via \\

18 This sample document demonstrates proper use of REVTeX 4.2 (and L^AT_EX 2_ε) in
19 manuscripts prepared for submission to APS journals. Further information can be found
20 in the REVTeX 4.2 documentation included in the distribution or available at [http:](http://journals.aps.org/revtex/)
21 [//journals.aps.org/revtex/](http://journals.aps.org/revtex/).

22 When commands are referred to in this example file, they are always shown with their
23 required arguments, using normal T_EX format. In this format, #1, #2, etc. stand for required
24 author-supplied arguments to commands. For example, in `\section{#1}` the #1 stands for
25 the title text of the author's section heading, and in `\title{#1}` the #1 stands for the title
26 text of the paper.

27 Line breaks in section headings at all levels can be introduced using `\\`. A blank input
28 line tells T_EX that the paragraph has ended. Note that top-level section headings are
29 automatically uppercased. If a specific letter or word should appear in lowercase instead,
30 you must escape it using `\lowercase{#1}` as in the word “via” above.

31 A. Second-level heading: Formatting

32 This file may be formatted in either the `preprint` or `reprint` style. `reprint` format
33 mimics final journal output. Either format may be used for submission purposes. `letter`
34 sized paper should be used when submitting to APS journals.

* Also at Physics Department, XYZ University.

† Contact author: Second.Author@institution.edu

‡ <http://www.Second.institution.edu/~Charlie.Author>

1. *Wide text (A level-3 head)*

The `widetext` environment will make the text the width of the full page, as on page ??.
(Note the use the `\pageref{#1}` command to refer to the page number.)

a. Note (Fourth-level head is run in). The width-changing commands only take effect in two-column formatting. There is no effect if text is in a single column.

B. Citations and references

A citation in text uses the command `\cite{#1}` or `\onlinecite{#1}` and refers to an entry in the bibliography. An entry in the bibliography is a reference to another document.

1. Citations

Because REVTeX uses the `natbib` package of Patrick Daly, the entire repertoire of commands in that package are available for your document; see the `natbib` documentation for further details. Please note that REVTeX requires version 8.31a or later of `natbib`.

a. Syntax. The argument of `\cite` may be a single *key*, or may consist of a comma-separated list of keys. The citation *key* may contain letters, numbers, the dash (-) character, or the period (.) character. New with `natbib` 8.3 is an extension to the syntax that allows for a star (*) form and two optional arguments on the citation key itself. The syntax of the `\cite` command is thus (informally stated)

`\cite { key },` or
`\cite { optarg+key },` or
`\cite { optarg+key , optarg+key...},`
where *optarg+key* signifies

key, or
**key*, or
[pre] key, or
[pre] [post] key, or even
**[pre] [post] key*.

61 where *pre* and *post* is whatever text you wish to place at the beginning and end, respectively,
62 of the bibliographic reference (see Ref. [?]] and the two under Ref. [?]). (Keep in mind that
63 no automatic space or punctuation is applied.) It is highly recommended that you put the
64 entire *pre* or *post* portion within its own set of braces, for example: `\cite { [ {text}]key}`.
65 The extra set of braces will keep L^AT_EX out of trouble if your *text* contains the comma (,) character.

67 The star (*) modifier to the *key* signifies that the reference is to be merged with the
68 previous reference into a single bibliographic entry, a common idiom in APS and AIP articles
69 (see below, Ref. [?]). When references are merged in this way, they are separated by a
70 semicolon instead of the period (full stop) that would otherwise appear.

71 *b. Eliding repeated information.* When a reference is merged, some of its fields may be
72 elided: for example, when the author matches that of the previous reference, it is omitted.
73 If both author and journal match, both are omitted. If the journal matches, but the author
74 does not, the journal is replaced by *ibid.*, as exemplified by Ref. [?]]. These rules embody
75 common editorial practice in APS and AIP journals and will only be in effect if the markup
76 features of the APS and AIP BibT_EX styles is employed.

77 *c. The options of the cite command itself.* Please note that optional arguments to the
78 *key* change the reference in the bibliography, not the citation in the body of the document.
79 For the latter, use the optional arguments of the `\cite` command itself: `\cite *[pre-cite]`
80 `[post-cite]{key-list}`.

81 2. Example citations

82 By default, citations are numerical [?]]. Author-year citations are used when the journal
83 is RMP. To give a textual citation, use `\onlinecite{#1}`: Refs. ? ? . By default, the
84 `natbib` package automatically sorts your citations into numerical order and “compresses”
85 runs of three or more consecutive numerical citations. REV_TE_X provides the ability to
86 automatically change the punctuation when switching between journal styles that provide
87 citations in square brackets and those that use a superscript style instead. This is done
88 through the `citeautoscript` option. For instance, the journal style `prb` automatically
89 invokes this option because *Physical Review B* uses superscript-style citations. The effect is
90 to move the punctuation, which normally comes after a citation in square brackets, to its

proper position before the superscript. To illustrate, we cite several together [? ? ? ? ? ?], and once again in different order (Refs. [? ? ? ? ? ?]). Note that the citations were both compressed and sorted. Furthermore, running this sample file under the `prb` option will move the punctuation to the correct place.

When the `prb` class option is used, the `\cite{#1}` command displays the reference's number as a superscript rather than in square brackets. Note that the location of the `\cite{#1}` command should be adjusted for the reference style: the superscript references in `prb` style must appear after punctuation; otherwise the reference must appear before any punctuation. This sample was written for the regular (non-`prb`) citation style. The command `\onlinecite{#1}` in the `prb` style also displays the reference on the baseline.

3. References

A reference in the bibliography is specified by a `\bibitem{#1}` command with the same argument as the `\cite{#1}` command. `\bibitem{#1}` commands may be crafted by hand or, preferably, generated by Bib_T_EX. REV_T_EX 4.2 includes Bib_T_EX style files `apsrev4-2.bst`, `apsrmp4-2.bst` appropriate for *Physical Review* and *Reviews of Modern Physics*, respectively.

4. Example references

This sample file employs the `\bibliography` command, which formats the `apssamp.bbl` file and specifies which bibliographic databases are to be used by Bib_T_EX (one of these should be by arXiv convention `apssamp.bib`). Running Bib_T_EX (via `bibtex apssamp`) after the first pass of L_AT_EX produces the file `apssamp.bbl` which contains the automatically formatted `\bibitem` commands (including extra markup information via `\bibinfo` and `\bibfield` commands). If not using Bib_T_EX, you will have to create the `thebibliography` environment and its `\bibitem` commands by hand.

Numerous examples of the use of the APS bibliographic entry types appear in the bibliography of this sample document. You can refer to the `apssamp.bib` file, and compare its information to the formatted bibliography itself.

C. Footnotes

Footnotes, produced using the `\footnote{#1}` command, usually integrated into the bibliography alongside the other entries. Numerical citation styles do this[?]; author-year citation styles place the footnote at the bottom of the text column. Note: due to the method used to place footnotes in the bibliography, *you must re-run BibTeX every time you change any of your document's footnotes.*

II. MATH AND EQUATIONS

Inline math may be typeset using the `$` delimiters. Bold math symbols may be achieved using the `bm` package and the `\bm{#1}` command it supplies. For instance, a bold α can be typeset as `$_\bm{\alpha}$` giving α . Fraktur and Blackboard (or open face or double struck) characters should be typeset using the `\mathfrak{#1}` and `\mathbb{#1}` commands respectively. Both are supplied by the `amssymb` package. For example, `$_\mathbb{R}$` gives $\mathbb{R}$ and `$_\mathfrak{G}$` gives $\mathfrak{G}$.

In $\text{\LaTeX}$ there are many different ways to display equations, and a few preferred ways are noted below. Displayed math will center by default. Use the class option `fleqn` to flush equations left.

Below we have numbered single-line equations; this is the most common type of equation in *Physical Review*:

$$\chi_+(p) \lesssim [2|\mathbf{p}|(|\mathbf{p}| + p_z)]^{-1/2} \begin{pmatrix} |\mathbf{p}| + p_z \\ px + ip_y \end{pmatrix}, \quad (1)$$

$$\left\{ \mathbb{1}234567890abc123\alpha\beta\gamma\delta1234556\alpha\beta\frac{1\sum_b^a}{A^2} \right\}. \quad (2)$$

Note the open one in Eq. (??).

Not all numbered equations will fit within a narrow column this way. The equation number will move down automatically if it cannot fit on the same line with a one-line equation:

$$\left\{ ab12345678abc123456abcdef\alpha\beta\gamma\delta1234556\alpha\beta\frac{1\sum_b^a}{A^2} \right\}. \quad (3)$$

When the `\label{#1}` command is used [cf. input for Eq. (??)], the equation can be referred to in text without knowing the equation number that $\text{\TeX}$ will assign to it. Just

142 use `\ref{#1}`, where `#1` is the same name that used in the `\label{#1}` command.

143 Unnumbered single-line equations can be typeset using the `\[, \]` format:

$$g^+g^+ \rightarrow g^+g^+g^+g^+ \dots, \quad q^+q^+ \rightarrow q^+g^+g^+ \dots$$

144 A. Multiline equations

145 Multiline equations are obtained by using the `eqnarray` environment. Use the `\nonumber`
146 command at the end of each line to avoid assigning a number:

$$\begin{aligned} \mathcal{M} = & \ i g_Z^2 (4E_1 E_2)^{1/2} (l_i^2)^{-1} \delta_{\sigma_1, -\sigma_2} (g_{\sigma_2}^e)^2 \chi_{-\sigma_2}(p_2) \\ & \times [\epsilon_j l_i \epsilon_i]_{\sigma_1} \chi_{\sigma_1}(p_1), \end{aligned} \tag{4}$$

147

$$\begin{aligned} \sum |M_g^{\text{viol}}|^2 = & \ g_S^{2n-4} (Q^2) N^{n-2} (N^2 - 1) \\ & \times \left(\sum_{i < j} \right) \sum_{\text{perm}} \frac{1}{S_{12}} \frac{1}{S_{12}} \sum_{\tau} c_{\tau}^f. \end{aligned} \tag{5}$$

148 **Note:** Do not use `\label{#1}` on a line of a multiline equation if `\nonumber` is also used
149 on that line. Incorrect cross-referencing will result. Notice the use `\text{#1}` for using a
150 Roman font within a math environment.

151 To set a multiline equation without *any* equation numbers, use the `\begin{eqnarray*}`,
152 `\end{eqnarray*}` format:

$$\begin{aligned} \sum |M_g^{\text{viol}}|^2 = & \ g_S^{2n-4} (Q^2) N^{n-2} (N^2 - 1) \\ & \times \left(\sum_{i < j} \right) \left(\sum_{\text{perm}} \frac{1}{S_{12} S_{23} S_{n1}} \right) \frac{1}{S_{12}}. \end{aligned}$$

153 To obtain numbers not normally produced by the automatic numbering, use the `\tag{#1}`
154 command, where `#1` is the desired equation number. For example, to get an equation number
155 of `(??)`,

$$g^+g^+ \rightarrow g^+g^+g^+g^+ \dots, \quad q^+q^+ \rightarrow q^+g^+g^+ \dots \tag{2.6'}$$

156 *a. A few notes on tags* `\tag{#1}` requires the `amsmath` package. Place the `\tag{#1}`
157 command before the `\label{#1}`, if any. The numbering produced by `\tag{#1}` *does not*
158 *affect* the automatic numbering in REVTeX; therefore, the number must be known ahead
159 of time, and it must be manually adjusted if other equations are added. `\tag{#1}` works

with both single-line and multiline equations. `\tag{#1}` should only be used in exceptional cases—do not use it to number many equations in your paper. Please note that this feature of the `amsmath` package is *not* compatible with the `hyperref` (6.77u) package.

Enclosing display math within `\begin{subequations}` and `\end{subequations}` will produce a set of equations that are labeled with letters, as shown in Eqs. (??) and (??) below. You may include any number of single-line and multiline equations, although it is probably not a good idea to follow one display math directly after another.

$$\begin{aligned} \mathcal{M} = & \ ig_Z^2(4E_1E_2)^{1/2}(l_i^2)^{-1}(g_{\sigma_2}^e)^2\chi_{-\sigma_2}(p_2) \\ & \times [\epsilon_i]_{\sigma_1}\chi_{\sigma_1}(p_1). \end{aligned} \quad (6a)$$

$$\left\{ abc123456abcdef\alpha\beta\gamma\delta1234556\alpha\beta\frac{1\sum_b^a}{A^2} \right\}, \quad (6b)$$

Giving a `\label{#1}` command directly after the `\begin{subequations}`, allows you to reference all the equations in the `subequations` environment. For example, the equations in the preceding `subequations` environment were Eqs. (??).

1. Wide equations

The equation that follows is set in a wide format, i.e., it spans the full page. The wide format is reserved for long equations that cannot easily be set in a single column:

$$\mathcal{R}^{(d)} = g_{\sigma_2}^e \left(\frac{[\Gamma^Z(3, 21)]_{\sigma_1}}{Q_{12}^2 - M_W^2} + \frac{[\Gamma^Z(13, 2)]_{\sigma_1}}{Q_{13}^2 - M_W^2} \right) + x_W Q_e \left(\frac{[\Gamma^\gamma(3, 21)]_{\sigma_1}}{Q_{12}^2 - M_W^2} + \frac{[\Gamma^\gamma(13, 2)]_{\sigma_1}}{Q_{13}^2 - M_W^2} \right). \quad (7)$$

This is typed to show how the output appears in wide format. (Incidentally, since there is no blank line between the `equation` environment above and the start of this paragraph, this paragraph is not indented.)

III. CROSS-REFERENCING

REVTeX will automatically number such things as sections, footnotes, equations, figure captions, and table captions. In order to reference them in text, use the `\label{#1}` and `\ref{#1}` commands. To reference a particular page, use the `\pageref{#1}` command.

181 The `\label{#1}` should appear within the section heading, within the footnote text,
 182 within the equation, or within the table or figure caption. The `\ref{#1}` command is used
 183 in text at the point where the reference is to be displayed. Some examples: Section ?? on
 184 page ??, Table ??, and Fig. ??.

187 IV. FLOATS: FIGURES, TABLES, VIDEOS, ETC.

188 Figures and tables are usually allowed to “float”, which means that their placement is
 189 determined by L^AT_EX, while the document is being typeset.

190 Use the `figure` environment for a figure, the `table` environment for a table. In each
 191 case, use the `\caption` command within to give the text of the figure or table caption along
 192 with the `\label` command to provide a key for referring to this figure or table. The typical
 193 content of a figure is an image of some kind; that of a table is an alignment.

196 Insert an image using either the `graphics` or `graphicx` packages, which define the
 197 `\includegraphics{#1}` command. (The two packages differ in respect of the optional
 198 arguments used to specify the orientation, scaling, and translation of the image.) To create
 199 an alignment, use the `tabular` environment.

200 The best place to locate the `figure` or `table` environment is immediately following its
 201 first reference in text; this sample document illustrates this practice for Fig. ??, which shows

TABLE I. A table that fits into a single column of a two-column layout. Note that REV_TE_X 4
 adjusts the intercolumn spacing so that the table fills the entire width of the column. Table
 captions are numbered automatically. This table illustrates left-, center-, decimal- and right-aligned
 columns, along with the use of the `ruledtabular` environment which sets the Scotch (double) rules
 above and below the alignment, per APS style.

Left ^a	Centered ^b	Decimal	Right
1	2	3.001	4
10	20	30	40
100	200	300.0	400

^a Note a.

^b Note b.

TABLE II. This is a wide table that spans the full page width in a two-column layout. It is formatted using the `table*` environment. It also demonstrates the use of `\multicolumn` in rows with entries that span more than one column.

Ion	D_{4h}^1		D_{4h}^5	
	1st alternative	2nd alternative	1st alternative	2nd alternative
K	$(2e) + (2f)$	$(4i)$	$(2c) + (2d)$	$(4f)$
Mn	$(2g)^a$	$(a) + (b) + (c) + (d)$	$(4e)$	$(2a) + (2b)$
Cl	$(a) + (b) + (c) + (d)$	$(2g)^a$	$(4e)^a$	
He	$(8r)^a$	$(4j)^a$	$(4g)^a$	
Ag		$(4k)^a$		$(4h)^a$

^a The z parameter of these positions is $z \sim \frac{1}{4}$.

a figure that is small enough to fit in a single column.

In exceptional cases, you will need to move the float earlier in the document, as was done with Table ??: L^AT_EX's float placement algorithms need to know about a full-page-width float earlier.

Fig. ?? has content that is too wide for a single column, so the `figure*` environment has been used.

The content of a table is typically a `tabular` environment, giving rows of type in aligned columns. Column entries separated by `&`'s, and each row ends with `\\`. The required argument for the `tabular` environment specifies how data are aligned in the columns. For instance, entries may be centered, left-justified, right-justified, aligned on a decimal point. Extra column-spacing may be specified as well, although REVTeX 4 sets this spacing so that the columns fill the width of the table. Horizontal rules are typeset using the `\hline` command. The doubled (or Scotch) rules that appear at the top and bottom of a table can be achieved enclosing the `tabular` environment within a `ruledtabular` environment. Rows whose columns span multiple columns can be typeset using the `\multicolumn{#1}{#2}{#3}` command (for example, see the first row of Table ??).

FIG. 1. A figure caption. The figure captions are automatically numbered.

FIG. 2. Use the `figure*` environment to get a wide figure that spans the page in `twocolumn` formatting.

220 Tables ??, ??, ??, and ?? show various effects. A table that fits in a single column
 221 employs the `table` environment. Table ?? is a wide table, set with the `table*` environment.
 222 Long tables may need to break across pages. The most straightforward way to accomplish
 223 this is to specify the `[H]` float placement on the `table` or `table*` environment. However,
 224 the $\text{\LaTeX} 2_{\epsilon}$ package `longtable` allows headers and footers to be specified for each page of
 225 the table. A simple example of the use of `longtable` can be found in the file `summary.tex`
 226 that is included with the REV $\text{\TeX}$ 4 distribution.

227 There are two methods for setting footnotes within a table (these footnotes will be dis-
 228 played directly below the table rather than at the bottom of the page or in the bibliogra-
 229 phy). The easiest and preferred method is just to use the `\footnote{#1}` command. This
 230 will automatically enumerate the footnotes with lowercase roman letters. However, it is
 231 sometimes necessary to have multiple entries in the table share the same footnote. In this
 232 case, there is no choice but to manually create the footnotes using `\footnotemark{#1}` and
 233 `\footnotetext{#1}{#2}`. `#1` is a numeric value. Each time the same value for `#1` is used,
 234 the same mark is produced in the table. The `\footnotetext{#1}{#2}` commands are placed
 235 after the `tabular` environment. Examine the $\text{\LaTeX}$ source and output for Tables ?? and
 236 ?? for examples.

TABLE III. Numbers in columns Three–Five are aligned with the “d” column specifier (requires the `dcolumn` package). Non-numeric entries (those entries without a “.”) in a “d” column are aligned on the decimal point. Use the “D” specifier for more complex layouts.

One	Two	Three	Four	Five
one	two	three	four	five
He	2	2.77234	45672.	0.69
C ^a	C ^b	12537.64	37.66345	86.37

^a Some tables require footnotes.

^b Some tables need more than one footnote.

Video 1. Students explain their initial idea about Newton’s third law to a teaching assistant. Clip (a): same force. Clip (b): move backwards.

237 Video ?? illustrates several features new with REVTeX4.2, starting with the `video` en-
 239 vironment, which is in the same category with `figure` and `table`. The `\setfloatlink`
 240 command causes the title of the video to be a hyperlink to the indicated URL; it may be
 241 used with any environment that takes the `\caption` command. The `\href` command has the
 242 same significance as it does in the context of the `hyperref` package: the second argument
 243 is a piece of text to be typeset in your document; the first is its hyperlink, a URL.

244 *Physical Review* style requires that the initial citation of figures or tables be in numerical
 245 order in text, so don’t cite Fig. ?? until Fig. ?? has been cited.

TABLE IV. A table with numerous columns that still fits into a single column. Here, several entries share the same footnote. Inspect the L^AT_EX input for this table to see exactly how it is done.

	r_c (Å)	r_0 (Å)	κr_0		r_c (Å)	r_0 (Å)	κr_0
Cu	0.800	14.10	2.550	Sn ^a	0.680	1.870	3.700
Ag	0.990	15.90	2.710	Pb ^b	0.450	1.930	3.760
Au	1.150	15.90	2.710	Ca ^c	0.750	2.170	3.560
Mg	0.490	17.60	3.200	Sr ^d	0.900	2.370	3.720
Zn	0.300	15.20	2.970	Li ^b	0.380	1.730	2.830
Cd	0.530	17.10	3.160	Na ^e	0.760	2.110	3.120
Hg	0.550	17.80	3.220	K ^e	1.120	2.620	3.480
Al	0.230	15.80	3.240	Rb ^c	1.330	2.800	3.590
Ga	0.310	16.70	3.330	Cs ^d	1.420	3.030	3.740
In	0.460	18.40	3.500	Ba ^e	0.960	2.460	3.780
Tl	0.480	18.90	3.550				

^a Here’s the first, from Ref. ? .

^b Here’s the second.

^c Here’s the third.

^d Here’s the fourth.

^e And etc.

246 **ACKNOWLEDGMENTS**

247 We wish to acknowledge the support of the author community in using REVTeX, offering
248 suggestions and encouragement, testing new versions,

249 **Appendix A: Appendixes**

250 To start the appendixes, use the `\appendix` command. This signals that all following
251 section commands refer to appendixes instead of regular sections. Therefore, the `\appendix`
252 command should be used only once—to setup the section commands to act as appendixes.
253 Thereafter normal section commands are used. The heading for a section can be left empty.
254 For example,

255 `\appendix`

256 `\section{}`

257 will produce an appendix heading that says “APPENDIX A” and

258 `\appendix`

259 `\section{Background}`

260 will produce an appendix heading that says “APPENDIX A: BACKGROUND” (note that
261 the colon is set automatically).

262 If there is only one appendix, then the letter “A” should not appear. This is suppressed
263 by using the star version of the appendix command (`\appendix*` in the place of `\appendix`).

264 **Appendix B: A little more on appendixes**

265 Observe that this appendix was started by using

266 `\section{A little more on appendixes}`

267 Note the equation number in an appendix:

$$E = mc^2. \tag{B1}$$

268 **1. A subsection in an appendix**

269 You can use a subsection or subsubsection in an appendix. Note the numbering: we are
270 now in Appendix ??.

271 Note the equation numbers in this appendix, produced with the subequations environ-
272 ment:

$$E = mc, \tag{B2a}$$

$$E = mc^2, \tag{B2b}$$

$$E \gtrsim mc^3. \tag{B2c}$$

273 They turn out to be Eqs. (??), (??), and (??).