Date No

① class HinhHoc {
    prablic void tinhDienTich () {
        System.out.println ("Tinh Dien Tich Hinh Hoc:");
    }
}

class HinhTron ~~{~~ extends HinhHoc {
    public ~~float~~ double r;
    public HinhTron (double r) {
        this.r = r; }
    ~~public get R () {~~
    @ Override
    public void tinhDienTich () {
        double DienTich = Math.PI * r * r;
        System.out.println ("DT Hinh Tron: " + DienTich);
    }
}
class HinhChuNhat extends HinhHoc {
    public double a;
    public double b;
    public HinhChuNhat (double a, double b) {
        this.a = a;

Date No

```
    this.b = b;
}
@Override
public void tinhDienTich(){
    double dienTich = a * b;
    System.out.println("DT HinhChuNhat: " + dienTich);
}
}
public class Main{
    public static void main(String[] args){

    HinhHoc h1 = new HinhTron(5);
    HinhHoc h2 = new HinhChuNhat(4, 6);

    h1.tinhDienTich();
    h2.tinhDienTich();
    }
}
```

* Đa hình là cùng 1 hành động với ngữ cảnh ≠ nhau cho ra ~ hành động / kết quả ≠ nhau

Date No

② class XeDap {
    ~~public~~ String ~~chay~~ ten;
    public XeDap (String ~~chay~~ ten) {
        this. ~~chay~~ ten = ~~chay~~ ten ;
    }
    public void run () {
        System. out. println (~~"Lach chay: " + chay~~ ten + " Lach chay"),
    }
}

class XeDapDien {
    public ~~String~~ XeDapDien (String ten) {
        super (ten) ;
    }
    @ Override
    public void run () {
        System. out. println (ten + " Vung ga!"),
    }
}

class Main {
    public ~~void~~ static void main (String [] args) {

        XeDapDien = new XeDapDien (" Pegabike "),

        XeDapDien. run () ;
}

Date No

(1)
```
class Person {
    private String name;
    private Date birthday;
    public Person ( String name, Date birthday ) {
        this. name = name;
        this. birthday = birthday;
    }

    ~~public getName ()~~
        ~~return. this. name; }~~
    public void setName ( String name ) {
        this.name = name; }
    public void setBirthday ( Date birthday ) {
        this. birthday = birthday; }
String public ~~void~~ getDetails () {
    return ~~System. out. println~~ ( ~~"Name~~ + name + " " + birthday);
    }
}

class Employee extends Person {
    private double salary;
    public Employee ( String name, Date birthday, double
                                                salary ) {

        this. salary = salary;
        super ( name, birthday );
    }
    (a) Overrode
    public void getDetails () {
        System. out. println ( name + birthday + salary);
    }
}
```

Date No

```
class Manager extends Employee {
    private Employee assistant;
    public Manager (String name, Date birthday, double
                    salary, Employee assistant){
        super (name, birthday, salary);
        this.assistant = assistant;
    }
    public void setAssistant (Employee assistant){
        this.assistant = assistant; }
    public String getDetails (){
        return name + birthday + salary + assistant; }
}
class Main {
    public static void main (String [] args){

    Employee epe1 = new Employee ("Ng Van A", "11/1/19
                                  2000000);
    Manager mng1 = new Manager ("Ng Van B", "22/12/2
                                30000000, epe1);
    epe1.getDetails();
    mng1.getDetails();
    }
}
```

Date No

1)
```
Class NganHang {
    public double rate;
    public NganHang ( double rate){
        this.rate = rate;
    }

    public void Tile (){
        System.out.println ("Tile lãi suất: " + rate),
    }
}

Class SBI extend NganHang {
    @Override
    public void Tile (){
        System.out.println ("Tile của SBI: " + rate);
    }
}

Class ICICI extend NganHang {
    @Override
    public void Tile (){
        System.out.println ("Tile của ICICI : " + rate);
    }
}

Class AXIS extend NganHang {
    @Override
    public void Tile(){
        System.out.println ("Tile của AXIS: " + rate);
    }
}
```

Date No

```
Class Main {
    public static void main ( String [] args ) {

        SBI s = new SBI ( 8.0 );
        ICICI i = new ICICI ( 7.0 );
        AXIS a = new AXIS ( 9.0 );

        s. Tile ();
        i. Tile ();
        a. Tile ();

    }
}
```

Date No

(5)
```
Class Car {
    public ~~String~~ void Move (){
        System. out. println (" Each chay ok. ");
    }
}
Class LandRover extends Car {
    @ Override
    public void Move (){
        System. out. println (" Each chay LandRover ");
    }
}
Class Ford extends Car {
    @ Override
    public void Move (){
        System. out. println ("Each chay Ford");
    }
}
Class Honda extends Car {
    @ Override
    public void Move(){
        System. out. println (" Each Chay Honda");
    }
}
Class Main {
    public ~~the~~ static void main (String [] args){

        Car c1 = new LandRover ();
```

MGP

No

Date

```
Car c2 = new Ford ();
Car c3 = new Hyundai ();

c1.Move ();
c2.Move ();
c3.Move ();
```