

```
In [1]: import findspark
findspark.init()
```

```
In [16]: spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()

print(spark)
rdd=spark.sparkContext.parallelize([1,2,3,4,56])
print("RDD count :"+str(rdd.count()))

rdd = spark.sparkContext.emptyRDD
print(rdd)
rdd2 = spark.sparkContext.parallelize([])
print(rdd2)
```

```
<pyspark.sql.session.SparkSession object at 0x000001E9F74C29D0>
RDD count :5
<bound method SparkContext.emptyRDD of <SparkContext master=local[*] appName=SparkByExamples.com>>
ParallelCollectionRDD[325] at readRDDFromFile at PythonRDD.scala:274
```

```
In [17]: spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()
rdd=spark.sparkContext.parallelize([1,2,3,4,5])

rddCollect = rdd.collect()
print("Number of Partitions: "+str(rdd.getNumPartitions()))
print("Action: First element: "+str(rdd.first()))
print(rddCollect)

emptyRDD = spark.sparkContext.emptyRDD()
emptyRDD2 = rdd=spark.sparkContext.parallelize([])

print(""+str(emptyRDD2.isEmpty()))
```

```
Number of Partitions: 8
Action: First element: 1
[1, 2, 3, 4, 5]
True
```

```

In [2]: import pyspark
        from pyspark.sql import SparkSession

spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()

data = [("James", "", "Smith", "36636", "M", 60000),
        ("Michael", "Rose", "", "40288", "M", 70000),
        ("Robert", "", "Williams", "42114", "", 400000),
        ("Maria", "Anne", "Jones", "39192", "F", 500000),
        ("Jen", "Mary", "Brown", "", "F", 0)]

columns = ["first_name", "middle_name", "last_name", "dob", "gender", "salary"]
pysparkDF = spark.createDataFrame(data = data, schema = columns)
pysparkDF.printSchema()
pysparkDF.show(truncate=False)

pandasDF = pysparkDF.toPandas()
print(pandasDF)

# Nested structure elements
from pyspark.sql.types import StructType, StructField, StringType, IntegerType
dataStruct = [(("James", "", "Smith"), "36636", "M", "3000"), \
              (("Michael", "Rose", ""), "40288", "M", "4000"), \
              (("Robert", "", "Williams"), "42114", "M", "4000"), \
              (("Maria", "Anne", "Jones"), "39192", "F", "4000"), \
              (("Jen", "Mary", "Brown"), "", "F", "-1") \
              ]

schemaStruct = StructType([
    StructField('name', StructType([
        StructField('firstname', StringType(), True),
        StructField('middlename', StringType(), True),
        StructField('lastname', StringType(), True)
    ])),
    StructField('dob', StringType(), True),
    StructField('gender', StringType(), True),
    StructField('salary', StringType(), True)
])

df = spark.createDataFrame(data=dataStruct, schema = schemaStruct)
df.printSchema()
df.show(truncate=False)

pandasDF2 = df.toPandas()
print(pandasDF2)

root
|-- first_name: string (nullable = true)
|-- middle_name: string (nullable = true)
|-- last_name: string (nullable = true)
|-- dob: string (nullable = true)
|-- gender: string (nullable = true)
|-- salary: long (nullable = true)

```

```

+-----+-----+-----+-----+-----+-----+

```

first_name	middle_name	last_name	dob	gender	salary
James		Smith	36636	M	60000
Michael	Rose		40288	M	70000
Robert		Williams	42114		400000
Maria	Anne	Jones	39192	F	500000
Jen	Mary	Brown		F	0

	first_name	middle_name	last_name	dob	gender	salary
0	James		Smith	36636	M	60000
1	Michael	Rose		40288	M	70000
2	Robert		Williams	42114		400000
3	Maria	Anne	Jones	39192	F	500000
4	Jen	Mary	Brown		F	0

```
root
```

```
-- name: struct (nullable = true)
|   |-- firstname: string (nullable = true)
|   |-- middlename: string (nullable = true)
|   |-- lastname: string (nullable = true)
|-- dob: string (nullable = true)
|-- gender: string (nullable = true)
|-- salary: string (nullable = true)
```

name	dob	gender	salary
{James, , Smith}	36636	M	3000
{Michael, Rose, }	40288	M	4000
{Robert, , Williams}	42114	M	4000
{Maria, Anne, Jones}	39192	F	4000
{Jen, Mary, Brown}		F	-1

	name	dob	gender	salary
0	(James, , Smith)	36636	M	3000
1	(Michael, Rose,)	40288	M	4000
2	(Robert, , Williams)	42114	M	4000
3	(Maria, Anne, Jones)	39192	F	4000
4	(Jen, Mary, Brown)		F	-1

```
In [3]: spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()

data = ["Project Gutenberg's",
        "Alice's Adventures in Wonderland",
        "Project Gutenberg's",
        "Adventures in Wonderland",
        "Project Gutenberg's"]
rdd=spark.sparkContext.parallelize(data)

for element in rdd.collect():
    print(element)

#Flatmap
rdd2=rdd.flatMap(lambda x: x.split(" "))
for element in rdd2.collect():
    print(element)
```

```
Project Gutenberg's
Alice's Adventures in Wonderland
Project Gutenberg's
Adventures in Wonderland
Project Gutenberg's
Project
Gutenberg's
Alice's
Adventures
in
Wonderland
Project
Gutenberg's
Adventures
in
Wonderland
Project
Gutenberg's
```

```
In [4]: spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()

dept = [("Finance",10),
        ("Marketing",20),
        ("Sales",30),
        ("IT",40)
        ]
rdd = spark.sparkContext.parallelize(dept)

df = rdd.toDF()
df.printSchema()
df.show(truncate=False)

deptColumns = ["dept_name","dept_id"]
df2 = rdd.toDF(deptColumns)
df2.printSchema()
df2.show(truncate=False)

deptDF = spark.createDataFrame(data=dept, schema = deptColumns)
deptDF.printSchema()
deptDF.show(truncate=False)

from pyspark.sql.types import StructType,StructField, StringType
deptSchema = StructType([
    StructField('dept_name', StringType(), True),
    StructField('dept_id', StringType(), True)
])

deptDF1 = spark.createDataFrame(data=dept, schema = deptSchema)
deptDF1.printSchema()
deptDF1.show(truncate=False)
```

```
root
|-- _1: string (nullable = true)
|-- _2: long (nullable = true)
```

```
+-----+-----+
|_1      |_2 |
+-----+-----+
|Finance |10 |
|Marketing|20 |
|Sales   |30 |
|IT      |40 |
+-----+-----+
```

```
root
|-- dept_name: string (nullable = true)
|-- dept_id: long (nullable = true)
```

```
+-----+-----+
|dept_name|dept_id|
+-----+-----+
|Finance  |10      |
|Marketing|20      |
|Sales    |30      |
|IT       |40      |
+-----+-----+
```

```
root
|-- dept_name: string (nullable = true)
|-- dept_id: long (nullable = true)
```

```
+-----+-----+
|dept_name|dept_id|
+-----+-----+
|Finance  |10      |
|Marketing|20      |
|Sales    |30      |
|IT       |40      |
+-----+-----+
```

```
root
|-- dept_name: string (nullable = true)
|-- dept_id: string (nullable = true)
```

```
+-----+-----+
|dept_name|dept_id|
+-----+-----+
|Finance  |10      |
|Marketing|20      |
|Sales    |30      |
|IT       |40      |
+-----+-----+
```

```
In [14]: spark: SparkSession = SparkSession.builder \
        .master("local[1]") \
        .appName("SparkByExamples.com") \
        .getOrCreate()

filePath="C:\\Users\\TanujaNekkanti\\Downloads\\groceries.csv"
df = spark.read.options(header='True', inferSchema='True') \
        .csv(filePath)

df.printSchema()
df.show(truncate=False)

df.na.drop().show(truncate=False)

df.na.drop(how="any").show(truncate=False)

df.na.drop(subset=["Bananas", "o1"]) \
    .show(truncate=False)
```

```
root
|-- o1: string (nullable = true)
|-- Seattle: string (nullable = true)
|-- Bananas: string (nullable = true)
|-- 01-01-2017: string (nullable = true)
|-- 7: integer (nullable = true)
```

```
+---+-----+-----+-----+---+
|o1 |Seattle |Bananas |01-01-2017|7 |
+---+-----+-----+-----+---+
|o2 |Kent     |Apples  |02-01-2017|20|
|o3 |Bellevue |Flowers |02-01-2017|10|
|o4 |Redmond  |Meat    |03-01-2017|40|
|o5 |Seattle  |Potatoes|04-01-2017|9 |
|o6 |Bellevue |Bread   |04-01-2017|5 |
|o7 |Redmond  |Bread   |05-01-2017|5 |
|o8 |Issaquah |Onion   |05-01-2017|4 |
|o9 |Redmond  |Cheese  |05-01-2017|15|
|o10|Issaquah |Onion   |06-01-2017|4 |
|o11|Renton   |Bread   |05-01-2017|5 |
|o12|Issaquah |Onion   |07-01-2017|4 |
|o13|Sammamish|Bread   |07-01-2017|5 |
|o14|Issaquah |Tomato  |07-01-2017|6 |
+---+-----+-----+-----+---+
```

```
+---+-----+-----+-----+---+
|o1 |Seattle |Bananas |01-01-2017|7 |
+---+-----+-----+-----+---+
|o2 |Kent     |Apples  |02-01-2017|20|
|o3 |Bellevue |Flowers |02-01-2017|10|
```

o4	Redmond	Meat	03-01-2017	40
o5	Seattle	Potatoes	04-01-2017	9
o6	Bellevue	Bread	04-01-2017	5
o7	Redmond	Bread	05-01-2017	5
o8	Issaquah	Onion	05-01-2017	4
o9	Redmond	Cheese	05-01-2017	15
o10	Issaquah	Onion	06-01-2017	4
o11	Renton	Bread	05-01-2017	5
o12	Issaquah	Onion	07-01-2017	4
o13	Sammamish	Bread	07-01-2017	5
o14	Issaquah	Tomato	07-01-2017	6

+---+-----+-----+-----+---+

+---+-----+-----+-----+---+

o1	Seattle	Bananas	01-01-2017	7
----	---------	---------	------------	---

+---+-----+-----+-----+---+

o2	Kent	Apples	02-01-2017	20
o3	Bellevue	Flowers	02-01-2017	10
o4	Redmond	Meat	03-01-2017	40
o5	Seattle	Potatoes	04-01-2017	9
o6	Bellevue	Bread	04-01-2017	5
o7	Redmond	Bread	05-01-2017	5
o8	Issaquah	Onion	05-01-2017	4
o9	Redmond	Cheese	05-01-2017	15
o10	Issaquah	Onion	06-01-2017	4
o11	Renton	Bread	05-01-2017	5
o12	Issaquah	Onion	07-01-2017	4
o13	Sammamish	Bread	07-01-2017	5
o14	Issaquah	Tomato	07-01-2017	6

+---+-----+-----+-----+---+

+---+-----+-----+-----+---+

o1	Seattle	Bananas	01-01-2017	7
----	---------	---------	------------	---

+---+-----+-----+-----+---+

o2	Kent	Apples	02-01-2017	20
o3	Bellevue	Flowers	02-01-2017	10
o4	Redmond	Meat	03-01-2017	40
o5	Seattle	Potatoes	04-01-2017	9
o6	Bellevue	Bread	04-01-2017	5
o7	Redmond	Bread	05-01-2017	5
o8	Issaquah	Onion	05-01-2017	4
o9	Redmond	Cheese	05-01-2017	15
o10	Issaquah	Onion	06-01-2017	4
o11	Renton	Bread	05-01-2017	5
o12	Issaquah	Onion	07-01-2017	4
o13	Sammamish	Bread	07-01-2017	5
o14	Issaquah	Tomato	07-01-2017	6

+---+-----+-----+-----+---+


```

In [15]: spark = SparkSession.builder.appName('SparkByExamples.com').getOrCreate()

data = [("James", "Smith", "USA", "CA"),
        ("Michael", "Rose", "USA", "NY"),
        ("Robert", "Williams", "USA", "CA"),
        ("Maria", "Jones", "USA", "FL")
        ]

columns = ["firstname", "lastname", "country", "state"]
df = spark.createDataFrame(data = data, schema = columns)
df.show(truncate=False)

df.select("firstname", "lastname").show()

#Using Dataframe object name
df.select(df.firstname, df.lastname).show()
df.select(df["firstname"], df["lastname"]).show()

# Using col function
from pyspark.sql.functions import col
df.select(col("firstname").alias("fname"), col("lastname")).show()

# Show all columns
df.select("*").show()
df.select([col for col in df.columns]).show()
df.select(*columns).show()

df.select(df.columns[:3]).show(3)
df.select(df.columns[2:4]).show(3)

df.select(df.colRegex("`^.*name*`")).show()

data = [
    (("James", None, "Smith"), "OH", "M"),
    (("Anna", "Rose", ""), "NY", "F"),
    (("Julia", "", "Williams"), "OH", "F"),
    (("Maria", "Anne", "Jones"), "NY", "M"),
    (("Jen", "Mary", "Brown"), "NY", "M"),
    (("Mike", "Mary", "Williams"), "OH", "M")
]

from pyspark.sql.types import StructType, StructField, StringType
schema = StructType([
    StructField('name', StructType([
        StructField('firstname', StringType(), True),
        StructField('middlename', StringType(), True),
        StructField('lastname', StringType(), True)
    ])),
    StructField('state', StringType(), True),
    StructField('gender', StringType(), True)
])

df2 = spark.createDataFrame(data = data, schema = schema)
df2.printSchema()
df2.show(truncate=False) # shows all columns

```

```
df2.select("name").show(truncate=False)
df2.select("name.firstname", "name.lastname").show(truncate=False)
df2.select("name.*").show(truncate=False)
```

```
+-----+-----+-----+-----+
|firstname|lastname|country|state|
+-----+-----+-----+-----+
|James    |Smith   |USA     |CA    |
|Michael  |Rose    |USA     |NY     |
|Robert   |Williams|USA     |CA     |
|Maria    |Jones   |USA     |FL     |
+-----+-----+-----+-----+
```

```
+-----+-----+
|firstname|lastname|
+-----+-----+
|   James |   Smith|
| Michael |   Rose |
|  Robert |Williams|
|   Maria |   Jones|
+-----+-----+
```

```
+-----+-----+
|firstname|lastname|
```

```
In [18]: spark = SparkSession.builder.master("local[1]") \
        .appName('SparkByExamples.com') \
        .getOrCreate()

data = [("James", "Smith", "USA", "CA"), ("Michael", "Rose", "USA", "NY"), \
        ("Robert", "Williams", "USA", "CA"), ("Maria", "Jones", "USA", "FL") \
        ]
columns=["firstname", "lastname", "country", "state"]
df=spark.createDataFrame(data=data, schema=columns)
df.show()
print(df.collect())

states1=df.rdd.map(lambda x: x[3]).collect()
print(states1)
#['CA', 'NY', 'CA', 'FL']
from collections import OrderedDict
res = list(OrderedDict.fromkeys(states1))
print(res)
#['CA', 'NY', 'FL']

#Example 2
states2=df.rdd.map(lambda x: x.state).collect()
print(states2)
#['CA', 'NY', 'CA', 'FL']

states3=df.select(df.state).collect()
print(states3)
#[Row(state='CA'), Row(state='NY'), Row(state='CA'), Row(state='FL')]

states4=df.select(df.state).rdd.flatMap(lambda x: x).collect()
print(states4)
#['CA', 'NY', 'CA', 'FL']

states5=df.select(df.state).toPandas()['state']
states6=list(states5)
print(states6)
#['CA', 'NY', 'CA', 'FL']

pandDF=df.select(df.state,df.firstname).toPandas()
print(list(pandDF['state']))
print(list(pandDF['firstname']))
```

```
+-----+-----+-----+-----+
|firstname|lastname|country|state|
+-----+-----+-----+-----+
|   James|   Smith|   USA|   CA|
| Michael|   Rose|   USA|  NY|
|  Robert|Williams|   USA|   CA|
|   Maria|   Jones|   USA|   FL|
+-----+-----+-----+-----+
```

```
[Row(firstname='James', lastname='Smith', country='USA', state='CA'), Row(first
name='Michael', lastname='Rose', country='USA', state='NY'), Row(firstname='Rob
ert', lastname='Williams', country='USA', state='CA'), Row(firstname='Maria', l
astname='Jones', country='USA', state='FL')]
['CA', 'NY', 'CA', 'FL']
```

```
['CA', 'NY', 'FL']  
['CA', 'NY', 'CA', 'FL']  
[Row(state='CA'), Row(state='NY'), Row(state='CA'), Row(state='FL')]  
['CA', 'NY', 'CA', 'FL']  
['CA', 'NY', 'CA', 'FL']  
['CA', 'NY', 'CA', 'FL']  
['James', 'Michael', 'Robert', 'Maria']
```

```
In [19]: spark = SparkSession.builder.master("local[1]") \
        .appName('SparkByExamples.com') \
        .getOrCreate()

columns = ["name", "languagesAtSchool", "currentState"]
data = [("James,,Smith", ["Java", "Scala", "C++"], "CA"), \
        ("Michael,Rose,", ["Spark", "Java", "C++"], "NJ"), \
        ("Robert,,Williams", ["CSharp", "VB"], "NV")]

df = spark.createDataFrame(data=data, schema=columns)
df.printSchema()
df.show(truncate=False)

from pyspark.sql.functions import col, concat_ws
df2 = df.withColumn("languagesAtSchool",
                    concat_ws(", ", col("languagesAtSchool")))
df2.printSchema()
df2.show(truncate=False)

df.createOrReplaceTempView("ARRAY_STRING")
spark.sql("select name, concat_ws(', ', languagesAtSchool) as languagesAtSchool, "
          " currentState from ARRAY_STRING") \
        .show(truncate=False)
```

```
root
```

```
-- name: string (nullable = true)
-- languagesAtSchool: array (nullable = true)
|   |-- element: string (containsNull = true)
-- currentState: string (nullable = true)
```

```
+-----+-----+-----+
|name          |languagesAtSchool |currentState|
+-----+-----+-----+
|James,,Smith  |[Java, Scala, C++]|CA          |
|Michael,Rose, |[Spark, Java, C++]|NJ          |
|Robert,,Williams|[CSharp, VB]      |NV          |
+-----+-----+-----+
```

```
root
```

```
-- name: string (nullable = true)
-- languagesAtSchool: string (nullable = false)
-- currentState: string (nullable = true)
```

```
+-----+-----+-----+
|name          |languagesAtSchool |currentState|
+-----+-----+-----+
|James,,Smith  |Java,Scala,C++    |CA          |
|Michael,Rose, |Spark,Java,C++    |NJ          |
|Robert,,Williams|CSharp,VB        |NV          |
+-----+-----+-----+
```

```
+-----+-----+-----+
|name          |languagesAtSchool |currentState|
+-----+-----+-----+
|James,,Smith  |Java,Scala,C++    |CA          |
```

Michael,Rose,	Spark,Java,C++	NJ	
Robert,,Williams	CSharp,VB	NV	
+-----+	+-----+	+-----+	+-----+

```

In [20]: spark = SparkSession.builder \
            .appName('SparkByExamples.com') \
            .getOrCreate()
data=[["1"],["2"]]
df=spark.createDataFrame(data,["id"])

from pyspark.sql.functions import *

#current_date() & current_timestamp()
df.withColumn("current_date",current_date()) \
    .withColumn("current_timestamp",current_timestamp()) \
    .show(truncate=False)

#SQL
spark.sql("select current_date(), current_timestamp()") \
    .show(truncate=False)

# Date & Timestamp into custom format
df.withColumn("date_format",date_format(current_date(),"MM-dd-yyyy")) \
    .withColumn("to_timestamp",to_timestamp(current_timestamp(),"MM-dd-yyyy HH mm ss SSS")) \
    .show(truncate=False)

#SQL
spark.sql("select date_format(current_date(),'MM-dd-yyyy') as date_format , " + \
    "to_timestamp(current_timestamp(),'MM-dd-yyyy HH mm ss SSS') as to_time") \
    .show(truncate=False)

```

```

+---+-----+-----+
|id |current_date|current_timestamp      |
+---+-----+-----+
|1  |2022-02-07  |2022-02-07 17:02:55.431|
|2  |2022-02-07  |2022-02-07 17:02:55.431|
+---+-----+-----+

```

```

+-----+-----+
|current_date()|current_timestamp()    |
+-----+-----+
|2022-02-07    |2022-02-07 17:03:00.942|
+-----+-----+

```

```

+---+-----+-----+
|id |date_format|to_timestamp            |
+---+-----+-----+
|1  |02-07-2022 |2022-02-07 17:03:00.996|
|2  |02-07-2022 |2022-02-07 17:03:00.996|
+---+-----+-----+

```

```

+-----+-----+
|date_format|to_timestamp            |
+-----+-----+
|02-07-2022 |2022-02-07 17:03:06.506|
+-----+-----+

```

In []: