

EDS Lab Assignments

Practical 3

Name: Tanuja Somnath Tidake

PRN: 202501040063

3.1.1 Numpy Array Operations

Problem Statement:

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers `r` and `c`, representing the number of rows and the number of columns.
- The next `r` lines contain `c` space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Code:

```
import numpy as np
rows, cols = map(int, input().split())
elements = []

for _ in range (rows):
    elements.extend(map(int, input().split()))

array = np.array(elements).reshape(rows, cols)
print(array)
print(array.ndim)
print(array.shape)
print(array.size)
```

Output:

Average time

0.039 s

39.00 ms

Maximum time

0.056 s

56.00 ms

2 out of 2 shown test case(s) passed

10 out of 10 hidden test case(s) passed

Test case 1

48 ms

Debug

Expected output

Actual output

3 4

3 4

1 2 3 4

1 2 3 4

5 6 7 8

5 6 7 8

9 10 11 12

9 10 11 12

[[.1,.2,.3,.4]]

[[.1,.2,.3,.4]]

.[.5,.6,.7,.8]]

.[.5,.6,.7,.8]]

.[.9.10.11.12]]

.[.9.10.11.12]]

2

2

(3,.4)

(3,.4)

12

12

Test case 2

14 ms

Debug

Expected output

Actual output

0 0

0 0

[]

[]

2

2

(0,.0)

(0,.0)

0

0

3.2.1 Numpy: Matrix Operations

Problem Statement:

The given code takes two 3×3 matrices, matrix_a, and matrix_b, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** (matrix_a + matrix_b)
2. **Subtraction** (matrix_a – matrix_b)
3. **Element-wise Multiplication** (matrix_a * matrix_b)
4. **Matrix Multiplication** (matrix_a · matrix_b)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for matrix_a, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for matrix_b, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

Code:

```
import numpy as np
```

```
# Input matrices
```

```
print("Enter Matrix A:")
```

```
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
```

```
print("Enter Matrix B:")
```

```
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])
```

```
# Addition
```

```
addition_result = matrix_a + matrix_b
```

```
print("Addition (A + B):")
```

```
print(addition_result)
```

Subtraction

```
subtraction_result = matrix_a - matrix_b
print("Subtraction (A - B):")
print(subtraction_result)
```

Multiplication (element-wise)

```
elementwise_multiplication_result = matrix_a * matrix_b
print("Element-wise Multiplication (A * B):")
print(elementwise_multiplication_result)
```

Matrix multiplication (dot product)

```
matrix_multiplication_result = np.dot(matrix_a, matrix_b)
print("A dot B:")
print(matrix_multiplication_result)
```

Transpose

```
transpose_a = matrix_a.T
print("Transpose of A:")
print(transpose_a)
```

Output:

Average time
0.147 s
147.00 ms

Maximum time
0.179 s
179.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 143 ms Debug

Expected output

Actual output

Enter Matrix A:	Enter Matrix A:
<code>1 2 3</code>	<code>1 2 3</code>
<code>4 5 6</code>	<code>4 5 6</code>
<code>7 8 9</code>	<code>7 8 9</code>
Enter Matrix B:	Enter Matrix B:
<code>1 1 1</code>	<code>1 1 1</code>
<code>1 1 1</code>	<code>1 1 1</code>
<code>1 1 1</code>	<code>1 1 1</code>
Addition (A + B):	Addition (A + B):
<code>[[2 3 4]]</code>	<code>[[2 3 4]]</code>
<code>[- 5 -6 -7]</code>	<code>[- 5 -6 -7]</code>
<code>[- 8 -9 -10]</code>	<code>[- 8 -9 -10]</code>
Subtraction (A - B):	Subtraction (A - B):
<code>[[0 1 2]]</code>	<code>[[0 1 2]]</code>
<code>[3 4 5]</code>	<code>[3 4 5]</code>
<code>[6 7 8]</code>	<code>[6 7 8]</code>
Element-wise Multiplication (A * B):	Element-wise Multiplication (A * B):
<code>[[1 2 3]]</code>	<code>[[1 2 3]]</code>
<code>[4 5 6]</code>	<code>[4 5 6]</code>
<code>[7 8 9]</code>	<code>[7 8 9]</code>
A dot B:	A dot B:
<code>[[6 6 6]]</code>	<code>[[6 6 6]]</code>
<code>[15 15 15]</code>	<code>[15 15 15]</code>
<code>[24 24 24]</code>	<code>[24 24 24]</code>
Transpose of A:	Transpose of A:

Average time
0.147 s
147.00 ms

Maximum time
0.179 s
179.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Transpose of A:	Transpose of A:
[[1 4 7]]	[[1 4 7]]
[2 5 8]	[2 5 8]
[3 6 9]]	[3 6 9]]

Test case 2 141 ms Debug

Expected output	Actual output
Enter Matrix A:	Enter Matrix A:
2 4 8	2 4 8
9 6 5	9 6 5
7 8 9	7 8 9
Enter Matrix B:	Enter Matrix B:
10 12 13	10 12 13
14 15 16	14 15 16
17 18 19	17 18 19
Addition (A + B):	Addition (A + B):
[[12 16 21]]	[[12 16 21]]
[23 21 21]	[23 21 21]
[24 26 28]]	[24 26 28]]
Subtraction (A - B):	Subtraction (A - B):
[[-8 -8 -5]]	[[-8 -8 -5]]
[[-5 -9 -11]]	[[-5 -9 -11]]
[-10 -10 -10]]	[-10 -10 -10]]
Element-wise Multiplication (A * B):	Element-wise Multiplication (A * B):
[[20 48 104]]	[[20 48 104]]
[126 90 80]	[126 90 80]
[119 144 171]]	[119 144 171]]

A dot B:	A dot B:
[[212 228 242]]	[[212 228 242]]
[259 288 308]	[259 288 308]
[335 366 390]]	[335 366 390]]
Transpose of A:	Transpose of A:
[[2 9 7]]	[[2 9 7]]
[4 6 8]	[4 6 8]
[8 5 9]]	[8 5 9]]

3.2.2 Numpy: Horizontal and Vertical Stacking of Arrays

Problem Statement:

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).
- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

Code:

```
import numpy as np

# Input matrices
print("Enter Array1:")
arr1 = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Array2:")
arr2 = np.array([list(map(int, input().split())) for i in range(3)])

# Perform horizontal stacking (hstack)
a = np.hstack((arr1, arr2))
print("Horizontal Stack:")
print(a)

# Perform vertical stacking (vstack)
b = np.vstack((arr1, arr2))
print("Vertical Stack:")
print(b)
```

Output:

Average time
0.150 s
149.75 ms

Maximum time
0.171 s
171.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 111 ms Debug

Expected output

Actual output

Enter Array1:	Enter Array1:
1 2 3	1 2 3
4 5 6	4 5 6
7 8 9	7 8 9
Enter Array2:	Enter Array2:
4 5 6	4 5 6
7 8 9	7 8 9
10 11 12	10 11 12
Horizontal Stack:	Horizontal Stack:
[[1 2 3 4 5 6]]	[[1 2 3 4 5 6]]
[-4 -5 -6 -7 -8 -9]	[-4 -5 -6 -7 -8 -9]
[-7 -8 -9 10 11 12]]	[-7 -8 -9 10 11 12]]
Vertical Stack:	Vertical Stack:
[[1 2 3]]	[[1 2 3]]
[-4 -5 -6]	[-4 -5 -6]
[-7 -8 -9]	[-7 -8 -9]
[-4 -5 -6]	[-4 -5 -6]
[-7 -8 -9]	[-7 -8 -9]
[10 11 12]]	[10 11 12]]

Test case 2 171 ms Debug

Expected output

Actual output

Enter Array1:	Enter Array1:
-1 -2 -3	-1 -2 -3
-4 -5 -6	-4 -5 -6
-7 -8 -9	-7 -8 -9
Enter Array2:	Enter Array2:
10 11 12	10 11 12
13 14 15	13 14 15
16 17 18	16 17 18
Horizontal Stack:	Horizontal Stack:
[[1 -2 -3 10 11 12]]	[[1 -2 -3 10 11 12]]
[-4 -5 -6 13 14 15]]	[-4 -5 -6 13 14 15]]
[-7 -8 -9 16 17 18]]	[-7 -8 -9 16 17 18]]
Vertical Stack:	Vertical Stack:
[[1 -2 -3]]	[[1 -2 -3]]
[-4 -5 -6]	[-4 -5 -6]
[-7 -8 -9]	[-7 -8 -9]
[10 11 12]	[10 11 12]
[13 14 15]	[13 14 15]
[16 17 18]]	[16 17 18]]

3.2.3 Numpy: Custom Sequence Generation

Problem Statement:

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.

Code:

```
import numpy as np
# Take user input for the start, stop, and step of the sequence
start = int(input())
stop = int(input())
step = int(input())
# Generate the sequence using np.arange()
a = np.arange(start, stop, step)
# Print the generated sequence
print(a)
```

Output:

Average time
0.039 s
39.00 ms

Maximum time
0.044 s
44.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 **44 ms** Debug

Expected output

3

10

2

[3 · 5 · 7 · 9]

Actual output

3

10

2

[3 · 5 · 7 · 9]

Test case 2 **40 ms** Debug

Expected output

10

20

30

[10]

Actual output

10

20

30

[10]

3.2.4 Numpy: Arithmetic and Statistical Operations, Mathematical Operations and Bitwise Operators

Problem Statement:

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

Code:

```
import numpy as np
```

```
def array_operations(A, B):  
    # Convert A and B to NumPy arrays  
    A = np.array(A)  
    B = np.array(B)  
  
    # Arithmetic Operations  
    sum_result = A + B  
    diff_result = A - B  
    prod_result = A * B  
  
    # Statistical Operations  
    mean_A = np.mean(A)  
    median_A = np.median(A)  
    std_dev_A = np.std(A)
```

```
# Bitwise Operations
```

```
and_result = A & B
```

```
or_result = A | B
```

```
xor_result = A ^ B
```

```
# Output results with one space between each element
```

```
print("Element-wise Sum:", ' '.join(map(str, sum_result)))
```

```
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
```

```
print("Element-wise Product:", ' '.join(map(str, prod_result)))
```

```
print(f"Mean of A: {mean_A}")
```

```
print(f"Median of A: {median_A}")
```

```
print(f"Standard Deviation of A: {std_dev_A}")
```

```
print("Bitwise AND:", ' '.join(map(str, and_result)))
```

```
print("Bitwise OR:", ' '.join(map(str, or_result)))
```

```
print("Bitwise XOR:", ' '.join(map(str, xor_result)))
```

```
A = list(map(int, input().split())) # Elements of array A
```

```
B = list(map(int, input().split())) # Elements of array B
```

```
array_operations(A, B)
```

Output:

Average time
0.036 s
35.67 ms

Maximum time
0.043 s
43.00 ms

1 out of 1 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 36 ms Debug

Expected output	Actual output
1 2 3 4	1 2 3 4
5 6 7 8	5 6 7 8
Element-wise Sum: 6 8 10 12	Element-wise Sum: 6 8 10 12
Element-wise Difference: -4 -4 -4 -4	Element-wise Difference: -4 -4 -4 -4
Element-wise Product: 5 12 21 32	Element-wise Product: 5 12 21 32
Mean of A: 2.5	Mean of A: 2.5
Median of A: 2.5	Median of A: 2.5
Standard Deviation of A: 1.118033988749895	Standard Deviation of A: 1.118033988749895
Bitwise AND: 1 2 3 0	Bitwise AND: 1 2 3 0
Bitwise OR: 5 6 7 12	Bitwise OR: 5 6 7 12
Bitwise XOR: 4 4 4 12	Bitwise XOR: 4 4 4 12

3.2.5 Numpy: Copying and Viewing Arrays

Problem Statement:

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:
Original array after modifying view: **<original_array>**
View array: **<view_array>**
- After modifying the copy:
Original array after modifying copy: **<original_array>**
Copy array: **<copy_array>**

Code:

```
import numpy as np
inputlist = list(map(int,input().split(" ")))

# Original array
original_array = np.array(inputlist)

# Create a view
view_array = original_array.view()

# Create a copy
copy_array = original_array.copy()

# Modify the view
view_array[0] = 99
print("Original array after modifying view:", original_array)
print("View array:", view_array)

# Modify the copy
copy_array[1] = 88
```

```
print("Original array after modifying copy:", original_array)
print("Copy array:", copy_array)
```

Output:

Average time
0.022 s
22.50 ms

Maximum time
0.027 s
27.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 27 ms Debug

Expected output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

Actual output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

Test case 2 23 ms Debug

Expected output

99 2 3 4 5

Original array after modifying view: [99 2 3 4 5]

View array: [99 2 3 4 5]

Original array after modifying copy: [99 2 3 4 5]

Copy array: [99 88 3 4 5]

Actual output

99 2 3 4 5

Original array after modifying view: [99 2 3 4 5]

View array: [99 2 3 4 5]

Original array after modifying copy: [99 2 3 4 5]

Copy array: [99 88 3 4 5]

3.2.6 Searching, Sorting, Counting, Broadcasting

Problem Statement:

The given code in the editor takes a single array, array1, as space-separated integers as input from the user.

Additionally, it takes the following inputs:

- search_value: The value to search for in the array.
- count_value: The value to count its occurrences in the array.
- broadcast_value: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

- 1. Searching:** Find the indices where search_value appears in array1 and print these indices.
- 2. Counting:** Count how many times count_value appears in array1 and print the count.
- 3. Broadcasting:** Add broadcast_value to each element of array1 using broadcasting, and print the resulting array.
- 4. Sorting:** Sort array1 in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing array1.
2. An integer search_value represents the value to search for in the array.
3. An integer count_value represents the value to count in the array.
4. An integer broadcast_value represents the value to add to each element of the array.

Output Format:

1. The indices where search_value occurs in array1.
2. The count of occurrences of count_value in array1.
3. The array after adding the broadcast_value to each element.
4. The sorted array.

Code:

```
import numpy as np

# Input array from the user
array1 = np.array(list(map(int, input().split()))))

# Searching
search_value = int(input("Value to search: "))
count_value = int(input("Value to count: "))
broadcast_value = int(input("Value to add: "))
```

```
# Find indices where value matches in array1
a = np.where(array1 == search_value)[0]
print(a)
```

```
# Count occurrences in array1
b = np.count_nonzero(array1 == count_value)
print(b)
```

```
# Broadcasting addition
c = array1 + broadcast_value
print(c)
```

```
# Sort the first array
d = np.sort(array1)
print(d)
```

Output:

Average time
0.051 s
50.50 ms

Maximum time
0.062 s
62.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 48 ms Debug

Expected output

Actual output

1 1 1 2 2 2

1 1 1 2 2 2

Value to search: 1

Value to search: 1

Value to count: 2

Value to count: 2

Value to add: 2

Value to add: 2

[0 1 2]

[0 1 2]

3

3

[3 3 3 4 4 4]

[3 3 3 4 4 4]

[1 1 1 2 2 2]

[1 1 1 2 2 2]

Test case 2 62 ms Debug

Expected output

Actual output

1 2 3 4 5

1 2 3 4 5

Value to search: 6

Value to search: 6

Value to count: 6

Value to count: 6

Value to add: 6

Value to add: 6

[]

[]

0

0

[7 8 9 10 11]

[7 8 9 10 11]

[1 2 3 4 5]

[1 2 3 4 5]

3.2.7 Student Data Analysis and Operations

Problem Statement:

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject:** Count the number of students who scored 90 or more marks in each subject.

- **Find the count of subjects in which each student scored ≥ 90 :** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1:** Identify the index positions of students who scored exactly 79 marks in Subject 1.

Code:

```
import numpy as np
```

```
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
```

```
roll = a[:, 0].astype(float)
```

```
s1 = a[:, 1]
```

```
s2 = a[:, 2]
```

```
s3 = a[:, 3]
```

```
# 1. Print all student details
```

```
print("All student Details:\n", a)
```

```
# 2. print total students
```

```
print("Total Students:", len(a))
```

```
# 3. Print all student Roll numbers
```

```
print("All Student Roll Nos", roll)
```

```
# 4. Print subject 1 marks
```

```
print("Subject 1 Marks", s1)
```

```
# 5. print minimum marks of Subject 2
```

```
print("Min marks in Subject 2", np.min(s2))
```

```
# 6. print maximum marks of Subject 3
```

```
print("Max marks in Subject 3", np.max(s3))
```

```
# 7. Print All subject marks
```

```
print("All subject marks:", a[:, 1:])
```

```
# 8. print Total marks of students
```

```
total = s1 + s2 + s3
```

```
print("Total Marks", total)
```

```
# 9. print average marks of each student
```

```

print(np.round(total/3, 1))

# 10. print average marks of each subject
print("Average Marks of each subject", np.mean(a[:, 1:], axis = 0))

# 11. print average marks of S1 and S2
print("Average Marks of S1 and S2", np.mean([s1, s2], axis = 1))

# 12. print average marks of S1 and S3
print("Average Marks of S1 and S3", np.mean([s1, s3], axis = 1))

# 13. print Roll number who got maximum marks in Subject 3
print("Roll no who got maximum marks in Subject 3", float(roll[np.argmax(s3)]))

# 14. print Roll number who got minimum marks in Subject 2
print("Roll no who got minimum marks in Subject 2", float(roll[np.argmin(s2)]))

# 15. print Roll number who got 24 marks in Subject 2
print("Roll no who got 24 marks in Subject 2", roll[s2 == 24].astype(float).reshape(1, -1))

# 16. print count of students who got marks in Subject 1 < 40
print("Count of students who got marks in Subject 1 < 40", np.sum(s1 < 40))

# 17. print count of students who got marks in Subject 2 > 90
print("Count of students who got marks in Subject 2 > 90:", np.sum(s2 > 90))

# 18. print count of students in each subject who got marks >= 90
print("Count of students in each subject who got marks >= 90:", np.sum(a[:, 1:] >= 90,
axis = 0))

# 19. print count of subjects in which each student got marks >= 90
print("Roll no:", roll)
print("Count of subjects in which student got marks >= 90:", np.sum(a[:, 1:] >= 90, axis =
1))

# 20. Print S1 marks in ascending order
print(np.sort(s1))

# 21. Print S1 marks >= 50 and <= 90
print(a[(s1 >= 50) & (s1 <= 90)].astype(float))
print(a.astype(float))

# 22. Print the index position of marks 79
print(np.where(s1 == 79))

```

Output:

Average time
0.019 s
19.00 ms

Maximum time
0.019 s
19.00 ms

1 out of 1 shown test case(s) passed

Test case 119 ms

Debug

Expected output

Actual output

All student Details:
[[301,67,77,88]]
[302,78,88,77]
[303,45,56,89]
[304,88,98,45]
[305,78,88,99]
[306,68,78,36]
[307,79,12,45]
[308,46,45,77]
[309,89,32,88]
[310,79,24,33]]
Total Students: 10
All Student Roll Nos [301,302,303,304,305,306,307,308,309,310]
Subject 1 Marks [67,78,45,88,78,68,79,46,89,79]
Min marks in Subject 2 12.0
Max marks in Subject 3 99.0
All subject marks: [[67,77,88]]
[78,88,77]
[45,56,89]
[88,98,45]
[78,88,99]
[68,78,36]
[79,12,45]
[46,45,77]
[89,32,88]

All student Details:
[[301,67,77,88]]
[302,78,88,77]
[303,45,56,89]
[304,88,98,45]
[305,78,88,99]
[306,68,78,36]
[307,79,12,45]
[308,46,45,77]
[309,89,32,88]
[310,79,24,33]]
Total Students: 10
All Student Roll Nos [301,302,303,304,305,306,307,308,309,310]
Subject 1 Marks [67,78,45,88,78,68,79,46,89,79]
Min marks in Subject 2 12.0
Max marks in Subject 3 99.0
All subject marks: [[67,77,88]]
[78,88,77]
[45,56,89]
[88,98,45]
[78,88,99]
[68,78,36]
[79,12,45]
[46,45,77]
[89,32,88]

Total Marks [232,243,190,231,265,182,136,168,209,136]
[77.3,81,63.3,77,88.3,60.7,45.3,56,69.7,45.3]
Average Marks of each subject [71.7,59.8,67.7]
Average Marks of S1 and S2 [71.7,59.8]
Average Marks of S1 and S3 [71.7,67.7]
Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [[310]]
Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90: 1
Count of students in each subject who got marks >= 90: [0,1,1]
Roll no: [301,302,303,304,305,306,307,308,309,310]
Count of subjects in which student got marks >= 90: [0,0,0,1,1,0,0,0,0,0]
[45,46,67,68,78,78,79,79,88,89]
[[301,67,77,88]]
[302,78,88,77]
[304,88,98,45]
[305,78,88,99]
[306,68,78,36]
[307,79,12,45]
[309,89,32,88]
[310,79,24,33]]
[[301,67,77,88]]
[302,78,88,77]
[303,45,56,89]
[304,88,98,45]
[305,78,88,99]

Total Marks [232,243,190,231,265,182,136,168,209,136]
[77.3,81,63.3,77,88.3,60.7,45.3,56,69.7,45.3]
Average Marks of each subject [71.7,59.8,67.7]
Average Marks of S1 and S2 [71.7,59.8]
Average Marks of S1 and S3 [71.7,67.7]
Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [[310]]
Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90: 1
Count of students in each subject who got marks >= 90: [0,1,1]
Roll no: [301,302,303,304,305,306,307,308,309,310]
Count of subjects in which student got marks >= 90: [0,0,0,1,1,0,0,0,0,0]
[45,46,67,68,78,78,79,79,88,89]
[[301,67,77,88]]
[302,78,88,77]
[304,88,98,45]
[305,78,88,99]
[306,68,78,36]
[307,79,12,45]
[309,89,32,88]
[310,79,24,33]]
[[301,67,77,88]]
[302,78,88,77]
[303,45,56,89]
[304,88,98,45]
[305,78,88,99]

[303...45...56...89.][Ⓜ]

[303...45...56...89.][Ⓜ]

[304...88...98...45.][Ⓜ]

[304...88...98...45.][Ⓜ]

[305...78...88...99.][Ⓜ]

[305...78...88...99.][Ⓜ]

[306...68...78...36.][Ⓜ]

[306...68...78...36.][Ⓜ]

[307...79...12...45.][Ⓜ]

[307...79...12...45.][Ⓜ]

[308...46...45...77.][Ⓜ]

[308...46...45...77.][Ⓜ]

[309...89...32...88.][Ⓜ]

[309...89...32...88.][Ⓜ]

[310...79...24...33.]][Ⓜ]

[310...79...24...33.]][Ⓜ]

(array([6, 9], dtype=int32),)[Ⓜ]

(array([6, 9], dtype=int32),)[Ⓜ]