RESTORE DATABASE BACKUP

Ticket Number	CCTNS 2504016
Date & Time of Call Received	03-04-2025
Name Of Police station	Kalapet
Caller Name	Sakthi Murugan
Issue	Database backup
Name of the Help Desk Resource	PUSHPARAJ
Status	Completed
Resolution , Date and Time	03-04-2025

❖ Connect to the SQL Server

- Open **SQL Server Management Studio (SSMS)**.
- Connect to the appropriate **Database Server**.
- Click on **"New Query"**.

❖ Verify FIR Records

- Execute the following query to check if FIRs exist for a specific Police Station (PS) and year:

```
SELECT * FROM t_fir_registration
WHERE PS_CD = 26001005
  AND REG_YEAR = 2025
ORDER BY FIR_SRNO DESC;
```

❖ Confirm Police Station Name

- Run the following query to get the Police Station name for the given `PS_CD`:

```
SELECT * FROM m_police_station
WHERE PS_CD = 26001005;
```

✅**Note**: Confirm the name of the station from the result.

❖ Go to the Application (APP) Server

- Check under the **Connection Manager** tab.
- If **any Police Station is already connected**, **disconnect** it **before proceeding**.
- In the same tab, **type the Police Station name** (confirmed in Step 3).
- **Right-click** on the station name and select **"Properties"**.

❖ Confirm Station IP Address

- In the **Properties** window:
  - Check the **IP address**.
  - Confirm it is the **correct Police Station**.
- Then, click **"Connect"**.

❖ Check Sequence Number for the PS

- Run the following query in SSMS to check the sequence number:

```
SELECT * FROM m_registration_seq_num;
```

✅Look for the row where `ps_cd = 26001005`.
Check if `reg_next_seq_srno = 1`.

❖ Update PS Code in Sequence Number Tables

- Run each of the following queries **one at a time**:

```
UPDATE m_registration_seq_num
SET ps_cd = 26001005;

UPDATE m_registration_gd_seq_num
SET ps_cd = 26001005;

UPDATE m_registration_other_seq_num
SET ps_cd = 26001005;
```

❖ Restore Offline Database Scripts

- Open the **Offline Database SQL script** in **Notepad**.
- Replace the placeholder **Police Station Code** with `26001008`.
- Copy the entire query.

❖ On the DB Server:

- Click **"New Query"**, then **paste** the modified SQL script.
- **Select all** the script and **execute** it.
- Once executed, **copy all the results**.

❖ Run the Results in the APP Server

- Go to the **APP Server**.

- **Paste** the previously executed result (from the DB server).
- Execute it there as well.

❖ Re-Check Sequence Number

- Again, run the following query to verify the sequence number:

```
SELECT * FROM m_registration_seq_num;
```

✅Now, `reg_next_seq_srno` should show **multiple values** (e.g., 3, 4, 5), indicating it's updated.

❖ Set GD Reset Time for the State

- Run the following query:

```
SELECT * FROM m_state
WHERE state_CD = 26;
```

- In the result, find the columns named `GD_RESET_TIME`.
- **Edit both columns** and set the value to:

```
07:00:00
```

❖ ✅Process Completed