

Computer Networks

Introduction

Prof. Navrati Saxena

San Jose State University

What is the Internet?

Internet – largest engineered system ever created by mankind!

Network of networks: all about connecting

Let's try to understand it and how it works

Chapter 1: roadmap

1.1 What *is* the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core

- circuit switching, packet switching, network structure

1.4 Delay, loss and throughput in packet-switched networks

1.5 Protocol layers, service models


What is the Internet?

Internet – largest engineered system ever created by mankind

End systems: connected together by a network of
communication links and **packet switches**

Let's try to understand it and how it works

What's the Internet: "nuts and bolts" view



- millions of connected computing devices:
hosts = end systems

- transmission rate =
bandwidth
 - ❖ Packets = chunks of data

- *Packet Switch - receives and forward*
 - ❖ Routers - core n/w
 - ❖ Link layer switches - Access n/w

- *communication links*

- ❖ Coaxial
- ❖ Copper wire
- ❖ Fiber
- ❖ Radio

- *Route / Path*

- ❖ Sequence of links & packet switches

- *ISPs (Internet Service Providers)*

- ❖ End systems access internet

The Internet is all about connecting end systems to each other. So the ISPs that provide access to end systems must also be interconnected

Packet-switched networks VS transportation networks


- ❑ Packet-switched networks - transport
- ❑ Transportation networks - transport vehicles
- ❑ Analogy:
 - ❖ packets to trucks,
 - ❖ communication links to highways and roads,
 - ❖ packet switches to intersections, and
 - ❖ end systems are analogous to buildings.
- ❑ Just as a truck takes a path through the transportation network, a packet takes a path through a computer network.

Protocols

- ❑ End systems, packet switches, and other pieces of the Internet run **protocols** that control the sending and receiving of information within the Internet.
- ❑ Most important protocols in the internet
 - ❖ The **Transmission Control Protocol (TCP)** and
 - ❖ The **Internet Protocol (IP)**
- ❑ The Internet's principal protocols are collectively known as **TCP/IP**.

Importance of protocols

- ❑ *protocols* control sending, receiving of msgs
 - ❖ e.g., TCP, IP, HTTP, Skype, Ethernet
- ❑ *Internet: “network of networks”*
 - ❖ Important that everyone agrees
 - ❖ To create interoperable systems/products
- ❑ Internet standards
 - ❖ IETF: Internet Engineering Task Force
 - ❖ RFC: Request for comments



What is the Internet?

Internet – an infrastructure that provides services to applications

Applications:

Email, Web surfing, social networks, instant messaging, Voiceover-IP (VoIP),
video streaming, distributed games, peer-to-peer (P2P) file sharing,
television over the Internet, remote login and much more!


Internet applications: Distributed applications

run on end systems—they do not run in the packet switches in the network core

Let's try to understand it and how it works

What's the Internet: A service view

- ❑ **communication *infrastructure***
enables distributed applications:
 - ❖ Web, VoIP, email, games, e-commerce, file sharing
- ❑ **communication services provided to apps:**
 - ❖ reliable data delivery from source to destination
 - ❖ “best effort” (unreliable) data delivery



Application Programming Interface (API)

- ❑ Specifies how a program running on one end system asks the Internet infrastructure to deliver data to a specific destination program running on another end system.
- ❑ **Set of rules** that the sending program must follow so that the Internet can deliver the data to the destination program.

Analogy: API with postal service

- ❑ The Internet has an API that the program sending data must follow to have the Internet deliver the data to the program that will receive the data.
- ❑ Postal service's services:
 - ❖ Express delivery, reception confirmation, ordinary use, etc.
- ❑ Similarly internet provides multiple services to its applications.
- ❑ When one develop an Internet application
 - ❖ Choose one of the Internet's services

What is an Internet

- ❑ In terms of its hardware and software components
- ❑ The other in terms of an infrastructure for providing services to distributed applications.

What's a protocol?

human protocols:

- ❑ “what’s the time?”
- ❑ “I have a question”
- ❑ introductions

... specific msgs sent

... specific actions taken
when msgs received, or
other events


network protocols:

- ❑ machines rather than humans
- ❑ all internet communication
activities governed by
protocols

*protocols define format,
order of msgs sent and
received among network
entities, and actions
taken on msg
transmission, receipt*

What's a protocol?

a human protocol and a computer network protocol:



Protocols

- ❑ Flow control protocols – flow of bits between wires
- ❑ Congestion control protocols – rate of transmission
- ❑ Routing protocols - packet's path from source to destination.
- ❑ Understanding computer networking = understanding the what, why, and how of networking protocols

Chapter 1: roadmap

✓ 1.1 What *is* the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core


- circuit switching, packet switching, network structure

1.4 Delay, loss and throughput in packet-switched networks

1.5 Protocol layers, service models

A closer look at network structure:

- network edge = end systems = hosts
 - ❖ applications and hosts
- access networks, physical media:
 - ❖ wired, wireless, optical
- network core:
 - ❖ interconnected routers
 - ❖ network of networks



The network edge

□ end systems (hosts):


- ❖ run application programs
- ❖ e.g. Web, email
- ❖ at “edge of network”

□ client/server model

- ❖ client host requests, receives service from always-on server
- ❖ e.g. Web browser/server; email client/server

□ peer-peer model:

- ❖ minimal (or no) use of dedicated servers
- ❖ e.g. Skype, BitTorrent




Access networks and physical media

Q: How to connect end systems to edge router?


- ❑ residential access nets
- ❑ institutional access networks (school, company)
- ❑ mobile access networks

Keep in mind:

- ❑ bandwidth (bits per second) of access network?
- ❑ shared or dedicated?



Dial-up Modem



- ❖ Uses existing telephony infrastructure
 - ❖ Home is connected to **central office**
- ❖ up to 56Kbps direct access to router (often less)
- ❖ Can't surf and phone at same time: not **"always on"**

Broadband residential access


- ❑ DSL – Digital Subscriber Line

- ❖ Provided by telephone company

- ❑ HFC – hybrid fiber-coaxial cable


- ❖ Extension of current cable network used for broadcasting cable television

Digital Subscriber Line (DSL)



- ❖ Also uses existing telephone infrastructure
- ❖ up to 1 Mbps upstream (today typically < 256 kbps)
- ❖ up to 8 Mbps downstream (today typically < 1 Mbps)
- ❖ dedicated physical line to telephone central office


DSL Internet Access




Residential access: cable modems

- ❑ Does not use telephone infrastructure
 - ❖ Instead uses cable TV infrastructure
- ❑ HFC: hybrid fiber coax
 - ❖ asymmetric: up to 30Mbps downstream, 2 Mbps upstream
- ❑ network of cable and fiber attaches homes to ISP router
 - ❖ homes share access to router
 - ❖ unlike DSL, which has dedicated access

A hybrid fiber-coaxial access network




Fiber to the Home




- ❑ Optical links from central office to the home
- ❑ Two competing optical technologies:
 - ❖ Passive Optical network (PON)
 - ❖ Active Optical Network (PAN)
- ❑ Much higher Internet rates; fiber also carries television and phone services

FTTH Internet access




Ethernet Internet access



- ❑ Typically used in companies, universities, etc
- ❑ 10 Mbs, 100Mbps, 1Gbps, 10Gbps Ethernet
- ❑ Today, end systems typically connect into Ethernet switch

Wireless access networks


- ❑ shared *wireless* access network connects end system to router
 - ❖ via base station aka “access point”
- ❑ **wireless LANs:**
 - ❖ 802.11b/g (WiFi): 11 or 54 Mbps
- ❑ **wider-area wireless access**
 - ❖ provided by telco operator
 - ❖ ~1Mbps over cellular system (EVDO, HSDPA)
 - ❖ next up (?): WiMAX (10's Mbps) over wide area



Home networks

Typical home network components:

- ❑ DSL or cable modem
- ❑ router/firewall/NAT
- ❑ Ethernet
- ❑ wireless access point



Physical Media

- ❑ **Bit:** propagates between transmitter/rcvr pairs
- ❑ **physical link:** what lies between transmitter & receiver
- ❑ **guided media:**
 - ❖ signals propagate in solid media: copper, fiber, coax
- ❑ **unguided media:**
 - ❖ signals propagate freely, e.g., radio

Twisted Pair (TP)


- ❑ two insulated copper wires
 - ❖ Category 3: traditional phone wires, 10 Mbps Ethernet
 - ❖ Category 5: 100Mbps Ethernet



Physical Media: coax, fiber

Coaxial cable:

- ❑ two concentric copper conductors
- ❑ bidirectional
- ❑ baseband:
 - ❖ single channel on cable
 - ❖ legacy Ethernet
- ❑ broadband:
 - ❖ multiple channels on cable
 - ❖ HFC



Fiber optic cable:

- ❑ glass fiber carrying light pulses, each pulse a bit
- ❑ high-speed operation:
 - ❖ high-speed point-to-point transmission (e.g., 10's-100's Gps)
- ❑ low error rate: repeaters spaced far apart ; immune to electromagnetic noise



Physical media: radio

- ❑ signal carried in electromagnetic spectrum
- ❑ no physical “wire”
- ❑ bidirectional
- ❑ propagation environment effects:
 - ❖ reflection
 - ❖ obstruction by objects
 - ❖ interference

Radio link types:

- ❑ **terrestrial microwave**
 - ❖ e.g. up to 45 Mbps channels
- ❑ **LAN** (e.g., Wifi)
 - ❖ 11Mbps, 54 Mbps
- ❑ **Wide-area** (e.g., cellular)
 - ❖ 3G cellular: ~ 1 Mbps
- ❑ **Satellite**
 - ❖ Kbps to 45Mbps channel (or multiple smaller channels)
 - ❖ 270 msec end-end delay
 - ❖ geosynchronous versus low altitude

Chapter 1: roadmap

✓ 1.1 What *is* the Internet?

✓ 1.2 Network edge

- end systems, access networks, links

1.3 Network core


- circuit switching, packet switching, network structure

1.4 Delay, loss and throughput in packet-switched networks

1.5 Protocol layers, service models

The Network Core


- ❑ Mesh of interconnected routers
- ❑ **Fundamental question:** how is data transferred through net?
 - ❖ **circuit switching:** dedicated circuit per call: telephone net
 - ❖ **packet-switching:** data sent thru net in discrete “chunks”



Network Core: Circuit Switching

End-end resources
reserved for “call”

- ❑ link bandwidth, switch capacity
- ❑ dedicated resources: no sharing
- ❑ circuit-like (guaranteed) performance
- ❑ call setup required



Network Core: Circuit Switching

network resources (e.g., bandwidth) **divided into “pieces”**

- ❑ pieces allocated to calls
- ❑ resource piece *idle* if not used by owning call (*no sharing*)

- ❑ dividing link bandwidth into “pieces”

- ❖ frequency division
- ❖ time division

Analogy: Restaurant Booking


Circuit Switching: FDM and TDM

Example:


4 users



FDM



TDM



Packet Switching

- Sending message: source to a destination end system
 - ❖ the source breaks long messages into smaller chunks of data known as **packets**.
 - ❖ Between source and destination, each packet travels through **communication links** and **packet switches** (routers and switches).
 - ❖ Packets are transmitted over each communication link at a rate equal to the **full transmission rate** of the link.
 - ❖ So, if a source end system or a packet switch is sending a packet of L bits over a link with transmission rate R bits/sec, then the time to transmit the packet is L/R seconds

Network Core: Packet Switching


each end-end data stream
divided into *packets*

- ❑ user A, B packets *share* network resources
- ❑ each packet uses full link bandwidth
- ❑ resources used *as needed*


resource contention:

- ❑ aggregate resource demand can exceed amount available
- ❑ congestion: packets queue, wait for link use
- ❑ store and forward: packets move one hop at a time
 - ❖ Node receives complete packet before forwarding

Bandwidth division into "pieces"
Dedicated allocation
Resource reservation




Packet Switching: Statistical Multiplexing



Sequence of A & B packets does not have fixed pattern, bandwidth shared on demand → **statistical multiplexing**.

TDM: each host gets same slot in revolving TDM frame.

Packet-switching: store-and-forward



- ❑ takes L/R seconds to transmit (push out) packet of L bits on to link at R bps
- ❑ **store and forward**: entire packet must arrive at router before it can be transmitted on next link
- ❑ delay = $3L/R$ (assuming zero propagation delay)

Example:

- ❑ $L = 7.5$ Mbits
- ❑ $R = 1.5$ Mbps
- ❑ transmission delay = 15 sec
 $[(7.5/1.5)*3]$
- ❑ *Transmission delay is actually time taken to push the data into the link by router/host.*

Packet switching VS circuit switching

□ Packet Switch:

- ❖ great for bursty data
 - resource sharing
 - simpler, no call setup
- ❖ **excessive congestion:** packet delay and loss
 - protocols needed for reliable data transfer, congestion control

□ Q: How to provide circuit-like behavior?

- ❖ bandwidth guarantees needed for audio/video apps
- ❖ still an unsolved problem (chapter 7)

Numerical example

❑ How long does it take to send a file of 640,000 bits from host A to host B over a circuit-switched network?

- ❖ All links are 1.536 Mbps
- ❖ Each link uses TDM with 24 slots/sec
- ❖ 500 msec to establish end-to-end circuit

- ❑ Link speed = 1.536 Mbps and link uses 24 slots/sec
- ❑ Transmission Rate of a circuit (slot) = $1.536/24 = 64\text{kbps}$
- ❑ Time taken to send the file = $640,000/64,000 = 10\text{ sec}$
- ❑ Total time taken = 10.5 sec

Chapter 1: roadmap

- ✓ 1.1 What *is* the Internet?

- ✓ 1.2 Network edge

 - end systems, access networks, links

- ✓ 1.3 Network core

 - circuit switching, packet switching, network structure

- 1.4 Delay, loss and throughput in packet-switched networks

- 1.5 Protocol layers, service models

Chapter 1

Introduction

A note on the use of these ppt slides:


We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- ☐ If you use these slides (e.g., in a class) in substantially unaltered form, that you mention their source (after all, we'd like people to use our book!)
- ☐ If you post any slides in substantially unaltered form on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2009

J.F Kurose and K.W. Ross, All Rights Reserved



*Computer Networking:
A Top Down Approach ,
5th edition.*

*Jim Kurose, Keith Ross
Addison-Wesley, April
2009.*

Thank you