

Computer Networks

The Application Layer

Prof. Navrati Saxena
San Jose State University

Force behind internet success -> Internet Applications

Popular Applications

■ 1970s and 1980s:

- text email, remote access to computers, file transfers, and newsgroups

■ Mid-1990s:

- World Wide Web, encompassing Web surfing, search, and electronic commerce.
- Instant messaging and P2P file sharing - the two killer applications introduced at the end of the millennium.

■ Since 2000:

- Explosion of popular voice and video applications, including:
 - voice-over-IP (VoIP) and video
- conferencing over IP such as Skype;
- user-generated video distribution such as YouTube; and
- movies on demand such as Netflix
- Multiplayer online games
- Social networking applications – Facebook, Twitter

Application layer: overview

- Principles of network applications
- Web and HTTP
- FTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP



Application layer: overview

Our goals:

- conceptual *and* implementation aspects of application-layer protocols
 - transport-layer service models
 - client-server paradigm
 - peer-to-peer paradigm
- learn about protocols by examining popular application-layer protocols and infrastructure
 - HTTP
 - SMTP, IMAP
 - DNS

Some network apps

- social networking
- Web
- text messaging
- e-mail
- multi-user network games
- streaming stored video (YouTube, Hulu, Netflix)
- P2P file sharing
- voice over IP (e.g., Skype)
- real-time video conferencing (e.g., Zoom)
- Internet search
- remote login
- ...

Creating a network app


write programs that:

- run on (different) end systems
- communicate over network
- e.g., web server software communicates with browser software

no need to write software for network-core devices

- network-core devices do not run user applications

Communication for a network application takes place between end systems at the application layer




Client-server paradigm

server:

- always-on host
- permanent IP address
- often in data centers, for scaling


clients:

- contact, communicate with server
- may be intermittently connected
- may have dynamic IP addresses
- do *not* communicate directly with each other
- examples: HTTP, IMAP, FTP



Peer-peer architecture

- *no* always-on server
- arbitrary end systems directly communicate
- peers request service from other peers, provide service in return to other peers
 - *self scalability* – new peers bring new service capacity, as well as new service demands
- peers are intermittently connected and change IP addresses
 - complex management
- example: P2P file sharing



Processes communicating

process: program running within a host

- within same host, two processes communicate using **inter-process communication** (defined by OS)
- processes in different hosts communicate by exchanging **messages**

clients, servers


client process: process that initiates communication

server process: process that waits to be contacted

- note: applications with P2P architectures have client processes & server processes

Sockets

- process sends/receives messages to/from its **socket**
- socket analogous to door
 - sending process shoves message out door
 - sending process relies on transport infrastructure on other side of door to deliver message to socket at receiving process
 - two sockets involved: one on each side



Socket: interface between the application layer and the transport layer ~ API

What transport service does an app need?

data integrity

- some apps (e.g., file transfer, web transactions) require 100% **reliable data transfer**
- other apps (e.g., audio) can **tolerate some loss**

timing

- some apps (e.g., Internet telephony, interactive games) require low delay to be “effective”

throughput

- **Bandwidth sensitive applications:**
 - some apps (e.g., multimedia) require minimum amount of throughput to be “effective”
- **Elastic applications**
 - make use of whatever throughput they get

security

- encryption, data integrity, authentication, ...

Transport Services Provided by the Internet

- The internet – TCP/IP networks makes two transport protocols
 - TCP
 - UDP
- When an application developer creates a new application, first decision to make is whether to use TCP or UDP

Transport Service Requirements: Common Apps

application	data loss	throughput	time sensitive?
-------------	-----------	------------	-----------------

file transfer/download	no loss	elastic	no
e-mail	no loss	elastic	no
Web documents	no loss	elastic	no
real-time audio/video	loss-tolerant	audio: 5Kbps-1Mbps video:10Kbps-5Mbps	yes, 10's msec
streaming audio/video	loss-tolerant	same as above	yes, few secs
interactive games	loss-tolerant	Kbps+	yes, 10's msec
text messaging	no loss	elastic	yes and no

Internet Transport Protocols Services

TCP service:

- *connection-oriented*: setup required between client and server processes
- *reliable transport* between sending and receiving process
 - *flow control*: sender won't overwhelm receiver
 - *congestion control*: throttle sender when network overloaded
 - *does not provide*: timing, minimum throughput guarantee, security

UDP service:

- *unreliable data transfer* between sending and receiving process
- *does not provide*: reliability, flow control, congestion control, timing, throughput guarantee, security, or connection setup.

Q: why bother? *Why* is there a UDP?

Internet applications, and transport protocols

application	application layer protocol	transport protocol
file transfer/download	FTP [RFC 959]	TCP
e-mail	SMTP [RFC 5321]	TCP
Web documents	HTTP 1.1 [RFC 7320]	TCP
Internet telephony	SIP [RFC 3261], RTP [RFC 3550], or proprietary	TCP or UDP
streaming audio/video	HTTP [RFC 7320], DASH	TCP
interactive games	WOW, FPS (proprietary)	UDP or TCP

Addressing processes

- to receive messages, process must have *identifier – 2 piece of information*
 - *Name or address of the host (IP)*
 - *An identifier that specifies the receiving process in the destination host (port number)*
- host device has unique 32-bit IP address
 - Q: does IP address of host on which process runs suffice for identifying the process?
 - A: no, many processes can be running on same host
- *identifier* includes both **IP address** and **port numbers** associated with process on host.
- example port numbers:
 - HTTP server: 80
 - mail server SMTP: 25
- to send HTTP message to sjsu.edu web server:
 - **IP address:** 123.456.789.10
 - **port number:** 80

An application-layer protocol defines:

- types of messages exchanged,
 - e.g., request, response
- message syntax:
 - what fields in messages & how fields are delineated
- message semantics
 - meaning of information in fields
- rules for when and how processes send & respond to messages

open protocols:

- defined in RFCs, everyone has access to protocol definition
- allows for interoperability
- e.g., HTTP, SMTP

proprietary protocols:

- e.g., Skype, Zoom

Application layer: overview

- Principles of network applications
- **Web and HTTP**
- FTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P Applications



The web and HTTP

- Tim Berners Lee
- Web operates - *On demand*
- *Anyone* can become a publisher at a low cost
- HTTP – Web's application layer protocol
 - Implemented in two programs – server and client, on different hosts
 - Communicate via HTTP messages

Web and HTTP

First, a quick review...

- web page consists of *objects*, each of which can be stored on different Web servers
- object can be HTML file, JPEG image, Java applet, audio file,...
- web page consists of *base HTML-file* which includes *several referenced objects, each* addressable by a *URL*, e.g.,

`www.someschool.edu/someDept/pic.gif`

host name

path name


HTTP overview

HTTP: hypertext transfer protocol

- Web's application-layer protocol
- client/server model:
 - *client*: browser that requests, receives, (using HTTP protocol) and “displays” Web objects
 - *server*: Web server sends (using HTTP protocol) objects in response to requests

HTTP defines:

1. How Web clients request Web pages from Web servers and
2. How servers transfer Web pages to clients



HTTP overview (continued)

HTTP uses TCP:

- client initiates TCP connection (creates socket) to server, port 80
- server accepts TCP connection from client
- HTTP messages (application-layer protocol messages) exchanged between browser (HTTP client) and Web server (HTTP server)
- TCP connection closed

HTTP is “stateless”

- server maintains *no* information about past client requests

aside
protocols that maintain “state” are complex!

- past history (state) must be maintained
- if server/client crashes, their views of “state” may be inconsistent, must be reconciled

HTTP connections: two types

Non-persistent HTTP

1. TCP connection opened
2. at most one object sent over TCP connection
3. TCP connection closed

downloading multiple objects required multiple connections

Persistent HTTP (by default)

- TCP connection opened to a server
- multiple objects can be sent over *single* TCP connection between client, and that server
- TCP connection closed

Non-persistent HTTP: example

User enters URL: `www.someSchool.edu/someDepartment/home.index`
(containing text, references to 10 jpeg images)



1a. HTTP client initiates TCP connection to HTTP server (process) at `www.someSchool.edu` on port 80



1b. HTTP server at host `www.someSchool.edu` waiting for TCP connection at port 80 “accepts” connection, notifying client

2. HTTP client sends HTTP *request message* (containing URL) into TCP connection socket. Message indicates that client wants object `someDepartment/home.index`

3. HTTP server receives request message, forms *response message* containing requested object, and sends message into its socket

time



Non-persistent HTTP: example (cont.)

User enters URL: `www.someSchool.edu/someDepartment/home.index`
(containing text, references to 10 jpeg images)



5. HTTP client receives response message containing html file, displays html. Parsing html file, finds 10 referenced jpeg objects

6. Steps 1-5 repeated for each of 10 jpeg objects

4. HTTP server closes TCP connection.




Non-persistent HTTP: response time

RTT (definition): time for a small packet to travel from client to server and back

HTTP response time (per object):

- one RTT to initiate TCP connection
- one RTT for HTTP request and first few bytes of HTTP response to return
- object/file transmission time



Non-persistent HTTP response time = 2RTT + file transmission time

RTT = propagation delay + queueing delay + packet processing delay

Persistent HTTP (HTTP 1.1)

Non-persistent HTTP issues:

- requires 2 RTTs per object
- OS overhead for *each* TCP connection
- browsers often open multiple parallel TCP connections to fetch referenced objects in parallel


Persistent HTTP (HTTP1.1):

- server leaves connection open after sending response
- subsequent HTTP messages between same client/server sent over open connection
- client sends requests as soon as it encounters a referenced object
- as little as one RTT for all the referenced objects (cutting response time in half)

HTTP request message

- two types of HTTP messages: *request, response*
- HTTP request message:
 - ASCII (human-readable)

HTTP request message: general format



Other HTTP request messages

POST method:

- web page often includes form input
- user input sent from client to server in entity body of HTTP POST request message

GET method (for sending data to server):

- include user data in URL field of HTTP GET request message (following a '?'):

`www.somesite.com/animalsearch?monkeys&banana`


HEAD method:

- requests headers (only) that would be returned *if* specified URL were requested with an HTTP GET method.

PUT method:

- uploads new file (object) to server
- completely replaces file that exists at specified URL with content in entity body of POST HTTP request message

HTTP response message

status line (protocol  HTTP/1.1 200 OK
status code status phrase)

Chapter 2

Application Layer

A note on the use of these PowerPoint slides:


We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

For a revision history, see the slide note for this page.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2020
J.F Kurose and K.W. Ross, All Rights Reserved



Computer Networking: A Top-Down Approach

8th edition n
Jim Kurose, Keith Ross
Pearson, 2020

Thank you