Unification in First order logic

```
import ast
from typing import Union, List, Dict, Tuple
from collections import deque
# Define Term Classes
class Term:
   def substitute(self, subs: Dict[str, 'Term']) -> 'Term':
       raise NotImplementedError
   def occurs(self, var: 'Variable') -> bool:
       raise NotImplementedError
   def eq (self, other):
       raise NotImplementedError
   def str (self):
        raise NotImplementedError
class Variable(Term):
   def init (self, name: str):
       self.name = name
   def substitute(self, subs: Dict[str, Term]) -> Term:
        if self.name in subs:
            return subs[self.name].substitute(subs)
        return self
   def occurs(self, var: 'Variable') -> bool:
       return self.name == var.name
   def eq (self, other):
```

```
return isinstance(other, Variable) and self.name == other.name
   def __str__(self):
       return self.name
class Constant(Term):
   def init (self, name: str):
       self.name = name
   def substitute(self, subs: Dict[str, Term]) -> Term:
       return self
   def occurs(self, var: 'Variable') -> bool:
       return False
   def eq (self, other):
       return isinstance(other, Constant) and self.name == other.name
   def str (self):
        return self.name
class Function(Term):
   def init (self, name: str, args: List[Term]):
        self.name = name
        self.args = args
   def substitute(self, subs: Dict[str, Term]) -> Term:
        substituted args = [arg.substitute(subs) for arg in self.args]
        return Function(self.name, substituted args)
   def occurs(self, var: 'Variable') -> bool:
        return any(arg.occurs(var) for arg in self.args)
   def eq (self, other):
       return (
            isinstance(other, Function) and
            self.name == other.name and
            len(self.args) == len(other.args) and
            all(a == b for a, b in zip(self.args, other.args))
```

```
def str (self):
        return f"{self.name}({', '.join(str(arg) for arg in self.args)})"
def parse expression(expr: List) -> Term:
    if not isinstance(expr, list) or not expr:
        raise ValueError("Expression must be a non-empty list")
    func name = expr[0]
   args = expr[1:]
   parsed args = []
    for arg in args:
        if isinstance(arg, list):
            parsed args.append(parse expression(arg))
        elif isinstance(arg, str):
            if arg[0].islower():
                parsed args.append(Variable(arg))
            elif arg[0].isupper():
                parsed args.append(Constant(arg))
            else:
                raise ValueError(f"Invalid argument format: {arg}")
            raise ValueError(f"Unsupported argument type: {arg}")
    return Function(func name, parsed args)
def unify terms(term1: Term, term2: Term) -> Union[Dict[str, Term], str]:
    # Initialize substitution set S
    S: Dict[str, Term] = {}
    # Initialize the equation list
    equations: deque[Tuple[Term, Term]] = deque()
    equations.append((term1, term2))
    while equations:
        s, t = equations.popleft()
        s = s.substitute(S)
        t = t.substitute(S)
```

```
if s == t:
            continue
        elif isinstance(s, Variable):
            if t.occurs(s):
                return "FAILURE"
            S[s.name] = t
            # Apply the substitution to existing substitutions
            for var in S:
                S[var] = S[var].substitute({s.name: t})
        elif isinstance(t, Variable):
            if s.occurs(t):
                return "FAILURE"
            S[t.name] = s
            for var in S:
                S[var] = S[var].substitute({t.name: s})
        elif isinstance(s, Function) and isinstance(t, Function):
            if s.name != t.name or len(s.args) != len(t.args):
               return "FAILURE"
            for s arg, t arg in zip(s.args, t.args):
                equations.append((s arg, t arg))
        elif isinstance(s, Constant) and isinstance(t, Constant):
            if s.name != t.name:
               return "FAILURE"
            # else, they are equal; continue
        else:
            return "FAILURE"
    return S
def format substitution(S: Dict[str, Term]) -> str:
    if not S:
       return "{}"
    return "{ " + ", ".join(f"{var} = {term}" for var, term in S.items())
+ " }"
def unify(expression1: List, expression2: List) -> Union[Dict[str, Term],
str]:
    try:
        term1 = parse_expression(expression1)
        term2 = parse expression(expression2)
```

```
except ValueError as e:
        return f"FAILURE: {e}"
    result = unify terms(term1, term2)
    return result
def main():
   print("=== Unification Algorithm ===\n")
   print("Tanush Prajwal S")
   print("1BM22CS304")
   print("Please enter the expressions in list format.")
   print("Example: [\"Eats\", \"x\", \"Apple\"]\n")
   try:
        expr1_input = input("Enter Expression 1: ")
        expression1 = ast.literal eval(expr1 input)
        if not isinstance(expression1, list):
            raise ValueError("Expression must be a list.")
        expr2 input = input("Enter Expression 2: ")
        expression2 = ast.literal eval(expr2 input)
        if not isinstance(expression2, list):
            raise ValueError("Expression must be a list.")
    except (SyntaxError, ValueError) as e:
        print(f"Invalid input format: {e}")
        return
    result = unify(expression1, expression2)
    if isinstance(result, str):
       print("\nUnification Result:")
       print(result)
    else:
       print("\nUnification Successful:")
        print(format substitution(result))
if __name__ == "__main__":
    main()
```

OUTPUT

```
=== Unification Algorithm ===
Tanush Prajwal S
1BM22CS304
Please enter the expressions in list format.
Example: ["Eats", "x", "Apple"]
Enter Expression 1: ["Eats", "x", "Apple"]
Enter Expression 2: ["Eats", "Riya", "y"]
Unification Successful:
\{ x = Riya, y = Apple \}
=== Unification Algorithm ===
Tanush Prajwal S
1BM22CS304
Please enter the expressions in list format.
Example: ["Eats", "x", "Apple"]
Enter Expression 1: ["f", "x"]
Enter Expression 2: ["f", ["g", "x"]]
Unification Result:
FAILURE
```