



**S. B. JAIN INSTITUTE OF TECHNOLOGY,
MANAGEMENT & RESEARCH, NAGPUR**

Session: 2026-2027 ODD

**Project Based Learning Report
On**

**“Opening and Closing for Smoothing Text Region
Morphological opening and closing.”**

Subject: - Image Processing

Semester/Year: III/V

Sr. No	Name of Students & USN	Problem Understanding & Objective[2M]	Implementation & Functionality[4 M]	Output Quality & Analysis[2 M]	Report/Presentation Quality[2 M]	Total[10M]
1	Tanushree Banait (CS24120)					

Date of Submission:

1. ABSTRACT

Morphological opening and closing are important mathematical morphology techniques used for improving and smoothing text regions in digital images. Opening is performed using erosion followed by dilation and helps remove small noise and unwanted objects. Closing uses dilation followed by erosion and helps fill small gaps and connect broken parts of text. These operations use a structuring element to modify the shape of image regions. They are useful in document processing, text extraction, character recognition, and image enhancement applications.

2. INTRODUCTION

Image processing involves analyzing and modifying digital images to obtain useful information and improve their quality. One important area of image processing is the processing of text regions, where noise, small gaps, and broken characters can affect the quality of the extracted text.

Morphological operations are techniques based on the shape and structure of objects in an image. Opening and closing are two fundamental morphological operations used for smoothing and improving text regions. Opening is performed by erosion followed by dilation. It removes small unwanted objects and noise while preserving the main structure of the text. Closing is performed by dilation followed by erosion. It fills small gaps and connects broken portions of text.

The scope of this project is to understand the mathematical principle of morphological opening and closing and implement these operations on text regions. The input image is processed using suitable structuring elements, and the resulting image is analyzed to observe the smoothing and improvement of text regions.

3. AIM AND OBJECTIVES

Aim: To implement and study morphological opening and closing operations for smoothing and improving text regions in digital images.

Objective:

1. To understand the concepts of morphological erosion, dilation, opening, closing, and structuring elements.
2. To implement morphological opening and closing operations on an image containing text regions.
3. To analyze the output and study the applications of opening and closing in text processing and image enhancement.

4. PROBLEM STATEMENT

Text regions in digital images may contain small unwanted noise, gaps, broken characters, or irregular boundaries. These problems can reduce the quality of text extraction and make further image processing difficult. Basic image-processing techniques may not always provide a suitable method for removing small unwanted regions while maintaining the main structure of the text.

The problem addressed in this project is the smoothing and improvement of text regions using morphological opening and closing operations. Morphological opening provides a solution for removing small objects and noise from the image.

5. LITERATURE REVIEW

Previous studies demonstrate that morphological operations are useful for analyzing and modifying the structural characteristics of objects in digital images. Erosion and dilation are fundamental morphological operations, while opening and closing are combinations of these operations used for noise removal and shape improvement. Morphological opening is particularly useful for removing small foreground objects and smoothing boundaries. Morphological closing is useful for filling small holes, closing narrow gaps, and connecting nearby regions.

However, the effectiveness of these operations depends on the selection of a suitable structuring element. A structuring element with an unsuitable size or shape may remove useful text information or fail to remove unwanted noise. Therefore, selecting an appropriate structuring element is important for obtaining a good output. The present study focuses on the fundamental morphological opening and closing operations and their application to smoothing text regions.

6. PROBLEM DEFINITION & METHODOLOGY

Problem Definition: The project considers a digital image containing text regions along with possible noise, small gaps, and broken portions. The input image is processed using suitable morphological operations. The input is a text image and a predefined structuring element. The output is an improved image in which unwanted small regions are reduced and gaps or breaks in the text regions are minimized.

Methodology: The methodology begins with obtaining a suitable text image. If necessary, the image is converted into grayscale and then into binary form. A binary image contains foreground and background information, which makes it suitable for morphological processing. After obtaining the binary image, a suitable structuring element is selected according to the size and structure of the text.

The first stage performs erosion on the image followed by dilation. This produces the morphological opening operation and helps remove small unwanted objects and noise. The second stage performs dilation followed by erosion.

This produces the morphological closing operation and helps fill small gaps and connect broken regions.

Finally, the original image and processed images are compared to observe the improvement in text regions.

Thus, the overall methodology consists of image preparation, binary conversion, structuring-element selection, opening, closing, and output analysis.

7. MATHEMATICAL EQUATION/ MODELING

Morphological opening is mathematically represented as:

$$A \circ B = (A \ominus B) \oplus B$$

Where:

A represents the input image.

B represents the structuring element.

- $\ominus$ represents morphological erosion.
- $\oplus$ represents morphological dilation.
- $\circ$ represents morphological opening.

The opening operation first erodes the image and then dilates the resulting image using the same structuring element.

Morphological closing is represented as:

$$A \bullet B = (A \oplus B) \ominus B$$

Where:

A represents the input image.

B represents the structuring element.

$\oplus$ represents morphological dilation.

$\ominus$ represents morphological erosion.

$\bullet$ represents morphological closing.

The closing operation first dilates the image and then erodes the resulting image.

Therefore:

Opening = Erosion + Dilation

Closing = Dilation + Erosion

Opening mainly helps in removing small unwanted regions, whereas closing helps in filling small gaps and connecting broken regions

8. PSEUDOCODE/ALGORITHM

Algorithm

The working procedure of morphological opening and closing can be explained theoretically as follows:

First, a text image is selected as the input. If the original image is not suitable for morphological processing, it is converted into grayscale and then binary form through an appropriate thresholding process.

Next, a suitable structuring element is selected according to the size and shape of the text regions.

For the opening operation, the binary image is first eroded using the selected structuring element. The eroded image is then dilated using the same structuring element. This removes small unwanted objects and noise.

For the closing operation, the image is first dilated using the structuring element. The dilated image is then eroded using the same structuring element. This fills small gaps and connects broken text regions. Finally, the original image is compared with the opened and closed images to analyze the improvement.

Basic Steps

1. Read the input text image.
2. Convert the image into grayscale.

3. Convert the image into binary form.
4. Select a suitable structuring element.
5. Apply erosion.
6. Apply dilation.
7. Obtain the opening result.
8. Apply dilation followed by erosion.
9. Obtain the closing result.
10. Display and analyze the output images

9. IMPLEMENTATION

Morphological opening and closing can be implemented using image-processing software and programming libraries. Python is suitable for this purpose because it provides libraries for image processing and numerical computation. OpenCV can be used for performing morphological operations, while NumPy can be used for representing and processing image arrays.

The implementation requires a text image and a suitable structuring element. The image is first read and converted into a binary representation. The selected structuring element is then used to perform opening and closing operations.

The opening operation removes small unwanted regions and noise from the text image. The closing operation fills small gaps and connects broken parts of text. A development environment such as Visual Studio Code, PyCharm, or Jupyter Notebook can be used for implementing the project.


10. RESULTS AND DISCUSSION

Result:

Parameter	Observation
Input Image	Text image containing different text regions
Pre-processing	Grayscale and binary conversion
Structuring Element	Selected according to text size
Opening	Removes small noise and unwanted regions
Closing	Fills small gaps and connects broken regions
Output	Smoothed and improved text regions
Quality	Depends on image quality and structuring

Input Image

Original image supplied for processing



OPENING Opening Result



CHANGE MAP Opening Changes



CLOSING Closing Result



CHANGE MAP Closing Changes



OPENING

Opening



CLOSING

Closing





Discussion:

The expected result of morphological opening and closing is an improved text image with smoother and cleaner text regions.

The original image may contain small noise, unwanted objects, gaps, or broken portions that can affect further processing. Morphological opening removes small unwanted foreground regions and helps smooth the boundaries of text.

It is especially useful when the image contains small noise around the text. Morphological closing improves the continuity of text by filling small gaps and connecting nearby or broken regions. This makes the text regions more complete and suitable for further processing. The result can be analyzed by comparing the original image with the opening and closing outputs.

11. CONCLUSION AND FUTURE SCOPE

Conclusion:

Morphological opening and closing are important techniques for improving text regions in digital images. Opening works through erosion followed by dilation and helps remove small noise and unwanted regions. Closing works through dilation followed by erosion and helps fill small gaps and connect broken text regions.

The study shows that these operations are simple and effective for smoothing and improving text regions. Their performance depends mainly on the selection of a suitable structuring element. These techniques provide a useful foundation for understanding more advanced morphological image-processing methods.

Future Scope :

The technique can be extended to more complex image-processing applications. Future work can focus on automatically selecting the size and shape of the structuring element according to different text sizes. The operations can also be combined with noise-removal and thresholding techniques to improve text extraction.

Opening and closing can further be used as preprocessing steps for Optical Character Recognition (OCR) and document analysis. Advanced image-processing and machine-learning techniques can also be combined with morphological operations for more accurate text detection and recognition.

12. REFERENCES

1. P. Soille, Morphological Image Analysis: Principles and Applications, Springer.
2. J. Serra, Image Analysis and Mathematical Morphology, Academic Press.
3. OpenCV Documentation, Morphological Transformations.
4. R. C. Gonzalez and R. E. Woods, Digital Image Processing, Pearson.
5. National Center for Biotechnology Information (NCBI), Morphological image processing and related text-region processing research, reference provided for the project:
6. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC9657866/>

13. Appendix:

A. Complete Python Code

```
import cv2
import numpy as np

# Read input image
img = cv2.imread("text.png", 0)

# Convert image into binary
_, binary = cv2.threshold(
    img, 127, 255, cv2.THRESH_BINARY
)
```

```
# Define structuring element
kernel = np.ones((3, 3), np.uint8)

# Apply Morphological Opening
opening = cv2.morphologyEx(
    binary, cv2.MORPH_OPEN, kernel
)

# Apply Morphological Closing
closing = cv2.morphologyEx(
    binary, cv2.MORPH_CLOSE, kernel
)

# Display images
cv2.imshow("Original Image", binary)
cv2.imshow("Opening Result", opening)
cv2.imshow("Closing Result", closing)

cv2.waitKey(0)
cv2.destroyAllWindows()
```

B. Applications

1. Morphological opening and closing have several applications in image processing and computer vision. They can be used for text-region smoothing, document analysis, optical character recognition, and text extraction.
2. Opening can help remove small unwanted noise from scanned documents and text images. Closing can help connect broken characters and fill small gaps in text regions.
3. These techniques are also useful in image enhancement, object segmentation, shape analysis, and preprocessing before OCR.
4. By improving the quality and continuity of text regions, morphological operations can make later image-processing tasks more re

