

You're almost there — sign up to start building in Notion today.

Sign up or login

Spec Document

1. Overview

Replace the stub in `database/db.py` with a working SQLite implementation.

This step establishes the **data layer foundation** for the Spendly application.

All future features (authentication, profile, expense tracking) depend on this being correctly implemented.

2. Depends on

Nothing — this is the first step.

3. Routes

- No new routes
- Existing placeholder routes in `app.py` remain unchanged

4. Database Schema

A. users

Column	Type	Constraints
id	INTEGER	Primary key, autoincrement
name	TEXT	Not null

email	TEXT	Unique, not null
password_hash	TEXT	Not null
created_at	TEXT	Default datetime('now')

B. expenses

Column	Type	Constraints
id	INTEGER	Primary key, autoincrement
user_id	INTEGER	Foreign key → users.id, not null
amount	REAL	Not null
category	TEXT	Not null
date	TEXT	Not null (YYYY-MM-DD format)
description	TEXT	Nullable
created_at	TEXT	Default datetime('now')

5. Functions to Implement (`database/db.py`)

A. `get_db()`

- Opens connection to `spendly.db` (or `expense_tracker.db`) in project root
- Sets:
 - `row_factory = sqlite3.Row`
 - `PRAGMA foreign_keys = ON`
- Returns the connection

B. `init_db()`

- Creates both tables using `CREATE TABLE IF NOT EXISTS`
- Safe to call multiple times
- Ensures schema is ready before app usage

C. `seed_db()`

- Checks if `users` table already contains data
 - If yes → return early (no duplication)
- Inserts one demo user:
 - name: Demo User
 - email: demo@spendly.com
 - password: demo123 (hashed using `werkzeug`)
- Inserts **8 sample expenses**:
 - All linked to demo user
 - Cover multiple categories
 - Dates spread across current month
 - At least one expense per category

6. Changes to `app.py`

- Import:
 - `get_db`
 - `init_db`
 - `seed_db`
- Call `init_db()` and `seed_db()` inside `app.app_context()` on startup
- Ensure DB is ready before routes are used

7. Files to Change

7. Files to Change

- `database/db.py` → implement all functions
- `app.py` → add imports and startup calls

8. Files to Create

- None

9. Dependencies

- No new pip packages
- Use:
 - `sqlite3` (standard library)
 - `werkzeug.security` (already installed)

10. Categories (Fixed List)

Use exactly these values:

- Food
- Transport
- Bills
- Health
- Entertainment
- Shopping
- Other

11. Rules for Implementation

- No ORMs (no SQLAlchemy)
- Use **parameterized queries only**

- Never use string formatting in SQL
- Enable `PRAGMA foreign_keys = ON` on every connection
- Store `amount` as REAL (float), not INTEGER
- Hash passwords using:

```
fromwerkzeug.securityimportgenerate_password_hash
```

- `seed_db()` must prevent duplicate inserts
- Dates must follow YYYY-MM-DD format consistently

12. Expected Behavior

- `get_db()` returns a working connection with:
 - dictionary-like row access
 - foreign key enforcement enabled
- `init_db()` :
 - creates tables safely
 - does not fail on repeated runs
- `seed_db()` :
 - inserts demo data only once
 - does not duplicate records on multiple runs
- Database enforces:
 - unique email constraint
 - valid foreign key relationships

13. Error Handling Expectations

- Inserting duplicate email → should fail (UNIQUE constraint)
- Inserting expense with invalid `user_id` → should fail (foreign key constraint)

constraint)

- Invalid queries → should raise clear errors for debugging

14. Definition of Done

- ☐ Database file is created on app startup
- ☐ Both tables exist with correct schema and constraints
- ☐ Demo user exists with hashed password
- ☐ 8 sample expenses exist across categories
- ☐ No duplicate seed data on repeated runs
- ☐ App starts without errors
- ☐ Foreign key enforcement works
- ☐ All queries use parameterized SQL