

Assignment 2

Ans1

```
> tup=(10,20,30,40,50)
print(tup[0])
print(tup[-1])
print(len(tup))
print(tup[1:4])
1] ✓ 0.0s
10
50
5
(20, 30, 40)
```

creating tuple then finding its elements

Ans 2

```
fruits=("apple","banana","mango","orange")
print(fruits[1])
print(fruits[-2:])
print(len(fruits))
✓ 0.1s
banana
('mango', 'orange')
4
```

Assignment 2

Ans 3

```
numbers={10,20,30,40,50}
print(numbers)
print(len(numbers))
print(30 in numbers)
```

✓ 0.0s

{50, 20, 40, 10, 30}
5
True

Ans 4

```
set1={1,2,3,4}
set2={3,4,5,6}
print("union",set1.union(set2))
print("intersection",set1.intersection(set2))
```

✓ 0.0s

union {1, 2, 3, 4, 5, 6}
intersection {3, 4}

an

Ans 5

Assignment 2

```
# dictoinroy=
student={"name":"kirti",
        "age":20,"course":"python"}
print(student)
print(student["name"])
print(student["age"])
print(student["course"])

#list anylusion
numbers_list=[12,45,7,23,56,89,34]
print(max(numbers_list))
anot_list=list(set(numbers_list))

anot_list.sort()
print(anot_list[-2])
```

✓ 0.0s

{'name': 'kirti', 'age': 20, 'course': 'python'}
kirti
20
python
89
56

Ans 6 reversing list wihtout reverse

```
def reverse_list(arr):
    return arr[::-1]
arr=[10,20,30,40,50,60]
print(reverse_list(arr))
```

✓ 0.0s

[60, 50, 40, 30, 20, 10]

Ans 7

Assignment 2

```
data=(5,10,15,20,25,30,35)
div_by_5=[x for x in data if x%5==0]
print(len(div_by_5))
total_sum=sum(data)
print(total_sum)
avreage=total_sum/len(data)
print(avreage)
```

✓ 0.0s

7
140
20.0

Ans 8

```
students={
    "aman":78,
    "riya":92,
    "kriti":88,
    "rahul":95
}
hightest_student=max(students,key=students.get)
lowest_student=min(students,key=students.get)
```

Python

Ans9

Assignment 2

```
def count_freq(arr):  
    frequenices={}  
    for item in arr:  
        frequenices[item]=frequenices.get(item,0)+1  
    for key,value in frequenices.items():  
        print(f"{key}->{value}times")  
  
arr=[1,2,3,3,1,4,2]  
count_freq(arr)
```

✓ 0.0s

Python

```
1->2times  
2->2times  
3->2times  
4->1times
```