

Project Details


Task: A2

Done by: Tan Wei Jie (A0202017B)

Repo Link: https://github.com/tanweijie123/CS3219_Sandbox/tree/main/Task_A/A2

Instructions on how to run

1. For my project, I will be using Docker Desktop with Kubernetes. As a start, ensure that Kubernetes is enabled on your Docker Desktop. You can do that by going to Docker Desktop > Settings, check on "Enable Kubernetes".



2. Next, check that your kubernetes is using the `docker-desktop` environment. You can do this by entering `kubectl config use-context docker-desktop`.

```
PS C:\Users\tanwe> kubectl config use-context docker-desktop
Switched to context "docker-desktop".
```

3. Build the docker image that you want to use for kubernetes. In this example, I will be using a simple webserver found in `./webserver/` directory. Run `docker build ./webserver/ -t my-static-web` to build the docker image, and name it `my-static-web`.

```
PS C:\Users\tanwe\Desktop\Git\CS3219_sandbox\Task_A\A2> docker build ./webserver/ -t my-static-web
[+] Building 0.2s (7/7) FINISHED
-> [internal] load build definition from Dockerfile
-> => transferring dockerfile: 132B
-> [internal] load .dockerignore
-> => transferring context: 2B
-> [internal] load metadata for docker.io/library/nginx:alpine
-> [internal] load build context
-> => transferring context: 315B
-> CACHED [1/2] FROM docker.io/library/nginx:alpine
-> [2/2] COPY ./usr/share/nginx/html
-> exporting to image
-> => exporting layers
-> => writing image sha256:8ee16888bc87212bd3a5d91b0ceae9431145813ee867d51daa0dd3e93f786424
-> => naming to docker.io/library/my-static-web

Use 'docker scan' to run Snyk tests against images to find vulnerabilities and learn how to fix them
PS C:\Users\tanwe\Desktop\Git\CS3219_sandbox\Task_A\A2>
```

4. Once the build is complete, execute `kubectl apply -f ./deployment-service.yml` to setup kubernetes configuration. Verify that you have 3 running pods for the `webserver-service` service. You should also note that

port 31111 is exposed due to the `deployment-service.yml` configuration.

```
37 lines (37 sloc) | 605 Bytes
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    namespace: default
5    name: webserver-deployment
6    labels:
7      app: web
8  spec:
9    replicas: 3
10   selector:
11     matchLabels:
12       app: web
13   template:
14     metadata:
15       labels:
16         app: web
17     spec:
18       containers:
19       - name: webserver
20         image: my-static-web
21         imagePullPolicy: Never
22         ports:
23         - containerPort: 80
24   ---
25   apiVersion: v1
26   kind: Service
27   metadata:
28     namespace: default
29     name: webserver-service
30   spec:
31     type: NodePort
32     selector:
33       app: web
34     ports:
35     - port: 3000
36       targetPort: 80
37       nodePort: 31111
```


```
PS C:\Users\tanwe\Desktop\Git\CS3219_sandbox\Task_A\A2> kubectl apply -f .\deployment-service.yml
deployment.apps/webserver-deployment created
service/webserver-service created
PS C:\Users\tanwe\Desktop\Git\CS3219_sandbox\Task_A\A2> kubectl get all
NAME                                READY    STATUS    RESTARTS   AGE
pod/webserver-deployment-648bf474bf-b7kg4  1/1      Running   0           29s
pod/webserver-deployment-648bf474bf-b86nw  1/1      Running   0           29s
pod/webserver-deployment-648bf474bf-p2rrd  1/1      Running   0           29s

NAME                                TYPE        CLUSTER-IP    EXTERNAL-IP  PORT(S)          AGE
service/kubernetes                  ClusterIP   10.96.0.1     <none>        443/TCP          15m
service/webserver-service           NodePort    10.106.233.39 <none>        3000:31111/TCP   29s

NAME                                READY    UP-TO-DATE    AVAILABLE   AGE
deployment.apps/webserver-deployment  3/3      3              3           30s

NAME                                DESIRED    CURRENT    READY    AGE
replicaset.apps/webserver-deployment-648bf474bf  3          3          3        30s
PS C:\Users\tanwe\Desktop\Git\CS3219_sandbox\Task_A\A2>
```

5. After running the above command, a browser will pop up with the assigned port. In this case, you can access the service at `http://localhost:31111/`.



6. To close kubernetes deployment and services, run `kubect1 delete -f ./deployment-service.yml`.

Learning Points

- In order to use locally created images, I need to set `imagePullPolicy: Never` and enable Docker Desktop's Kubernetes settings.
- Kubernetes are usually run on cloud, it is rarely run locally.

Resources

Resources that are used and referred to during the creation of this project.

Desc	Link
How to Run Locally Built Docker Images in Kubernetes	https://medium.com/swlh/how-to-run-locally-built-docker-images-in-kubernetes-b28fbc32cc1d
To expose port of service in Minikube	https://stackoverflow.com/questions/40767164/expose-port-in-minikube
Deploy Docker Desktop on Kubernetes	https://docs.docker.com/desktop/kubernetes/