

CAP 379

Artificial Intelligence

Tanzeela Javid Kaloo (32638)

Assistant Professor

System And Architecture

Lovely Professional University

Introduction to Neural Network


Tanzeela Javid Kaloo (32638)

Assistant Professor

System And Architecture

Lovely Professional University

The Perceptron: Forward Propagation



Output


Linear combination of inputs

$$\hat{y} = g \left(w_0 + \sum_{i=1}^m x_i w_i \right)$$

Non-linear activation function

Bias

The Perceptron: Forward Propagation




$$\hat{y} = g \left(w_0 + \sum_{i=1}^m x_i w_i \right)$$

$$\hat{y} = g (w_0 + \mathbf{X}^T \mathbf{W})$$

$$\text{where: } \mathbf{X} = \begin{bmatrix} x_1 \\ \vdots \\ x_m \end{bmatrix} \text{ and } \mathbf{W} = \begin{bmatrix} w_1 \\ \vdots \\ w_m \end{bmatrix}$$

The Perceptron: Forward Propagation




Activation Functions

$$\hat{y} = g(w_0 + \mathbf{X}^T \mathbf{W})$$


- Example: sigmoid function

$$g(z) = \sigma(z) = \frac{1}{1 + e^{-z}}$$



Importance of Activation Functions


The purpose of activation functions is to **introduce non-linearities** into the network




What if we wanted to build a neural network to distinguish green vs red points?

Importance of Activation Functions

*The purpose of activation functions is to **introduce non-linearities** into the network*




Linear activation functions produce linear decisions no matter the network size



Non-linearities allow us to approximate arbitrarily complex functions

The Perceptron: Example




We have: $w_0 = 1$ and $\mathbf{W} = \begin{bmatrix} 3 \\ -2 \end{bmatrix}$


$$\begin{aligned}\hat{y} &= g(w_0 + \mathbf{X}^T \mathbf{W}) \\ &= g\left(1 + \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}^T \begin{bmatrix} 3 \\ -2 \end{bmatrix}\right) \\ \hat{y} &= g(1 + 3x_1 - 2x_2)\end{aligned}$$

This is just a line in 2D!


The Perceptron: Example



$$\hat{y} = g(1 + 3x_1 - 2x_2)$$




The Perceptron: Example





Assume we have input: $\mathbf{X} = \begin{bmatrix} -1 \\ 2 \end{bmatrix}$

$$\begin{aligned}\hat{y} &= g(1 + (3 * -1) - (2 * 2)) \\ &= g(-6) \approx 0.002\end{aligned}$$

$$\hat{y} = g(1 + 3x_1 - 2x_2)$$




The Perceptron: Example



Building Neural Networks with Perceptrons

The Perceptron: Simplified

$$\hat{y} = g(w_0 + \mathbf{X}^T \mathbf{W})$$



Inputs


Weights

Sum

Non-Linearity


Output

The Perceptron: Simplified



$$z = w_0 + \sum_{j=1}^m x_j w_j$$


Multi Output Perceptron




$$z_i = w_{0,i} + \sum_{j=1}^m x_j w_{j,i}$$

Multi Output Perceptron


Because all inputs are densely connected to all outputs, these layers are called **Dense** layers



```
 import tensorflow as tf  
  
layer = tf.keras.layers.Dense(  
    units=2)
```

$$z_i = w_{0,i} + \sum_{j=1}^m x_j w_{j,i}$$


Single Layer Neural Network



$$z_i = w_{0,i}^{(1)} + \sum_{j=1}^m x_j w_{j,i}^{(1)}$$


$$\hat{y}_i = g \left(w_{0,i}^{(2)} + \sum_{j=1}^{d_1} g(z_j) w_{j,i}^{(2)} \right)$$

Single Layer Neural Network



$$\begin{aligned} z_2 &= w_{0,2}^{(1)} + \sum_{j=1}^m x_j w_{j,2}^{(1)} \\ &= w_{0,2}^{(1)} + x_1 w_{1,2}^{(1)} + x_2 w_{2,2}^{(1)} + x_m w_{m,2}^{(1)} \end{aligned}$$


Multi Output Perceptron



```
import tensorflow as tf


model = tf.keras.Sequential([
    tf.keras.layers.Dense(n),
    tf.keras.layers.Dense(2)
])
```

Deep Neural Network



$$z_{k,i} = w_{0,i}^{(k)} + \sum_{j=1}^{n_{k-1}} g(z_{k-1,j}) w_{j,i}^{(k)}$$

Deep Neural Network



$$z_{k,i} = w_{0,i}^{(k)} + \sum_{j=1}^{n_{k-1}} g(z_{k-1,j}) w_{j,i}^{(k)}$$



```
import tensorflow as tf

model = tf.keras.Sequential([
    tf.keras.layers.Dense(n1),
    tf.keras.layers.Dense(n2),
    :
    tf.keras.layers.Dense(2)
])
```

Applying Neural Networks

Example Problem


Will I pass this class?

Let's start with a simple two feature model


x_1 = Number of lectures you attend

x_2 = Hours spent on the final project


Example Problem: Will I pass this class?




Example Problem: Will I pass this class?



Example Problem: Will I pass this class?




Example Problem: Will I pass this class?



Quantifying Loss


The **loss** of our network measures the cost incurred from incorrect predictions



$$\mathcal{L}(\underbrace{f(x^{(i)}; \mathbf{W})}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

Empirical Loss

The **empirical loss** measures the total loss over our entire dataset




Also known as:

- Objective function
- Cost function
- Empirical Risk

$$J(\mathbf{W}) = \frac{1}{n} \sum_{i=1}^n \mathcal{L}(\underbrace{f(x^{(i)}; \mathbf{W})}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}})$$

Binary Cross Entropy Loss

Cross entropy loss can be used with models that output a probability between 0 and 1




$$J(W) = -\frac{1}{n} \sum_{i=1}^n \underbrace{y^{(i)}}_{\text{Actual}} \log \left(\underbrace{f(x^{(i)}; W)}_{\text{Predicted}} \right) + (1 - \underbrace{y^{(i)}}_{\text{Actual}}) \log \left(1 - \underbrace{f(x^{(i)}; W)}_{\text{Predicted}} \right)$$



```
loss = tf.reduce_mean( tf.nn.softmax_cross_entropy_with_logits(y, predicted) )
```

Mean Squared Error Loss

Mean squared error loss can be used with regression models that output continuous real numbers



```
loss = tf.reduce_mean( tf.square(tf.subtract(y, predicted)) )  
loss = tf.keras.losses.MSE( y, predicted )
```