

pf lab q1.cpp

```
1  #include<stdio.h>
2  int main()
3  {
4      int amount,withdrawls=0;
5      int balance = 50000;
6
7      printf("enter withdrawl amount");
8      scanf("%d",&amount);
9
10     while(amount>0){
11         if(amount<=balance)
12         {
13             balance=balance-amount;
14             withdrawls++;
15         }
16         else{
17             printf("insufficient balance\n");
18         }
19         printf("enter withdrawl amount");
20         scanf("%d",&amount);
21     }
22
23     printf("\nremaining balance is %d\n",balance);
24     printf("\nnumber of withdrawls is %d\n",withdrawls);
25
26 }
```

C:\Users\HP\Documents\pf la

enter withdrawl amount400

enter withdrawl amount0

remaining balance is 49600

number of withdrawls is 1

Process exited after 39.69 seconds with return value 0
Press any key to continue . . .

```

1  #include<stdio.h>
2  int main()
3  {
4      int marks,total=0,students=0;
5      float avg;
6      printf("enter total marks :(0-100)");
7          scanf("%d",&marks);
8      while(marks!=-1)
9      {
10         if(marks>=0 && marks<=100){
11             total=total+marks;
12             students++;
13         }else{
14             printf("invalid marks");
15         }
16         printf("enter total marks :(0-100)");
17         scanf("%d",&marks);
18     }
19     if(students>0){
20         avg=total/students;
21     }
22
23
24
25
26     printf("\ntotal marks is %d\n",total);
27     printf("\nnumber of students is %d\n",students);
28     printf("\naverage marks is %.2f\n",avg);
29
30

```

```

C:\Users\HP\Documents\Unti
enter total marks :(0-100)60
enter total marks :(0-100)90
enter total marks :(0-100)-1

total marks is 150

number of students is 2

average marks is 75.00

-----
Process exited after 19.06 seconds with return value 0
Press any key to continue . . .

```

```

pr iab q1.ccpp      Untitled2.cpp
1  #include<stdio.h>
2  int main()
3  {
4      int amount, attempts=0, total=0;
5
6      printf("enter recharge amount");
7      scanf("%d",&amount);
8
9      while(amount!=0){
10         total=total + amount;
11         attempts++;
12         printf("enter recharge amount");
13         scanf("%d",&amount);
14     }
15
16     if(total>5000){
17         printf("Recharge limit reached");
18     }
19
20     printf("total recharge amount is %d",total);
21     printf("recharge attempts are %d",attempts);
22 }

```

```

C:\Users\HP\Documents\Unti  X  +  v
enter recharge amount4000
enter recharge amount700
enter recharge amount900
enter recharge amount0
Recharge limit reachedtotal recharge amount is 5600recharge attempts are 3
-----
Process exited after 55.47 seconds with return value 0
Press any key to continue . . .

```

mn.cpp

```
1 #include<stdio.h>
2 int main()
3 {
4     int price[5];
5     printf("enter price");
6     scanf("%d",&price[0]);
7     printf("enter price");
8     scanf("%d",&price[1]);
9     printf("enter price");
10    scanf("%d",&price[2]);
11    printf("enter price");
12    scanf("%d",&price[3]);
13    printf("enter price");
14    scanf("%d",&price[4]);
15
16    int total=0,discout,final_amount;
17    int i;
18    for(i=0;i<5;i++){
19        total=total+price[i];
20    }
21
22
23    if(total>10000){
24        discout=total*0.1;
25    }
26    final_amount=total-discout;
27
28    printf("\ntotal price is %d\n",total);
29    printf("\ntotal discount is %d\n",discout);
30    printf("\nfinal amount is %d\n",final_amount);
31 }
```

C:\Users\HP\Documents\mn.c

```
enter price500
enter price800
enter price9000
enter price700
enter price400
```

```
total price is 11400
```

```
total discount is 1140
```

```
final amount is 10260
```

```
-----
Process exited after 18.09 seconds with return value 0
Press any key to continue . . . |
```

```

f lab q1.cpp  x  Untitled2.cpp  x
1  #include<stdio.h>
2  int main()
3  {
4      int price,item,total=0,final_bill;
5      float discount;
6      printf("enter price of each item");
7      scanf("%d",&price);
8      printf("would you like to order another item(1=yes,0=no)");
9      scanf("%d",&item);
10
11     while(item==1){
12         total=total+price;
13         printf("enter price of each item");
14         scanf("%d",&price);
15         printf("would you like to order another item(1=yes,0=no)");
16         scanf("%d",&item);
17     }
18     total=total+price;
19     if(total>5000)
20     {
21         discount=total*0.05;
22     }
23     final_bill=total-discount;
24
25     printf("\ntotal bill is %d\n",total);
26     printf("\ndiscounted price is %f\n",discount);
27     printf("\nfinal bill is %d\n",final_bill);
28 }

```

```

enter price of each item500
would you like to order another item(1=yes,0=no)1
enter price of each item700
would you like to order another item(1=yes,0=no)1
enter price of each item800
would you like to order another item(1=yes,0=no)0

total bill is 2000

discounted price is 0.000000

final bill is 2000

-----
Process exited after 16.13 seconds with return value 0
Press any key to continue . . .

```

```

n.cpp
#include<stdio.h>
int main()
{
    int i,pin=1234,pass; //pass=password

    for(i=1;i<=3;i++){

        printf("enter pin");
        scanf("%d",&pass);

        if(pin==pass){

            printf("login successful\n");
            break;
        }else{
            printf("\nwrong pin. remaining attempts are %d",3-i);
        }
    }

    if(i>3)
    {
        printf("\naccount locked");
    }

    return 0;
}

```

```

C:\Users\HP\Documents\mn.c
enter pin4567

wrong pin. remaining attempts are 2enter pin8907

wrong pin. remaining attempts are 1enter pin1234
login successful

-----
Process exited after 7.814 seconds with return value 0
Press any key to continue . . . |

```

```

1  #include<stdio.h>
2  int main()
3  {
4      int marks[5];
5      printf("enter marks");
6      scanf("%d",&marks[0]);
7      printf("enter marks");
8      scanf("%d",&marks[1]);
9      printf("enter marks");
10     scanf("%d",&marks[2]);
11     printf("enter marks");
12     scanf("%d",&marks[3]);
13     printf("enter marks");
14     scanf("%d",&marks[4]);
15
16     int total=0,max,min;
17     float avg;
18     int i;
19     max=marks[0];
20     min=marks[0];
21
22     for(i=0;i<5;i++){
23         total=total+marks[i];
24         if(marks[i]>max){
25             max=marks[i];
26         }
27         if(marks[i]<min){
28             min=marks[i];
29         }
30     }
31     avg=total/5.0;
32
33     printf("\ntotal marks are %d",total);
34     printf("\naverage marks are %f",avg);
35     printf("\nhighest marks are %d",max);
36     printf("\nlowest marks are %d",min);
37 }

```

```

enter marks20
enter marks60
enter marks80
enter marks90
enter marks50

```

```

total marks are 300
average marks are 60.000000
highest marks are 90
lowest marks are 20

```

```

-----
Process exited after 10.2 seconds with return value 0
Press any key to continue . . . |

```

mn.cpp

```
1 #include<stdio.h>
2 int main()
3 {
4     int price[5];
5     printf("enter price");
6     scanf("%d",&price[0]);
7     printf("enter price");
8     scanf("%d",&price[1]);
9     printf("enter price");
10    scanf("%d",&price[2]);
11    printf("enter price");
12    scanf("%d",&price[3]);
13    printf("enter price");
14    scanf("%d",&price[4]);
15
16    int total=0,discout,final_amount;
17    int i;
18    for(i=0;i<5;i++){
19        total=total+price[i];
20    }
21
22
23    if(total>10000){
24        discout=total*0.1;
25    }
26    final_amount=total-discout;
27
28    printf("\ntotal price is %d\n",total);
29    printf("\ntotal discout is %d\n",discout);
30    printf("\nfinal amount is %d\n",final_amount);
31 }
```

C:\Users\HP\Documents\mn.c

```
enter price500
enter price800
enter price9000
enter price700
enter price400
```

```
total price is 11400
```

```
total discout is 1140
```

```
final amount is 10260
```

```
-----
Process exited after 18.09 seconds with return value 0
Press any key to continue . . . |
```

n.cpp

```
printf("enter the electricity units consumed");
scanf("%d",&bill[1]);
printf("enter the electricity units consumed");
scanf("%d",&bill[2]);
printf("enter the electricity units consumed");
scanf("%d",&bill[3]);
printf("enter the electricity units consumed");
scanf("%d",&bill[4]);

int i,total=0,highest,lowest;
float amount,totalAmount;
highest=bill[0];
lowest=bill[0];

for(i=0;i<5;i++){
    total=total+bill[i];

    if(bill[i]>highest){
        highest=bill[i];
    }
    if(bill[i]<lowest){
        lowest=bill[i];
    }
    amount=bill[i]*10;

    if(bill[i]>500){
        amount=amount+amount*0.05;
    }
    totalAmount=totalAmount+amount;
}

printf("\ntotal units consumed is %d",total);
printf("\nhighest units consumed is %d",highest);
printf("\nlowest units consumed is %d",lowest);
printf("\ntotal amount collected is %.2f",totalAmount);
}
```

C:\Users\HP\Documents\mn.e

```
enter the electricity units consumed600
enter the electricity units consumed80
enter the electricity units consumed6
enter the electricity units consumed59
enter the electricity units consumed30
```

```
total units consumed is 775
highest units consumed is 600
lowest units consumed is 6
total amount collected is 8050.00
-----
```

```
Process exited after 16.69 seconds with return value 0
Press any key to continue . . .
```