Decoupling Urgency and Emotion in Automated Telecom Complaint Triage

Liqiang Cheng (25078815)[1] **Olena Brylinska** (25190473)[1] **Yuansheng Tao** (25155204)[1]
Yuyi Song (25206842)[1] **Yuzhi Zhao** (25172008)[1]

[1]UCL School of Management, University College London
MSIN0221 Group Assignment — Group 16

March 28, 2026

Abstract

Automated complaint triage in telecommunications requires two simultaneous judgements: how operationally severe is the underlying issue, and how emotionally escalated is the customer? These dimensions are conceptually orthogonal yet are routinely conflated by existing prioritisation systems. This paper introduces a 5,000-complaint synthetic UK telecoms dataset with independently controlled urgency and emotion labels across a 3×3 grid, and evaluates four classification architectures: few-shot Claude Haiku 4.5, TF-IDF + Logistic Regression, frozen Sentence-BERT + Logistic Regression, and fine-tuned DeBERTa-v3-base with dual classification heads. DeBERTa achieves the strongest combined performance (macro F1 = 0.830), with a particularly clear advantage on emotion classification (0.857 vs. 0.764 for TF-IDF). An 18.6 percentage-point gain in urgency F1 from dataset v2 to v3 demonstrates that generation quality was the primary bottleneck. Contrastive error analysis using Informative Correct Pairs identifies recurring blind spots in both heads, validated through targeted adversarial stress testing.

Word count: [PLACEHOLDER]

Team Contributions

#	Name	Actual Contributions	Report Section
1	Liqiang Cheng	Introduction, Literature Review, Research Framework Design, Error Analysis (co-lead)	Section 1: Introduction & Literature Review; Section 5
2	Yuansheng Tao	Synthetic Dataset Design (v1–v3), DeBERTa Architecture & Training (Runs 1–8)	Section 2: Data; Section 3: Methodology
3	Yuzhi Zhao	EDA, TF-IDF / SBERT / Haiku Baselines, Model Comparison & Evaluation	Section 4: Results & Evaluation
4	Olena Brylinska	Contrastive Error Analysis (co-lead), Blindspot Taxonomy, Adversarial Testing, Limitations	Section 5: Error Analysis & Discussion
5	Yuyi Song	Conclusion, Business Application, Report Integration & Presentation	Section 6: Conclusions

1 Introduction

Customer-facing complaint handling in the telecommunications sector presents a triage challenge that is difficult to automate. When a support agent receives an inbound complaint, they must make two simultaneous judgements: how objectively serious is the underlying issue, and how emotionally escalated is the customer expressing that issue? These are not the same questions. A customer who writes *"I would like to **flag**, at your earliest convenience, that our office has had no **connectivity** for seventy-two hours and we are losing approximately three thousand pounds per day"* is describing a catastrophic situation in perfectly calm prose. A customer who writes *"THIS IS ABSOLUTELY DISGUSTING I CANNOT BELIEVE YOU CHANGED THE APP FONT"* is emotionally escalated about something trivial. Misrouting these two cases is precisely the failure mode that automated triage must avoid. Research also shows that even the best available language models often mix up closely related emotion categories when they have not been fine-tuned for the specific domain (Zhang et al., 2024).

The case for automating complaint triage with NLP is well established. Vairetti et al. (2024) demonstrate that transformer-based deep learning models can automatically label and prioritise large volumes of complaints with high accuracy, achieving 92.1% accuracy on over 44,000 complaints using a BERT-based architecture combined with multicriteria decision-making. More recently, Roumeliotis et al. (2025) evaluated fourteen LLMs on zero-shot consumer complaint classification, finding that while reasoning models offer improved contextual understanding, they incur significantly higher processing time and inference cost compared to fine-tuned specialist models. Long et al. (2024) propose a generic framework for LLM-based synthetic dataset generation, demonstrating that LLMs can produce diverse, task-relevant training examples at low cost. However, Tan et al. (2024) caution that LLM-generated annotations carry inherent quality risks, motivating careful quality control in any synthetically labelled pipeline.

A key gap in existing literature motivates the present work. Existing complaint prioritisation frameworks treat urgency as a composite label that conflates objective issue severity with the emotional tone of the customer. Athira and Gupta (2025) find that different model architectures perform best on different complaint analysis dimensions, with no single architecture achieving uniform high performance across

sentiment, emotion, and severity simultaneously — suggesting these dimensions require distinct modelling approaches rather than treatment as a unified composite label.

Against this background, this paper asks: *How effectively can different NLP models classify urgency and emotional intensity independently in synthetic UK telecom complaints, and what error patterns emerge when these dimensions are disentangled by design?*

This paper presents three contributions. First, we introduce a 5,000-complaint synthetic dataset of UK telecoms complaints with fine-grained orthogonal control over multiple dimensions. Second, we train and compare four classification architectures. Third, we conduct a per-instance causal error analysis augmented by Informative Correct Predictions (ICP), a concept adapted from Ashury-Tahan et al. (2026).

2 Data

2.1 Why Synthetic Data

No publicly available dataset provides dual ground-truth labels for both urgency and emotional intensity in customer complaints. Existing open complaint corpora are either unlabelled on these dimensions, domain-mismatched, or annotated for a single dimension only. Real-world telecoms complaints additionally carry privacy constraints that limit redistribution. Generating synthetic data allowed us to guarantee label correctness by design: rather than annotating text post-hoc, we instructed the generation model to write each complaint to a specified urgency and emotion level, making the intended label the ground truth by construction.

2.2 Dataset Design and Generation

The dataset consists of 5,000 complaints structured as a 3×3 grid, with urgency on one axis and emotion on the other. The urgency distribution reflects a realistic skew where critical operational contacts are assumed to be less frequent than routine ones. Emotion is distributed evenly within each urgency group. The dataset is split 70/15/15 into training (3,500), validation (750), and test (750) sets, stratified on the full urgency-by-emotion cell.



Figure 1: Joint urgency × emotion distribution (%) across the 5,000-complaint synthetic dataset.

Each complaint is assigned four characteristics prior to generation, ensuring linguistic diversity within and across cells (Table 1).

Dimension	Options	Purpose
Scenario	20 UK telecoms topics	Controls subject matter
Writing style	8 styles (e.g. formal, sarcastic, legalistic)	Controls surface-level form
Customer profile	8 personas (e.g. elderly, small business)	Controls voice and framing
Complaint history	4 depths (first contact to escalation)	Controls implied severity context

Table 1: Synthetic data creation rules: the four characteristics assigned to each complaint before generation.

No two complaints within the same grid cell share an identical combination of all four characteristics. A scenario-urgency affinity map further enforces realism by restricting which scenarios may appear at each urgency level (Appendix A).

Complaints were generated using GPT-5-mini in batches of five. Each batch prompt included urgency and emotion level definitions, a tone instruction specifying how emotion should manifest through word choice rather than explicit vocabulary, and the four assigned characteristics. Three distinct system prompt

templates were rotated across batches to prevent stylistic convergence.

2.3 Dataset Versioning and Quality Validation

Model performance on held-out data was used as a diagnostic signal for dataset quality, with three successive versions produced.

Version 1 applied explicit vocabulary instructions per emotion level and restricted writing styles per emotion level. This introduced data leakage: the model learned a vocabulary lookup table rather than genuine emotional understanding, producing unrealistically high emotion classification performance.

Version 2 removed both artefacts by permitting all writing styles at all emotion levels and replacing vocabulary instructions with structural tone guidance. Despite this, urgency classification plateaued across all hyperparameter configurations, and human inspection revealed further instances of label-complaint mismatch.

Version 3 addressed this by upgrading the generation model from GPT-4o-mini to GPT-5-mini and reducing batch size from 15 to 5 complaints per API call. Smaller batches under a stronger model produced more consistent label-to-text fidelity. The quantitative impact of these changes is reported in Section 4.2.

This iterative process reflects a broader principle: when the training signal is machine-produced, dataset quality engineering can be as consequential as model architecture selection (Iskander et al., 2024).

3 Methodology

3.1 Task Formulation

The task is formulated as dual multi-class classification. Given a customer complaint text, the model must independently predict an urgency level and an emotion level, each drawn from $\{\text{Low}, \text{Medium}, \text{High}\}$. Urgency captures the operational severity of the issue described; emotion captures the affective intensity of the language used.

3.2 Baselines

Three baseline models of increasing representational capacity were evaluated. All baselines were evaluated on the same stratified test split of 750 complaints.

Few-shot Claude Haiku 4.5 establishes whether a general-purpose LLM can perform the task from definitions and labelled examples alone. Nine labelled examples were provided in the system prompt (one per urgency-by-emotion cell), with complaints batched in groups of ten per API call at temperature 0.

TF-IDF + Logistic Regression grounds classification in surface-level lexical features. Texts were vectorised using TF-IDF with unigram and bigram features, a maximum vocabulary of 20,000 terms, and sublinear TF scaling. Two independent logistic regression classifiers (L2, $C{=}1.0$, LBFGS) were trained, one per target dimension.

Frozen Sentence-BERT + Logistic Regression replaces sparse lexical features with dense semantic representations. Texts were encoded using all-MiniLM-L6-v2, a sentence transformer producing 384-

dimensional embeddings (Reimers and Gurevych, 2019), with all encoder weights frozen. The same logistic regression configuration was applied on top of these embeddings.

3.3 Fine-Tuned DeBERTa-v3-base

DeBERTa-v3-base was selected for its disentangled attention mechanism (He et al., 2021), with the v3 variant further improving pre-training efficiency through an ELECTRA-style replaced token detection objective (He et al., 2023). This architecture enables the model to distinguish between what a word means and where it appears in the sequence, a property particularly relevant for complaint classification where positional cues carry diagnostic value.

The model uses a shared encoder with two independent linear classification heads, following the parallel multi-task architecture described by Chen et al. (2024). The `[CLS]` token representation (768 dimensions) is passed to both an urgency head and an emotion head, each projecting to three output classes. Both heads are trained jointly by summing their respective cross-entropy losses. The urgency head applies class weights of $[1.0,\ 1.5,\ 1.2]$ for Low, Medium, and High respectively: Medium receives the highest weight not because of class frequency (it is the most frequent class at 40%) but because it structurally overlaps with both adjacent classes. The emotion head uses unweighted cross-entropy, as emotion classes are evenly distributed.

Early stopping monitors the combined validation macro F1, defined as the mean of validation urgency and emotion macro F1, halting after three consecutive epochs with no improvement. Training hyperparameters are summarised in Table 2.

Parameter	**Value**
Base model	`microsoft/deberta-v3-base`
Max sequence length	192 tokens
Batch size	16
Optimiser	AdamW
Learning rate	2×10^{-5}
LR schedule	Linear warmup (10%) + linear decay
Gradient clipping	Max norm 1.0
Max epochs	10
Early stopping patience	3 (on combined macro F1)
Urgency class weights	$[1.0,\ 1.5,\ 1.2]$ (Low / Med / High)
Emotion class weights	None (uniform)
Mixed precision	FP16 on CUDA

Table 2: DeBERTa-v3-base training configuration.

3.4 Evaluation Metrics

All models are evaluated using macro-averaged F1 score, defined as the unweighted mean of per-class F1 scores across the three classes. Macro averaging weights each class equally regardless of frequency, penalising models that perform well on frequent classes but poorly on rare ones. Per-class F1 scores are additionally reported for each model and each dimension.

4 Results & Evaluation

4.1 Overall Model Comparison



Figure 2: Test-set macro F1 by model for urgency and emotion classification.

The fine-tuned DeBERTa-v3-base achieves the highest combined performance with a mean macro F1 of 0.830 (urgency 0.803, emotion 0.857), followed by TF-IDF + LR at 0.792, frozen Sentence-BERT + LR at 0.661, and few-shot Claude Haiku 4.5 at 0.516. TF-IDF outperforms DeBERTa on urgency by 1.6 percentage points (0.819 vs. 0.803), suggesting that urgency is partly solvable by lexical features alone. DeBERTa's advantage concentrates on emotion, where it gains 9.3 percentage points over TF-IDF (0.857 vs. 0.764), as emotion classification requires interpreting tone, register, and pragmatic intent that bag-of-words features cannot capture.

The frozen SBERT baseline underperforms TF-IDF on both dimensions by over 12 percentage points, reflecting a domain gap: all-MiniLM-L6-v2 optimises for paraphrase detection, compressing complaints into a semantic space that discards fine-grained lexical signals. Few-shot Haiku 4.5 scores lowest, consistent with Roumeliotis et al. (2025), who observe that general-purpose LLMs struggle with fine-grained ordinal distinctions without task-specific training.



Figure 3: Per-class F1 scores on the test set across models and dimensions.

Medium is the worst-performing class across every model and both dimensions, consistent with Lu et al. (2024), who demonstrate that classifiers systematically concentrate confusion at middle categories. DeBERTa's urgency Medium F1 (0.734) trails Low (0.835) and High (0.839) by approximately 10 percentage points.

4.2 Dataset Versioning with DeBERTa-v3



Figure 4: Test macro F1 score across eight training runs spanning three dataset versions, illustrating the impact of data quality on model performance.

Figure 4 traces DeBERTa-v3-base performance across eight training runs spanning three dataset versions. The single run on Dataset v1 produced an emotion macro F1 of 0.991, an implausibly high result confirming the data leakage described in Section 2.3. Dataset v2 corrected the leakage artefacts, and emotion macro F1 fell to a credible range of 0.835–0.866, but urgency macro F1 remained invariant across three runs (0.603–0.622) regardless of changes to learning rate, class weights, and sequence length. The narrow range points unambiguously to a data quality constraint rather than a modelling problem.

The transition to Dataset v3 produced an immediate improvement in urgency macro F1, rising from 0.615 on the final v2 run to 0.801 on the first v3 run, an increase of 18.6 percentage points achieved without any modification to the model architecture or training configuration. This confirms that the v2 urgency ceiling was caused by generation quality rather than model capacity, aligning with Iskander et al. (2024). Across four runs on Dataset v3, urgency macro F1 remained stable between 0.801–0.811, and emotion macro F1 between 0.830–0.857. Run 8 was selected as the final model on the basis of achieving the highest combined macro F1.

4.3 Training Dynamics – Run 8



Figure 5: DeBERTa training dynamics for Run 8. Validation loss diverges from training loss after epoch 3, yet validation F1 continues improving until epoch 6 where early stopping fires.

The model was selected at Epoch 6 by early stopping on validation combined F1. Validation loss diverges from training loss after epoch 3, rising from 0.957 to 1.745, yet validation F1 continues improving until epoch 6 (combined F1 of 0.830). Had we used loss-based early stopping, the model would have been selected at epoch 3 (combined F1 of 0.813), forfeiting 1.7 percentage points. The emotion head converges

by epoch 3, while the urgency head continues climbing until epoch 6, consistent with the fact that urgency requires longer training to synthesise situational details distributed across complaint texts.

4.4 Confusion Structure



Figure 6: Confusion matrices for DeBERTa urgency (left) and emotion (right) classification on the test set.

DeBERTa makes 151 urgency errors (20.1%) and 107 emotion errors (14.3%). For urgency, 97.4% of mistakes are single-step confusions between adjacent classes, suggesting the model largely preserves the ordinal structure of the labels. The dominant asymmetry is *downward* error: the most common urgency misclassification is Medium predicted as Low (64 cases, 42.4% of urgency errors). Low urgency has high recall (89.7%) but lower precision (78.1%), indicating the Low class absorbs cases from higher true classes. Medium shows the weakest recall (67.7%), while High remains comparatively stable (precision 82.1%, recall 85.6%). For emotion, the dominant error goes in the opposite direction: Medium is most often predicted as High (36 cases, 33.6% of emotion errors), suggesting a mild upward shift in that head.

5 Contrastive Error Analysis

To evaluate the DeBERTa model's dual-head performance beyond standard aggregate metrics, we implemented a Contrastive Error Analysis pipeline. Rather than looking at aggregate failure rates, this method systematically matches incorrect predictions with successful predictions that share the exact same metadata (ground truth label, scenario, and communication style). These matched Informative Correct Pairs (ICPs) allow us to isolate specific linguistic, structural, or contextual features, enabling identification of underlying algorithmic blind spots.

5.1 Dual-Head Accuracy Comparison

Consistent with the performance gap reported in Section 4.1, the urgency head produced substantially more classification errors than the emotion head. In practice, the severity of an issue is often defined by

company-internal documents and is harder to infer from language alone; emotion, even though nuanced, often has more apparent vocabulary triggers.



Figure 7: DeBERTa misclassification error distribution for urgency (blue) and emotion intensity (red), grouped by error type (true class → predicted class).

5.2 Urgency Head Analysis

Blind Spot	Description
Emotional & Vulnerability Over-indexing	The model misinterprets expressions of emotional distress or personal vulnerability as High urgency, while failing to adequately weigh explicit statements of patience or willingness to wait.
Contextual Misinterpretation of Deadlines	The model over-prioritises explicit deadlines or external escalation threats (e.g. Ombudsman, legal action) without sufficiently contextualising the actual impact or immediacy.
Failure to Synthesise Problem History	The model struggles to weigh the cumulative effect of repeated service failures, over-indexing on single recent events instead of persistent crises.

Table 3: Top 3 urgency head blind spots identified via contrastive error analysis.

5.3 Emotion Head Analysis

Blind Spot	Description
Misinterpreting Cumulative Impact	The model struggles to infer emotion from the cumulative weight of repeated issues or severe financial strain without explicit high-impact angry keywords.
Over-reliance on Overt Aggressive Language	The model over-indexes on explicit personal frustration or aggressive 'power phrases', misclassifying intensity when the tone is strictly formal but legally threatening.
Under-recognition of Internal Escalation	The model fails to identify Medium or High emotional severity in initial contacts due to critical system failures without explicit threats.

Table 4: Top 3 emotion head blind spots identified via contrastive error analysis.

5.4 Adversarial Stress Testing

To validate the blind spots identified through contrastive analysis, we constructed 10 targeted adversarial cases, each designed to isolate a specific failure mode. Notably, the four cases that produced incorrect predictions mapped precisely onto Blind Spots 1, 2, and 3 for each head. For example, the adversarial test 'Passive-Aggressive Legal Threat' (True Emotion: High, Predicted: Low) failed exactly as predicted by Emotion Blind Spot 2: it lacked explicit angry words but carried extreme threat. Similarly, 'Sarcastic Praise' failed because the model misinterpreted cumulative impact (Emotion Blind Spot 1) when masked by mathematically positive words. While 10 adversarial cases are insufficient for quantitative claims, the specificity of the failures — each incorrect prediction corresponding to a previously identified blind spot — suggests the contrastive analysis has diagnostic validity.

6 Limitations

The model is trained exclusively on machine-generated text, learning linguistic patterns characteristic of large language models rather than genuine human writing. Real-world complaints tend to be considerably more chaotic, incorporating severe spelling errors, SMS abbreviations, and stream-of-consciousness formatting that the synthetic corpus does not capture.

The dataset is constructed around a fixed set of scenarios, writing styles, and customer profiles, with strict logical rules governing label assignments. Real customers routinely produce contradictory complaints that violate such boundaries, and the full range of real-world telecommunications situations extends considerably beyond the controlled grid used here.

The model is evaluated exclusively on a held-out partition of the same synthetic dataset used for training. Without validation on genuine telecoms complaints, it remains uncertain whether the classification boundaries learned from synthetic text transfer to the broader linguistic variation present in live production environments.

7 Conclusion

This paper examined whether urgency and emotional intensity can be separated through deliberate dataset design and task-specific modelling. The results suggest they can be decoupled to a practically useful extent within a controlled synthetic setting.

Among the four evaluated models, the fine-tuned DeBERTa-v3-base achieved the strongest balanced performance (combined macro F1 = 0.830). TF-IDF marginally outperformed DeBERTa on urgency alone, indicating that part of the urgency signal is recoverable from lexical cues, whereas DeBERTa's clear advantage on emotion suggests emotional intensity depends more heavily on contextual and pragmatic interpretation.

The dataset versioning process was central to the final outcome. The 18.6 percentage-point improvement in urgency macro F1 between Dataset v2 and v3 strongly suggests that generation quality was a major constraint, reinforcing the principle that in synthetic pipelines, improving the training signal can matter at least as much as model selection (Iskander et al., 2024).

The contrastive error analysis identified recurring blind spots in both heads, and adversarial testing was consistent with the diagnosed blind spots, providing preliminary support for the ICP-based methodology.

The dual-head framework provides the technical foundation for an automated complaint prioritisation system in which urgency determines queue position while emotional intensity provides agents with advance context about the customer's affective state. In the UK telecoms context, this carries direct regulatory relevance, as Ofcom requires prioritised handling of vulnerable customer complaints.

Validation on real telecom data is the most important next step, alongside a data augmentation strategy that injects adversarial edge cases targeting the identified blind spots.

References

Shira Ashury-Tahan, Yao Mai, Elron Bandel, Michal Shmueli-Scheuer, and Leshem Choshen. 2026. ErrorMap and ErrorAtlas: Charting the failure landscape of large language models. *Preprint*, arXiv:2601.15812.

Adith M. Athira and Deepak Gupta. 2025. Effective complaint detection in financial services through complaint, severity, emotion and sentiment analysis. *Procedia Computer Science*, 258:2220–2231.

Shaowei Chen, Yu Zhang, and Qiang Yang. 2024. Multi-task learning in natural language processing: An overview. *ACM Computing Surveys*, 56(12):1–32.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. In *International Conference on Learning Representations (ICLR)*.

Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. 2021. DeBERTa: Decoding-enhanced BERT with disentangled attention. *Preprint*, arXiv:2006.03654.

Shir Iskander, Sapir Tolmach, Ori Shapira, Nadav Cohen, and Zohar Karnin. 2024. Quality matters: Evaluating synthetic data for tool-using LLMs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4958–4976, Miami, Florida. Association for Computational Linguistics.

Leilei Long, Rui Wang, Rui Xiao, Jingwei Zhao, Xin Ding, Guanting Chen, and Houfeng Wang. 2024. On LLMs-driven synthetic data generation, curation, and evaluation: A survey. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 11065–11082.

Zhan Lu, Jintao Tian, Wei Wei, Xiaoye Qu, Yu Cheng, Wenfang Xie, and Dangyang Chen. 2024. Mitigating boundary ambiguity and inherent bias for text classification in the era of large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 7841–7864, Bangkok, Thailand. Association for Computational Linguistics.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*.

Konstantinos I. Roumeliotis, Nikolaos D. Tselikas, and Dimitrios K. Nasiopoulos. 2025. Think before you classify: The rise of reasoning large language models for consumer complaint detection and classification. *Electronics*, 14(6):1070.

Zhen Tan, Dawei Li, Song Wang, Alimohammad Beigi, Bohan Jiang, Amrita Bhattacharjee, Mansooreh Karami, Jundong Li, Lu Cheng, and Huan Liu. 2024. Large language models for data annotation: A survey. *Preprint*, arXiv:2402.13446.

Carla Vairetti, Ignacio Aránguiz, Sebastián Maldonado, Juan Pablo Karmy, and Alexis Leal. 2024. Analytics-driven complaint prioritisation via deep learning and multicriteria decision-making. *European Journal of Operational Research*, 312(3):1108–1118.

Wenxuan Zhang, Yue Deng, Bing Liu, Sinno Jialin Pan, and Lidong Bing. 2024. Sentiment analysis in the era of large language models: A reality check. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 2937–2958, Mexico City. Association for Computational Linguistics.

A Code and Data Availability

All code and data for this project are publicly available at:

`https://github.com/tao-yuansheng/nlp_urgency_ranking`

The repository includes: the synthetic dataset generation scripts and all three dataset versions (v1–v3); baseline model implementations (TF-IDF, Sentence-BERT, Claude Haiku); the DeBERTa-v3-base multi-task fine-tuning pipeline with all eight training run configurations; the contrastive error analysis and adversarial stress testing scripts; and the figure generation code used in this report.

B Generative AI Tool Acknowledgment

This project used generative AI tools in an assistive capacity, consistent with the MSIN0221 "Assistive" AI category. Specifically:

- **OpenAI GPT-5-mini** was used to generate the synthetic complaint dataset (Sections 2.2–2.3). All generated complaints were reviewed for label-to-text fidelity, and dataset quality was validated iteratively through model performance diagnostics.
- **Anthropic Claude Haiku 4.5** was used as a few-shot classification baseline (Section 3.2). Its outputs were evaluated solely as model predictions on the held-out test set.
- **Claude Code (Anthropic)** was used in an assistive role to support code development, debugging, and report formatting. All analytical decisions, interpretations, and written content represent the authors' own work.

C Adversarial Stress Test Outcomes

Results of the 10-item adversarial evaluation used to probe decoupled urgency–emotion reasoning under sarcasm, legal threats, and emotional masking.

ID	Case	Expected U/E	Predicted U/E	Result	Why Difficult
01	Sarcastic Praise	Med / High	High / Low	FAIL	Glowing words mask intense frustration
02	Polite Catastrophe	High / Low	High / Low	PASS	Full outage described with total calm
03	Aggressive Triviality	Low / High	Low / High	PASS	Maximum fury over a cosmetic change
04	Passive-Aggressive Legal Threat	High / High	Low / Low	FAIL	Cold legal language, no exclamation marks
05	Rambling Confusion	Low / Low	Low / Low	PASS	Long message; mild self-billing confusion
06	Urgent but Cheerful	High / Low	High / Low	PASS	Complete call failure reported with enthusiasm
07	Sincere Heartbreak	Low / High	Low / High	PASS	Deep sadness over a minor plan change
08	Pure Machine Logic	High / Low	High / Low	PASS	Network jargon with zero emotional language
09	Ambiguous Broken	Med / Med	Low / Low	FAIL	Mild recurring issue, hint of exasperation
10	Overreaction to a Fix	Low / High	Med / Med	FAIL	Issue resolved; sarcasm signals residual anger

Table 5: Adversarial stress test outcomes. U = Urgency, E = Emotion.

D Training Run Hyperparameters

Summary of all DeBERTa training runs and the hyperparameter or dataset changes introduced across iterations.

Run	Dataset	Max Len	LR Setup	Max Epochs	Key Change
1	v1	128	2×10^{-5}	5	Baseline. Unified LR, FP16, no class weights
2	v2	128	2×10^{-5}	5	Dataset updated to v2; all settings identical
3	v2	192	2×10^{-5}	10	Max length 128→192; epochs extended to 10
4	v2	192	1×10^{-5}	10	Unified LR halved
5	v3	192	2×10^{-5}	10	Dataset updated to v3; LR restored
6	v3	192	1×10^{-5} / 5×10^{-5}	10	Split LR: lower for encoder, higher for heads
7	v3	192	1×10^{-5} / 2×10^{-5}	15	Head LR reduced; weight decay 0.05 added
8	v3	192	2×10^{-5}	10	Early stopping on combined macro F1 (**selected**)

Table 6: DeBERTa training run hyperparameters across all dataset versions.

E Scenario-Urgency Affinity Matrix



Figure 8: Scenario-urgency affinity matrix showing which UK telecoms complaint scenarios were permitted at Low, Medium, and High urgency during synthetic dataset construction.

F Metadata Coverage



Figure 9: Coverage of scenario, style, profile, and history attributes across the 5,000-complaint synthetic dataset, demonstrating broad metadata distribution rather than concentration in any single category.

G Writing Style – Emotion Independence



Figure 10: Writing style distribution across emotion intensity levels, demonstrating that all styles appear at all emotion levels (no style-to-emotion leakage).

H Text Length and Token Truncation



Figure 11: Text length distribution by urgency and emotion class.



Figure 12: Token truncation analysis at the 192-token sequence length limit.