



#### ADSORPTION MATERIAL

## Activated Carbon

Granular activated carbon for buyers reviewing iodine value, strength, ash, apparent density, particle size and treatment requirements.

**COMMON USES**    Water treatment / Gas treatment / Industrial adsorption

### Catalog indicators

|                             |                       |
|-----------------------------|-----------------------|
| Iodine value                | 525 mg/g              |
| Strength                    | 90.2%                 |
| Apparent density            | 445 g/L               |
| Ash                         | 11.8%                 |
| BET surface area            | 597 m <sup>2</sup> /g |
| CCl <sub>4</sub> adsorption | 21.1%                 |
| Size                        | 0–15 mm range         |

#### TO START AN INQUIRY

Tell us the feed stream, target contaminant, test method, size and quantity.

# Start with a short message.

You do not need to complete a long RFQ before contacting us. Choose a product, leave your business email and tell Eric what you need. Add the details below only if they are already available.

**01** Product or application

**02** Required grade, chemistry or size

**03** Estimated quantity

**04** Destination port or country

**05** Packing, inspection or document needs

## CONTACT ERIC

### Shenmu Zhonghao New Energy Technology Co., Ltd.

Email: [eric@smzhenergy.com](mailto:eric@smzhenergy.com)

WhatsApp: +852 4666 2447

Website: <https://smzhenergy.com/>

Catalog figures are reference values. Final product and commercial terms are confirmed for the order.