

MapReduce Algorithm Design


Adapted from Jimmy Lin's slides

MapReduce: Recap

- Programmers must specify:
 - map** $(k, v) \rightarrow \langle k', v' \rangle^*$
 - reduce** $(k', v') \rightarrow \langle k', v' \rangle^*$
 - All values with the same key are reduced together
- Optionally, also:
 - partition** $(k', \text{number of partitions}) \rightarrow \text{partition for } k'$
 - Often a simple hash of the key, e.g., $\text{hash}(k') \bmod n$
 - Divides up key space for parallel reduce operations
 - combine** $(k', v') \rightarrow \langle k', v' \rangle^*$
 - Mini-reducers that run in memory after the map phase
 - Used as an optimization to reduce network traffic
- The execution framework handles everything else...

“Everything Else”


- The execution framework handles everything else...
 - Scheduling: assigns workers to map and reduce tasks
 - “Data distribution”: moves processes to data
 - Synchronization: gathers, sorts, and shuffles intermediate data
 - Errors and faults: detects worker failures and restarts
- Limited control over data and execution flow
 - All algorithms must be expressed in m, r, c, p
- You don’t know:
 - Where mappers and reducers run
 - When a mapper or reducer begins or finishes
 - Which input a particular mapper is processing
 - Which intermediate key a particular reducer is processing



Tools for Synchronization

- Cleverly-constructed data structures
 - Bring partial results together
- Sort order of intermediate keys
 - Control order in which reducers process keys
- Partitioner
 - Control which reducer processes which keys
- Preserving state in mappers and reducers
 - Capture dependencies across multiple keys and values

Preserving State




Scalable Hadoop Algorithms: Themes

- Avoid object creation
 - Inherently costly operation
 - Garbage collection
- Avoid buffering
 - Limited heap size
 - Works for small datasets, but won't scale!

Importance of Local Aggregation

- Ideal scaling characteristics:
 - Twice the data, twice the running time
 - Twice the resources, half the running time
- Why can't we achieve this?
 - Synchronization requires communication
 - Communication kills performance
- Thus... avoid communication!
 - Reduce intermediate data via local aggregation
 - Combiners can help

Shuffle and Sort



Word Count: Baseline

```
1: class MAPPER
2:   method MAP(docid  $a$ , doc  $d$ )
3:     for all term  $t \in \text{doc } d$  do
4:       EMIT(term  $t$ , count 1)

1: class REDUCER
2:   method REDUCE(term  $t$ , counts  $[c_1, c_2, \dots]$ )
3:      $sum \leftarrow 0$ 
4:     for all count  $c \in \text{counts } [c_1, c_2, \dots]$  do
5:        $sum \leftarrow sum + c$ 
6:     EMIT(term  $t$ , count  $s$ )
```

What's the impact of combiners?

Word Count: Version 1

```
1: class MAPPER
2:   method MAP(docid  $a$ , doc  $d$ )
3:      $H \leftarrow$  new ASSOCIATIVEARRAY
4:     for all term  $t \in$  doc  $d$  do
5:        $H\{t\} \leftarrow H\{t\} + 1$ 
6:     for all term  $t \in H$  do
7:       EMIT(term  $t$ , count  $H\{t\}$ )
```

▷ Tally counts for entire document

Are combiners still needed?

Word Count: Version 2

```
1: class MAPPER
2:   method INITIALIZE
3:      $H \leftarrow \text{new ASSOCIATIVEARRAY}$ 
4:   method MAP(docid  $a$ , doc  $d$ )
5:     for all term  $t \in \text{doc } d$  do
6:        $H\{t\} \leftarrow H\{t\} + 1$ 
7:   method CLOSE
8:     for all term  $t \in H$  do
9:        $\text{EMIT}(\text{term } t, \text{count } H\{t\})$ 
```

Key: preserve state across
input key-value pairs!

▷ Tally counts *across* documents

Are combiners still needed?

Design Pattern for Local Aggregation

- “In-mapper combining”
 - Fold the functionality of the combiner into the mapper by preserving state across multiple map calls
- Advantages
 - Speed
 - Why is this faster than actual combiners?
- Disadvantages
 - Explicit memory management required
 - Potential for order-dependent bugs

Combiner Design

- Combiners and reducers share same method signature
 - Sometimes, reducers can serve as combiners
 - Often, not...
- Remember: combiner are optional optimizations
 - Should not affect algorithm correctness
 - May be run 0, 1, or multiple times
- Example: find average of all integers associated with the same key

Computing the Mean: Version 1

```
1: class MAPPER
2:   method MAP(string  $t$ , integer  $r$ )
3:     EMIT(string  $t$ , integer  $r$ )

1: class REDUCER
2:   method REDUCE(string  $t$ , integers  $[r_1, r_2, \dots]$ )
3:      $sum \leftarrow 0$ 
4:      $cnt \leftarrow 0$ 
5:     for all integer  $r \in$  integers  $[r_1, r_2, \dots]$  do
6:        $sum \leftarrow sum + r$ 
7:        $cnt \leftarrow cnt + 1$ 
8:        $r_{avg} \leftarrow sum / cnt$ 
9:       EMIT(string  $t$ , integer  $r_{avg}$ )
```

Why can't we use reducer as combiner?

Computing the Mean: Version 2

```
1: class MAPPER
2:   method MAP(string  $t$ , integer  $r$ )
3:     EMIT(string  $t$ , integer  $r$ )

1: class COMBINER
2:   method COMBINE(string  $t$ , integers  $[r_1, r_2, \dots]$ )
3:      $sum \leftarrow 0$ 
4:      $cnt \leftarrow 0$ 
5:     for all integer  $r \in$  integers  $[r_1, r_2, \dots]$  do
6:        $sum \leftarrow sum + r$ 
7:        $cnt \leftarrow cnt + 1$ 
8:     EMIT(string  $t$ , pair ( $sum, cnt$ ))           ▷ Separate sum and count

1: class REDUCER
2:   method REDUCE(string  $t$ , pairs  $[(s_1, c_1), (s_2, c_2) \dots]$ )
3:      $sum \leftarrow 0$ 
4:      $cnt \leftarrow 0$ 
5:     for all pair  $(s, c) \in$  pairs  $[(s_1, c_1), (s_2, c_2) \dots]$  do
6:        $sum \leftarrow sum + s$ 
7:        $cnt \leftarrow cnt + c$ 
8:      $r_{avg} \leftarrow sum / cnt$ 
9:     EMIT(string  $t$ , integer  $r_{avg}$ )
```

Why doesn't this work?

Computing the Mean: Version 3

```
1: class MAPPER
2:   method MAP(string  $t$ , integer  $r$ )
3:     EMIT(string  $t$ , pair ( $r$ , 1))

1: class COMBINER
2:   method COMBINE(string  $t$ , pairs  $[(s_1, c_1), (s_2, c_2) \dots]$ )
3:      $sum \leftarrow 0$ 
4:      $cnt \leftarrow 0$ 
5:     for all pair  $(s, c) \in$  pairs  $[(s_1, c_1), (s_2, c_2) \dots]$  do
6:        $sum \leftarrow sum + s$ 
7:        $cnt \leftarrow cnt + c$ 
8:     EMIT(string  $t$ , pair ( $sum$ ,  $cnt$ ))

1: class REDUCER
2:   method REDUCE(string  $t$ , pairs  $[(s_1, c_1), (s_2, c_2) \dots]$ )
3:      $sum \leftarrow 0$ 
4:      $cnt \leftarrow 0$ 
5:     for all pair  $(s, c) \in$  pairs  $[(s_1, c_1), (s_2, c_2) \dots]$  do
6:        $sum \leftarrow sum + s$ 
7:        $cnt \leftarrow cnt + c$ 
8:      $r_{avg} \leftarrow sum / cnt$ 
9:     EMIT(string  $t$ , pair ( $r_{avg}$ ,  $cnt$ ))
```

Fixed?

Computing the Mean: Version 4

```
1: class MAPPER
2:   method INITIALIZE
3:      $S \leftarrow \text{new ASSOCIATIVEARRAY}$ 
4:      $C \leftarrow \text{new ASSOCIATIVEARRAY}$ 
5:   method MAP(string  $t$ , integer  $r$ )
6:      $S\{t\} \leftarrow S\{t\} + r$ 
7:      $C\{t\} \leftarrow C\{t\} + 1$ 
8:   method CLOSE
9:     for all term  $t \in S$  do
10:       EMIT(term  $t$ , pair ( $S\{t\}, C\{t\}$ ))
```

Are combiners still needed?

Algorithm Design: Running Example

- Term co-occurrence matrix for a text collection
 - $M = N \times N$ matrix (N = vocabulary size)
 - M_{ij} : number of times i and j co-occur in some context
(for concreteness, let's say context = sentence)
- Why?
 - Distributional profiles as a way of measuring semantic distance
 - Semantic distance useful for many language processing tasks

MapReduce: Large Counting Problems

- Term co-occurrence matrix for a text collection = specific instance of a large counting problem
 - A large event space (number of terms)
 - A large number of observations (the collection itself)
 - Goal: keep track of interesting statistics about the events
- Basic approach
 - Mappers generate partial counts
 - Reducers aggregate partial counts

How do we aggregate partial counts efficiently?

First Try: “Pairs”

- Each mapper takes a sentence:
 - Generate all co-occurring term pairs
 - For all pairs, emit (a, b) → count
- Reducers sum up counts associated with these pairs
- Use combiners!

Pairs: Pseudo-Code

```
1: class MAPPER
2:   method MAP(docid  $a$ , doc  $d$ )
3:     for all term  $w \in \text{doc } d$  do
4:       for all term  $u \in \text{NEIGHBORS}(w)$  do
5:         EMIT(pair ( $w, u$ ), count 1)      ▷ Emit count for each co-occurrence

1: class REDUCER
2:   method REDUCE(pair  $p$ , counts  $[c_1, c_2, \dots]$ )
3:      $s \leftarrow 0$ 
4:     for all count  $c \in \text{counts } [c_1, c_2, \dots]$  do
5:        $s \leftarrow s + c$                   ▷ Sum co-occurrence counts
6:     EMIT(pair  $p$ , count  $s$ )
```

“Pairs” Analysis

- Advantages
 - Easy to implement, easy to understand
- Disadvantages
 - Lots of pairs to sort and shuffle around (upper bound?)
 - Not many opportunities for combiners to work

Another Try: “Stripes”

- Idea: group together pairs into an associative array

(a, b) \rightarrow 1

(a, c) \rightarrow 2

(a, d) \rightarrow 5

(a, e) \rightarrow 3

(a, f) \rightarrow 2

$a \rightarrow \{ b: 1, c: 2, d: 5, e: 3, f: 2 \}$

- Each mapper takes a sentence:
 - Generate all co-occurring term pairs
 - For each term, emit $a \rightarrow \{ b: \text{count}_b, c: \text{count}_c, d: \text{count}_d \dots \}$
- Reducers perform element-wise sum of associative arrays

$$\begin{array}{rcl} & a \rightarrow \{ b: 1, & d: 5, e: 3 \} \\ + & a \rightarrow \{ b: 1, c: 2, d: 2, & f: 2 \} \\ \hline & a \rightarrow \{ b: 2, c: 2, d: 7, e: 3, f: 2 \} \end{array}$$

**Key: cleverly-constructed data structure
brings together partial results**

Stripes: Pseudo-Code


```
1: class MAPPER
2:   method MAP(docid  $a$ , doc  $d$ )
3:     for all term  $w \in \text{doc } d$  do
4:        $H \leftarrow \text{new ASSOCIATIVEARRAY}$ 
5:       for all term  $u \in \text{NEIGHBORS}(w)$  do
6:          $H\{u\} \leftarrow H\{u\} + 1$  ▷ Tally words co-occurring with  $w$ 
7:        $\text{EMIT}(\text{Term } w, \text{Stripe } H)$ 

1: class REDUCER
2:   method REDUCE(term  $w$ , stripes  $[H_1, H_2, H_3, \dots]$ )
3:      $H_f \leftarrow \text{new ASSOCIATIVEARRAY}$ 
4:     for all stripe  $H \in \text{stripes } [H_1, H_2, H_3, \dots]$  do
5:        $\text{SUM}(H_f, H)$  ▷ Element-wise sum
6:      $\text{EMIT}(\text{term } w, \text{stripe } H_f)$ 
```

“Stripes” Analysis

- Advantages
 - Far less sorting and shuffling of key-value pairs
 - Can make better use of combiners
- Disadvantages
 - More difficult to implement
 - Underlying object more heavyweight
 - Fundamental limitation in terms of size of event space


Comparison of "pairs" vs. "stripes" for computing word co-occurrence matrices



Cluster size: 38 cores

Data Source: Associated Press Worldstream (APW) of the English Gigaword Corpus (v3), which contains 2.27 million documents (1.8 GB compressed, 5.7 GB uncompressed)

Effect of cluster size on "stripes" algorithm



Relative Frequencies

- How do we estimate relative frequencies from counts?

$$f(B | A) = \frac{\text{count}(A, B)}{\text{count}(A)} = \frac{\text{count}(A, B)}{\sum_{B'} \text{count}(A, B')}$$

- Why do we want to do this?
- How do we do this with MapReduce?

$f(B|A)$: “Stripes”

- Easy!
 - One pass to compute $(a, *)$
 - Another pass to directly compute $f(B|A)$

$f(B|A)$: “Pairs”

$(a, *) \rightarrow 32$

Reducer holds this value in memory

$(a, b_1) \rightarrow 3$

$(a, b_2) \rightarrow 12$

$(a, b_3) \rightarrow 7$

$(a, b_4) \rightarrow 1$

...



$(a, b_1) \rightarrow 3 / 32$

$(a, b_2) \rightarrow 12 / 32$

$(a, b_3) \rightarrow 7 / 32$

$(a, b_4) \rightarrow 1 / 32$

...

○ For this to work:

- Must emit extra $(a, *)$ for every b_n in mapper
- Must make sure all a 's get sent to same reducer (use partitioner)
- Must make sure $(a, *)$ comes first (define sort order)
- Must hold state in reducer across different key-value pairs

“Order Inversion”

- Common design pattern
 - Computing relative frequencies requires marginal counts
 - But marginal cannot be computed until you see all counts
 - Buffering is a bad idea!
 - Trick: getting the marginal counts to arrive at the reducer before the joint counts
- Optimizations
 - Apply in-memory combining pattern to accumulate marginal counts
 - Should we apply combiners?

Synchronization: Pairs vs. Stripes

- Approach 1: turn synchronization into an ordering problem
 - Sort keys into correct order of computation
 - Partition key space so that each reducer gets the appropriate set of partial results
 - Hold state in reducer across multiple key-value pairs to perform computation
 - Illustrated by the “pairs” approach
- Approach 2: construct data structures that bring partial results together
 - Each reducer receives all the data it needs to complete the computation
 - Illustrated by the “stripes” approach

Secondary Sorting

- MapReduce sorts input to reducers by key
 - Values may be arbitrarily ordered
- What if want to sort value also?
 - E.g., $k \rightarrow (v_1, r), (v_3, r), (v_4, r), (v_8, r) \dots$

Secondary Sorting: Solutions

- Solution 1:
 - Buffer values in memory, then sort
 - Why is this a bad idea?
- Solution 2:
 - “Value-to-key conversion” design pattern:
form composite intermediate key, (k, v_1)
 - Let execution framework do the sorting
 - Preserve state across multiple key-value
pairs to handle processing
 - Anything else we need to do?

Recap: Tools for Synchronization

- Cleverly-constructed data structures
 - Bring data together
- Sort order of intermediate keys
 - Control order in which reducers process keys
- Partitioner
 - Control which reducer processes which keys
- Preserving state in mappers and reducers
 - Capture dependencies across multiple keys and values

Issues and Tradeoffs

- Number of key-value pairs
 - Object creation overhead
 - Time for sorting and shuffling pairs across the network
- Size of each key-value pair
 - De/serialization overhead
- Local aggregation
 - Opportunities to perform local aggregation varies
 - Combiners make a big difference
 - Combiners vs. in-mapper combining
 - RAM vs. disk vs. network