



Compilers

Scope

- Matching identifier declarations with uses
 - Important static analysis step in most languages
 - Including COOL!

- Example 1

let y: String ← "abc" in y + 3

- Example 2


? let y: Int in x + 3

- The *scope* of an identifier is the portion of a program in which that identifier is accessible
- The same identifier may refer to different things in different parts of the program
 - Different scopes for same name don't overlap
- An identifier may have restricted scope

- Most languages have static scope
 - Scope depends only on the program text, not run-time behavior
 - Cool has static scope
- A few languages are dynamically scoped
 - Lisp, SNOBOL
 - Lisp has changed to mostly static scoping
 - Scope depends on execution of the program

Scope

```
let x: Int <- 0 in  
{  
  x;  
  let x: Int <- 1 in  
    x;  
  x;  
}
```

- A dynamically-scoped variable refers to the closest enclosing binding in the execution of the program
- Example


```
g(y) = let a ← 4 in f(3);  
f(x) = a;
```
- More about dynamic scope later . . .

- Cool identifier bindings are introduced by
 - Class declarations (introduce class names)
 - Method definitions (introduce method names)
 - Let expressions (introduce object id's)
 - Formal parameters (introduce object id's)
 - Attribute definitions (introduce object id's)
 - Case expressions (introduce object id's)

- Not all identifiers follow the most-closely nested rule
- For example, class definitions in Cool
 - Cannot be nested
 - Are globally visible throughout the program
- A class name can be used before it is defined

```
Class Foo {  
    ... let y: Bar in ...  
};
```

```
Class Bar {  
    ...  
};
```

Attribute names are global within the class in which they are defined

```
Class Foo {  
  f(): Int {a};  
  a: Int ← 0;  
}
```

- Method names have complex rules
- A method need not be defined in the class in which it is used, but in some parent class
- Methods may also be redefined (overridden)

Choose whether or not each variable use binds to the name on the given line

- ☐ Line 6 binds to line 2
- ☐ Line 9 binds to line 7
- ☐ Line 11 binds to line 2
- ☐ Line 11 binds to line 14

Scope

```
1  Class Foo {  
2      f(x: Int): Int {  
3          {  
4              let x: Int <- 4 in {  
6                  x;  
7                  let x: Int <- 7 in  
8                      x;  
9                      x;  
10                 };  
11                 x;  
12             };  
13         };  
14         x: Int <- 14;  
15     }
```