



Compilers

Code Generation II


A language with integers and integer operations

$$P \rightarrow D; P \mid D$$
$$D \rightarrow \text{def } \underline{\text{id}(\text{ARGS}) = E};$$
$$\text{ARGS} \rightarrow \text{id}, \text{ARGS} \mid \text{id}$$
$$\left[\begin{array}{l} E \rightarrow \text{int} \mid \underline{\text{id}} \mid \text{if } E_1 = E_2 \text{ then } E_3 \text{ else } E_4 \\ \quad \mid E_1 + E_2 \mid E_1 - E_2 \mid \underline{\text{id}(E_1, \dots, E_n)} \end{array} \right]$$

- Code for function calls and function definitions depends on the layout of the AR
- A very simple AR suffices for this language:
 - The result is always in the accumulator
 - No need to store the result in the AR
 - The activation record holds actual parameters
 - For $f(x_1, \dots, x_n)$ push x_n, \dots, x_1 on the stack
 - These are the only variables in this language

- The stack discipline guarantees that on function exit \$sp is the same as it was on function entry
 - No need for a control link
- We need the return address
- A pointer to the current activation is useful
 - This pointer lives in register \$fp (frame pointer)

- Summary: For this language, an AR with the caller's frame pointer, the actual parameters, and the return address suffices
- Picture: Consider a call to f(x,y), the AR is:



- The calling sequence is the instructions (of both caller and callee) to set up a function invocation

- New instruction: jal label

jal L
→ add —

- Jump to label, save address of next instruction in \$ra
- On other architectures the return address is stored on the stack by the “call” instruction

caller side

```
cgen(f(e1, ..., en)) =  
  sw $fp 0($sp)  
  addiu $sp $sp -4  
  cgen(en)  
  sw $a0 0($sp)  
  addiu $sp $sp -4  
  ...  
  cgen(e1)  
  sw $a0 0($sp)  
  addiu $sp $sp -4  
  jal f_entry
```

- The caller saves its value of the frame pointer
- Then it saves the actual parameters in reverse order
- Finally the caller saves the return address in register $\$ra$
- The AR so far is $4*n+4$ bytes long

Code Generation II

- New instruction: jr reg
 - Jump to address in register reg

$\{ \text{entry: } \text{cgen}(\text{def } f(x_1, \dots, x_n) = e) = \text{move } \$fp \ \$sp$

```
move $fp $sp
```

```
sw $ra 0($sp)
```

```
addiu $sp $sp -4
```

cgen(e)

lw \$ra 4(\$sp)

```
addiu $sp $sp z
```


$$lw \text{ } \$fp \ 0(\$sp)$$

jr \$ra


- Note: The frame pointer points to the top, not bottom of the frame
- The callee pops the return address, the actual arguments and the saved value of the frame pointer
- $z = 4 * n + 8$ [return addr.
ctd fp]

Code Generation II


Before call




On entry



Before exit



After call




- Variable references are the last construct
- The “variables” of a function are just its parameters
 - They are all in the AR
 - Pushed by the caller
- Problem: Because the stack grows when intermediate results are saved, the variables are not at a fixed offset from $\$sp$

- Solution: use a frame pointer
 - Always points to the return address on the stack
 - Since it does not move it can be used to find the variables
- Let $\underline{x_i}$ be the i^{th} ($i = 1, \dots, n$) formal parameter of the function for which code is being generated

$\text{cgen}(\underline{x_i}) = \text{lw } \underline{\$a0}, \underline{z}(\underline{\$fp})$

$(z = \underline{4*i})$

- Example: For a function `def f(x,y) = e` the activation and frame pointer are set up as follows:



- X is at fp + 4
- Y is at fp + 8

Code Generation II

For the function definitions at right, which of the following appear in the activation record on a call to `f()`?

☐ `x`

☐ `t`

☐ `g`

☐ `z`

```
def f(x,y,z) =  
  if x  
  then g(y)  
  else g(z)
```

```
def g(t) =  
  t + 1
```

- The activation record must be designed together
with the code generator
- Code generation can be done by recursive traversal of the AST
- We recommend you use a stack machine for your Cool compiler (it's simple)

- Production compilers do different things
 - Emphasis is on keeping values in registers
 - Especially the current stack frame
 - Intermediate results are laid out in the AR, not pushed and popped from the stack