

Comment	Description	Designator	Footprint	LibRef	Quantity
100nF, 50V	CAP CER 0.1UF 50V X7R 0402	C1	CAPC1005X55N	CL05B104KB5NNNC	1
22u	Capacitor SMD 0805 16V	C3, C4	CAP_0805	CAP_0805	2
2u2	Capacitor SMD 0603	C5, C12	CAP_0603	CAP_0603	2
10p	Capacitor SMD 0402 16V	C7, C8	CAP_0402	CAP_0402	2
2n2	Capacitor SMD 0402 16V	C11	CAP_0402	CAP_0402	1
100n	Capacitor SMD 0402, Capacitor SMD 0402 16V	C, C6, C9, C10, C13, C14, C15, C16, C17	CAP_0402	CAP_0402	9
GREEN	LED 0402 GREEN SMD	D1	LED_0402_GREEN	LED_0402_GREEN	1
RED	LED 0402 RED SMD	D2	LED_0402_RED	LED_0402_RED	1
AQ3045-01ETG	Bi 30Kv 5V 0.35Pf Automotive Tvs Sod882 T&r Rohs Compliant: Yes	D3, D4, D5	SOD882	AQ3045-01ETG	3
217179-0001	USB Connector, USB Type C, USB 2.0, Receptacle, 16 Ways, Surface Mount, Through Hole Mount	J1	FP-2171790001-MFG	217179-0001	1
SM06B-GHS-TB	Header Connector 6 Position 1.25MM Pitch SMD Horizontal JST GH	J3	SM06B-GHS-TB	SM06B-GHS-TB	1
1k	Resistor SMD 0402	R1, R4	RES_0402	RES_0402	2
2k2	Resistor SMD 0402	R2, R3	RES_0402	RES_0402	2
10k	Resistor SMD 0402	R5, R7	RES_0402	RES_0402	2
0R	Resistor SMD 0402 0R	R6	RES_0402	RES_0402	1
5K1	Res Thick Film 0402 5.1K Ohm 1% 0.063W(1/16W) ±100ppm/C Pad SMD Automotive T/R	R8, R9	RESC1005X37N	AC0402FR-075K1L	2
ams1117	1A LOW DROPOUT VOLTAGE REGULATOR	U1	FP-ams1117-IPC_C	CMP-209535-000002-1	1
STM32F411CEU6	ARM Cortex-M4 32-bit MCU+FPU, 512 KB Flash, 128 KB RAM, 36 I/Os, 48-Pin UFQFPN, -40 to 85 degC, Tray	U2	STM-UFQFPN48_L	CMP-0243-00165-1	1
MPU-6050	3-Axis Gyroscope, Accelerometer and a Digital Motion Processor(TM) (DMP), 2.375 to 3.46 V, -40 to 85 degC, 24-Pin QFN, RoHS, Tape and Reel	U3	IS-QFN-24_V	CMP-1753-00002-2	1
24MHz	Crystal SMD 24MHz 10PPM 7pF 3225	X1	XTAL_3225	TSX-3225_24.0000MF15X-AC	1