

Comment	Description	Designator	Footprint	LibRef	Quantity
100n, 100nF, 50V, 22u, 2u2, 10p, 2n2, GREEN, RED, AQ3045-01ETG, 217179-0001, SM06B-GHS-TB, 1k, 2k2, 10k, 0R, 5K1, ams1117, STM32F411CEU6, MPU-6050, 24MHz	Capacitor SMD 0402, CAP CER 0.1UF 50V X7R 0402, Capacitor SMD 0805 16V, Capacitor SMD 0603, Capacitor SMD 0402 16V, LED 0402 GREEN SMD, LED 0402 RED SMD, Bi 30Kv 5V 0.35Pf Automotive Tvs Sod882/T&r Rohs Compliant: Yes, USB Connector, USB Type C, USB 2.0, Receptacle, 16 Ways, Surface Mount, Through Hole Mount, Header Connector 6 Position 1.25MM Pitch SMD Horizontal JST GH, Resistor SMD 0402, Resistor SMD 0402 0R, Res Thick Film 0402 5.1K Ohm 1% 0.063W(1/16W) ±100ppm/C Pad SMD Automotive T/R, 1A LOW DROPOUT VOLTAGE REGULATOR, ARM Cortex-M4 32-bit MCU+FPU, 512 KB Flash, 128 KB RAM, 36 I/Os, 48-Pin UFQFPN, -	C, C1, C3, C4, C5, C6, C7, C8, C9, C10, C11, C12, C13, C14, C15, C16, C17, D1, D2, D3, D4, D5, J1, J3, R1, R2, R3, R4, R5, R6, R7, R8, R9, U1, U2, U3, X1	CAP_0402, CAPC1005X55N, CAP_0805, CAP_0603, LED_0402_GREEN, LED_0402_RED, SOD882, FP-2171790001-MFG, SM06B-GHS-TB, RES_0402, RESC1005X37N, FP-ams1117-IPC_C, STM-UFQFPN48_L, IS-QFN-24_V, XTAL_3225	CAP_0402, CL05B104KB5NNNC, CAP_0805, CAP_0603, LED_0402_GREEN, LED_0402_RED, AQ3045-01ETG, 217179-0001, SM06B-GHS-TB, RES_0402, AC0402FR-075K1L, CMP-209535-000002-1, CMP-0243-00165-1, CMP-1753-00002-2, TSX-3225_24.0000MF15X-AC	37