-


High Level Design
Spread out as much as world
CLIENT
Browser
WebApp
Mobile App
IP
OS


TLD
CDNs


T1 + T3
T1
T2
T3
A
B
Latency (A)
= Σ T1


T1 + T3
DNS
FB


A


ICANN
Client
DNS
IP
ISPs
Google
FB
US Army
FB.com
IP
newFB.com
hdfc.com.


Client
DNS
IP
Waterfall
IP1 IP2 IP3 IP4 IP5
Shuffle
IP4
IP2
IP1
IP 5
System
IP
Proxying
GATEWAY = Load Balancer
Horizontal Scaling
App Servers
I
II
Vertical
much easier to get some gains
Horizontal
flexibility with changing load
Cost effective





→ prevent load on down boxes

internet → spin new boxes

→ balance out


Layer 4 ≡ Transport Layer
addition security
Source IP
Source Port
Dest IP
Dest Port
fast
Simple


Layer 7 LB ≡ Application
user-id ≡ 707
uid = 107
much better flexibility
Slow


Stateful
Stateless
17+15
a+5
a+b
Calculate
LB
Stateless
A1
A2
A3
App Server
Chatbot
LB
Stateful
App Server
Hi
Hello



Load Balancing

Stateless

→ Round Robin

WRR

→ (Least Connection first)

→ WLR ARR

Load Balancing in Stateful

Sol (1) Maintain Map BAD

Load Balancing func will slow down

map-size = order of key-size

Sol (2) Hash

BAD!!!

10 boxes ≡ 10 App Server

uid %. 10 = 0-9



→ gaurd of stickiness using hashing

→ LB

Do consider
On server inc/dec
you will have to move state of all boxes manually



Bottleneck: Add / Removal of servers is inefficient

---

4 Consistent Hashing

LB for Stateful Applications


4 servers
$H_R(R_1) = V_1 = 10,000$
$[0 - 10^{18}]$
H_S (Server id)
H_3 (s_id - 1)
H_3 (s_id 2)
S_1
S_2
S_3
S_4
R_1
R_2
R_3
R_4
piggybacking on people @ random
distance = Sharding key
ry_id = user id
ry_id = location id
$0 - 10^{18}$
akhmat


H_R (ry_id)
$[0 - 10^{18}]$
S_5
S_1
S_4
S_2
S_3
R_2
R_3
R_1
R_{10}
Agmk
S_4
Sajar
S_5
S_2
Add (S_5)


Amount of state transfer that happens has been reduced a lot
by a factor of # servers
downtime will also be low.....
you don't have downtime for every server. Small set of users get impacted


S1
S3
S4


LB
Durable

→ we are not keeping the ultimate source of truth

(A) cold starts ≡ request latency inc for some time

Hi:

Node

B1

A1

B2

A2

Online Learning Algo's model

(B) pre-emptive copying

(I) ← Storage layer → new App Server

(II) ← Mslave

Solved problem

Impact of server addition or removal is minimized

S1

S3

Implication of S2

✓ S1 → same

S4 → almost doubled

✓ S3 → same S4

S2

S1 ≡ Same

S3 ≡ JX





solved

Cascadiy Failures

Cause, the load will get divided almost equally.



$|H_S| \uparrow\uparrow \equiv$ Randomness $\uparrow\uparrow$

↓

Equitable Distribution $\uparrow\uparrow$

$|H_S| \uparrow\uparrow\uparrow \equiv$ Time for Resolution $\uparrow\uparrow\uparrow$

ASG







High Level Design

OSI Layers




outside
XYZ
P3
private IP
private IP
private IP
A
B
C
E
F
PL
IP
VPN
Reverse Proxy
Load Balancer
Gateway
Proxy ≡ Gateway to the outside world
Reverse Proxy ≡ Gateway to the inside world
cisco.com
domain
uri
IP
redirect
redirect
Local
VPN
IP
India


Laptop A
MAC A
Proxy
WiFi
Laptop B
MAC B
Router
MAC E
Laptop C
WiFi
Static
M1
M2
M3
Internet
Router
Router
OSI Layers
Open Systems Interconnection


HTTP
GET header
origination of request happen
7th
Application Layer
6th
Presentation Layer
- Encode your request
- Encryption
- Compression
https
tagged by a session_id
5th
Session Layer
4th
Transport Layer
3rd
Network Layer


S_ip
d_ip
S_ip
d_ip
S
d
S
d


2nd
Data Link layer
Source MAC
Add
dest MAC
ARP


1st
Physical layer
chic / light / Radio


M_id
Machine


7
Application
6
Presentation
5
Session
Client
4
Transport
3
Network
2
Data Link
1
Physical Layer
devices
Physical Layer
X N
Dest MAC No
=
Your MAC No
Data Link Layer
X N
Network Layer
X 1
Transport Layer
Session


App
Parent
App


S_M = d_M = A_MAC
d_M
I
II
III
IV
Source
destination
A
B
"NOT in same"
Same network
ARP(B)
MAC B
RoutyTable (A)
M
nexthop(N)
hop
dest
A,B NOT in same network
hop = A
dest → B
A, B
ARP
TTL
SAME NETW
ARP(M)
MAC M
S_M
d_M
M'
S_M
d_M
Add of next hop
ARP

CAP THEOREM

Only guarantee $\frac{2}{3}$ properties simultaneously

- C ≡ Consistency
- A ≡ Availability
- P ≡ Partition Tolerance

I Consistency → Immediate Consistency

Any read that you do, must return the value after the latest write

II Availability

Every and any request that goes to a non-dead server, must be responded to

III Partition Tolerance

The system as a whole is allowed to have partitions

OR

You have accepted the fact
that network partitions can happen at any
time
and the system as a whole will NOT
stop functioning

Event Reminder Service



Consistent

Available



Partition Tolerance

NOT CONSISTENT



CONSISTENT

PARTION TOLERANT

NOT AVAILABLE

CP OR AP

→ CA — if you are doing vertical scaling




CP
OR
AP
C vs A


CA


Not compatible
IMMEDIATELY
CONSISTENT
happily
Unavailable


Eventually Consistent


A
B
A
B


Never confuse latency
with consistency


Mobile
Client
LB
CONSISTENCY AT SERVER
WAS ALWAYS MAINTAINED


CACHING
Understand Codes
(Small)
Cache
Memory
Ready to Use


A
B

I
II
Profile Info
PSP
Images
Videos
lighter





Content Delivery Network
CDN







Company → CDN

CDN Hub → CDN Switches

User → CDN

---

cdn



Cache Invalidation

A → Time to Live (TTL)
= url should automatically become void after this time

B → Start sending a new URL

C → Versioning

Privacy in CDNs

1. CDN urls are by design not guessable
2. encrypted format
3. Authentication

(2) Client Side Caching

Browser
Mobile App
Desktop App

You can choose to store some amount of "important" data on the client's side

---

Typeahead



Browser Optimization

Automatically identify a few static resources for you and cache them

Hard Reload / Forced Reload

'ctrl + shift + R'

III App Server Cache

Client side Cache II

Cache Replacement

A LRU → Least Recently Used

B MFU

C



Cache Miss II

Cache Hit I

Access Time for Cache = x

" " DB = 100x

k calls

Without Cache

Avg DB Access Time

Time = [k X Avg + k X Avg Network Access Time]

80-20

With Cache

[70% Cache Hit Rate
30% Cache Miss Rate]

Time = [70/100 X k] X Cache Access Time
+
[30/100 X k] X Cache Access Time
+
0.3k X DB Access Time
+
0.3k Network Time



9 Global Cache


A
B
C


Client
push bar
Raj
Jay
Royale
LB
Stateful
Global Cache
Pushkar
B
Jay
Raj
B


L.B
App
A


Tinder
Cache invalidation
Client
Android
iOS
CDN
get Profile
get Profile Info



1. Client has Code : Profile Info

Timeline

Design a Facebook News Feed

① Enlist all the features → Minimum Viable Product

② Estimate the scale

③ Trade Offs

④ Architecture Design
→ APIs
→ Data Storage
→ Data Flows

Linked In
Instagram
Quora
Twitter

I. Ability to view posts of interest

II. Like / Comment / share a post

III. Multimedia Support → share Images / videos

IV. Bookmark a post

(B) Estimation of scale

(1) # users = 2 B → 400 M → new feeds

(2) DAU = 400 M

(3) # people who produce content OR read a post = 40 M

(4) # new posts / day = 2.5 × 40 M = 100 M

6 MINUTE WALK

(A) writes / day = 100 M

(B) Reads / day = [ ] → × read factor

= 400 M × 25

= 10,000 M

10,000 M → 1,15,000

30M →

= (10B) ...

Read QPS = 10 B × 10 / 24 × 60 × 60

= 115000 QPS

= 115k QPS

Write QPS 100M / 86400 = 1000 ...

2 × avg

avg = 115k

Read QPS = 115k × 2

= 230k

Write QPS = 2000

How QPS 1 machine can support?

1 box / 1 server

8 queries/sec

50 – 100

1M/s

- hardware
- computation
- data fetch



1000

$\frac{230\text{ k}}{100}$ = # boxes

2300 boxes

Load Factor => 65% - 75%

$\frac{2300}{0.7}$ = ~4000

EC2 ≡ App Server



III Trade Off

CAP Theorem


C vs A
CP
AP
Available
Partition Tolerant
Stateful
OR
stateless
Client
DNS
Load Balancer
VIP
App Servers
Storage
Storage layer


2TB
MySQL

Sharding



Normalization




[A - D]
[E - H]
Hot Shards


Client
Load Balancer
CH
u.id = 10x


Time Based Shards
30-60
0-2
2day - 30 days
4 - 10p
12 - 4
10p - 11:59a






```
Select *
from us_friends
                    x N
```

JOINS



Intra Shard → JOIN

Inter shard JOIN





Inter shard JOIN → Avoid



(I) denormalized way




duplicated data
Ranguli
170
u_id
user_submissi
uid
102
problem_id
11110007
recent_submissions_task
u_id
p_id
t..
8 hours







Mastr Slave Replication

MS Replication

- allows to scale READS
- requirement of backup has reduced
- increased READ Availability








N/2 +1
W1
W1
available
not consistent
latency


READ
M-S Replication
→ scale READ
→ give you comfort of backup
→ inc. availability
→ less latency
M
S1
S2
S3


A
B
C
D


Master - Master Replication
P2P
W1