

CHEM 10 UPE SD



PROCESSING EQUIPMENT

Chemical and corrosive products
Transfer



APPLICATIONS

Chemical resistant suction and delivery hose.

TECHNICAL DESCRIPTION

Inner tube: chemical resistant UPE, white, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather and chemical resistant EPDM, green, fabric impression.

Temperature range: -30°C to +100°C.

Electrical properties: built-in conductive wire.



| PROCESSING EQUIPMENT | | | CHEM 10 | UPE SD | | | | | |
|---|-----------------|----------------------------|-----------------------------|-----------------------|-------------------------|-----------------------|--------------------|-------------------|---------------------------------|
| ID mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | MAX. VACUUM bar | BENDING RADIUS mm | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK (1) or min. order m |
| 13.0 | 25.0 ±1 | 10 | 40 | 0.9 | 65 | 0.47 | 40 | 5513680 | ı |
| 19.0 | 31.0 ±1 | 10 | 40 | 0.9 | 100 | 0.62 | 40 | 5513681 | I |
| 25.0 | 37.0 ±1 | 10 | 40 | 0.9 | 125 | 0.79 | 40 | 5513682 | I |
| 38.0 | 51.0 ±1.2 | 10 | 40 | 0.9 | 200 | 1.21 | 40 | 5513683 | I |
| 51.0 | 65.0 ±1.2 | 10 | 40 | 0.9 | 250 | 1.87 | 40 | 5513684 | I |
| 63.0 | 78.0 ±1.2 | 10 | 40 | 0.9 | 310 | 2.46 | 40 | 5513745 | I |
| 76.0 | 91.0 ±1.2 | 10 | 40 | 0.9 | 400 | 2.92 | 40 | 5513685 | I |
| 102.0 | 118.0 ±1.2 | 10 | 40 | 0.9 | 500 | 4.35 | 40 | 5513686 | 160 |
| Folerance on length: ±1% (ISO 1307 Standard). | | | | | | | | | |

