

BIOVAST



APPLICATIONS

For steam cleaning at temperatures up to +165 °C and hot water washing in food processing plants.

Also for transfer of hot liquid foodstuffs.

Suitable for reel mounted applications.

ADVANTAGES

- A hose specially designed for dairies, canneries, fish markets, etc.
- Highly flexible.
- A non staining cover compound.
- Resistant to animal and vegetable fats.
- Contains no phthalate.

TECHNICAL DESCRIPTION

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, blue, smooth.

Temperature range:

Water: -20°C to +100°C, WP=20bar.

Saturated or superheated steam: +165°C/6bar.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

ŒU

FDA regulation No. 21 CFR 177.2600.

FDA

German legislation: BfR recommendation XXI cat.

BfR

French legislation.

RF

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

TRELLEBORG



BIOVAST ☑ - FDA - BFRXXI Cat2 - WP 20 BAR STEAM/VAPEUR 165°C - 6 BAR - Made in France



Tolerance on length: ±1% (ISO 1307 Standard).





