BURAK™
METERING
people behind measurement

Solutions for Liquid Flow Measurement



Turbine flow meter

ACCURATE RESULTS
Very fast response time

EASY PROCESS MONITORING
Effective and inexpensive measurements

TOTAL FLOW
High accuracy and reliable measurements

TYPES OF MODEL:



TURBINE FLOW METER
Flanged Connection
(BR-4000-G)



TURBINE FLOW METER
Screwed Connection
(BR-4000-V)



TURBINE FLOW METER
Triclover Connection
(BR-4000-E)

Accessories:



Panel mount indicator
(BA-PA100)



Online Monitoring Device
(BA-IoT-100)

TECHNICAL SPECIFICATION

Measuring principle:	Turbine pickup sensor
Display:	LCD display
Contrast:	25%, 50%, 75%, 100% user selectable
Accuracy:	± 1.5 % of reading
Flow Unit Adjustment via display:	ltr/min, ltr/hr, ltr/day, m3/min, m3/hr, Usgal//min, Usgal/hr, Usgal/day, barrel/min,barrel/hr,barrel/day,kg/min,kg/day
Wetted parts:	SS 304,SS304L,SS316,SS316L
Measuring range:	Refer range table
Tube diameter:	Inline type: DN15 ... DN150
Process connection:	BSP (M/F), NPT (M/F) thread, Flange ANSI/ B16.5,JIS B2220, DIN EN 1092-1
Measuring Medium:	Clear liquids
Operating temperature:	-20 ... + 120°c (Standard Version) -20 ... +250°C (Optional)
Operating pressure:	0 - 16 Bar (Standard Version) 0 - 25 Barg (Optional) 0 - 50 Barg (Optional) 0 - 400 Barg (Optional)
Analogue output:	4 ... 20 mA, 3 – Wire
Viscosity max:	Up to 100 cp
Fieldbus:	RS 485 Modbus RTU (Standard) RS 232 Modbus RTU (Optional) HART (Optional)
Pulse:	Floating-point number user programmable
Power supply:	24 VDC, 2 AMP
Enclosure:	Explosion Proof Zone 1 & 2 , Gas Group IIB
Housing:	Die-cast Aluminum
Approvals:	Petroleum And Explosives Safety Organisation (PESO) ATEX / IECEx / FM (Optional)

Line Size	Qmin(M3/hr)	Qmax(M3/hr)
1/2"	0.3	3
3/4"	0.8	8
1"	1.6	16
1.1/4"	2.5	25
1.1/2"	3.4	34
2"	6.8	68
3"	13.5	135
4"	27	270
6"	55	550