BURAK METERING
people behind measurement

burak.in

PRODUCT CATALOGUE



OVAL GEAR FLOW METER

BG - 2000 Series

Swift Response

Easy Process Monitoring

Accurate Measurement

DESCRIPTION

An oval gear flow meter is a type of positive displacement flow meter that measures the flow of liquid by counting the rotations of two oval-shaped gears. As the fluid passes through the meter, it drives the gears to rotate, and the volume of liquid passing through is determined by the number of gear rotations. The gear rotations are measured by a magnetic or optical sensor, which generates pulses corresponding to the flow rate. Oval gear flow meters are known for their high accuracy, ability to handle viscous fluids, and suitability for applications in various industries such as chemical processing, oil and gas, and food and beverage production.

FEATURES

- Graphical LCD Display, Configurable
- Display parameter: Flow and Total Value
- 4-20 mA
- RS 485 Modbus RTU for Network Communication
- Option for batch control
- Robust construction
- Temperature and Pressure Resilience
- Suitable for high viscous application
- No upstream and downstream required

APPLICATION

Fuel Oils	*Diesel*
Gasoline	*Heavy Fuel Oil*
Lubricating Oil	*Hydraulic Oil*
Light Crude Oil	*Vegetable oil*
Cooking Oil	*Cream & Lotions*
Molasses	*Chemicals*
Solvents	*Resins*
Adhesives	*Coolants*
Ink	*Glycerin*
Polymer Solutions	*Heavy Syrups*
Grease	*Paints*

BENEFITS

High Accuracy
They provide precise flow measurements, even at low flow rates, ensuring reliable data.

Versatility
Suitable for a wide range of fluids, including viscous liquids, chemicals, and fuels.

Stable Performance
They maintain consistent accuracy and performance regardless of fluid viscosity or density changes.

Durability
Constructed from robust materials, they are highly durable and resistant to wear and corrosion.

Low Pressure Drop
Designed to minimize pressure loss in the system, ensuring efficient fluid flow.

Simple Design
The straightforward design with few moving parts makes them easy to maintain and repair.

Bidirectional Measurement
Capable of measuring flow in both directions, adding to their versatility.

Compact Size
Their compact design allows for easy installation in limited spaces.

TECHNICAL SPECIFICATION

Measuring Principle	Positive displacement principle
Display	LCD display
Fluid	Diesel, Kerosene, Gasoline, Light Oils, Heavy Oils, Food Oils, Solvents, Lubrication Oils, Chemicals, Pharma Chemicals, Clear Water etc.
Flow Unit Adjustment via display	ltr/min, ltr/hr, m3/min, m3/hr, kg/min, kg/hr
Measuring range	Refer range table
Accuracy	± 0.5% of reading
Repeatability	± 0.1% of Span
Oval Gear	Aluminum, SS 304
Sealing	Viton, NBR
Body	Aluminum, SS 304
Shaft	SS 316
Meter Size	Inline type: DN4...DN80
Process Connection	Thread BSP (F), Flange ANSI / B16.5, JIS B2220, DIN EN 1092-1
Operating temperature	-20 ... +120°C
Operating Pressure	0-16 Bar : Standard Version , upto 50 Bar (Optional)
Viscosity max	Up to 10000 cp
Analogue output	4 ... 20 mA, 3 wire source ouput
Communication	RS 485 Modbus RTU
Power supply	24 VDC, Standard And 230 VAC (optional)
Enclosure	Weatherproof for remote model & Flameproof for integrated model
Housing Material	PP for W/P model & Die-cast Aluminumfor FLP model
Enclosure Rating	Weather proof IP 66 & Flame proof FLP Type Ex'd' IIB T6, EPL Gb & Db