

Development of PGA barrier polymer at VTT

Jouni Lattu
VTT Technical Research
Centre of Finland Ltd







PGA polymer development

From monomer through polymer into multilayer films



Our place as a performer of R&D work

BASIC RESEARCH



UNIVERSITIES

APPLIED RESEARCH



VTT

DEVELOPMENT



INDUSTRY



PLACE %

'PGA from a new process by VTT' - Superior oxygen barrier and mechanical performance polymer

- Target market is barrier films for food and beverage packaging.
- Global packaging barrier polymer market
 1 billion FUR.
- Targeting market entry with PGA production in 2018, growing the capacity to 8 000 tons by 2021.
- Patented polymerization technology enabling affordable availability of PGA polymer.



09/03/2016 4



Barrier polymer market

EVOH 130 ktn Total barrier polymer market potential

>1 billion EUR > 70% in


packaging

PGA 5 ktn

PVDC 125 ktn

Nylon / MXD6 80 ktn

The new production solution





Performance advantage

ltem	new PGA	Market PGA	MXD6	EVOH 44%
Biodegradable	yes	yes	no	no
T _m [°C]	207	220	218	168
OTR	0.4	0.1	1.0	0.5
Tensile strength [MPa]	79	117	99	61
Elongation [%]	>100	13	3.5	280
Tensile Modulus [GPa]	7.3	7.0	4.7	2.1
Price [€/kg]	"x"	"5.5x"	"1.7x"	"X"

→ Price / Performance advantage




PGA for shelf stable retort packs

- Retort is the commercial method to sterilize the food (in 121 - 130 C, 10 - 40 min) inside a sealed barrier package.
- Typical materials for retort packaging are flexible and rigid plastic, and metal.
- Typically results in 12 24 month shelf life without refrigeration.
- Flexible plastic is the fastest growing segment in retort.



Flexible retort pouch




Source: Frost & Sullivan




PLACE %

Global retort pouch market





Bio-based glycolic acid value chain



Key benefits:

- Bio-based alternative routes
- Biodegradable polymer
- High performing barrier polymer
- Reduced consumption of other packaging components



'new PGA' summary

- 1. PGA performance benefits in packaging applications are already largely known
- 2. Restricted availability
- 3. Resin kg price for packaging barrier market
- 4. VTT's future process enabling access to the packaging market



New PGA pilot manufacturing

- Produced in scalable batches (hundreds of kilos)
- High Molecular Weight (M_{w.GPC} ~ 250,000 g/mol)
- Applied for multilayer films
- Tested for applications





Thank you

PRESENTED BY

Jouni Lattu VTT Technical Research Centre of Finland Ltd jouni.lattu@vtt.fi